Natalyx MVP Fixes

Work Package 04: Node 0 workspace and paid-case separation

L. Rhodes (plan owner) - A. Zhao (technical review requested)

2026-07-10

Contents

1 Work Package 04: Node 0 workspace and paid-case separation **2**

1.1 Purpose and outcome 2

1.2 Verified current-state evidence 3

1.3 Architecture and contracts 3

1.4 Explicit PR sequence 6

1.5 Cross-repository coordination 13

1.6 Test and acceptance matrix 13

1.7 Risks and decisions 14

1.8 Existing-work salvage 15

1.9 Ownership recommendation 16

1.10 Definition of done 17

1 Work Package 04: Node 0 workspace and paid-case separation

Review draft only. Ownership and sequencing remain recommendations until Luke and Alan approve the plan together.

Plan	Value
Work package	WP04
Plan file	`WP04 - Node 0 workspace and paid-case separation.md`
Proposed PRs	P04-01, P04-02, P04-03
Inspection snapshot	2026-07-10 20:12 America/New_York

1.1 Purpose and outcome

Problem. PR #124 creates a synthetic canonical case as soon as Node 0 is opened, collapsing free exploration, workspace membership, commercial commitment, and paid-case truth.

Why this package exists. It creates a reviewable boundary so the programme can progress without mixing product, data, security, infrastructure and rollout concerns in one oversized change.

Completed outcome. A distinct Node 0 workspace aggregate with attributable revisions and an idempotent, purpose-limited projection into one paid case only after the authorized commercial event.

Explicit non-goals.

- No payment processor
- No full Node 0 UI

- No clinical or legal truth promotion
- No deletion of legacy rows during compatibility window

1.2 Verified current-state evidence

Classification is explicit: **verified** is observed code/PR/live behavior; **verified limitation** records an evidence gap; **design authority** is an approved planning source; **design decision** is proposed future behavior. None is silently treated as another.

ID	Class	Repository / ref	File, construct or location	Finding
E-010	verified	app / PR #124@84a5a84	app/routes/node0.py:63-90	Opening Node 0 calls create_byos_case_for_ip with is_synthetic=True; there is no separate free workspace or authorized promotion.
E-011	verified	app / PR #124@84a5a84	app/storage/node0.py:400-462; app/routes/node0.py:605-652	Node 0 can issue an unaddressed GC invitation and redemption ultimately creates case membership, collapsing low-risk onboarding possession with case access.
E-013	verified	app / PR #124@84a5a84	app/node0.py:252-482,622-878,975-1001	Nineteen IP-entered candidate answers about relationship and third-party circumstances/health derive a 0-100 score, readiness/status, ordering, guide route and evidence packet without per-field provenance or verification.
E-014	verified	app / PR #124@84a5a84	app/storage/node0.py:42-200,509-600; tests/python/test_node0_routes.py:441-490	IP/co-IP own candidate reads; GC onboarding writes separate shared/private facts and does not read IP-entered assertion. The GC cannot see or correct the IP candidate record.
E-015	verified	app / PR #122@e853821	app/storage/facts.py:19-69,107-127	Facts have broad provenance and visibility values but no subject-versus-author role, verification state, derived-from, or supersedes link.

1.3 Architecture and contracts

- Workspace, entitlement, commercial, payment, and case lifecycles are separate entities and state machines.
- Promotion copies only allowlisted projections with provenance, visibility, and verification intact.
- Compatibility adapters read old case-shaped Node 0 records while new writes target the workspace model.

Contract area	Package rule
Ownership boundary	`app`; repository-specific PRs remain separate.
Entities/state	`node0_workspace`
Authorization	Authenticated subject/service plus entity membership, role, purpose, consent and expected revision; query parameters, links and UI state are never authority.
API/service	No broad public contract; use the focused commands/events in each PR.
Storage	Add node0_workspaces, workspace_memberships, candidate assertion linkage and constraints. Append-only assertion/revision and projection-audit records. Idempotent backfill with source identifiers and exception report.
Audit	Use the common transition envelope and append-only source/event identifiers; redact tokens, raw documents, prompts and sensitive payloads.
Failure	Fail closed for authorization, provenance, money, document and PHI boundaries; expose a bounded actionable error and preserve retry/repair evidence.
Observability	Correlation, policy/schema/config version, transition and dependency result metrics without PHI/PII payload logging.
Compatibility	Additive/dual-compatible changes, explicit version pins, old/new revision window and named forward repair.
Privacy/PHI	Synthetic only through A2; approved PII only at B1; PHI remains blocked until formal B2.

1.3.1 Applicable state machines

1.3.2 Node 0 workspace (`node0_workspace`)

Owner: **natalyx-app**. States: `draft`, `active`, `match_ready`, `promotion_pending`, `promoted`, `archived`.

Transition: `none` -> `draft`

- **Actor:** authenticated IP
- **Evidence:** first explicit Node 0 start
- **Idempotency key:** `workspace:{owner}:create`
- **Invalid transitions:** Existing active workspace returns existing
- **Audit event:** `workspace_created`
- **Retry:** Unique owner/idempotency key
- **Recovery:** Forward repair orphan membership

Transition: `draft` -> `active`

- **Actor:** IP

- **Evidence:** minimum workspace consent/profile
- **Idempotency key:** `workspace:{id}:activate:{revision}`
- **Invalid transitions:** Missing consent/owner
- **Audit event:** `workspace_activated`
- **Retry:** Return current active revision
- **Recovery:** Correct inputs and retry

Transition: `active` -> `match_ready`

- **Actor:** IP + selected GC evidence policy
- **Evidence:** selected candidate + required provisional/GC-authored fields
- **Idempotency key:** `workspace:{id}:ready:{revision}`
- **Invalid transitions:** Critical unknown/decline/revoked claim
- **Audit event:** `workspace_match_ready`
- **Retry:** No duplicate event
- **Recovery:** Reopen active with reason revision

Transition: `match_ready` -> `promotion_pending`

- **Actor:** promotion event consumer
- **Evidence:** valid byos.workspace_promotion_authorized.v1
- **Idempotency key:** `promotion:{commitment}:v1`
- **Invalid transitions:** No authorization; already promoted; stale config
- **Audit event:** `workspace_promotion_requested`
- **Retry:** Replay resumes/finds same promotion
- **Recovery:** Forward-repair incomplete transaction

Transition: `promotion_pending` -> `promoted`

- **Actor:** promotion service
- **Evidence:** paid case + manifest committed
- **Idempotency key:** `promotion:{commitment}:v1`
- **Invalid transitions:** Projection invariant/privacy failure
- **Audit event:** `workspace_promoted`
- **Retry:** Return same case ID
- **Recovery:** Repair from immutable manifest; never duplicate

Transition: `draft|active|match_ready` -> `archived`

- **Actor:** IP/operator per policy
- **Evidence:** explicit archive + retention policy
- **Idempotency key:** `workspace:{id}:archive:{request}`
- **Invalid transitions:** Promotion pending/promoted
- **Audit event:** `workspace_archived`
- **Retry:** Idempotent
- **Recovery:** Restore only through new audited revision if policy permits

1.3.3 Data authorship/provenance rules

- Every assertion/revision records subject_ref, semantic_key, author_subject/person/role, authorship_class, provenance, verification_status, visibility, purpose, source_ref, derived_from, supersedes_id, promotion_event_id, policy version and immutable timestamps.
- Class 1 defaults IP-private; class 2 defaults IP-private/internal and visibly says reported by the intended parent, not confirmed by the GC.
- Class 3 is GC-authored and shared only per field/purpose; class 4 is GC-only private; class 5 requires an evidence-linked role-gated reviewer/provider rail.
- GC confirmation appends a class-3 revision referencing the class-2 assertion. Relationship answers can coexist; disagreement is not an overwrite.
- Unselected candidates, raw health assertions, ranking scores and private IP notes do not promote. Derived values inherit the weakest source status.
- Copying, promotion, generic proposal approval, IP assertion or AI inference can never create Natalyx-reviewed, provider-confirmed, medically cleared, legally cleared or insurance-verified truth.

1.4 Explicit PR sequence

Order	ID	Title	Repository	Dependencies	Gate	Size	Readiness
1	P04-01	Separate Node 0 workspace storage from paid cases	app	P02-03	A1	Exceptional	Dependencies unmet
2	P04-02	Add attributable workspace revision and projection contracts	app	P04-01	A1	Large	Dependencies unmet
3	P04-03	Adapt legacy Node 0 case-shaped data without semantic promotion	app	P04-02	A1	Large	Dependencies unmet

1.4.1 P04-01 - Separate Node 0 workspace storage from paid cases

Field	Plan
Repository / base	`app` (`main`)
Gate / size / readiness	A1 / Exceptional / Dependencies unmet
Dependencies	P02-03
Blocking decisions/checkpoints	CHECK-ALAN-122-124
Source / salvage	PR #124 _ensure_node0_case as behavior to replace, candidate worktrees

1.4.1.1 Objective Introduce workspace, workspace membership, candidate, and selection entities so opening Node 0 never creates a canonical paid case.

1.4.1.2 Scope

- Workspace aggregate and memberships
- Candidate rows linked to workspace
- Case tables remain paid/manageable aggregate

1.4.1.3 Explicit non-goals

- No UI rewrite
- No promotion
- No legacy deletion

1.4.1.4 Expected files or modules

- `migrations/versions/*_node0_workspaces.py`
- `app/storage/workspaces.py`
- `app/storage/workspace_memberships.py`
- `app/storage/node0.py`

1.4.1.5 Change map

Area	Planned change
Schema/model	Add node0_workspaces, workspace_memberships, candidate assertion linkage and constraints.
API/routes	No public API/route contract change.
UI/product surface	No visible participant/operator UI change.
Infrastructure/workflow	No cloud/infrastructure resource or workflow change.
Migration/backfill	Expand only; old records remain readable.
Security/privacy	Preserve existing fail-closed boundaries; validate the PR-specific privacy/security cases.
Architecture/docs/config	Document the contract, version pins and safe partial-merge behavior.

1.4.1.6 Tests and validation Objective tests:

- Opening Node 0 creates no case
- workspace authorization
- candidate isolation
- concurrent workspace creation
- old app compatibility

Local validation:

- `python -m unittest discover -s tests/python`
- Run the focused test module(s) named above against SQLite and PostgreSQL where applicable.

Cloud validation: run only through Gate **A1** on a known revision, using synthetic data until B1 and no PHI until B2. A merge or green deployment is not gate acceptance.

1.4.1.7 Diagnostics and observability Emit correlation/idempotency/policy/version identifiers, transition/result counters and bounded failure reasons; never log tokens, processor payloads, raw documents, prompts, PHI or unnecessary PII.

1.4.1.8 Rollout Ship expand-only and dark by default; run the one-off migrator, verify readiness/old-revision compatibility, then enable writers/readers in a later compatible step.

1.4.1.9 Rollback or forward repair Prefer application rollback within the expand/contract window and a new forward-repair migration. An irreversible schema reversal requires its own approval and backup evidence.

1.4.1.10 Dependencies and parallel work Hard dependencies: P02-03. Parallel opportunities: P04-03

1.4.1.11 Objective acceptance criteria

- ☐ Introduce workspace, workspace membership, candidate, and selection entities so opening Node 0 never creates a canonical paid case.
- ☐ Every listed objective test passes locally and at the required gate where applicable.
- ☐ Every explicit non-goal remains out of the diff and no protected worktree/branch is modified during extraction.
- ☐ Rollout/repair evidence is attached before merge; unresolved decisions remain blocked rather than encoded as guesses.

1.4.1.12 Ownership and review

Role	Recommendation
DRI	Alan
Implementer	Alan (proposed; pending consolidated-plan sign-off)
Reviewer	Luke
Final approver	Luke
Required expertise	domain modelling, PostgreSQL, authorization
Higher-capability review	Mandatory before merge

1.4.2 P04-02 - Add attributable workspace revision and projection contracts

Field	Plan
Repository / base	`app` (`main`)
Gate / size / readiness	A1 / Large / Dependencies unmet
Dependencies	P04-01
Blocking decisions/checkpoints	D-DATA-01, D-DATA-02, CHECK-ALAN-122-124
Source / salvage	Current facts/memory models, GC authorship audit

1.4.2.1 Objective

Represent IP assertions, GC confirmations, private notes, and reviewer/provider confirmations as attributable append-only revisions with purpose-limited projections.

1.4.2.2 Scope

- Authorship classes and supersedes links
- Verification/visibility/purpose metadata
- Projection allowlists for IP, GC, case, intelligence, provider

1.4.2.3 Explicit non-goals

- No provider transmission
- No silent in-place overwrite

1.4.2.4 Expected files or modules

- `migrations/versions/*_authored_assertions.py`
- `app/storage/assertions.py`
- `app/domain/projections.py`
- `tests/python/test_authorship_projections.py`

1.4.2.5 Change map

Area	Planned change
Schema/model	Append-only assertion/revision and projection-audit records.
API/routes	No public API/route contract change.
UI/product surface	No visible participant/operator UI change.
Infrastructure/workflow	No cloud/infrastructure resource or workflow change.
Migration/backfill	Apply through the named versioned migration; no ad-hoc startup DDL. Backfill is none unless explicitly listed in scope.
Security/privacy	Default deny between roles; explicit purpose projection.
Architecture/docs/config	Document the contract, version pins and safe partial-merge behavior.

1.4.2.6 Tests and validation

Objective tests:

- IP provisional remains attributed
- GC revision does not erase source
- private cross-role denial
- AI cannot upgrade verification
- provider projection allowlist

Local validation:

- `python -m unittest discover -s tests/python`

- Run the focused test module(s) named above against SQLite and PostgreSQL where applicable.

Cloud validation: run only through Gate **A1** on a known revision, using synthetic data until B1 and no PHI until B2. A merge or green deployment is not gate acceptance.

1.4.2.7 Diagnostics and observability Emit correlation/idempotency/policy/version identifiers, transition/result counters and bounded failure reasons; never log tokens, processor payloads, raw documents, prompts, PHI or unnecessary PII.

1.4.2.8 Rollout Ship expand-only and dark by default; run the one-off migrator, verify readiness/old-revision compatibility, then enable writers/readers in a later compatible step.

1.4.2.9 Rollback or forward repair Prefer application rollback within the expand/contract window and a new forward-repair migration. An irreversible schema reversal requires its own approval and backup evidence.

1.4.2.10 Dependencies and parallel work Hard dependencies: P04-01. Parallel opportunities: None inside this package beyond review/test preparation.

1.4.2.11 Objective acceptance criteria

- ☐ Represent IP assertions, GC confirmations, private notes, and reviewer/provider confirmations as attributable append-only revisions with purpose-limited projections.
- ☐ Every listed objective test passes locally and at the required gate where applicable.
- ☐ Every explicit non-goal remains out of the diff and no protected worktree/branch is modified during extraction.
- ☐ Rollout/repair evidence is attached before merge; unresolved decisions remain blocked rather than encoded as guesses.

1.4.2.12 Ownership and review

Role	Recommendation
DRI	Alan
Implementer	Alan (proposed; pending consolidated-plan sign-off)
Reviewer	Luke
Final approver	Luke
Required expertise	data provenance, privacy, authorization
Higher-capability review	Mandatory before merge

1.4.3 P04-03 - Adapt legacy Node 0 case-shaped data without semantic promotion

Field	Plan
Repository / base	`app` (`main`)
Gate / size / readiness	A1 / Large / Dependencies unmet
Dependencies	P04-02
Blocking decisions/checkpoints	None beyond dependencies and plan approval
Source / salvage	PRs #117/#121/#123/#124 and dirty candidate worktrees

1.4.3.1 Objective Provide a compatibility reader and controlled backfill that maps existing Node 0 rows to workspaces while preserving provenance and never treating legacy scores as verified truth.

1.4.3.2 Scope

- Dry-run audit and deterministic mapping
- Dual-read compatibility window
- Forward repair and per-row exception ledger

1.4.3.3 Explicit non-goals

- No destructive legacy cleanup
- No case creation

1.4.3.4 Expected files or modules

- `migrations/versions/*_node0_legacy_backfill.py`
- `app/storage/node0_compat.py`
- `scripts/audit_node0_backfill.py`
- `tests/fixtures/node0_legacy/`

1.4.3.5 Change map

Area	Planned change
Schema/model	None in this PR; any later schema change stays in its named migration PR.
API/routes	No public API/route contract change.
UI/product surface	No visible participant/operator UI change.
Infrastructure/workflow	No cloud/infrastructure resource or workflow change.
Migration/backfill	Idempotent backfill with source identifiers and exception report.
Security/privacy	Preserve existing fail-closed boundaries; validate the PR-specific privacy/security cases.
Architecture/docs/config	Document the contract, version pins and safe partial-merge behavior.

1.4.3.6 Tests and validation Objective tests:

- Legacy fixtures

- retry after interruption
- duplicate prevention
- mixed old/new writes
- privacy/provenance preservation

Local validation:

- `python -m unittest discover -s tests/python`
- Run the focused test module(s) named above against SQLite and PostgreSQL where applicable.

Cloud validation: run only through Gate **A1** on a known revision, using synthetic data until B1 and no PHI until B2. A merge or green deployment is not gate acceptance.

1.4.3.7 Diagnostics and observability

Counts/checksums and unmapped-row alerts.

1.4.3.8 Rollout

Ship expand-only and dark by default; run the one-off migrator, verify readiness/old-revision compatibility, then enable writers/readers in a later compatible step.

1.4.3.9 Rollback or forward repair

Prefer application rollback within the expand/contract window and a new forward-repair migration. An irreversible schema reversal requires its own approval and backup evidence.

1.4.3.10 Dependencies and parallel work

Hard dependencies: P04-02. Parallel opportunities: P04-01

1.4.3.11 Objective acceptance criteria

- ☐ Provide a compatibility reader and controlled backfill that maps existing Node 0 rows to workspaces while preserving provenance and never treating legacy scores as verified truth.
- ☐ Every listed objective test passes locally and at the required gate where applicable.
- ☐ Every explicit non-goal remains out of the diff and no protected worktree/branch is modified during extraction.
- ☐ Rollout/repair evidence is attached before merge; unresolved decisions remain blocked rather than encoded as guesses.

1.4.3.12 Ownership and review

Role	Recommendation
DRI	Alan
Implementer	Alan (proposed; pending consolidated-plan sign-off)
Reviewer	Luke
Final approver	Luke
Required expertise	Python/FastAPI, PostgreSQL, security-aware product engineering
Higher-capability review	Mandatory before merge

1.5 Cross-repository coordination

Repository	Authority after merge
`app`	routing, validation, authorization, participant/case/workflow truth, PHI policy and commercial domain

Merge order inside this package: `P04-01` → `P04-02` → `P04-03`.

Handoff rule: producer contract/version must merge and be pinned before its consumer enables the feature. During a partial merge, consumers fail closed or retain the last approved version; they do not fabricate data or silently broaden access.

Compatibility window: keep prior readers/writers and rollback image usable through the named gate; contract/migration PRs document the exact removal point.

1.6 Test and acceptance matrix

Test dimension	Method	Objective result
Happy path	One workspace/one promotion; Retry/concurrency; No implicit fact upgrade; Private candidate isolation; Old/new revision coexistence	Expected state/event/UI and named evidence are produced once.
Authorization failure	Wrong/no subject, role, membership, purpose or consent	403/404 as appropriate; no write or data leak; audit safe failure.
Role differences	Separate IP, GC, operator, provider/service identities	Only the approved lens/projection/actions appear.
Retries/duplicates	Repeat same canonical request/event	Original result returned; no duplicate membership/case/invoice/document/event.
Concurrency	Two writers/claimants/migrators/workers	One valid transition; loser receives deterministic stale/conflict response.
Stale state	Old revision/config/terms/token/artifact	Fail closed or approved compatibility behavior; never silent coercion.
Malformed input	Boundary, encoding, size, enum, redirect and identifier corpus	Validation before side effects; safe error.
Unavailable dependency	Database, intelligence, processor, S3/scanner or auth unavailable	Explicit degraded/blocked behavior; no hallucinated success.
Partial failure	Crash between external effect, DB transaction and outbox	Retry/forward repair converges from durable evidence.
Logout/login/resume	Session expires/restarts mid-flow	Return to authorized current state; no query/link authority.
Mobile/accessibility	320/375/768 widths, keyboard, focus, reduced motion	Core task completes with truthful state and no clipped controls.

Test dimension	Method	Objective result
Synthetic cloud	Known dev revision and synthetic identities/data	Gate artifact records SHA, dependency status, audit and cleanup.
Audit/observability	Inspect events/metrics/logs	Versions, actor/authority, correlation and reason present; no sensitive payload.

1.7 Risks and decisions

Type	ID / risk	Owner	Affected PRs / latest point	Treatment
Blocking/product/compliance decision	D-DATA-01 - Which provisional IP assertions may the GC see, which GC answers may the IP see, and which fields survive promotion/provider projection?	Luke	P04-02, P06-02, P06-03, P07-03, P07-04, P09-05, P10-01, P10-02; Before P04-02	D-DATA-01 - Default deny; expose only explicit purpose-limited projections. Class 1/2 and class 4 never automatically cross roles.
Blocking/product/compliance decision	D-DATA-02 - How long to retain unselected candidate assertions and how are GC corrections, conflicting relationship answers, and private IP notes represented?	Luke	P04-02, P04-03, P06-02; Before P04-02	D-DATA-02 - Append revisions with supersedes/derived-from; never silently erase source; shortest justified retention for unselected candidates.
Implementation risk	Semantic data corruption during backfill	Alan or named PR DRI	Package PRs; before associated gate	Mitigate through the explicit tests, rollout and forward-repair plan
Implementation risk	Duplicate cases	Alan or named PR DRI	Package PRs; before associated gate	Mitigate through the explicit tests, rollout and forward-repair plan
Implementation risk	Private candidate leakage	Alan or named PR DRI	Package PRs; before associated gate	Mitigate through the explicit tests, rollout and forward-repair plan
Implementation risk	Older app revision writes legacy shape	Alan or named PR DRI	Package PRs; before associated gate	Mitigate through the explicit tests, rollout and forward-repair plan

1.8 Existing-work salvage

Source	Head	Valuable content	Destination	Recommendation	Extraction status/safety
app#117	5ac09f0cdd92	Deterministic candidate questionnaire, scoring/status calculation, conversation-guide resource, routes and extensive Node 0 tests.	P04-01, P04-02	Selective port and rewrite	Unextracted; algorithm/test review required after Alan checkpoint and Luke field/score decision.
app#119	a8cd2f428535	Concise product-leverage framing and boundaries for the MVP flow.	P04-01	Retain as source or merge separately after plan decision	Catalogued; reconcile terminology into approved programme.
app#122	e85382150853	Case projection/lens surfaces, safe return_to, invitation TTL/CAS/self-member/one-GC constraints, transactional membership, fail-closed Learn, SQL-limited timeline, responsive/a11y tests and Python CI workflow.	P04-02	Retain pending Alan reconciliation; selective port or rebase only after architecture approval	Reinspected at latest head. It is exactly e853821 (no newer delta); retention strengthened, but final extraction waits for Alan checkpoint.

Source	Head	Valuable content	Destination	Recommendation	Extraction status/safety
app#124	84a5a847fea7	Current consolidation of Node 0 questionnaire/guide/surfaces, GC onboarding, participant case shell, invitations, DS assets and large focused test suites.	P04-01, P04-02, P04-03	Retain unchanged as evidence; selective port/rewrite after checkpoint	Unextracted; Alan review explicitly incomplete and unresolved.
detached candidate rewrite	9605d88	substantial uncommitted Node 0 quiz rewrite	P04-02/P05-02	Selective port from protected worktree	Preserve; compare with predecessor and #117/#124 before any discard.
detached predecessor candidate model	dc6a2f0	substantial uncommitted predecessor model	P04-02/P05-02 if unique	Selective port from protected worktree	Preserve until rewrite diff/extraction ledger is complete.

Package source inventory:

- PR #124 candidate/outreach behavior and tests by selective port
- PR #122 case projection primitives after reconciliation
- Older candidate-model and rewrite worktrees

1.9 Ownership recommendation

Alan owns domain/schema implementation; Luke approves entity boundaries and promotion contract. Joint high-capability review is mandatory.

PR	DRI	Implementer	Reviewer	Final approver	External/high-capability review
P04-01	Alan	Alan (proposed)	Luke	Luke	Mandatory
P04-02	Alan	Alan (proposed)	Luke	Luke	Mandatory
P04-03	Alan	Alan (proposed)	Luke	Luke	Mandatory

Luke decides product/lifecycle/commercial/privacy/PHI/provider policy and accepts gates. Alan proposes implementation design, decomposition, migrations, code, tests, rollout and repair. This is a recommendation pending Alan's review/sign-off, not a compulsory assignment.

1.10 Definition of done

- ☐ Every proposed PR is merged in dependency order or explicitly dispositioned, with its objective acceptance criteria and review record complete.
- ☐ All package blocking decisions are resolved by the named owner; no commercial/privacy/security value is guessed in code.
- ☐ Local, PostgreSQL, role/authorization, retry/concurrency, failure, mobile and synthetic-cloud evidence required by this package is attached.
- ☐ Cross-repository contracts and artifact/migration versions are pinned; partial-merge behavior is fail-closed or explicitly degraded.
- ☐ Observability is sufficient to identify revision, transition, dependency and safe failure without sensitive payloads.
- ☐ Existing PR/worktree value and reviewer findings are extracted before closure; no cleanup occurs without team confirmation.
- ☐ The associated programme gate is accepted by Luke and any required external reviewer; tests/deploy alone do not establish B1/B2.