

Paidly — Database Structure

Generated 2026-05-16 · PostgreSQL (Supabase) · 46 public tables · Source: `supabase/schema.postgres.sql` + migrations

Scope: Application tables in `public` schema. Auth users live in `auth.users` (Supabase managed). Row Level Security (RLS) is enabled on user/org data; admin bypass uses `public.is_admin()` from JWT `app_metadata.role`.

Core & tenancy

public.companies

COLUMN	TYPE	CONSTRAINTS / FK
<code>id</code>	uuid PRIMARY KEY DEFAULT uuid_generate_v4()	—
<code>org_id</code>	uuid NOT NULL	REFERENCES public.organizations(id) ON DELETE CASCADE
<code>name</code>	text NOT NULL	—
<code>logo_url</code>	text	—
<code>created_at</code>	timestamptz NOT NULL DEFAULT now()	—
<code>updated_at</code>	timestamptz NOT NULL DEFAULT now()	—

public.memberships

COLUMN	TYPE	CONSTRAINTS / FK
<code>id</code>	uuid primary key default uuid_generate_v4()	—
<code>org_id</code>	uuid not null	references public.organizations(id) on delete cascade
<code>user_id</code>	uuid not null	references auth.users(id) on delete cascade
<code>role</code>	text not null default 'member'	—
<code>created_at</code>	timestamptz not null default now()	—

public.organizations

COLUMN	TYPE	CONSTRAINTS / FK
<code>id</code>	uuid primary key default uuid_generate_v4()	—
<code>name</code>	text not null	—
<code>owner_id</code>	uuid not null	references auth.users(id) on delete cascade
<code>created_at</code>	timestamptz not null default now()	—
<code>logo_url</code>	TEXT	—

public.profiles

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key	references auth.users(id) on delete cascade
full_name	text	—
email	text	—
avatar_url	text	—
logo_url	text	—
company_name	text	—
company_address	text	—
phone	text	—
subscription_plan	text default 'starter'	—
currency	text default 'USD'	—
timezone	text default 'UTC'	—
invoice_template	text default 'classic'	—
invoice_header	text	—
business	jsonb	—
reminder_settings	jsonb	—
quote_reminder_settings	jsonb	—
last_active_at	timestampz	—
last_active_path	text	—
created_at	timestampz not null default now()	—
updated_at	timestampz not null default now()	—
is_pro	boolean DEFAULT false, ADD COLUMN IF NOT EXISTS payfast_token text, ADD COLUMN IF NOT EXISTS subscription_status text	—
role	text	—
user_role	text	—
list_filter_prefs	jsonb NOT NULL DEFAULT '{}'::jsonb	—
plan	text	—
subscription_status	text NOT NULL DEFAULT 'inactive'	—
trial_ends_at	timestampz	—

CRM & catalog

public.clients

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
name	text not null	—
email	text	—
phone	text	—
address	text	—
contact_person	text	—
website	text	—
tax_id	text	—
fax	text	—
alternate_email	text	—
notes	text	—
internal_notes	text	—
industry	text	—
payment_terms	text default 'net_30'	—
payment_terms_days	integer default 30	—
follow_up_enabled	boolean default true	—
segment	text	—
total_spent	numeric(12,2) default 0	—
last_invoice_date	timestampz	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestampz not null default now()	—
updated_at	timestampz not null default now()	—

public.services

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
name	text not null	—
description	text	—
item_type	text not null default 'service' check (item_type in ('service', 'product', 'labor', 'material', 'expense'))	—
default_unit	text not null	—
default_rate	numeric(12,2) not null default 0	—
tax_category	text default 'standard' check (tax_category in ('standard', 'reduced', 'zero', 'exempt'))	—
is_active	boolean default true	—
rate	numeric(12,2) default 0	—
unit	text	—
unit_price	numeric(12,2)	—
unit_of_measure	text	—
service_type	text	—
sku	text	—
price	numeric(12,2)	—
billing_unit	text	—
role	text	—
hourly_rate	numeric(12,2)	—
unit_type	text	—
cost_rate	numeric(12,2)	—
cost_type	text check (cost_type in ('fixed', 'variable'))	—
default_cost	numeric(12,2)	—
category	text	—
pricing_type	text check (pricing_type in ('hourly', 'fixed', 'per_item', 'daily', 'weekly', 'monthly'))	—
min_quantity	integer default 1	—
tags	text[]	—
estimated_duration	text	—
requirements	text	—
price_locked	boolean default false	—
price_locked_at	timestampz	—
price_locked_reason	text	—
usage_count	integer default 0	—
last_used_date	timestampz	—

COLUMN	TYPE	CONSTRAINTS / FK
type_specific_data	jsonb	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
type	text CHECK (type IN ('product', 'service')) NOT NULL DEFAULT 'service'	—
stock_quantity	integer, ADD COLUMN IF NOT EXISTS cost_price numeric(12,2), ADD COLUMN IF NOT EXISTS low_stock_threshold integer DEFAULT 5	—

Inventory

public.deliveries

COLUMN	TYPE	CONSTRAINTS / FK
id	text PRIMARY KEY	—
product_id	text NOT NULL	REFERENCES public.products(id) ON DELETE CASCADE
quantity	numeric NOT NULL	—
status	text NOT NULL DEFAULT 'pending' CHECK (status IN ('pending','in_transit','delivered','cancelled'))	—
supplier	text	—
expected_date	date	—
tracking_number	text	—
notes	text	—
created_date	timestamptz	—
updated_date	timestamptz	—
created_by_id	text	—
created_by	text	—
is_sample	boolean DEFAULT false	—

public.inventory_movements

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT uuid_generate_v4()	—
product_id	uuid	—
quantity	integer	—
type	text, -- 'in' 'out'	—
source	text, -- e.g. 'invoice'	—
reference_id	uuid	—
created_at	timestamp DEFAULT now()	—

public.products

COLUMN	TYPE	CONSTRAINTS / FK
id	text PRIMARY KEY	—
name	text NOT NULL	—
sku	text	—
category	text	—
count_style	text NOT NULL DEFAULT 'units' CHECK (count_style IN ('units','cases','packs','boxes','pallets','bottles','bags','rolls'))	—
units_per_count	numeric DEFAULT 1	—
stock_on_hand	numeric DEFAULT 0	—
reorder_level	numeric DEFAULT 10	—
price	numeric	—
image_url	text	—
created_date	timestampz	—
updated_date	timestampz	—
created_by_id	text	—
created_by	text	—
is_sample	boolean DEFAULT false	—

public.stock_transactions

COLUMN	TYPE	CONSTRAINTS / FK
id	text PRIMARY KEY	—
product_id	text NOT NULL	REFERENCES public.products(id) ON DELETE CASCADE
type	text NOT NULL CHECK (type IN ('sold','received','adjusted','returned'))	—
quantity	numeric NOT NULL	—
notes	text	—
date	date	—
created_date	timestampz	—
updated_date	timestampz	—
created_by_id	text	—
created_by	text	—
is_sample	boolean DEFAULT false	—

Documents (legacy)

public.invoice_items

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
invoice_id	uuid not null	references public.invoices(id) on delete cascade
service_name	text	—
description	text	—
quantity	numeric(12,2) not null default 1	—
unit_price	numeric(12,2) not null default 0	—
total_price	numeric(12,2) not null default 0	—
service_id	uuid references public.services(id)	—

public.invoices

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
client_id	uuid	references public.clients(id) on delete set null
invoice_number	text	—
status	text not null default 'draft'	—
project_title	text	—
project_description	text	—
invoice_date	date	—
delivery_date	date	—
delivery_address	text	—
subtotal	numeric(12,2) not null default 0	—
tax_rate	numeric(6,2) not null default 0	—
tax_amount	numeric(12,2) not null default 0	—
total_amount	numeric(12,2) not null default 0	—
currency	text default 'USD'	—
notes	text	—
terms_conditions	text	—
created_by	uuid	references auth.users(id) on delete set null
user_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
banking_detail_id	uuid	—
upfront_payment	numeric(12,2)	—
milestone_payment	numeric(12,2)	—
final_payment	numeric(12,2)	—
milestone_date	date	—
final_date	date	—
pdf_url	text	—
recurring_invoice_id	uuid	—
public_share_token	text	—
sent_to_email	text	—
owner_company_name	text	—
owner_company_addresses	text	—
owner_logo_url	text	—
owner_email	text	—
owner_currency	text	—
company_id	uuid REFERENCES public.companies(id) ON DELETE SET NULL	—

COLUMN	TYPE	CONSTRAINTS / FK
document_brand_primary	text, ADD COLUMN IF NOT EXISTS document_brand_secondary text	—
client_operation_id	text	—

public.quote_items

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
quote_id	uuid not null	references public.quotes(id) on delete cascade
service_name	text	—
description	text	—
quantity	numeric(12,2) not null default 1	—
unit_price	numeric(12,2) not null default 0	—
total_price	numeric(12,2) not null default 0	—

public.quotes

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
client_id	uuid	references public.clients(id) on delete set null
quote_number	text	—
status	text not null default 'draft'	—
project_title	text	—
project_description	text	—
valid_until	date	—
subtotal	numeric(12,2) not null default 0	—
tax_rate	numeric(6,2) not null default 0	—
tax_amount	numeric(12,2) not null default 0	—
total_amount	numeric(12,2) not null default 0	—
currency	text default 'USD'	—
notes	text	—
terms_conditions	text	—
owner_company_name	text	—
owner_company_addresses	text	—
owner_logo_url	text	—
owner_email	text	—
owner_currency	text	—
created_by	uuid	references auth.users(id) on delete set null
user_id	uuid	references auth.users(id) on delete set null
created_at	timestampz not null default now()	—
updated_at	timestampz not null default now()	—
public_share_token	text	—
document_brand_primary	text, ADD COLUMN IF NOT EXISTS document_brand_secondary text	—
banking_detail_id	uuid references public.banking_details(id) on delete set null	—
sent_date	timestampz null	—

Documents (unified engine)

public.document_events

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
document_id	uuid not null	references public.documents(id) on delete cascade
org_id	uuid not null	references public.organizations(id) on delete cascade
event_type	text not null	—
payload	jsonb not null default '{}':jsonb	—
actor_user_id	uuid	references auth.users(id) on delete set null
created_at	timestampz not null default now()	—

public.document_items

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
document_id	uuid not null	references public.documents(id) on delete cascade
line_order	int not null default 0	—
description	text	—
quantity	numeric(14,4) not null default 1	—
unit_price	numeric(14,2) not null default 0	—
total_price	numeric(14,2) not null default 0	—
metadata	jsonb not null default '{}':jsonb	—
created_at	timestampz not null default now()	—
updated_at	timestampz not null default now()	—

public.document_sends

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
document_type	text not null check (document_type in ('invoice', 'quote'))	—
document_id	uuid not null	—
client_id	uuid	references public.clients(id) on delete set null
channel	text not null check (channel in ('email', 'whatsapp'))	—
sent_at	timestampz not null default now()	—
created_at	timestampz not null default now()	—

public.documents

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
type	text not null check (type in ('invoice', 'quote', 'payslip'))	—
status	text not null default 'draft'	—
client_id	uuid	references public.clients(id) on delete set null
document_number	text	—
title	text	—
issue_date	date	—
due_date	date	—
valid_until	date	—
subtotal	numeric(14,2) not null default 0	—
tax_rate	numeric(10,4) default 0	—
tax_amount	numeric(14,2) not null default 0	—
discount_amount	numeric(14,2) not null default 0	—
total_amount	numeric(14,2) not null default 0	—
currency	text not null default 'ZAR'	—
metadata	jsonb not null default '{}'::jsonb	—
public_share_to_ken	text	—
source_document_id	uuid	references public.documents(id) on delete set null
created_by	uuid	references auth.users(id) on delete set null
user_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
source_quote_id	uuid references public.documents (id) on delete set null	—
base_currency	text not null default 'ZAR', add column if not exists exchange_rate numeric(18,8) not null default 1	—

Billing & payments

public.banking_details

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
bank_name	text not null	—
account_name	text	—
account_number	text	—
routing_number	text	—
swift_code	text	—
payment_method	text default 'bank_transfer'	—
additional_info	text	—
payment_gateway_url	text	—
is_default	boolean default false	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—

public.packages

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid	references public.organizations(id) on delete cascade
name	text not null	—
price	numeric(12,2) not null default 0	—
currency	text default 'ZAR'	—
frequency	text default '/month'	—
features	jsonb default '[]'	—
is_recommended	boolean default false	—
website_link	text	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
is_sample	boolean default false	—

public.payments

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
invoice_id	uuid	references public.invoices(id) on delete set null
client_id	uuid	references public.clients(id) on delete set null
amount	numeric(12,2) not null default 0	—
status	text not null default 'pending'	—
paid_at	timestamptz	—
method	text	—
reference	text	—
notes	text	—
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
document_id	uuid references public.documents(id) on delete set null	—
currency	text not null default 'ZAR', add column if not exists exchange_rate numeric(18,8) not null default 1	—
payment_method	text	—
reference_number	text	—
payment_date	timestamptz	—

public.recurring_invoices

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
profile_name	text	—
client_id	uuid	references public.clients(id) on delete set null
invoice_template	jsonb	—
frequency	text not null default 'monthly'	—
start_date	date	—
end_date	date	—
next_generation_date	date	—
status	text not null default 'active'	—
last_generated_invoice_id	uuid	references public.invoices(id) on delete set null
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—

public.subscription_dunning_events

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
subscription_id	uuid NOT NULL	REFERENCES public.subscriptions(id) ON DELETE CASCADE
user_id	uuid	REFERENCES auth.users(id) ON DELETE SET NULL
event_type	text NOT NULL	—
attempt_no	integer	—
details	jsonb NOT NULL DEFAULT '{}'::jsonb	—
created_at	timestamptz NOT NULL DEFAULT now()	—

public.subscriptions

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
email	text NOT NULL	—
full_name	text	—
user_email	text	—
user_name	text	—
plan	text	—
current_plan	text	—
status	text NOT NULL DEFAULT 'active'	—
amount	numeric	—
custom_price	numeric	—
billing_cycle	text DEFAULT 'monthly'	—
next_billing_date	timestamptz	—
created_at	timestamptz NOT NULL DEFAULT now()	—
updated_at	timestamptz NOT NULL DEFAULT now()	—
user_id	uuid REFERENCES auth.users (id) ON DELETE SET NULL	—
start_date	timestamptz	—
payfast_token	text	—
provider	text DEFAULT 'payfast'	—
failure_count	integer NOT NULL DEFAULT 0	—
last_payment_at	timestamptz	—
next_retry_at	timestamptz	—
dunning_stage	integer NOT NULL DEFAULT 0	—
past_due_at	timestamptz	—
canceled_at	timestamptz	—
last_payment_failure_at	timestamptz	—
max_retry_attempts	integer NOT NULL DEFAULT 3	—
retry_interval_hours	integer NOT NULL DEFAULT 24	—
payfast_subscription_id	text	—

Payroll

public.payslips

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
payslip_number	text	—
employee_name	text	—
employee_id	text	—
employee_email	text	—
employee_phone	text	—
position	text	—
department	text	—
pay_period_start	date	—
pay_period_end	date	—
pay_date	date	—
basic_salary	numeric(12,2) default 0	—
overtime_hours	numeric(12,2) default 0	—
overtime_rate	numeric(12,2) default 0	—
allowances	jsonb default '[]'	—
gross_pay	numeric(12,2) default 0	—
tax_deduction	numeric(12,2) default 0	—
uif_deduction	numeric(12,2) default 0	—
pension_deduction	numeric(12,2) default 0	—
medical_aid_deduction	numeric(12,2) default 0	—
other_deductions	jsonb default '[]'	—
total_deductions	numeric(12,2) default 0	—
net_pay	numeric(12,2) default 0	—
status	text default 'draft'	—
public_share_token	text	—
user_id	uuid	references auth.users(id) on delete set null
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
is_sample	boolean default false	—
sent_to_email	text	—

Finance

public.expenses

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
expense_number	text	—
category	text	—
description	text	—
amount	numeric(12,2) not null default 0	—
date	date not null default (current_date)	—
payment_method	text	—
vendor	text	—
receipt_url	text	—
is_claimable	boolean default false	—
claimed	boolean default false	—
notes	text	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
is_sample	boolean default false	—
vat	numeric(12,2)	—

Operations

public.notifications

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
user_id	uuid not null	references auth.users(id) on delete cascade
message	text not null	—
read	boolean not null default false	—
created_at	timestamptz not null default now()	—

public.tasks

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
title	text	—
description	text	—
client_id	uuid	references public.clients(id) on delete set null
assigned_to	text	—
due_date	date	—
priority	text default 'medium'	—
status	text default 'pending'	—
category	text default 'other'	—
parent_task_id	uuid	references public.tasks(id) on delete set null
depends_on	jsonb default '[]'	—
estimated_hours	numeric(12,2)	—
tags	text[] default '{}'	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
is_sample	boolean default false	—

Analytics & tracking

public.invoice_views

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
invoice_id	uuid not null	references public.invoices(id) on delete cascade
client_id	uuid	references public.clients(id) on delete set null
viewed_at	timestamptz not null default now()	—
ip_address	text	—
user_agent	text	—
is_read	boolean default false	—
created_by_id	uuid	references auth.users(id) on delete set null
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
is_sample	boolean default false	—

Messaging

public.client_portal_messages

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
client_id	uuid not null	references public.clients(id) on delete cascade
sender_type	text not null check (sender_type in ('client', 'business'))	—
subject	text	—
content	text not null default ''	—
attachments	jsonb not null default '[]'::jsonb	—
is_read	boolean not null default false	—
created_at	timestampz not null default now()	—

public.message_deliveries

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default gen_random_uuid()	—
message_id	uuid not null	references public.admin_platform_messages (id) on delete cascade
user_id	uuid not null	references public.profiles (id) on delete cascade
channel	text not null check (channel in ('email', 'in_app'))	—
status	text not null default 'pending'	—
sent_at	timestampz	—
read_at	timestampz	—
created_at	timestampz not null default now()	—
updated_at	timestampz not null default now()	—

public.message_logs

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default uuid_generate_v4()	—
org_id	uuid not null	references public.organizations(id) on delete cascade
document_type	text	—
document_id	uuid	—
client_id	uuid	references public.clients(id) on delete set null
channel	text	—
recipient	text	—
sent_at	timestampz	—
opened_at	timestampz	—
viewed	boolean default false	—
paid	boolean default false	—
payment_date	timestampz	—
tracking_token	text	—
created_at	timestampz not null default now()	—
clicked_at	timestampz	—

Growth

public.waitlist_signups

COLUMN	TYPE	CONSTRAINTS / FK
id	UUID PRIMARY KEY DEFAULT gen_random_uuid()	—
email	TEXT NOT NULL	—
name	TEXT	—
source	TEXT	—
created_at	TIMESTAMPTZ NOT NULL DEFAULT now()	—
converted	boolean NOT NULL DEFAULT false	—

Affiliates

public.affiliate_applications

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
email	text NOT NULL	—
full_name	text NOT NULL	—
why_promote	text	—
audience_platform	text	—
status	text NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'approved', 'rejected'))	—
user_id	uuid	REFERENCES auth.users (id) ON DELETE SET NULL
created_at	timestampz NOT NULL DEFAULT now()	—
updated_at	timestampz NOT NULL DEFAULT now()	—
commission_rate	numeric	—

public.affiliate_clicks

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
affiliate_id	uuid NOT NULL	REFERENCES public.affiliates (id) ON DELETE CASCADE
created_at	timestampz NOT NULL DEFAULT now()	—

public.affiliates

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
user_id	uuid NOT NULL	REFERENCES auth.users (id) ON DELETE CASCADE
application_id	uuid	REFERENCES public.affiliate_applications (id) ON DELETE SET NULL
referral_code	text NOT NULL	—
commission_rate	numeric NOT NULL DEFAULT 0.2 CHECK (commission_rate >= 0 AND commission_rate <= 1)	—
status	text NOT NULL DEFAULT 'active' CHECK (status IN ('active', 'suspended'))	—
created_at	timestamptz NOT NULL DEFAULT now()	—
updated_at	timestamptz NOT NULL DEFAULT now()	—

public.commissions

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
affiliate_id	uuid NOT NULL	REFERENCES public.affiliates (id) ON DELETE CASCADE
referral_id	uuid	REFERENCES public.referrals (id) ON DELETE SET NULL
amount	numeric NOT NULL CHECK (amount >= 0)	—
currency	text NOT NULL DEFAULT 'ZAR'	—
status	text NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'approved', 'paid'))	—
source	text	—
created_at	timestamptz NOT NULL DEFAULT now()	—
updated_at	timestamptz NOT NULL DEFAULT now()	—

public.referrals

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
affiliate_id	uuid NOT NULL	REFERENCES public.affiliates (id) ON DELETE CASCADE
referred_user_id	uuid NOT NULL	REFERENCES auth.users (id) ON DELETE CASCADE
status	text NOT NULL DEFAULT 'signed_up' CHECK (status IN ('signed_up', 'subscribed', 'paid'))	—
created_at	timestamptz NOT NULL DEFAULT now()	—
updated_at	timestamptz NOT NULL DEFAULT now()	—

Drafts

public.draft_versions

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default gen_random_uuid()	—
user_id	uuid not null	references auth.users(id) on delete cascade
document_type	text not null check (document_type in ('invoice', 'payslip'))	—
draft_key	text not null default 'default'	—
form_data	jsonb not null default '{}'::jsonb	—
version	bigint not null default 0	—
created_at	timestamptz not null default now()	—

public.drafts

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default gen_random_uuid()	—
user_id	uuid not null	references auth.users(id) on delete cascade
document_type	text not null check (document_type in ('invoice', 'payslip'))	—
draft_key	text not null default 'default'	—
form_data	jsonb not null default '{}'::jsonb	—
version	bigint not null default 0	—
updated_at	timestamptz not null default now()	—
created_at	timestamptz not null default now()	—

Admin & audit

public.admin_broadcast_jobs

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default gen_random_uuid()	—
idempotency_key	text not null unique	—
sender_id	uuid not null	references public.profiles(id) on delete cascade
subject	text not null	—
content	text not null	—
recipient_rows	jsonb not null default '[]'::jsonb	—
total_recipients	integer not null default 0	—
notifications_inserted	integer not null default 0	—
messages_inserted	integer not null default 0	—
email_sent	integer not null default 0	—
email_skipped	integer not null default 0	—
email_failed	integer not null default 0	—
status	text not null default 'queued'	—
error	text null	—
created_at	timestamptz not null default now()	—
updated_at	timestamptz not null default now()	—
started_at	timestamptz null	—
finished_at	timestamptz null	—

public.admin_platform_messages

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid primary key default gen_random_uuid()	—
recipient_id	uuid not null	references public.profiles (id) on delete cascade
sender_id	uuid not null	references public.profiles (id) on delete cascade
subject	text not null default ''	—
content	text not null default ''	—
is_read	boolean not null default false	—
created_at	timestamptz not null default now()	—

public.admin_settings

COLUMN	TYPE	CONSTRAINTS / FK
key	text PRIMARY KEY	—
value	jsonb NOT NULL DEFAULT '{}'::jsonb	—
updated_by	uuid	—
updated_at	timestamptz NOT NULL DEFAULT now()	—

public.admin_system_state

COLUMN	TYPE	CONSTRAINTS / FK
id	boolean PRIMARY KEY DEFAULT true CHECK (id = true)	—
maintenance_mode	boolean NOT NULL DEFAULT false	—
last_reset_at	timestamptz	—
updated_by	uuid	—
updated_at	timestamptz NOT NULL DEFAULT now()	—
reset_reason	text	—

public.audit_logs

COLUMN	TYPE	CONSTRAINTS / FK
id	uuid PRIMARY KEY DEFAULT gen_random_uuid()	—
category	text NOT NULL DEFAULT 'settings'	—
action	text NOT NULL DEFAULT ''	—
description	text	—
before	jsonb	—
after	jsonb	—
actor_name	text	—
actor_email	text	—
actor_role	text	—
target_label	text	—
created_at	timestamptz NOT NULL DEFAULT now()	—
actor_id	uuid, ADD COLUMN IF NOT EXISTS entity text, ADD COLUMN IF NOT EXISTS metadata jsonb NOT NULL DEFAULT '{}':jsonb	—

Platform

public.api_rate_limit_buckets

COLUMN	TYPE	CONSTRAINTS / FK
bucket_key	text PRIMARY KEY	—
hit_count	integer NOT NULL DEFAULT 0	—
window_reset_at	timestamptz NOT NULL	—