

Lecture 2

Enhanced Entity-Relationship (EER) Modeling



5th Edition

Elmasri / Navathe

EERD Model

- EER stands for Enhanced ER or Extended ER
- EER Model Concepts
 - Includes all modeling concepts of basic ER
 - Additional concepts:
 - subclasses/superclasses
 - specialization/generalization
 - categories (UNION types)
 - attribute and relationship inheritance
- The additional EER concepts are used to model applications more completely and more accurately
 - EER includes some object-oriented concepts, such as inheritance


Subclasses and Superclasses (1)

- An entity type may have additional meaningful subgroupings of its entities
 - Example: EMPLOYEE may be further grouped into:
 - SECRETARY, ENGINEER, TECHNICIAN, ...
 - Based on the EMPLOYEE's Job
 - MANAGER
 - EMPLOYEEs who are managers
 - SALARIED_EMPLOYEE, HOURLY_EMPLOYEE
 - Based on the EMPLOYEE's method of pay
- EER diagrams extend ER diagrams to represent these additional subgroupings, called *subclasses* or *subtypes*

Subclasses and Superclasses

Figure 4.1

EER diagram notation to represent subclasses and specialization.



Subclasses and Superclasses (2)

- Each of these subgroupings is a subset of EMPLOYEE entities
- Each is called a subclass of EMPLOYEE
- EMPLOYEE is the superclass for each of these subclasses
- These are called superclass/subclass relationships:
 - EMPLOYEE/SECRETARY
 - EMPLOYEE/TECHNICIAN
 - EMPLOYEE/MANAGER
 - ...

Subclasses and Superclasses (3)

- These are also called IS-A relationships
 - SECRETARY IS-A EMPLOYEE, TECHNICIAN IS-A EMPLOYEE,
- Note: An entity that is member of a subclass represents the same real-world entity as some member of the superclass:
 - The subclass member is the same entity in a *distinct specific role*
 - An entity cannot exist in the database merely by being a member of a subclass; it must also be a member of the superclass
 - A member of the superclass can be optionally included as a member of any number of its subclasses


Subclasses and Superclasses (4)

- Examples:
 - A salaried employee who is also an engineer belongs to the two subclasses:
 - ENGINEER, and
 - SALARIED_EMPLOYEE
 - A salaried employee who is also an engineering manager belongs to the three subclasses:
 - MANAGER,
 - ENGINEER, and
 - SALARIED_EMPLOYEE
- It is not necessary that every entity in a superclass be a member of some subclass

Representing Specialization in EER Diagrams

Figure 4.4

EER diagram notation for an attribute-defined specialization on Job_type.



Attribute Inheritance in Superclass / Subclass Relationships

- An entity that is member of a subclass *inherits*
 - All attributes of the entity as a member of the superclass
 - All relationships of the entity as a member of the superclass
- Example:
 - In the previous slide, SECRETARY (as well as TECHNICIAN and ENGINEER) inherit the attributes Name, SSN, ..., from EMPLOYEE
 - Every SECRETARY entity will have values for the inherited attributes

Specialization (1)

- Specialization is the process of defining a set of subclasses of a superclass
- The set of subclasses is based upon some distinguishing characteristics of the entities in the superclass
 - Example: {SECRETARY, ENGINEER, TECHNICIAN} is a specialization of EMPLOYEE based upon *job type*.
 - May have several specializations of the same superclass


Specialization (2)

- Example: Another specialization of EMPLOYEE based on *method of pay* is {SALARIED_EMPLOYEE, HOURLY_EMPLOYEE}.
 - Superclass/subclass relationships and specialization can be diagrammatically represented in EER diagrams
 - Attributes of a subclass are called *specific* or *local* attributes.
 - For example, the attribute TypingSpeed of SECRETARY
 - The subclass can also participate in specific relationship types.
 - For example, a relationship BELONGS_TO of HOURLY_EMPLOYEE

Specialization (3)

Figure 4.1

EER diagram notation to represent subclasses and specialization.



Generalization

- Generalization is the reverse of the specialization process
- Several classes with common features are generalized into a superclass;
 - original classes become its subclasses
- Example: CAR, TRUCK generalized into VEHICLE;
 - both CAR, TRUCK become subclasses of the superclass VEHICLE.
 - We can view {CAR, TRUCK} as a specialization of VEHICLE
 - Alternatively, we can view VEHICLE as a generalization of CAR and TRUCK

Generalization (2)




Figure 4.3

Generalization. (a) Two entity types, CAR and TRUCK.
(b) Generalizing CAR and TRUCK into the superclass VEHICLE.

Generalization and Specialization (1)

- Diagrammatic notation are sometimes used to distinguish between generalization and specialization
 - Arrow pointing to the generalized superclass represents a generalization
 - Arrows pointing to the specialized subclasses represent a specialization
 - We *do not use* this notation because it is often subjective as to which process is more appropriate for a particular situation
 - We advocate not drawing any arrows

Generalization and Specialization (2)

- Data Modeling with Specialization and Generalization
 - A superclass or subclass represents a collection (or set or grouping) of entities
 - It also represents a particular *type of entity*
 - Shown in rectangles in EER diagrams (as are entity types)
 - We can call all entity types (and their corresponding collections) **classes**, whether they are entity types, superclasses, or subclasses

Constraints on Specialization and Generalization (1)

- If we can determine exactly those entities that will become members of each subclass by a condition, the subclasses are called predicate-defined (or condition-defined) subclasses
 - Condition is a constraint that determines subclass members
 - Display a predicate-defined subclass by writing the predicate condition next to the line attaching the subclass to its superclass


Constraints on Specialization and Generalization (2)

- If all subclasses in a specialization have membership condition on same attribute of the superclass, specialization is called an attribute-defined specialization
 - Attribute is called the defining attribute of the specialization
 - Example: JobType is the defining attribute of the specialization {SECRETARY, TECHNICIAN, ENGINEER} of EMPLOYEE
- If no condition determines membership, the subclass is called user-defined
 - Membership in a subclass is determined by the database users by applying an operation to add an entity to the subclass
 - Membership in the subclass is specified individually for each entity in the superclass by the user

Displaying an attribute-defined specialization in EER diagrams

Figure 4.4

EER diagram notation for an attribute-defined specialization on Job_type.



Constraints on Specialization and Generalization (3)

- Two basic constraints can apply to a specialization/generalization:
 - Disjointness Constraint:
 - Completeness Constraint:

Constraints on Specialization and Generalization (4)

- Disjointness Constraint:
 - Specifies that the subclasses of the specialization must be *disjoint*:
 - an entity can be a member of at most one of the subclasses of the specialization
 - Specified by **d** in EER diagram
 - If not disjoint, specialization is *overlapping*:
 - that is the same entity may be a member of more than one subclass of the specialization
 - Specified by **o** in EER diagram

Constraints on Specialization and Generalization (5)

- **Completeness Constraint:**
 - *Total* specifies that every entity in the superclass must be a member of some subclass in the specialization/generalization
 - Shown in EER diagrams by a **double line**
 - *Partial* allows an entity not to belong to any of the subclasses
 - Shown in EER diagrams by a single line


Constraints on Specialization and Generalization (6)

- Hence, we have four types of specialization/generalization:
 - Disjoint, total
 - Disjoint, partial
 - Overlapping, total
 - Overlapping, partial
- Note: Generalization usually is total because the superclass is derived from the subclasses.

Example of disjoint partial Specialization

Figure 4.4

EER diagram notation for an attribute-defined specialization on Job_type.



Example of overlapping total Specialization




Figure 4.5
EER diagram notation
for an overlapping
(nondisjoint)
specialization.

Specialization/Generalization Hierarchies, Lattices & Shared Subclasses (1)

- A subclass may itself have further subclasses specified on it
 - forms a hierarchy or a lattice
- **Hierarchy** has a constraint that every subclass has only one superclass (called **single inheritance**); this is basically a **tree structure**
- In a **lattice**, a subclass can be subclass of more than one superclass (called **multiple inheritance**)

Shared Subclass “Engineering_Manager”




Figure 4.6

A specialization lattice with shared subclass ENGINEERING_MANAGER.

Specialization/Generalization Hierarchies, Lattices & Shared Subclasses (2)

- In a lattice or hierarchy, a subclass inherits attributes not only of its direct superclass, but also of all its predecessor superclasses
- A subclass with more than one superclass is called a shared subclass (multiple inheritance)
- Can have:
 - *specialization* hierarchies or lattices, or
 - *generalization* hierarchies or lattices,
 - depending on how they were *derived*
- We just use *specialization* (to stand for the end result of either specialization or generalization)

Specialization/Generalization Hierarchies, Lattices & Shared Subclasses (3)

- In *specialization*, start with an entity type and then define subclasses of the entity type by successive specialization
 - called a *top down* conceptual refinement process
- In *generalization*, start with many entity types and generalize those that have common properties
 - Called a *bottom up* conceptual synthesis process
- In practice, a *combination of both processes* is usually employed

Specialization / Generalization Lattice Example (UNIVERSITY)




Figure 4.7

A specialization lattice with multiple inheritance for a UNIVERSITY database.

Alternative diagrammatic notations

- ER/EER diagrams are a specific notation for displaying the concepts of the model diagrammatically
- DB design tools use many alternative notations for the same or similar concepts
- One popular alternative notation uses *UML class diagrams*
- see next slides for UML class diagrams and other alternative notations

UML Example for Displaying Specialization / Generalization




Figure 4.10

A UML class diagram corresponding to the EER diagram in Figure 4.7, illustrating UML notation for specialization/generalization.

Alternative Diagrammatic Notations




Figure A.1

Alternative notations. (a) Symbols for entity type/class, attribute, and relationship. (b) Displaying attributes. (c) Displaying cardinality ratios. (d) Various (min, max) notations. (e) Notations for displaying specialization/generalization.

Mapping EER Model Constructs to Relations

■ Step8: Options for Mapping Specialization or Generalization.

Convert each specialization with m subclasses $\{S_1, S_2, \dots, S_m\}$ and generalized superclass C , where the attributes of C are $\{k, a_1, \dots, a_n\}$ and k is the (primary) key, into relational schemas using one of the four following options:


Option 8A: Multiple relations-Superclass and subclasses.

Create a relation L for C with attributes $\text{Attrs}(L) = \{k, a_1, \dots, a_n\}$ and $\text{PK}(L) = k$. Create a relation L_i for each subclass S_i , $1 < i < m$, with the attributes $\text{Attrs}(L_i) = \{k\} \cup \{\text{attributes of } S_i\}$ and $\text{PK}(L_i) = k$. This option works **for any specialization** (total or partial, disjoint or over-lapping).

Option 8B: Multiple relations-Subclass relations only

Create a relation L_i for each subclass S_i , $1 < i < m$, with the attributes $\text{Attr}(L_i) = \{\text{attributes of } S_i\} \cup \{k, a_1, \dots, a_n\}$ and $\text{PK}(L_i) = k$. This option only works for a specialization whose subclasses are **total** (every entity in the superclass must belong to (at least) one of the subclasses).

EER diagram notation for an attribute-defined specialization on JobType.



Options for Mapping Specialization or Generalization.

(a) Mapping the EER schema using option 8A.

(a) EMPLOYEE

<u>SSN</u>	FName	MInit	LName	BirthDate	Address	JobType
------------	-------	-------	-------	-----------	---------	---------

SECRETARY

<u>SSN</u>	TypingSpeed
------------	-------------


TECHNICIAN

<u>SSN</u>	TGrade
------------	--------

ENGINEER

<u>SSN</u>	EngType
------------	---------

Generalizing CAR and TRUCK into the superclass VEHICLE.



Options for Mapping Specialization or Generalization.

(b) Mapping the EER schema using option 8B.

(b) CAR

<u>VehicleId</u>	LicensePlateNo	Price	MaxSpeed	NoOfPassengers
------------------	----------------	-------	----------	----------------

TRUCK

<u>VehicleId</u>	LicensePlateNo	Price	NoOfAxles	
------------------	----------------	-------	-----------	--

Mapping EER Model Constructs to Relations


Option 8C: Single relation with one type attribute.

Create a single relation L with attributes $\text{Attrs}(L) = \{k, a_1, \dots, a_n\} \cup \{\text{attributes of } S_1\} \cup \dots \cup \{\text{attributes of } S_m\} \cup \{t\}$ and $\text{PK}(L) = k$. The attribute t is called a type (or **discriminating**) attribute that indicates the subclass to which each tuple belongs

Option 8D: Single relation with multiple type attributes.

Create a single relation schema L with attributes $\text{Attrs}(L) = \{k, a_1, \dots, a_n\} \cup \{\text{attributes of } S_1\} \cup \dots \cup \{\text{attributes of } S_m\} \cup \{t_1, t_2, \dots, t_m\}$ and $\text{PK}(L) = k$. Each t_i , $1 < i < m$, is a Boolean type attribute indicating whether a tuple belongs to the subclass S_i .

EER diagram notation for an attribute-defined specialization on JobType.




Options for Mapping Specialization or Generalization.

(c) Mapping the EER schema using option 8C.

(c) EMPLOYEE

<u>SSN</u>	FName	MInit	LName	BirthDate	Address	JobType	TypingSpeed	TGrade	
------------	-------	-------	-------	-----------	---------	---------	-------------	--------	--

EER diagram notation
for an overlapping
(nondisjoint)
specialization.



Options for Mapping Specialization or Generalization.

(d) Mapping using option 8D with Boolean type fields Mflag and Pflag.

(d) PART

<u>PartNo</u>	Description	MFlag	DrawingNo	ManufactureDate	BatchNo	PFlag	SupplierName	ListPrice
---------------	-------------	-------	-----------	-----------------	---------	-------	--------------	-----------

Mapping EER Model Constructs to Relations

- **Mapping of Shared Subclasses (Multiple Inheritance)**

A shared subclass, such as STUDENT_ASSISTANT, is a subclass of several classes, indicating multiple inheritance. These classes must all have the same key attribute; otherwise, the shared subclass would be modeled as a category.

We can apply any of the options discussed in Step 8 to a shared subclass, subject to the restriction discussed in Step 8 of the mapping algorithm. Below both 8C and 8D are used for the shared class STUDENT_ASSISTANT.