Globally Optimal, Certified Quantum Circuit Timing via Geometric Programming: Convex Duality, Nonunitary Error Bounds, and Scalable Hardware Evaluation

Youssef Ahmed Ramadan
Department of Artificial Intelligence Engineering, School of Engineering
University of Science and Technology at Zewail City
Giza, Egypt
Email: p-youssef.ramdan@zewailcity.edu.eg

***Abstract*— Quantum circuit compilation requires navigating a fundamental physical tension between gate execution speed, control drive power, decoherence exposure, and circuit makespan. We present an exact, unified mathematical framework for continuous gate duration allocation on fixed circuit dependency graphs formulated as a Geometric Program (GP) and an equivalent ordinary convex program. The unconstrained latency problem admits a specialized path-flow dual algorithm that computes an inspectable optimum bracket using an $O(m + r)$ longest-path DAG oracle. We prove rigorous operational certificates bounding diamond-norm channel distance and output fidelity under nonunitary Markovian Lindblad relaxation, dephasing, and coherent generator mismatch. For discrete pulse libraries, a mixed-integer linear program (MILP) optimizes Watrous semidefinite programming Choi bounds, bridged to the continuous optimum via an explicit residual transfer inequality. To overcome the exponential superoperator simulation barrier, we extend the framework to exact Pauli-observable constrained scheduling on Clifford circuits via symplectic adjoint tracking. We evaluate the framework across 144 configurations calibrated with IBM's 133-qubit Heron processor parameters (*ibm_torino*), spanning 4 to 128 qubits, complemented by 144 full physical Lindblad channels on 2–3 qubits. The observable-constrained convex engine solves in a median of 69.9 ms across feasible configurations (reaching 32 qubits), while an analytic pre-filter certifies unachievable operational targets across deep 64- and 128-qubit circuits in $O(\mathrm{nnz}(H))$ time (median 2.44 ms at 128 qubits, maximum 5.57 ms overall) without invoking interior-point solvers. Geometric log-grid quantization preserves certified observable expectations with zero target violations by construction. Unconstrained duration allocation delivers significant fidelity gains (+3.97 and +15.34 percentage points) with latency trade-offs, while strict matched-deadline scheduling demonstrates that critical-path latency dominates the error budget (−0.009 to +0.026 pp gains). Independent numerical audits confirm mathematical agreement with dense density-matrix evolution to machine precision ($< 10^{-14}$) and forward Pauli-frame Monte Carlo sampling (16,384 shots) within simultaneous Hoeffding confidence bounds.

***Index Terms*— Quantum compilation, geometric programming, convex optimization, gate scheduling, Markovian noise, pulse libraries, Pauli tracking, Heron architecture.

I. Introduction

QUANTUM compilation connects abstract unitary circuits to executable physical pulses and schedules. Gate count, circuit depth, physical latency, and noisy-state fidelity are related but fundamentally distinct quantities. A continuous optimizer cannot infer a physically admissible schedule from aggregate gate counts alone, and minimizing circuit makespan does not monotonically raise fidelity when faster operations demand stronger drives that induce leakage or non-adiabatic errors. This motivates a compilation framework that explicitly models physical control tradeoffs, provides globally optimal duration allocation, and establishes certified bounds on operational noise.

The mathematical structure of time-cost tradeoffs on directed acyclic dependency graphs (DAGs) traces back to the foundational network-flow duality of Kelley [1] and Fulkerson [2]. Geometric programming (GP) provides an established positive-variable optimization language with an exact convex transformation under logarithmic change of variables [3]. Its historical application to digital CMOS circuit sizing and timing closure revolutionized classical electronic design automation (EDA) [4]. In quantum computing, when gate durations are fixed, makespan minimization reduces to a longest-path computation on a DAG. However, physical quantum devices operate under a different decision space: continuous gate durations and discrete pulse implementations that preserve target local unitaries while trading off drive strength, environmental decoherence, and circuit latency.

In this work, we introduce a unified, certified quantum

gate scheduling framework operating across continuous duration allocation, discrete pulse library selection, and multi-qubit Pauli-observable constraints. We make seven primary contributions, summarized in Section XI and evaluated across Sections VIII–X:

1) **Innovation 1 — Exact Convex Duration Allocation:** We prove that continuous duration allocation on a fixed circuit DAG is an exact GP and an ordinary convex program with a uniquely determined optimal duration vector under positive objective weights (Section III). **Quantified impact:** guarantees machine-precision agreement $|\Delta_{\text{form}}| \leq 1.69 \times 10^{-9}$ with direct convex programming and solves in 69.9 ms median latency.
2) **Innovation 2 — Inspectable Path-Flow Duality Certification:** We derive a specialized path-flow dual algorithm that solves the continuous allocation problem with an $O(m + r)$ longest-path DAG oracle (Section IV). **Quantified impact:** computes an independent mathematical lower bound certifying duality gaps within 0.01% of the true global infimum ($\epsilon_{\text{gap}} \leq 1.09 \times 10^{-4}$).
3) **Innovation 3 — Nonunitary Operational Error Certificates:** We establish deterministic lower bounds on output state fidelity ($F_{\text{pur}} \geq e^{-R}$) and upper bounds on completely bounded diamond distance ($\frac{1}{2}\|\mathcal{N} - \mathcal{U}\|_\diamond \leq 1 - e^{-R}$) under nonunitary Lindblad relaxation, dephasing, and coherent generator mismatch (Section V). **Quantified impact:** validated against dense Runge–Kutta numerical integration to $< 10^{-14}$ error.
4) **Innovation 4 — Discrete Pulse Library Optimization and Bound Transfer:** For characterized hardware pulse libraries, we formulate a MILP minimizing Watrous semidefinite programming (SDP) Choi bounds and prove a conservative residual transfer inequality (Section VI). **Quantified impact:** validates continuous GP as a rigorous lower bound for discrete pulse implementations with mean transfer gap 0.418.
5) **Innovation 5 — Scalable Stabilizer Tracking via Symplectic Adjoint Tracking:** We develop an exact Pauli-observable sensitivity model using Clifford symplectic tracking in the Heisenberg picture, mapping stabilizer generator expectations $\langle S_k \rangle \geq \tau_k^{\text{target}}$ to exact posynomial constraints with zero approximation error (Section VII). **Quantified impact:** breaks the exponential $4^N \times 4^N$ superoperator simulation wall, scaling up to 128 qubits in under 15 MB of RAM.
6) **Innovation 6 — Sub-Millisecond $O(\text{nnz}(H))$ Infeasibility Pre-Screening and Safe Quantization:** We introduce a closed-form hazard pre-filter that certifies physically unachievable targets before invoking numerical solvers, coupled with exposure-amplified log-grid rounding ($q = 1.02$) (Sections VII-B, VIII). **Quantified impact:** screens 117 infeasible configurations in median 0.70 ms (2.44 ms at 128Q; max 5.57 ms) and guarantees 100% target satisfaction with zero violation by construction.
7) **Innovation 7 — Multi-Objective Pareto Navigation and ZNE Co-Design:** We extend the continuous GP formulation to multi-objective exploration, tracing the Pareto frontier between makespan compression and control drive effort, while providing an exact physical knob for Zero-Noise Extrapolation (Sections IX-D, X-E). **Quantified impact:** suppresses microwave drive heating by 66.2% with only 3.1% latency penalty, and yields up to +15.34 pp fidelity gains over baseline heuristics.

The remainder of the paper proceeds as follows. Section II reviews related work in duration-aware scheduling and classical network-flow duality. Section III establishes the continuous duration model and proves exact convexity. Section IV develops the path-flow dual algorithm and optimality certificates. Section V derives the nonunitary operational error bounds. Section VI formalizes discrete pulse library optimization via MILP. Section VII develops scalable Pauli-observable tracking and algebraic prescreening. Section VIII presents the comprehensive evaluation on IBM Heron calibration parameters. Section IX details compiler integration, multi-objective Pareto navigation, and production transpiler protocols. Section X provides a critical assessment of novelty, empirical boundaries, and failure modes. Section XI concludes with a breakthrough synthesis.

II. Related Work and Scientific Context

A. Duration-Aware Quantum Scheduling

Lussi, de Santiago, and Duzzioni recently introduced duration-aware quantum scheduling by assigning fast pulse implementations to critical-path operations and robust, longer implementations to available off-critical slack [5]. Our work builds upon this insight by formulating continuous duration allocation as an exact convex program, deriving analytical primal-dual optimality certificates, and incorporating nonunitary open-system channel bounds. In quantum compiler systems, noise-adaptive mapping and crosstalk-aware scheduling have been investigated by Murali et al. [12], [13], while pulse-efficient transpilation was developed by Earnest et al. [14].

B. Convex Scheduling and Classical Foundations

Convex project time-cost optimization on DAGs originates in the classic network-flow duality of Kelley [1] and Fulkerson [2], subsequently generalized to convex cost dual network flow by Ahuja et al. [6]. Geometric programming supplies an exact convex representation when all cost terms are positive monomials or posynomials [3]. For the proposed inverse-duration-plus-duration costs, the original variables also yield an ordinary convex formulation, establishing that efficiency stems from convexity rather than logarithmic change of variables alone.

C. Noise Modeling and Stabilizer Observables

The no-jump branch of a quantum-trajectory representation underlies the channel certificate [7]. Conditional-gradient methods provide established optimization-gap machinery [8]. Compositional robustness for quantum programs has been formalized by Hung et al. [10], while robust quantum control via sequential convex programming was investigated by Kosut et al. [11]. Sparse Pauli-Lindblad noise characterization has been established by van den Berg et al. [15]. Recently, P. Aigner et al. [16] developed analytical and compressed simulation techniques for noisy stabilizer circuits. Our framework leverages duration-dependent noise sensitivity to convert analytical stabilizer tracking into an *exact posynomial constraint*, enabling convex interior-point optimization for compiler scheduling.

III. Continuous Duration Model and Exact Convexity

Let a native circuit contain m unitary gates and a dependency DAG $\mathcal{D}$ with r edges. Per-qubit order is fixed by the logical circuit; concurrent operations on overlapping qubit supports are forbidden. Gate i has continuous duration $\tau_i \in [\ell_i, u_i]$, with $0 < \ell_i \le u_i$, generated by a Hermitian Hamiltonian $H_i = K_i/\tau_i$ such that

$$e^{-\mathrm{i}K_i} = e^{\mathrm{i}\phi_i} U_i, \quad K_i = \theta_i P_i/2, \tag{1}$$

where P_i denotes the generating Hamiltonian. On superconducting transmon processors such as IBM Heron, native operations comprise single-qubit rotations (SX, X, and virtual RZ) and two-qubit Controlled-Z (CZ) entangling interactions; entangling gates like RXX decompose into native CZ and single-qubit rotations. Because K_i is fixed, the ideal local unitary is duration-independent.

Define the integrated squared control effort $E(\tau) = \sum_i \kappa_i^2/\tau_i$, where $\kappa_i = \|K_i\|_2$. For a schedule with makespan M, the integrated noise hazard satisfies

$$\Lambda \le R(\tau, M) = bM + \sum_i \left(\frac{a_i}{\tau_i} + \gamma_i \tau_i \right), \tag{2}$$

where $b, a_i, \gamma_i > 0$. The inverse-plus-linear term $a_i/\tau_i + \gamma_i\tau_i$ represents a stylized phenomenological noise model capturing the fundamental engineering tension between drive-power-induced errors (leakage, non-adiabaticity, and amplifier distortion at small τ_i) and environmental decoherence exposure (T_1, T_2 relaxation and dephasing at large τ_i).

The objective balances noise hazard, makespan, and control effort:

$$J(\tau, M) = w_R \frac{R}{R_0} + w_M \frac{M}{M_0} + w_E \frac{E}{E_0}, \tag{3}$$

subject to precedence constraints $f_i + \tau_j \le f_j$ for $(i \to j) \in \mathcal{D}$, completion constraints $\tau_i \le f_i \le M$, and duration bounds $\ell_i \le \tau_i \le u_i$.

Theorem 1 (Exactness and Unique Optimal Durations)**.** *Assuming positive objective weights ($w_R > 0$ with $a_i > 0$, or $w_E > 0$), the duration allocation problem* (3) *is an exact geometric program and an ordinary convex program. The optimal duration vector τ^* is uniquely determined.*

Proof. Under logarithmic variable substitutions $\tau_i = e^{x_i}$, $f_i = e^{y_i}$, $M = e^z$, all inverse-duration terms $a_i e^{-x_i}$ and linear terms $\gamma_i e^{x_i}$ become convex exponentials, and precedence constraints $(e^{y_i} + e^{x_j})/e^{y_j} \le 1$ become convex log-sum-exp constraints. In original variables τ_i, each $1/\tau_i$ term is strictly convex on $\tau_i > 0$ whenever $a_i > 0$, while makespan $M(\tau) = \max_{p\in\mathcal{P}} \sum_{i\in p} \tau_i$ is a convex pointwise maximum of linear functions. The sum of strictly convex terms and a convex function is strictly convex on the compact box $\prod_i [\ell_i, u_i]$, establishing uniqueness of τ^*. □

Proposition 1 (Rectangular Box Robustness)**.** *If each coefficient in* (2) *belongs independently to a declared interval $[a_i^{\min}, a_i^{\max}]$, its maximum over that rectangle is attained at the upper endpoints. Replacing coefficients by those endpoints yields an exact robust GP.*

Proof. Each coefficient multiplies a nonnegative term, so R is coordinatewise monotone. The upper endpoint vector belongs to the uncertainty rectangle and attains its maximum for every feasible schedule. □

Proposition 2 (Quantization Rounding Certificate)**.** *If a rounded vector τ' remains within $[\ell, u]$, then*

$$|R(\tau') - R(\tau)| \le \sum_i \left(\frac{a_i}{\ell_i^2} + \gamma_i + b \right) |\tau_i' - \tau_i|. \tag{4}$$

Proof. Every path sum changes by at most $\sum_i |\tau_i' - \tau_i|$, bounding makespan change. The derivative magnitude of $a_i/\tau_i + \gamma_i\tau_i$ on $[\ell_i, u_i]$ is bounded by $a_i/\ell_i^2 + \gamma_i$. Summing yields the result. □

IV. Path-Flow Dual and Algorithm

Let $\mathcal{P}$ denote the set of all root-to-sink path incidence vectors in $\mathcal{D}$. Makespan is $M(\tau) = \max_{p\in\mathcal{P}} p^\top \tau$. Combining objective coefficients into $A_i, C_i > 0$ and $B > 0$, the unconstrained deadline problem becomes

$$\min_{\ell \le \tau \le u} \sum_i \left(\frac{A_i}{\tau_i} + C_i \tau_i \right) + B \max_{p\in\mathcal{P}} p^\top \tau. \tag{5}$$

Theorem 2 (Path-Flow Dual Bracket)**.** *For any dual flow vector $\rho \in B\,\mathrm{conv}(\mathcal{P})$, define the dual objective and duration response:*

$$D(\rho) = \sum_i \min_{\ell_i \le t \le u_i} \left[\frac{A_i}{t} + (C_i + \rho_i) t \right], \tag{6}$$

$$\tau_i(\rho) = \mathrm{clip}\left(\sqrt{\frac{A_i}{C_i + \rho_i}}, \ell_i, u_i \right). \tag{7}$$

Then strong duality holds: $\max_\rho D(\rho) = \min_\tau J(\tau)$. Moreover, every dual-feasible ρ provides an inspectable optimality gap:

$$0 \le J(\tau(\rho)) - J^* \le BM(\tau(\rho)) - \rho^\top \tau(\rho). \tag{8}$$

Proof. The function $L(\tau,\rho) = \sum_i (A_i/\tau_i + C_i\tau_i) + \rho^\top\tau$ is continuous, convex in τ, and affine in ρ over compact convex domains. By Sion's minimax theorem, $\min_\tau \max_\rho L(\tau,\rho) = \max_\rho \min_\tau L(\tau,\rho)$. Separable minimization over each gate coordinate yields $\tau_i(\rho)$. Subtracting $D(\rho)$ from the primal value cancels all non-path terms, yielding the exact bracket. □

Because $\nabla D(\rho) = \tau(\rho)$, a longest-path oracle on the DAG solves the linear subproblem in $O(m+r)$ time. A conditional gradient (Frank–Wolfe) update $\rho \leftarrow (1-\alpha)\rho + \alpha Bp$ with bisection line search guarantees dual-feasible monotonic ascent.

V. Nonunitary Operational Certificates

We extend operational guarantees to open quantum systems governed by the Lindblad master equation:

$$\dot\rho = -\mathrm{i}[H(t),\rho] + \sum_\mu \left(L_\mu \rho L_\mu^\dagger - \tfrac{1}{2}\{L_\mu^\dagger L_\mu, \rho\}\right). \quad (9)$$

Let $\Delta H(t)$ denote coherent Hamiltonian mismatch, $N = \int \sum_\mu \|L_\mu(t)\|_\infty^2 dt$, and $C = \int \|\Delta H(t)\|_\infty dt$.

Theorem 3 (Unital Operational Certificate)**.** *Suppose coherent Hamiltonian mismatch vanishes ($\Delta H(t) = 0$, so $C = 0$) and Lindblad jumps are $L_\mu(t) = \sqrt{r_\mu(t)}V_\mu(t)$ with $V_\mu^\dagger V_\mu = I$, corresponding to unital channels (e.g., pure dephasing with Z, bit-flip with X, and isotropic depolarizing noise). If $\Lambda = \int \sum_\mu r_\mu(t)\,dt \le R$, then for implemented channel $\mathcal{N}$ and ideal channel $\mathcal{U}$:*

$$F_{\mathrm{pur}} \ge e^{-R}, \quad (10)$$

$$\tfrac{1}{2}\|\mathcal{N}-\mathcal{U}\|_\diamond \le 1 - e^{-R}. \quad (11)$$

Proof. Since $\Delta H(t) = 0$, the no-jump effective Hamiltonian is $H_{\mathrm{eff}} = H - \mathrm{i}h(t)I/2$ with $h = \sum_\mu r_\mu$. Since $V_\mu^\dagger V_\mu = I$, the jump dissipation operator satisfies $\sum_\mu L_\mu^\dagger L_\mu = h(t)I$, so its propagator is $e^{-\Lambda/2}U$, irrespective of jump-control commutation. Normalization gives a CPTP channel $\mathcal{Q}$ with $\mathcal{N} = e^{-\Lambda}\mathcal{U} + (1-e^{-\Lambda})\mathcal{Q}$. Positivity gives overlap at least $e^{-\Lambda}$. Monotonicity and trace-norm duality establish the bounds. □

Proposition 3 (General Markovian Operational Certificates)**.** *For general Markovian dynamics including nonunital amplitude damping (T_1 relaxation via $L = \sigma^-$, where $(\sigma^-)^\dagger\sigma^- \ne I$), with integrable bounds N and C, the implemented channel $\mathcal{N}$ and ideal channel $\mathcal{U}$ satisfy:*

$$\tfrac{1}{2}\|\mathcal{N}-\mathcal{U}\|_\diamond \le \min(1, N + C), \quad (12)$$

$$F_{\mathrm{pur}} \ge \max\left\{(1-N-C)_+, \left(1-\tfrac{N}{2}-C\right)_+^2\right\}. \quad (13)$$

Proof. Variation-of-constants writes $\mathcal{N}-\mathcal{U}$ as an integral of generator differences between CPTP propagators. In the interaction picture, $\dot K_0 = (-\mathrm{i}\Delta\widetilde{H} - \widetilde{\Gamma}/2)K_0$ with $\Gamma = \sum_\mu L_\mu^\dagger L_\mu \ge 0$. Since $\|K_0\|_\infty \le 1$, integration yields $\|K_0 - I\| \le C + N/2$. The overlap against any normalized purification is at least $(1 - C - N/2)_+$. Squaring gives the reduced-state floor. □

Our physical spin model uses $K_i = \theta_i P_i/2$. Always-on memory jumps are $\sqrt{1/T_{1q}}\sigma_q^-$ and $\sqrt{1/(2T_{\phi q})}Z_q$, while gate-dependent drive jumps are $\sqrt{\eta_i}K_i/\tau_i$ and $\sqrt{\gamma_i}P_i$. While Theorem 3 provides an exponential floor for unital jump generators, Proposition 3 rigorously bounds general nonunital T_1 relaxation.

VI. Discrete Pulse Libraries and Certificate Transfer

When hardware restricts controls to a discrete pulse library $\{d_{ik}\}_{k=1}^K \subset [\ell_i, u_i]$, duration selection is governed by binary indicators $x_{ik} \in \{0,1\}$ with $\sum_k x_{ik} = 1$ and $\tau_i = \sum_k d_{ik}x_{ik}$.

For each pulse implementation $\mathcal{E}_{ik}$ and target $\mathcal{U}_i$, let J_{ik} be the unnormalized Choi matrix of their difference. Watrous's SDP [9] yields the dual upper bound $\delta_{ik} = \min\{1, \frac{1}{2}\|\operatorname{Tr}_{\mathrm{out}}|J_{ik}|\|_\infty\}$. Summing over disjoint gates with memory dissipation rate b_i gives compositional channel error $Q(x,M) = bM + \sum_{ik}(\delta_{ik} - b_i d_{ik})x_{ik}$.

Proposition 4 (GP-to-Library Transfer Bound)**.** *Let D_{GP} be a continuous GP dual lower bound. Define residual errors $e_{ik} = (\delta_{ik} - b_i d_{ik} - a_i/d_{ik} - \gamma_i d_{ik})/R_0$. The discrete characterized optimum satisfies:*

$$J^*_{\mathrm{char}} \ge \max\left\{0, D_{\mathrm{GP}} + \sum_i \min_k e_{ik}\right\}. \quad (14)$$

Proof. Every library policy lies in the GP duration box. At such a policy, the characterized objective equals the GP objective plus $\sum_i e_{i,k(i)}$. Weak duality lower-bounds the former by D_{GP}, and each residual is bounded by its gatewise minimum. Minimizing preserves the inequality. □

VII. Scalable Observable-Constrained Scheduling

While dense superoperator simulation is limited to few qubits ($4^n \times 4^n$ dimensionality), quantum algorithms, stabilizer codes, and benchmarking sequences frequently target specific Pauli observables or stabilizer generators.

A. Clifford Adjoint Tracking on Stabilizer Circuits

Consider a Clifford circuit with stabilizer generators $\{S_k\}_{k=1}^n$. Under backward Heisenberg evolution through the circuit DAG, each generator transforms via symplectic updates. Restricting circuit gates to the Clifford group guarantees that each Pauli operator propagates deterministically to a Pauli operator at each time slice. At gate j with support $\mathrm{supp}(j)$, local Pauli errors propagate to the output. The sensitivity of observable S_k to noise at gate j is given by the average anticommutation rate over non-identity local Paulis $\mathcal{P}_j^*$:

$$h_{kj} = \frac{1}{|\mathcal{P}_j^*|}\sum_{P\in\mathcal{P}_j^*}[S_k(t_j) \text{ anticommutes with } P], \quad (15)$$

where $|\mathcal{P}_j^*| = 4^{|\operatorname{supp}(j)|} - 1$. Consider continuous-time open quantum system dynamics where each gate j is subjected to a continuous-time isotropic Pauli Markov generator:

$$\mathcal{L}_j(\rho) = \frac{\lambda_j(t)}{|\mathcal{P}_j^*|} \sum_{P \in \mathcal{P}_j^*} (P\rho P - \rho), \tag{16}$$

distributing jump rates uniformly over all non-identity local Paulis $\mathcal{P}_j^*$. The quantity $\Lambda_j(\tau_j) = a_j/\tau_j + \gamma_j \tau_j$ represents the **integrated jump intensity** $\Lambda_j = \int_0^{\tau_j} \lambda_j(t)\, dt$, rather than an ordinary discrete gate error probability. In the Heisenberg picture, the adjoint generator acts on Pauli observable S_k as $\mathcal{L}_j^\dagger(S_k) = \frac{\lambda_j(t)}{|\mathcal{P}_j^*|} \sum_{P \in \mathcal{P}_j^*} (PS_kP - S_k) = -2\lambda_j(t) h_{kj} S_k$, yielding $\dot{S}_k = -2\lambda_j(t) h_{kj} S_k$. Integrating over the gate execution interval yields the *exact* scalar expectation formula:

$$\langle S_k \rangle = \exp\left(-2 \sum_j h_{kj} \Lambda_j(\tau_j) \right). \tag{17}$$

We emphasize that this exact exponential form strictly requires a continuous-time isotropic Pauli Markov process. For general anisotropic noise, Pauli twirling produces direction-dependent error rates (p_X, p_Y, p_Z), which necessitate component-wise anticommutation decomposition rather than a single scalar intensity [16]. Imposing the operational reliability constraint $\langle S_k \rangle \geq \tau_k^{\text{target}}$ yields:

$$\sum_j h_{kj} \left(\frac{a_j}{\tau_j} + \gamma_j \tau_j \right) \leq -\frac{1}{2} \ln \tau_k^{\text{target}} \equiv \beta_k. \tag{18}$$

Because $h_{kj}, a_j, \gamma_j \geq 0$, (18) is an **exact posynomial constraint**!

B. Sub-Millisecond Analytic Infeasibility Filter

Before invoking any numerical solver, the gatewise unconstrained noise minimum is evaluated: $\tau_j^{\text{unc}} = \text{clip}(\sqrt{a_j/\gamma_j}, \ell_j, u_j)$ in $O(m)$ time. Given the precomputed sensitivity matrix $H \in \mathbb{R}^{K \times m}$, evaluating the minimum achievable noise vector $\mu = H(a/\tau^{\text{unc}} + \gamma\tau^{\text{unc}})$ requires a sparse matrix-vector multiplication taking $O(\text{nnz}(H))$ operations (at most $O(Km)$ across K target observables). If $\max_k(\mu_k - \beta_k) > 0$, the operational target is certified physically infeasible in $O(\text{nnz}(H))$ time (with a median screening latency of 0.70 ms across all configurations, 2.44 ms at 128 qubits, and a recorded maximum of 5.57 ms), completely preventing costly solver timeouts.

C. Certified Log-Grid Geometric Quantization

Hardware pulse controllers enforce discrete timing increments. For a geometric ratio $q > 1$ (e.g., $q = 1.02$), available durations form a grid $d_j^{(m)} = \ell_j q^m \leq u_j$. To guarantee that discrete quantization never violates the operational threshold, we solve the continuous posynomial program using an amplified exposure factor $\tilde{\gamma}_j = q\gamma_j$. Given continuous solution τ^*, discrete allocations are obtained by upward rounding with upper-bound box clamping:

$$d_j^* = \min\left(u_j, \ell_j q^{\lceil \log_q(\tau_j^*/\ell_j) \rceil} \right). \tag{19}$$

Because $d_j^* \in [\tau_j^*, q\tau_j^*]$, the inverse drive term satisfies $a_j/d_j^* \leq a_j/\tau_j^*$, while decoherence satisfies $\gamma_j d_j^* \leq q\gamma_j\tau_j^* = \tilde{\gamma}_j \tau_j^*$. Consequently,

$$\sum_j h_{kj} \left(\frac{a_j}{d_j^*} + \gamma_j d_j^* \right) \leq \sum_j h_{kj} \left(\frac{a_j}{\tau_j^*} + \tilde{\gamma}_j \tau_j^* \right) \leq \beta_k, \tag{20}$$

guaranteeing that the quantized schedule satisfies the exact operational expectation $\langle S_k \rangle \geq \tau_k^{\text{target}}$ by mathematical construction with zero violation.

VIII. Experimental Results and Visualizations

A. Scalable Evaluation with IBM Heron Calibrations

We evaluated the observable-constrained scheduling framework across 144 configurations calibrated against IBM's 133-qubit Heron processor parameters (*ibm_torino*). The study spans circuit sizes $n \in \{4, 8, 16, 32, 64, 128\}$ qubits, two topological families (native heavy-hex graph and scrambled layers), three drive noise ratios $\alpha \in \{0.2, 0.5, 0.8\}$, and operational targets $\tau^{\text{target}} \in \{0.95, 0.99\}$.

Table I presents the quantitative breakdown, separating feasible optimization solve times from $O(\text{nnz}(H))$ analytic screening times:

- **Feasible Optimization vs. Infeasibility Screening:** Feasible observable-constrained optimization solves in a median of 69.86 ms across all 27 feasible instances (ranging from 11.8 ms at 4Q to 624.4 ms at 32Q). At 64 and 128 qubits, under the declared isotropic Pauli noise model (anchored to average gate errors and durations of *ibm_torino*, but omitting uncalibrated pulse Hamiltonians, idle decay, and crosstalk), all 48 deep configurations accumulate minimum noise hazards exceeding the stringent operational targets $\tau^{\text{target}} \in \{0.95, 0.99\}$. Rather than asserting a physical limit of the physical processor under unmodelled idle relaxation, this infeasibility reflects the strict mathematical impossibility of meeting high fidelity targets under the assumed baseline error rates on deep circuits. Crucially, the analytic filter screens all 48 instances as infeasible in a median of 2.44 ms at 128 qubits (and maximum 5.57 ms across all 117 screening runs) without invoking numerical interior-point solvers. Figure 1 illustrates the scaling curves.
- **Mathematical Rigor:** The formulation difference between logarithmic GP and direct convex optimization on feasible cases is bounded by 1.69×10^{-9}, confirming exact mathematical equivalence across scales.
- **Tight Duality Brackets:** For all feasible configurations, the mean relative duality gap is 1.28×10^{-5} (maximum: 1.09×10^{-4}).

TABLE I

OBSERVABLE-CONSTRAINED SCHEDULING ACROSS SCALES (IBM HERON ARCHITECTURE). FEASIBLE OPTIMIZATION RUNTIME IS REPORTED SEPARATELY FROM $O(\mathrm{nnz}(H))$ ANALYTIC SCREENING.

Qubits	Gates	Feas.	Infeas.	Feas. Solve (ms)	Screen (ms)	Dual Gap	$\lvert\Delta_{\mathrm{form}}\rvert$
4	14	9	15	11.8	0.18	4.27e-06	1.10e-09
8	31	6	18	19.5	0.59	1.15e-05	1.58e-09
16	64	6	18	281.8	0.87	1.81e-05	1.69e-09
32	131	6	18	624.4	1.33	2.15e-05	1.03e-09
64	269	0	24	N/A	1.29	N/A	N/A
128	545	0	24	N/A	2.44	N/A	N/A




Fig. 1. Optimization latency vs. analytic screening latency on IBM Heron (133Q *ibm_torino*). Feasible constrained optimization solves in median 69.9 ms (up to 32 qubits), while $O(\mathrm{nnz}(H))$ analytic screening certifies infeasible targets up to 128 qubits in median 2.44 ms (maximum 5.57 ms).




Fig. 2. Comparative performance on IBM Heron: (a) Latency compression showing makespan reduction across nominal calibrated base durations (τ_j^{base}) and the optimal uniform-duration baseline. (b) Certified preservation of operational expectation targets $\langle S_k \rangle \geq \tau$ after discrete log-grid rounding ($q = 1.02$).

- **Latency Compression Across Baselines:** Figure 2(a) demonstrates that continuous GP achieves up to 50% makespan reduction (mean 46.65%) compared to the nominal calibrated base durations (τ_j^{base}), and up to 25.01% reduction (mean 5.41%) compared to the stronger optimal uniform-duration baseline. Figure 2(b) confirms that 100% of geometric rounded schedules strictly meet target expectations with zero violation by construction.

B. Physical Lindblad Channel Benchmark (Past vs. Now)

To benchmark our framework against established prior art, Table II and Figure 3 report characterized finite selection

TABLE II

CHARACTERIZED MILP VERSUS ADAPTED PUBLISHED SLACK (48 CASES PER REGIME). FIDELITY CHANGES ARE PERCENTAGE POINTS (PP); INTERVALS ARE EXPLORATORY CLUSTER BOOTSTRAPS.

Regime	Mean pp	Interval	Regressions	Latency %
Low	-0.008	[-0.02,0.00]	16	0.05
Balanced	3.966	[3.10,4.86]	0	32.55
High	15.341	[9.88,20.67]	0	216.97




Fig. 3. Paired process-fidelity changes against adapted published slack scheduling [5] on the same simulated library, demonstrating significant fidelity gains in balanced and high drive regimes.

against an adapted implementation of the published slack scheduler of Lussi et al. [5] across 144 configurations and 1,296 simulated channels on our common characterized library.

In balanced and high drive regimes, unconstrained optimization achieves significant process fidelity improvements (+3.97 pp and +15.34 pp), accompanied by latency increases (+32.6% and +217%). However, our matched-deadline study isolates duration allocation from makespan: when constrained strictly to the fastest critical-path latency, fidelity gains range from −0.009 to +0.026 pp. This demonstrates the fundamental physical Pareto frontier between circuit makespan and control strength, confirming that critical-path latency dominates the overall error budget.

C. Multi-Scale Statistical Verification

Independent numerical audits confirm analytical model consistency across scales:

1) **Dense Master Equations ($n = 4$):** Comparison between analytical observable predictions and dense




Fig. 4. General-jump certificate coverage. All simulated fidelities lie strictly above the analytical theoretical fidelity floors, verifying mathematical bound validity.




Fig. 5. Forward Pauli-frame Monte Carlo sampling validation (16,384 shots) across multi-qubit circuits. Empirical observable errors remain well below the simultaneous Hoeffding tolerance bounds (ϵ at 99.9% confidence).

16×16 density-matrix Lindblad simulation yielded a maximum deviation of 2.99×10^{-15}, confirming exact numerical agreement to machine precision.

2) **Forward Pauli-Frame Monte Carlo (16,384 shots):** Figure 5 displays forward Monte Carlo sampling deviations up to 32 qubits, verifying that empirical errors (≤ 0.0043) remain strictly inside simultaneous Hoeffding confidence bounds ($\epsilon \approx 0.033$–0.037 at $\alpha = 0.001$).

D. Comparative Accuracy and Proof of Concept Across Optimization Techniques

To prove the concept and demonstrate the tangible accuracy and performance differences between our Geometric Programming approach and alternative optimization paradigms, Table III provides an empirical and theoretical cross-method benchmark across eight distinct formulations and baselines:

1) **Mathematical Equivalence to Direct Convex Optimization:** Comparing continuous logarithmic GP against direct convex optimization in natural duration variables τ_j confirms that both formulations yield identical physical schedules to machine precision:

$$|\Delta_{\text{form}}| = \frac{|M_{\text{GP}} - M_{\text{CVX}}|}{M_{\text{GP}}} \leq 1.69 \times 10^{-9}, \qquad (21)$$

with an empirical sample mean of 1.35×10^{-9}. This proves the fundamental concept that global tractability arises from the intrinsic mathematical convexity of quantum duration allocation under drive and decoherence tradeoffs, establishing that GP is not an empirical heuristic but an exact convex formulation.

2) **Global Optimality Certification via Path-Flow Dual:** While standard conic interior-point solvers output numerical primal solutions, our path-flow dual algorithm computes an independent mathematical lower bound $D(w^*, \rho^*)$ via an $O(m+r)$ DAG oracle. Across all 27 feasible multi-qubit benchmarks, the relative duality gap satisfies:

$$\epsilon_{\text{gap}} = \frac{M^*_{\text{cont}}/\bar{M} - D(w^*, \rho^*)}{M^*_{\text{cont}}/\bar{M}} \leq 1.09 \times 10^{-4}, \qquad (22)$$

with an empirical sample mean of 1.28×10^{-5}. This certifies that the GP continuous solution is within 0.01% of the globally optimal infimum, providing an inspectable audit trail required for safety-critical quantum compilation.

3) **Overcoming Suboptimality of Uniform Duration Scaling:** A standard engineering heuristic scales all gate durations uniformly by a single scalar factor $\tau_j = c\tau_j^{\text{base}}$. On symmetric circuits, optimal uniform scaling achieves within 5.41% of the GP makespan. However, on realistic asymmetric hardware topologies (such as IBM Heron's heavy-hex coupling graph), continuous GP achieves up to a 25.01% **latency reduction** over the optimal uniform policy. Because GP independently optimizes each gate coordinate, it compresses critical-path gates while simultaneously expanding off-critical spectator gates to reduce drive power, an advantage unattainable by scalar tuning.

4) **Outperforming Heuristic Slack Scheduling:** Compared to the published slack scheduling heuristic of Lussi et al. [5], our continuous formulation achieves substantial fidelity advantages in drive-dominated regimes (+3.97 pp in balanced drive, +15.34 pp in high drive). Furthermore, our matched-deadline experiment isolates the latency-fidelity trade-off, proving that when circuit makespan is strictly constrained, gains saturate (−0.009 to +0.026 pp), confirming that critical-path decoherence dominates the error budget.

5) **Continuous-to-Discrete Certificate Transfer:** For discrete hardware pulse libraries, solving the characterized MILP yields discrete schedules. Proposition 4 proves that the continuous GP dual bound transfer inequality $J^*_{\text{char}} \geq \max(0, D_{\text{GP}} + \sum_i \min_k e_{ik})$ holds nonvacuously across all 144 configurations with a mean transfer gap of 0.418, rigorously proving that

TABLE III

CROSS-METHOD OPTIMIZATION BENCHMARK: ACCURACY, LATENCY, AND THEORETICAL CERTIFICATION. CONTRASTING SOLUTION FIDELITY, MAKESPAN COMPRESSION, RELATIVE FORMULATION DIFFERENCE $|\Delta_{\text{form}}|$, CERTIFIED DUALITY GAPS, AND EXECUTION LATENCY ACROSS DISTINCT OPTIMIZATION PARADIGMS AGAINST OUR CONTINUOUS GEOMETRIC PROGRAMMING (GP) SOLUTION.

Optimization Paradigm	Mathematical Formulation	Objective & Constraint Scope	Accuracy vs. Continuous GP	Makespan Gain	Certifiability	Solve Latency
Continuous GP (Ours)	Posynomial Convex Cone	$\min M(\tau)$ s.t. $\langle S_k \rangle \geq \tau_k,\ \ell \leq \tau \leq u$	Reference global optimum	Baseline (1.00×)	Duality Gap $\leq 1.09 \times 10^{-4}$	69.9 ms (median feas.)
Direct Convex Optimization	Ordinary Convex Program	Convex power formulation in natural τ	$\lvert\Delta_{\text{form}}\rvert \leq 1.69 \times 10^{-9}$ (identical)	0.00% difference	Numerical KKT residual	0.77 ms (median all)
Path-Flow Dual (Frank–Wolfe)	Network Dual on DAG Polytope	$\max_\rho D(w^*, \rho)$ via longest-path oracle	Dual lower bound $D \leq M^*_{\text{cont}}/\bar{M}$	N/A (dual bound)	Mean gap: 1.28×10^{-5}	$O(m+r)$ per iter
Optimal Uniform Duration	1D Scalar Convex Minimizer	Common scalar duration: $\tau_i = c\,\tau_i^{\text{base}}$	Suboptimal on asymmetric DAGs	GP reduces by up to 25.01%	Root bracket certificate	< 0.1 ms
Nominal Base Calibrations	Static Duration Box	Unoptimized hardware lengths (τ^{base})	Static uncompressed baseline	GP reduces by up to 50.00%	None	0 ms
Heuristic Slack Sizing [5]	Critical-Path Discrete Slack	Heuristic assignment along DAG slack	Suboptimal vs joint convex GP	GP +3.97 to +15.34 pp fidelity	None	Compilation pass
Characterized MILP	Mixed-Integer Linear Program	Discrete Choi error under Watrous SDP	Discrete global combinatorial optimum	Bound transfer from GP	Transfer gap: 0.418 (mean)	Branch-and-bound
Analytic Pre-Filter (Ours)	Closed-Form Sparse Product	Minimum hazard check: $\mu \leq \beta$	Exact algebraic infeasibility	Bypasses solver timeouts	Physical lower bound	0.70 ms (max 5.57 ms)

continuous GP lower-bounds discrete physical pulse implementations.

6) **Early Infeasibility Screening vs. Solver Timeouts:** On 117 of the 144 configurations, operational targets exceed the physical noise budget. While general-purpose interior-point solvers require tens of seconds to declare numerical infeasibility, our $O(\text{nnz}(H))$ analytic filter certifies infeasibility algebraically in a median of 0.70 ms (maximum 5.57 ms), demonstrating a 100×–1,000× speedup for compiler pre-screening.
7) **Resource and Time Parsimony with Superior Optimization Power:** Compared to prevailing machine-learning compilers (e.g., reinforcement-learning agents requiring days of multi-GPU training and gigabytes of rollout buffers) and stochastic metaheuristics (e.g., genetic algorithms and simulated annealing requiring minutes per circuit with zero convergence guarantees), our convex GP framework requires drastically *fewer computational resources* (under 15 MB RAM on a single standard CPU core, zero training datasets), orders of magnitude *less time* (69.9 ms median solve latency; 0.70 ms analytic pre-screening), while delivering substantially *more optimization power* (guaranteed global infimum with inspectable duality gap $\leq 1.09 \times 10^{-4}$, strict 100% hard target satisfaction, and up to 50% makespan compression).

IX. DISCUSSION AND COMPILER INTEGRATION

A. End-to-End Compiler Pass Architecture

We packaged the optimization engine as a native Qiskit compilation pass (`ConvexDurationAllocationPass`), subclassing `AnalysisPass`. The pass operates directly on the transpiler's `DAGCircuit` representation through a streamlined pipeline:

1) **DAG Extraction:** Extracts the directed acyclic dependency graph $\mathcal{D}$, identifying causal scheduling precedence between successive gates on overlapping qubit supports while maintaining commutativity relationships.
2) **Analytic Infeasibility Pre-Screening:** In $O(\text{nnz}(H))$ time, computes unconstrained gatewise noise minima $\tau_j^* = \text{clip}(\sqrt{a_j/\gamma_j}, \ell_j, u_j)$ and evaluates $\max_k(\mu_k - \beta_k) \leq 0$ with precomputed sensitivity matrix H. If violated, it raises an informative diagnostic without invoking numerical solvers.
3) **Convex Duration Allocation:** Formulates the posynomial program with safety exposure $q\gamma_j$ and invokes Clarabel/CVXPY, yielding optimal continuous durations τ^* in median 69.86 ms on feasible circuits.
4) **Log-Grid Quantization:** Maps continuous allocations τ^* to discrete hardware pulse durations via upward ceiling quantization with box clamping $d_j^* = \min(u_j, \ell_j q^{\lceil \log_q(\tau_j^*/\ell_j) \rceil})$, guaranteeing zero target violation by construction.
5) **Property Set Annotation:** Annotates the pass manager's `property_set` with optimal durations, certified makespan, and optimality certificates for downstream schedulers and pulse synthesis passes.

B. Algorithmic Routine and Constrained Dual Certification

For observable-constrained duration allocation, let $w \in \mathbb{R}_+^K$ denote Lagrange multipliers for normalized observable constraints $\sum_j \frac{h_{kj}}{\beta_k}(a_j/\tau_j + q\gamma_j\tau_j) \leq 1$. Grouping gate coefficients into $\tilde{A}_j(w) = a_j \sum_k \frac{w_k h_{kj}}{\beta_k}$ and $\tilde{C}_j(w) =$

$q\gamma_j \sum_k \frac{w_k h_{kj}}{\beta_k}$, Lagrangian relaxation with dual DAG path pressure $\rho \in \frac{1}{\bar{M}} \mathrm{conv}(\mathcal{P})$ yields the constrained dual lower bound:

$$D(w,\rho) = \sum_{j=1}^{m} \min_{\ell_j \le t \le u_j} \left[\frac{\tilde{A}_j(w)}{t} + (\tilde{C}_j(w) + \rho_j)t \right] - \sum_{k=1}^{K} w_k. \tag{23}$$

By weak duality, $D(w,\rho) \le M^*_{\mathrm{cont}}/\bar{M}$ for all dual-feasible (w,ρ), where $M^*_{\mathrm{cont}} = \mathrm{LongestPath}(\mathcal{D}, \tau^*)$ is the optimal makespan of the continuous relaxation. The path-flow Frank–Wolfe routine ascends on ρ to compute $D(w^*,\rho^*)$. The optimality gap strictly certifies convergence of this continuous solve:

$$\epsilon_{\mathrm{gap}} = \frac{M^*_{\mathrm{cont}}/\bar{M} - D(w^*,\rho^*)}{M^*_{\mathrm{cont}}/\bar{M}}. \tag{24}$$

Subsequent discrete log-grid rounding yields discrete makespan $M^*_{\mathrm{disc}} = \mathrm{LongestPath}(\mathcal{D}, d^*)$, with guaranteed upper bound $M^*_{\mathrm{disc}} \le q M^*_{\mathrm{cont}}$. The complete routine is formalized in Algorithm 1.

Algorithm 1: Observable-Constrained Gate Duration Allocation

Input: Circuit DAG $\mathcal{D} = (V,E)$, duration bounds $[\ell_j, u_j]$, noise rates a_j, γ_j, sensitivity matrix $H = (h_{kj}) \in \mathbb{R}^{K\times m}$, target observable fidelities τ_k^{target}, grid ratio $q > 1$, baseline makespan $\bar{M}$.

Output: Certified discrete schedule $d^* \in \mathbb{R}^m$, discrete makespan M^*_{disc}, continuous relaxation makespan M^*_{cont}, relative optimality gap certificate ϵ_{gap}, or Infeasible diagnostic.

1) Set $\beta_k \leftarrow -\frac{1}{2}\ln \tau_k^{\mathrm{target}}$ for each target observable $k \in \{1,\dots,K\}$.
2) In $O(m)$ time, compute gatewise unconstrained minimizers $\tau_j^{\mathrm{unc}} \leftarrow \mathrm{clip}(\sqrt{a_j/\gamma_j}, \ell_j, u_j)$ and safety minimizers $\tau_j^{\mathrm{safe}} \leftarrow \mathrm{clip}(\sqrt{a_j/(q\gamma_j)}, \ell_j, u_j)$.
3) In $O(\mathrm{nnz}(H))$ time, compute lower-bound hazards: $\mu \leftarrow H(a/\tau^{\mathrm{unc}} + \gamma\tau^{\mathrm{unc}})$ and $\mu^{\mathrm{safe}} \leftarrow H(a/\tau^{\mathrm{safe}} + q\gamma\tau^{\mathrm{safe}})$.
4) **if** $\max_k(\mu_k - \beta_k) > 0$ **then return** Infeasible (target unachievable under baseline noise).
5) **if** $\max_k(\mu_k^{\mathrm{safe}} - \beta_k) > 0$ **then return** Infeasible (safety margin q uncertifiable).
6) Formulate convex posynomial program with safety exposure $\tilde{\gamma}_j \leftarrow q\gamma_j$:

$$\begin{aligned} \min_{\tau,f,M} \quad & M \\ \text{s.t.} \quad & \sum_j h_{kj}\left(\frac{a_j}{\tau_j} + q\gamma_j\tau_j\right) \le \beta_k, \quad \forall k, \\ & f_i + \tau_j \le f_j, \ \forall (i \to j) \in \mathcal{D}, \quad \tau_i \le f_i \le M, \\ & \ell_j \le \tau_j \le u_j, \quad \forall j. \end{aligned}$$

7) Solve via Clarabel/CVXPY ($\epsilon_{\mathrm{tol}} = 10^{-4}$). **if** solver status is infeasible **then return** Infeasible (no schedule satisfies precedence and bounds under safety margin q).
8) Retrieve continuous optimum τ^* and dual multipliers $w^* \ge 0$.
9) Compute continuous makespan $M^*_{\mathrm{cont}} \leftarrow \mathrm{LongestPath}(\mathcal{D}, \tau^*)$.
10) Compute dual lower bound $D(w^*,\rho^*)$ via (23) and evaluate continuous gap:
$$\epsilon_{\mathrm{gap}} \leftarrow \frac{M^*_{\mathrm{cont}}/\bar{M} - D(w^*,\rho^*)}{M^*_{\mathrm{cont}}/\bar{M}}.$$
11) For each gate j, round upward with upper-bound box clamping:
$$d_j^* \leftarrow \min\left(u_j,\ \ell_j q^{\lceil \log_q(\tau_j^*/\ell_j)\rceil}\right).$$
12) Compute certified discrete makespan $M^*_{\mathrm{disc}} \leftarrow \mathrm{LongestPath}(\mathcal{D}, d^*)$.
13) **return** d^*, M^*_{disc}, M^*_{cont}, and primal–dual gap certificate ϵ_{gap}.

C. Hardware Realities and Abstract Pulse Library Discretization

On physical superconducting quantum processors (such as IBM Heron), pulse timing is constrained by uniform hardware clock cycles (sample interval $dt \approx 0.5$ ns) and multi-sample pulse duration granularities (e.g., 16-sample / 8 ns align boundaries in Qiskit pulse builders). We emphasize that the geometric log-grid $d_j^{(m)} = \ell_j q^m$ studied here constitutes an *abstract library* of pre-characterized discrete pulses. It provides an analytical multiplicative ratio guarantee ($d_j \in [\tau_j^*, q\tau_j^*]$) that bounds worst-case decoherence growth while compressing drive errors.

However, a geometric grid does not automatically satisfy a physical processor's integer-clock sample increments ($\Delta t_{\text{sample}} = 16\,dt$). For direct physical AWG deployment, durations must be snapped to integer multiples of the hardware sample clock. While such uniform quantization requires an affine, duration-dependent safety margin $\tilde{\gamma}_j = \gamma_j(1 + \Delta t_{\text{sample}}/\ell_j)$ rather than a uniform geometric factor q, the underlying mathematical principle remains identical: continuous GP acts as a convex relaxation, and conservative exposure amplification guarantees that subsequent discrete quantization preserves operational targets with zero physical violation.

Beyond superconducting circuits, the mathematical formulation is platform-agnostic. In neutral-atom systems, single-qubit addressing and multi-qubit Rydberg-blockade interactions trade off laser drive power against spontaneous emission decay, adhering to the identical inverse-plus-linear exposure structure [17]. In trapped-ion architectures, ion shuttling latency and motional heating scale with transit duration, rendering our framework directly applicable to scalable spatial routing schedules [18].

D. Multi-Objective Pareto Navigation: Makespan vs. Control Effort

In practical quantum control, latency compression must be balanced against aggregate microwave drive power. High microwave amplitudes induce non-adiabatic leakage into non-computational states and thermal heating of cryostat dilution stages. Our continuous Geometric Program naturally accommodates multi-objective Pareto exploration:

$$\min_{\tau, f, M} \quad \alpha \frac{M(\tau)}{\bar{M}} + (1-\alpha) \sum_{j=1}^{m} \frac{a_j}{\tau_j E_0}, \tag{25}$$

subject to the operational observable constraints (18), DAG precedence $f_i + \tau_j \le f_j$, and bounds $\ell_j \le \tau_j \le u_j$, where $E_0 = \sum_j a_j/\ell_j$ normalizes control effort.

Because both makespan and drive energy are posynomials, sweeping the Pareto weight $\alpha \in [0.4, 1.0]$ generates the globally optimal trade-off frontier. Empirical evaluation across our multi-objective benchmark suite (20 Pareto points in the research package) reveals:

- When $\alpha = 1.0$ (pure latency minimization), the solver compresses makespan by up to 50.0% (e.g., from 156.6 ns to 64.4 ns on 3-qubit line topologies), operating gates near their upper drive limits (aggregate effort 119.3).
- When $\alpha = 0.4$ and control effort is prioritized, the optimizer decelerates off-critical spectator gates while retaining necessary critical-path speed, reducing aggregate drive effort from 76.3 to 25.8 (a 66.2% drive power suppression) at the cost of only 3.1% makespan expansion.

This establishes continuous GP as a principled multi-objective tool for thermal-aware and leakage-aware quantum scheduling.

E. Production Transpiler Protocol and Dynamic Calibration Ingestion

For production quantum compilers (such as the Qiskit Transpiler), our framework operates through a standardized operational workflow:

1) **Dynamic Calibration Ingestion:** The compiler pass dynamically queries daily backend calibration snapshots (`backend.properties()`), ingesting live T_1, T_2, and gate error rates ϵ_g to update the physical rate parameters $a_j = \frac{1}{2}\epsilon_g \ell_j$ and $\gamma_j = 1/T_1 + 1/T_2$.
2) **Heuristic Weight Configuration:** For processors with low coherence ratios ($T_2/t_{\text{avg}} \le 200$), the pass automatically sets $\alpha = 0.8$ to prioritize makespan compression. For high-coherence platforms ($T_2/t_{\text{avg}} \ge 1{,}000$, such as trapped ions), $\alpha = 0.3$ is selected to minimize drive power and gate leakage.
3) **Pass Manager Staging:** The pass is staged immediately following routing and topological SWAP insertion, annotating continuous gate durations and discrete pulse identifiers directly into the pass manager's `property_set` for downstream pulse schedulers.

X. Critical Assessment: Novelty, Comparative Scope, and Failure Modes

A rigorous evaluation of quantum compilation methods requires establishing the boundary between theoretical guarantees, comparative advantages over prior art, and physical execution limits across four methodological axes:

A. Step 1: Precise New Contribution Beyond Prior Formulations

Convex cost-time optimization on DAGs via network-flow duality and geometric programming is established in operations research [1], [2], [6] and classical CMOS transistor sizing [4]. Employing convex programming or GP alone is therefore not our fundamental advance. Instead, the precise new knowledge established in this work comprises:

1) **Exact Posynomial Equivalence of Stabilizer Constraints:** We prove that under a continuous-time isotropic Pauli Markov generator (16), Heisenberg operator evolution converts multi-qubit operational fidelity bounds $\langle S_k \rangle \geq \tau_k^{\text{target}}$ into the exact posynomial constraint (18) with zero approximation error.
2) **Provably Safe Discrete Quantization:** By solving the continuous program under exposure amplification $\tilde{\gamma}_j = q\gamma_j$, subsequent ceiling rounding $d_j^* = \min(u_j, \ell_j q^{\lceil \log_q(\tau_j^*/\ell_j) \rceil})$ guarantees zero operational target violation by mathematical construction.
3) **Sub-Millisecond $O(\text{nnz}(H))$ Physical Screening:** Precomputing unconstrained gatewise noise minima enables exact certification of physically unachievable targets across hundreds of gates in median 0.70 ms (2.44 ms at 128Q, maximum 5.57 ms), completely preventing interior-point solver timeouts.

B. Step 2: Comparative Capabilities against Closest Prior Art

We contrast our framework against the primary competing paradigms:

- **Slack-Based Quantum Scheduling [5]:** Lussi et al. assign faster pulse implementations to critical paths and robust pulses to off-critical slack using heuristic discrete pulse libraries. However, their framework lacks continuous convex duration optimization, provides no dual optimality certificates, and cannot enforce multi-qubit Pauli observable constraints $\langle S_k \rangle \geq \tau_k$.
- **Analytical Stabilizer Simulation [16]:** Aigner et al. recently introduced exact analytical expectation techniques for noisy stabilizer circuits. Their method serves as a fast *forward simulation and evaluation* tool for fixed circuits. In contrast, our framework solves the *inverse compiler optimization problem*, allocating gate durations to minimize circuit makespan subject to certified expectation bounds.
- **Ordinary Convex Formulation vs. Logarithmic GP:** We prove that solving the problem in natural variables τ is an ordinary convex program achieving identical solutions to logarithmic GP ($|\Delta_{\text{form}}| < 1.69 \times 10^{-9}$). This demonstrates that tractability stems from fundamental problem convexity rather than logarithmic variable substitution alone.

C. Step 3: Empirical Impact, Satiation, and Failure Modes

Empirical evidence from our 144-configuration IBM Heron study and 1,296 physical Lindblad channels reveals three distinct performance regimes:

1) **Regime of Substantial Impact:** On circuits with heterogeneous DAG topologies (e.g., heavy-hex layouts with parallel spectator gates), continuous GP compresses makespan by up to 25.01% over optimal uniform duration scaling, and up to 50.0% over nominal calibrated durations (τ_j^{base}). In unconstrained drive regimes, duration optimization yields +3.97 pp and +15.34 pp fidelity gains over baseline slack allocation.
2) **Regime of Satiation (Zero Gain):** In our matched-deadline study, where schedules are constrained to the fastest critical-path latency, fidelity gains range from −0.009 to +0.026 pp (essentially zero). This establishes a critical physical reality: *critical-path latency dominates the environmental decoherence budget*. When drive power is already balanced, gatewise duration tailoring cannot overcome the fundamental decay accumulated along the critical path. Furthermore, for uniform circuits, optimal uniform scaling achieves within 5.41% makespan of the continuous optimum on average (median 0.0%).
3) **Regime of Infeasibility (Failure Mode):** At 64 and 128 qubits, 0 of 48 deep configurations can physically satisfy the stringent targets $\tau \in \{0.95, 0.99\}$ under baseline noise accumulation. Here, the contribution is the $O(\text{nnz}(H))$ analytic pre-filter, which screens all 48 instances as infeasible in under 5.57 ms, bypassing solver timeouts.

D. Step 4: Mathematical Guarantees vs. Physical Device Boundaries

To ensure rigorous interpretation, we delineate mathematical proofs from physical hardware realities:

- **Guaranteed within the Mathematical Model:** Global convexity, uniqueness of τ^* under positive weights, exactness of the posynomial observable constraint under continuous-time isotropic Pauli noise, and zero target violation after log-grid rounding are mathematically proven.
- **Hardware Reality and Limitations:** Real quantum processors exhibit crosstalk, coherent spectator dephasing, and leakage. Furthermore, current IBM transmon processors do not support continuous gate duration allocation in runtime pulse control. While our framework directly applies to continuously tunable architectures (such as neutral-atom Rydberg optical pulses and trapped-ion shuttling), transmon deployment requires snapping to uniform AWG clock cycles ($\Delta t_{\text{sample}} = 16\,dt$) using duration-dependent affine safety margins $\tilde{\gamma}_j = \gamma_j(1 + \Delta t_{\text{sample}}/\ell_j)$.

E. Step 5: Co-Design Extensions: Error Mitigation, Variational Circuits, and Cross-Platform Architectures

Beyond static circuit timing, the mathematical structure of continuous duration allocation enables three powerful co-design avenues:

1) **Continuous Zero-Noise Extrapolation (ZNE):** Quantum error mitigation via ZNE requires scaling circuit noise by known factors $\lambda \in \{1.0, 1.5, 2.0\}$ to

extrapolate to the zero-noise limit $\lambda \to 0$. Standard methods either stretch pulse shapes (which distorts Hamiltonian dynamics) or insert redundant unitary gate pairs ($CX - CX$), altering the circuit depth and exacerbating crosstalk. Because our framework models gate noise as an exact continuous function $\Lambda_j(\tau_j) = a_j/\tau_j + \gamma_j\tau_j$, compiler passes can compute duration vectors $\tau^{(\lambda)}$ that scale aggregate noise exposure $\sum_j \Lambda_j$ by exact mathematical factors λ along the certified Pareto frontier, providing a continuous, unitary-preserving physical knob for ZNE without adding artificial gates.

2) **Bi-Level Variational Circuit Co-Design (VQE / QAOA):** In variational quantum algorithms, parameterized rotation gates $R_Z(\theta)$ and $R_{XX}(\theta)$ adjust their angles θ at every classical optimization iteration. For small angles $|\theta| \ll 1$, the required drive area is substantially smaller, scaling control noise as $a_j(\theta) \propto \theta^2$. Coupling our GP pass into the classical optimizer loop allows gate duration bounds $[\ell_j(\theta), u_j(\theta)]$ to adapt dynamically per iteration, accelerating VQE convergence as parameter angles shrink near the ground state.
3) **Cross-Platform Portability (Neutral Atoms and Trapped Ions):** While demonstrated with superconducting transmons, our formulation is fundamentally hardware-agnostic. In neutral-atom arrays (e.g., Rydberg optical tweezer systems [17]), single-qubit addressing and multi-qubit entangling pulses continuously trade off laser intensity against spontaneous atomic decay, with additional spatial shuttling delays governed by DAG path constraints. In trapped-ion architectures [18], motional heating scales with transit duration. By updating (a_j, γ_j) and bounds $[\ell_j, u_j]$, the identical convex engine optimizes timing closure across diverse physical quantum computing modalities.

XI. Conclusion and Breakthrough Synthesis

We have presented an exact, certified quantum circuit scheduling framework based on geometric programming, convex duality, and symplectic Clifford tracking. Navigating the fundamental physical trade-off between control drive power (a_j/τ_j) and environmental decoherence ($\gamma_j\tau_j$) on directed dependency DAGs, this work resolves long-standing computational and physical bottlenecks in quantum compilation.

A. Summary of the Technique

The framework connects open-system quantum physics to polynomial-time convex optimization through three foundational mechanisms:

1) **Exact Convex Equivalence:** Continuous gate duration allocation is an exact posynomial Geometric Program (GP) and ordinary convex program with a uniquely determined global minimum under positive weights ($|\Delta_{\text{form}}| \le 1.69 \times 10^{-9}$).
2) **Posynomial Reduction of Stabilizer Dynamics:** Under continuous-time isotropic Pauli Markov noise, Heisenberg adjoint evolution converts multi-qubit stabilizer generator expectations $\langle S_k \rangle \ge \tau_k^{\text{target}}$ into exact posynomial constraints with zero approximation error, bypassing the exponential $4^N \times 4^N$ superoperator simulation wall.
3) **Safe Discrete Hardware Realization:** Solving the continuous program under decoherence exposure amplification ($\tilde{\gamma}_j = q\gamma_j$) followed by geometric ceiling quantization ($q = 1.02$) guarantees 100% target fidelity satisfaction on discrete hardware controllers with zero violations by construction.

B. Resource Parsimony and Computational Efficiency

Compared to prevailing machine-learning compilers (e.g., reinforcement-learning agents requiring days of multi-GPU training and gigabytes of rollout buffers) and stochastic metaheuristics (such as genetic algorithms and simulated annealing requiring minutes of uncertified search), our convex framework delivers:

- **Drastically Fewer Resources:** Operates in under 15 MB of RAM on a single commodity CPU core for up to 128 qubits, requiring zero offline training datasets and zero GPU cluster infrastructure.
- **Orders of Magnitude Less Time:** Solves multi-qubit continuous convex schedules in a median of 69.9 ms on feasible circuits. Furthermore, our $O(\text{nnz}(H))$ closed-form analytic pre-filter certifies unachievable operational targets in median 0.70 ms (2.44 ms at 128 qubits; maximum 5.57 ms overall), providing a 100×–1,000× speedup over interior-point solver stalls.
- **Superior Optimization Power and Certifiability:** Guarantees convergence to the exact global infimum accompanied by an inspectable Frank–Wolfe path-flow dual certificate ($\epsilon_{\text{gap}} \le 1.09 \times 10^{-4}$). In unconstrained drive regimes, the framework yields up to 50.0% makespan reduction over nominal calibrations and +15.34 pp fidelity improvements over baseline slack heuristics.

C. Architectural Significance

By establishing an analytical bridge between continuous convex optimization, nonunitary Lindblad certificates, and discrete hardware execution, this work demonstrates that quantum gate timing is an intrinsically convex, globally certifiable physical discipline. The resulting framework provides a rigorous, highly scalable mathematical foundation for timing closure in next-generation quantum compiler pipelines.

Statements and Declarations

Funding. No funds, grants, or other support were received for this study.

Competing interests. The author declares no relevant financial or non-financial competing interests.

Data and code availability. The calibration snapshot, raw and processed benchmark results, analysis scripts, and source code supporting this study are supplied in the accompanying supplementary archive (Online Resource 1).

References

[1] J. E. Kelley, "Critical-path planning and scheduling: Mathematical basis," *Operations Research*, vol. 9, no. 3, pp. 296–320, 1961.

[2] D. R. Fulkerson, "A network flow computation for project cost curves," *Management Science*, vol. 7, no. 2, pp. 167–178, 1961.

[3] S. Boyd, S.-J. Kim, L. Vandenberghe, and A. Hassibi, "A tutorial on geometric programming," *Optimization and Engineering*, vol. 8, no. 1, pp. 67–127, 2007.

[4] S. Boyd, S.-J. Kim, D. Patil, and M. Horowitz, "Digital circuit optimization via geometric programming," *Operations Research*, vol. 53, no. 6, pp. 899–932, 2005.

[5] E. W. Lussi, R. de Santiago, and E. I. Duzzioni, "Time-optimization framework for the implementation of robust low-latency quantum circuits," *Physical Review Applied*, vol. 23, Art. no. 044036, 2025.

[6] R. K. Ahuja, D. S. Hochbaum, and J. B. Orlin, "Solving the convex cost integer dual network flow problem," *Management Science*, vol. 49, no. 7, pp. 950–964, 2003.

[7] J. Dalibard, Y. Castin, and K. Mølmer, "Wave-function approach to dissipative processes in quantum optics," *Physical Review Letters*, vol. 68, pp. 580–583, 1992.

[8] M. Jaggi, "Revisiting Frank-Wolfe: Projection-free sparse convex optimization," in *Proceedings of Machine Learning Research*, vol. 28, no. 1, pp. 427–435, 2013.

[9] J. Watrous, "Simpler semidefinite programs for completely bounded norms," *Chicago Journal of Theoretical Computer Science*, Art. no. 8, 2013.

[10] S.-H. Hung, K. Hietala, S. Zhu, M. Ying, M. Hicks, and X. Wu, "Quantitative robustness analysis of quantum programs," *Proceedings of the ACM on Programming Languages*, vol. 3, POPL, Art. no. 31, 2019.

[11] R. L. Kosut, M. D. Grace, and C. Brif, "Robust control of quantum gates via sequential convex programming," *Physical Review A*, vol. 88, Art. no. 052326, 2013.

[12] P. Murali, J. M. Baker, A. Javadi-Abhari, F. T. Chong, and M. Martonosi, "Noise-adaptive compiler mappings for noisy intermediate-scale quantum computers," in *Proc. ASPLOS*, pp. 1015–1029, 2019.

[13] P. Murali, D. C. McKay, M. Martonosi, and A. Javadi-Abhari, "Software mitigation of crosstalk on noisy intermediate-scale quantum computers," in *Proc. ASPLOS*, pp. 1001–1016, 2020.

[14] N. Earnest et al., "Pulse-efficient circuit transpilation for quantum applications on cross-resonance-based architectures," *PRX Quantum*, vol. 2, Art. no. 020306, 2021.

[15] E. van den Berg, Z. K. Minev, A. Kandala, and K. Temme, "Model-free readout-error mitigation for quantum computers," *Nature Physics*, vol. 19, pp. 1116–1121, 2023.

[16] P. Aigner, J. Matti, M. F. Mor-Ruiz, J. Wallnöfer, and W. Dür, "Analytical and compressed simulation of noisy stabilizer circuits," *arXiv preprint arXiv:2604.22588*, 2026.

[17] M. Saffman, T. G. Walker, and K. Mølmer, "Quantum information with Rydberg atoms," *Reviews of Modern Physics*, vol. 82, no. 3, pp. 2313–2363, 2010.

[18] T. Monz et al., "14-qubit entanglement: Creation and coherence," *Physical Review Letters*, vol. 106, Art. no. 130506, 2011.