

6. * رقم الكمبيوتر

3

7. * الكود (قد تمت مراجعة بيانات الطالب ورقم الجلوس)

OAIL

8. What does a readyState value of 1 indicate? (1 Point)

- ☐ A) The request is finished
- ☐ B) The request is being sent
- ☒ C) The request has been initialized
- ☐ D) The response is being received

9. Which of the following is NOT a valid HTTP request method? (1 Point)

- ☐ A) GET
- ☐ B) POST
- ☒ C) FETCH
- ☐ D) None of the above

10. What does the typeof operator return for an array? (1 Point)

- ☐ A) "array"

- ☒ B) "object"
- ☐ C) "list"
- ☐ D) "collection"

11. What does the innerHTML property do? (1 Point)

- ☐ A) Returns the text content of an element
- ☒ B) Sets or gets the HTML markup contained within an element
- ☐ C) Returns the HTML structure of the document
- ☐ D) Modifies the style of an element

12. Which of the following will correctly declare a variable? (1 Point)

- ☐ A) var name;
- ☐ B) let name;
- ☐ C) const name;
- ☒ D) All of the above

13. Which of the following can be used to send data to a server using AJAX? (1 Point)

- ☐ A) GET only
- ☐ B) POST only
- ☒ C) Both GET and POST

☐ D) PUT only

14. Which of the following will correctly add an event listener to a button? (1 Point)

☐ A) `button.addEventListener('onclick', function() { ... });`

☒ B) `button.onclick = function() { ... };`

☐ C) Both A and B

☐ D) `button.eventListener('click', function() { ... });`

15. What will the following code output?
`const div = document.createElement('div');div.setAttribute('data-info', 'example');console.log(div.getAttribute('data-info'));` (1 Point)

☒ A) example

☐ B) data-info

☐ C) undefined

☐ D) Error

16. Which object is commonly used to create an AJAX request in JavaScript? (1 Point)

☒ A) XMLHttpRequest

☐ B) AjaxRequest

☐ C) HttpClient

☐ D) FetchAPI

17. What is the purpose of the onreadystatechange property in an XMLHttpRequest? (1 Point)

- ☐ A) To specify the response data type
- ☐ B) To set the HTTP method
- ☒ C) To handle changes in the request's state
- ☐ D) To send data to the server

18. What is the typical use case for AJAX in web applications? (1 Point)

- ☐ A) To load an entire new webpage
- ☒ B) To update parts of a webpage without refreshing
- ☐ C) To send static files to the server
- ☐ D) To create new HTML elements

19. Which HTTP status code indicates a successful request? (1 Point)

- ☐ A) 400
- ☐ B) 404
- ☐ C) 500
- ☒ D) 200

20. Which property would you use to change the text content of an HTML element? (1 Point)

- ☐ A) innerHTML

- ☒ B) textContent
- ☐ C) contentText
- ☐ D) htmlText

21. Which method is used to add an element to the end of an array? (1 Point)

- ☒ A) push()
- ☐ B) pop()
- ☐ C) unshift()
- ☐ D) shift()

22. Which of the following correctly creates an object in JavaScript? (1 Point)

- ☐ A) let obj = {};
- ☐ B) let obj = new Object();
- ☒ C) All of the above
- ☐ D) None of the above

23. How can you handle errors in an AJAX request? (1 Point)

- ☐ A) By checking the status property
- ☐ B) By using a try-catch block
- ☐ C) By checking the readyState

☒ D) All of the above

24. Which of the following methods can be used to extract a substring from a string in JavaScript? (1 Point)

☐ A) string.extract(start, end)

☐ B) string.slice(start, end)

☐ C) string.substring(start, end)

☒ D) Both B and C

25. Which loop will execute at least once, regardless of the condition? (1 Point)

☐ A) for loop

☐ B) while loop

☒ C) do...while loop

☐ D) none of the above

26. How can you access the first child of an element? (1 Point)

☐ A) firstChildNode

☒ B) firstChild

☐ C) firstChildNodes

☐ D) None of the above

27. Which of the following methods can be used to remove an element from the DOM? (1 Point)

- ☐ A) deleteElement()
- ☒ B) removeChild()
- ☐ C) detach()
- ☐ D) childRemove()

28. What does the send() method do in an AJAX request? (1 Point)

- ☐ A) Initializes the request
- ☒ B) Sends the request to the server
- ☐ C) Closes the request
- ☐ D) Starts the timer for the request

29. What does DOM stand for in JavaScript? (1 Point)

- ☒ A) Document Object Model
- ☐ B) Document Oriented Model
- ☐ C) Data Object Model
- ☐ D) Document Object Management

30. What will the following code output if run in a browser? `const div = document.createElement('div');div.innerHTML = '<span>Hello</span><span>World</span>';console.log(div.firstChild.innerHTML);` (1 Point)

- ☒ A) Hello
- ☐ B) `<span> Hello </span>`
- ☐ C) HelloWorld
- ☐ D) undefined

31. Which readyState value indicates that the request has completed? (1 Point)

- ☐ A) 0
- ☐ B) 1
- ☐ C) 2
- ☒ D) 4

32. How can you listen for a key press event on an input element? (1 Point)

- ☐ A) `inputElement.addEventListener('onkeypress', function() { ... });`
- ☒ B) `inputElement.onkeypress = function() { ... };`
- ☐ C) Both A and B
- ☐ D) `inputElement.keypress = function() { ... };`

password.

Microsoft Forms | AI-Powered surveys, quizzes and polls [Create my own form](#)

[Privacy and cookies](#) | [Terms of use](#)