



Disable Immersive Reader



Clear Form

قواعد البيانات المتقدمة

9:00-11:00

1/1/2025

د/ابراهيم العوضى

Faculty of Computers & Information, Assiut University

Course code: IS411

4th Level

Final Exam

Duration: Two hours

This exam for the following program(s) : (Add the program's name(s))

Points: -/48

1

* الإسم الرباعي (بالعربي فقط)

Amr Ayman Hussain Ahmed

2

* رقم الجلوس

162021225

3

المستوي *



Disable Immersive Reader



Clear Form

- ☐ الاول
- ☐ الثاني
- ☐ الثالث
- ☐ الرابع 2014
- ☐ الرابع 2015
- ☐ الرابع 2016
- ☐ الرابع 2017
- ☐ الرابع 2018
- ☐ الرابع 2019
- ☐ الرابع 2020
- ☒ الرابع 2021

4

البرنامج *



- ☒ عام
- ☐ بايو
- ☐ هندسة

☐ ذكاء صناعي

5

* رقم المعمل



Disable Immersive Reader



Clear Form

☐ ج٠

☐ د٠

☐ ه٠

☐ اب

☐ اج

☐ اد

☐ اه١

☐ أ٢

☐ ب٢

☐ ج٢

☐ د٢

☐ ه٢

☐ أ٣

☐ ب٣

☐ ج٣

☒ د٣

☐ ه٣

☐ أ☐ ب☐ ج☐ د☐ هـ

Disable Immersive Reader



Clear Form

6

رقم الكمبيوتر *



3

7

الكود * (قد تمت مراجعة بيانات الطالب ورقم الجلوس)



ZSFP



Will be reviewed

8

Applications should rely on ROWID

☒ True☐ False

Will be reviewed

9

HTML

```
<html> <body> <form method="post" action="demo_request.php">  
Name: <input type="text" name="fname"> <input type="submit">  
</form> </body>
```

```
PHP$name = $_F  
echo $name;
```



Disable Immersive Reader



Clear Form

these codes

- ☐ generate an error
- ☒ display the name from HTML form
- ☐ do not send something to the client

Will be reviewed

10

The data storage models used in DBMS are

- ☒ N-ary Storage Model
- ☒ Decomposition Storage Model
- ☒ Hybrid Storage Model
- ☐ Others

Will be reviewed

11

PHP contains one type of array

- ☐ True

☒ False

 **Will be review**



Disable Immersive Reader



Clear Form

12

the function **fseek(FILE *stream, long int offset, int whence)** returns



☐ void

☐ int

☒ char

☐ char *

 **Will be reviewed**

13

You are given a hash table of 5 buckets, each of size 2. Using the **first** bucket hash method described above, put key value 42 into the hash table. 

☐ HashTable[0]

☐ HashTable[1]

☐ HashTable[2]

☒ HashTable[3]

☐ HashTable[4]

☐ HashTable[5]

☐ HashTable[6]

☐ HashTable[7]

☐ HashTable[8]☐ HashTable[9]☐ HashTable[10]☐ Overflow[0]☐ Overflow[1]☐ Overflow[2]

Disable Immersive Reader



Clear Form

Will be reviewed

14

For each table in database, we can have triggers

☐ 1☐ 2☐ 3☐ 4☐ 5☒ 6 **Will be reviewed**

15

Relation should have no multivalued attributes or nested relations, this problem is called

☒ 1NF

☐ 2NF

☐ 3NF

☐ 4NF

☐ 5NF

 Disable Immersive Reader

 Clear Form

 **Will be reviewed**

16

The less common layout scheme is called slotted pages. [X]

☒ True

☐ False

 **Will be reviewed**

17

Old PHP version, such as PHP4, has no object oriented 

☐ True

☒ False

 **Will be reviewed**

18

In SQL programming,
WHILE <condition> DO
<statement list>

The last line must be 

- ☒ END
- ☐ END DO
- ☐ END WHILE
- ☐ empty line

 Disable Immersive Reader
 Clear Form

 **Will be reviewed**

19

OS Page may reach to 1GB. 

- ☐ True
- ☒ False

 **Will be reviewed**

20

This is the IP (Internet Protocol) address of the client user computer that is accessing the server, for example 129.107.61.8. 

- ☐ \$_SERVER['SERVER_NAME']
- ☐ \$_SERVER['REMOTE_ADDRESS']
- ☒ \$_SERVER['REMOTE_HOST']
- ☐ \$_SERVER['PATH_INFO']

E3 Will be reviewed

21

Most newer DB systems on raw block storage.



Disable Immersive Reader



Clear Form

☒ True☐ False**E3 Will be reviewed**

22

You are given a hash table of 5 buckets, each of size 2. Using the **first** bucket hash method described above, put key value 32 into the hash table. EU

☐ HashTable[0]☐ HashTable[1]☒ HashTable[2]☐ HashTable[3]☐ HashTable[4]☐ HashTable[5]☐ HashTable[6]☐ HashTable[7]☐ HashTable[8]☐ HashTable[9]☐ HashTable[10]

☐ Overflow[0]

☐ Overflow[1]

☐ Overflow[2]

OR Disable Immersive Reader

23

suppose that the search key field is $V = 9$ bytes long, the block size is $B = 1024$ bytes, a record pointer is $Pr = 7$ bytes, and a block pointer is $P = 6$ bytes. An internal node of the B+-tree can have up to **ptree** pointers and $p - 1$ search field values; these must fit into a single block. What is value of **ptree** ER

☐ 31

☐ 30

☐ 32

☐ 62

☐ 63

☐ 64

☒ 65

☐ Will be reviewed

24

A page is a block of data ER

☒ fixed-size

☐ variable-size

☐ large-size

☐ small-size

OR) Disable Immersive Reader

S Will be review

 Clear Form

25

In PHP, msq1 referes to ER

Q Mini SQL

☐ Microsoft SQL Server

☐ Oracle

☒ MySQL

S Will be reviewed

26

The next figure is in ER

☐ 1NF

☐ 2NF

☐ 3NF

☒ BCNF

O Will be reviewed

27

The advantages of using stored procedures and functions are 

- ☒ Reducing duplicati  re modularity.
- ☒ Executing a progre  transfer and communication cost be-
tween the client and server in certain situations
- ☒ Checking for complex constraints that are beyond the specification power of assertions and triggers

EZj **Will be reviewed**

28

What is true about denormalize 0^

- ☒ are related tuples and store them together in the same page.
- ☐ are potentially reduces the amount of I/O for common workload patterns
- ☒ are potentially increases the amount of I/O for common workload patterns
- ☒ can make updates more expensive
- ☐ can make updates more easy

O **Will be reviewed**

29

Several NoSQL DBMSs use denormalize ER

☒ True

☐ False

 **Will be reviewed**

30

Databases and data management are not important component of everyday life in modern society.



Disable Immersive Reader



Clear Form

☐ True

☒ False

 **Will be reviewed**

31

The DBMS assumes that the primary storage location of the database is on non-volatile disk. 

☒ True

☐ False

 **Will be reviewed**

32

The storage model of the next figure is 

☐ PAX

☒ DSM

☐ NSM

 **Will be reviewed**

33

Database file contains 

- ☐ one directory and
- ☒ set of pages
- ☐ set of pages where each page contains s header



Disable Immersive Reader



Clear Form

 **Will be reviewed**

34

In PHP, what is the value of y

\$x = '7';

\$y = "3\$x";



- ☒ '37'
- ☐ '3&x'
- ☐ '3' and address x

 **Will be reviewed**

35

In the next statement, stdout must be defined before used.

fprintf(stdout, "%d %s %.2f\n", account, name, balance);

- ☐ True

☒ False

 **Will be review**

36

PHP built-in array variable called 

☐ auto-global

☒ \$_POST

☐ DB connect

 **Will be reviewed**

37

The access time of is for SSD 

☐ 16,000 ns

☒ 2,000,000 ns

☐ 100 ns

 **Will be reviewed**

38

The storage model of the next figure is 

☒ PAX

☐ DSM

☐ NSM

 **Will be review**

39



Disable Immersive Reader



Clear Form

The client can run c++/java program in the client, where this program generates outputs as HTML format. This technology is called 

☐ Active pages

☐ Common-gateway interface

☐ Web 2.0

☒ Web technogies

 **Will be reviewed**

40

PHP is language 

☐ low-level

☐ high level

☒ scripting

☐ web

 **Will be reviewed**

41

Relation should not have a nonkeyattribute functionally determined byanother nonkey attribute (or by a set ofnonkey attributes). That is, there

should be no transitive dependency of a nonkey attribute on the primary key. this problem is called

☐ 1NF

☐ 2NF

☒ 3NF

☐ 4NF

☐ 5NF



Disable Immersive Reader



Clear Form

Will be reviewed

42

Assume that you have 10,000,000,000 values, and B+ tree node has 5 pointers. What is the highest depth of this + tree?

☐ 10

☐ 11

☐ 12

☐ 13

☐ 14

☒ 15

☐ 16

Will be reviewed

43

The model that has been used to specify active database rules is referred to as the

Event-Action model 

☒ True

☐ False

 Disable Immersive Reader
 Clear Form

 **Will be reviewed**

44

CALL statement is used to call procedure 

☒ True

☐ False



This content is created by the owner of the form. The data you submit will be sent to the form owner. Microsoft is not responsible for the privacy or security practices of its customers, including those of this form owner. Never give out your password.

Microsoft Forms | AI-Powered surveys, quizzes and polls [Create my own form](#)

[Privacy and cookies](#) | [Terms of use](#)