API CONSUMER REFERENCE

Eligibility API

Quick integration guide • MSISDN + National ID eligibility check

1. Connection details

Setting	Value
Base URL	http://<host>:8080 (use the host supplied by Operations)
API endpoint	POST /api/v1/eligibility/check
Required headers	Content-Type: application/json | X-API-Key: <api-key>

Use the approved internal network path. The production API key must be shared securely, not embedded in documents or URLs.

2. Request format

Field	Requirement
msisdn	Required string; exactly 12 digits beginning with 20 (e.g. 201066257228).
nid	Required string; exactly 14 digits (e.g. 29901011234567).

JSON request

```
{
  "msisdn": "201066257228",
  "nid": "29901011234567"
}
```

The check uses the combined (MSISDN, NID) pair, not the MSISDN alone.

3. Successful responses (HTTP 200)

Eligible — result: OK

```
{
  "requestId": "req-7c2a0b1e-4f0a-4c1d-9a11-0b5e6d7c8a90",
  "msisdn": "201055555555",
  "nid": "29901011234560",
  "result": "OK",
  "reason": "",
  "blacklistVersion": "20261015"
}
```

Not eligible — result: KO

```
{
  "requestId": "req-001",
  "msisdn": "201066257228",
  "nid": "29901011234567",
  "result": "KO",
  "reason": "Anti-fraud : Anti-Fraud (Vishing), Anti-Fraud (Financial Fraud)",
  "blacklistVersion": "20261015"
}
```

The KO reason contains all active blacklist causes. requestId is also available in the X-Request-Id response header.

DECISION & ERROR HANDLING

Caller implementation rules

4. Interpret the API result

200 + OK	Eligible. The caller may proceed with the request.
200 + KO	Not eligible. Reject and retain/display the reason.
Any non-200	No eligibility decision. Do not approve the request.

5. HTTP status codes

HTTP	Meaning / caller action
200	Decision returned. Read result = OK or KO.
400	Invalid/missing msisdn or nid, malformed JSON or unknown field. Correct the request.
401	Missing/invalid X-API-Key. Check the provisioned credential.
415	Unsupported media type. Use application/json.
503	Blacklist/readiness/audit not available. Fail closed; retry only after service is ready.
500	Unexpected server error. Do not approve; escalate with requestId.

6. Example API call

cURL — replace <host>; load the key securely into MSISDN_API_KEY

```
curl -sS -D - http://<host>:8080/api/v1/eligibility/check \
  -H 'Content-Type: application/json' \
  -H "X-API-Key: ${MSISDN_API_KEY}" \
  -d '{"msisdn":"201066257228","nid":"29901011234567"}'
```

7. Health check & integration checklist

Check	Details
Readiness	GET /actuator/health/readiness (no API key required).
Traceability	Capture requestId / X-Request-Id for support escalation.
Decision logic	Branch on HTTP status and result, not free-text reason/message.
Sensitive data	Keep API key out of logs; mask MSISDN and NID in caller logs.

Note: These examples and rules reflect the supplied Eligibility API caller contract. Runtime host and production key are provided by Operations.