

## Course 2: Supervised Learning



### Summary

#### Last session

- What is not AI ?
- AI definition
- Applications
- Open issues

#### Today's session

- Learning from labeled examples
- Challenges of supervised learning

### Last session

- 1 What is not AI ?
- 2 AI definition
- 3 Applications
- 4 Open issues

### Today's session

- Learning from labeled examples
- Challenges of supervised learning

Vector space ( $\mathbb{R}^d$ )



## Notations

Vector space ( $\mathbb{R}^d$ )




We denote a vector space of real values in dimension  $d$ . We will consider vectors  $x$  in this space, and the set big  $X$  of all such vectors.

## Notations




Vector space ( $\mathbb{R}^d$ )




We denote a vector space of real values in dimension  $d$ . We will consider vectors  $x$  in this space, and the set big  $X$  of all such vectors.

## Notations



Vector space ( $\mathbb{R}^d$ )




We denote a vector space of real values in dimension  $d$ . We will consider vectors  $x$  in this space, and the set big  $X$  of all such vectors.

## Definition

Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

## Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...



## Supervised learning

Supervised Learning

Definition  
Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...


- We insist here one more time on the fact that learning is not memorizing. We need to say orally that an expert is needed to provide the labels, that is why it is "supervised".
- Give here a few examples of regression tasks (predicting the price of a product in the stock market, the age of a person based on his/her face, ...) and classification tasks (recognizing apples versus oranges).
- When the plot appears, say that for example if we have the points labeled in blue and the points labeled in red, a simple function could be learnt by just dividing the space in two regions.
- However if we present a new point (not part of training) that lies in the red region and is supposed to be "blue", then it means we are not generalizing.
- Finally, we present here another way to "learn", by defining the so-called Voronoi diagram (you can write it on the board), which are the regions of the space that are closer to one point than any other point.

## Definition

Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

## Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...



## Supervised learning

**Definition**  
Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

**Examples**

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...




- We insist here one more time on the fact that learning is not memorizing. We need to say orally that an expert is needed to provide the labels, that is why it is "supervised".
- Give here a few examples of regression tasks (predicting the price of a product in the stock market, the age of a person based on his/her face, ...) and classification tasks (recognizing apples versus oranges).
- When the plot appears, say that for example if we have the points labeled in blue and the points labeled in red, a simple function could be learnt by just dividing the space in two regions.
- However if we present a new point (not part of training) that lies in the red region and is supposed to be "blue", then it means we are not generalizing.
- Finally, we present here another way to "learn", by defining the so-called Voronoi diagram (you can write it on the board), which are the regions of the space that are closer to one point than any other point.

## Definition

Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

## Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...



## Supervised learning

Supervised learning

**Definition**  
Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

**Examples**

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...

- We insist here one more time on the fact that learning is not memorizing. We need to say orally that an expert is needed to provide the labels, that is why it is "supervised".
- Give here a few examples of regression tasks (predicting the price of a product in the stock market, the age of a person based on his/her face, ...) and classification tasks (recognizing apples versus oranges).
- When the plot appears, say that for example if we have the points labeled in blue and the points labeled in red, a simple function could be learnt by just dividing the space in two regions.
- However if we present a new point (not part of training) that lies in the red region and is supposed to be "blue", then it means we are not generalizing.
- Finally, we present here another way to "learn", by defining the so-called Voronoi diagram (you can write it on the board), which are the regions of the space that are closer to one point than any other point.




## Definition

Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

## Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...




## Supervised learning

Supervised learning

**Definition**  
Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

**Examples**

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...




- We insist here one more time on the fact that learning is not memorizing. We need to say orally that an expert is needed to provide the labels, that is why it is "supervised".
- Give here a few examples of regression tasks (predicting the price of a product in the stock market, the age of a person based on his/her face, ...) and classification tasks (recognizing apples versus oranges).
- When the plot appears, say that for example if we have the points labeled in blue and the points labeled in red, a simple function could be learnt by just dividing the space in two regions.
- However if we present a new point (not part of training) that lies in the red region and is supposed to be "blue", then it means we are not generalizing.
- Finally, we present here another way to "learn", by defining the so-called Voronoi diagram (you can write it on the board), which are the regions of the space that are closer to one point than any other point.

## Definition

Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

## Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...



## Supervised learning

Supervised learning

**Definition**  
Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

**Examples**

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...


- We insist here one more time on the fact that learning is not memorizing. We need to say orally that an expert is needed to provide the labels, that is why it is "supervised".
- Give here a few examples of regression tasks (predicting the price of a product in the stock market, the age of a person based on his/her face, ...) and classification tasks (recognizing apples versus oranges).
- When the plot appears, say that for example if we have the points labeled in blue and the points labeled in red, a simple function could be learnt by just dividing the space in two regions.
- However if we present a new point (not part of training) that lies in the red region and is supposed to be "blue", then it means we are not generalizing.
- Finally, we present here another way to "learn", by defining the so-called Voronoi diagram (you can write it on the board), which are the regions of the space that are closer to one point than any other point.

## Definition

Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

## Examples

- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...



## Supervised learning

Supervised learning

**Definition**  
Supervised learning methods use **labels**  $y$  associated to examples  $x \in X$  to learn a function  $f$  such as  $y = f(X)$ , with the aim of **generalizing** ( $\neq$  memorizing) to unlabeled examples.

**Examples**


- Regression ( $y$  is scalar)
- Classification ( $y$  is categorical)
- Tons of applications:
  - Pattern recognition,
  - Prediction...

- We insist here one more time on the fact that learning is not memorizing. We need to say orally that an expert is needed to provide the labels, that is why it is "supervised".
- Give here a few examples of regression tasks (predicting the price of a product in the stock market, the age of a person based on his/her face, ...) and classification tasks (recognizing apples versus oranges).
- When the plot appears, say that for example if we have the points labeled in blue and the points labeled in red, a simple function could be learnt by just dividing the space in two regions.
- However if we present a new point (not part of training) that lies in the red region and is supposed to be "blue", then it means we are not generalizing.
- Finally, we present here another way to "learn", by defining the so-called Voronoi diagram (you can write it on the board), which are the regions of the space that are closer to one point than any other point.

# Challenges of supervised learning (1/5)

## An ill-defined problem

- An infinity of potential solutions, one must be the "best one" but is unreachable,
- $\Rightarrow$  requires a priori, constraints.



2018-10-23


## Course 2: Supervised Learning

### └ Challenges of supervised learning (1/5)

Challenges of supervised learning (1/5)

An ill-defined problem

- An infinity of potential solutions, one must be the "best one" but is unreachable,
- $\Rightarrow$  requires a priori, constraints.




The point here is simply illustrate the fact that the solution is not unique. One way to find a solution that could be "better" than another one is to use prior knowledge or constraints of the problem at hand.

# Challenges of supervised learning (1/5)

## An ill-defined problem

- An infinity of potential solutions, one must be the "best one" but is unreachable,
- $\Rightarrow$  requires a priori, constraints.



2018-10-23

## Course 2: Supervised Learning

### └ Challenges of supervised learning (1/5)

The point here is simply illustrate the fact that the solution is not unique. One way to find a solution that could be "better" than another one is to use prior knowledge or constraints of the problem at hand.


Challenges of supervised learning (1/5)

- An ill-defined problem
- An infinity of potential solutions, one must be the "best one" but is unreachable,
- $\Rightarrow$  requires a priori, constraints.

# Challenges of supervised learning (1/5)

## An ill-defined problem

- An infinity of potential solutions, one must be the "best one" but is unreachable,
- $\Rightarrow$  requires a priori, constraints.




2018-10-23

## Course 2: Supervised Learning

### └ Challenges of supervised learning (1/5)

Challenges of supervised learning (1/5)

- An ill-defined problem
- An infinity of potential solutions, one must be the "best one" but is unreachable,
- $\Rightarrow$  requires a priori, constraints.




The point here is simply illustrate the fact that the solution is not unique. One way to find a solution that could be "better" than another one is to use prior knowledge or constraints of the problem at hand.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)



In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.


To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.



# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off

- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

## Course 2: Supervised Learning

### Challenges of supervised learning (2/5)


In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

## Course 2: Supervised Learning

### Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)



In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.


To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.



# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

## Course 2: Supervised Learning

### Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

## Course 2: Supervised Learning

### Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



## Challenges of supervised learning (2/5)

In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.


To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.



# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off


- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.



2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (2/5)

## Bias/variance trade-off

- A simple solution that almost matches is better than a complex one that fully matches,
- Mimicking is not learning: overfitting problem.




## Crossvalidation

- To quantify overfitting, split training dataset in two parts:
  - 1 A first part is used to train,
  - 2 A second part is used to validate,

2018-10-23

Course 2: Supervised Learning

## Challenges of supervised learning (2/5)




In the first part, the goal is to show what happens when trying to learn a polynomial function. With one point, we can learn a line, with two points a parabola, etc. If the 5 points are chosen carefully, it is possible to learn something very close to the "true" function. If we take five other points, we might end up with a result that is relatively close. However, if trying to learn polynomials of a higher order, the result can be completely off while the values taken at the training points (red) are correct.

To prevent this, explain what is cross-validation. The diagram on the left shows the error (in regression or classification). The X axis is illustrative, it doesn't correspond to something specific (although one could imagine it to correspond to order of a polynomial, epochs of training a neural net, ...) but it illustrates the situations of underfitting and overfitting.

# Challenges of supervised learning (3/5)

## Curse of dimensionality

- Geometry is not intuitive in high dimension,
- Efficient methods in 2D are not necessarily still valid.



$$V_d^s = \frac{\pi^{d/2} R^d}{\Gamma(d/2 + 1)} \text{ versus } V_d^c = (2R)^d$$


see <http://www.maths.manchester.ac.uk/~mlotz/teaching/surprises.pdf>

2018-10-23

## Course 2: Supervised Learning

### Challenges of supervised learning (3/5)

The point here is to show that when the dimension increases, the space tends to be more and more "empty".  $V_d^s$  is the volume of the hypersphere, and  $V_d^c$  is the volume of the hypercube. The crosses in the different figures are generated by each coordinates following a uniform distribution  $\mathcal{U}(0, R)$  (so on average they have a value of  $R/2$ ). When  $d$  increases, the ratio between the hypersphere and the hypercube becomes smaller and smaller, so that the majority of the volume of the hypercube lies in the corners. Therefore, the intuitions we have easily in 2D are not valid anymore, so we can imagine why it is difficult to build good classifiers in high dimensions.






# Challenges of supervised learning (3/5)

## Curse of dimensionality

- Geometry is not intuitive in high dimension,
- Efficient methods in 2D are not necessarily still valid.




$$V_d^S = \frac{\pi^{d/2} R^d}{\Gamma(d/2 + 1)} \text{ versus } V_d^C = (2R)^d$$

see <http://www.maths.manchester.ac.uk/~mloetz/teaching/surprises.pdf>

2018-10-23

## Course 2: Supervised Learning


### Challenges of supervised learning (3/5)



The point here is to show that when the dimension increases, the space tends to be more and more "empty".  $V_d^S$  is the volume of the hypersphere, and  $V_d^C$  is the volume of the hypercube. The crosses in the different figures are generated by each coordinates following a uniform distribution  $\mathcal{U}(0, R)$  (so on average they have a value of  $R/2$ ). When  $d$  increases, the ratio between the hypersphere and the hypercube becomes smaller and smaller, so that the majority of the volume of the hypercube lies in the corners. Therefore, the intuitions we have easily in 2D are not valid anymore, so we can imagine why it is difficult to build good classifiers in high dimensions.

# Challenges of supervised learning (4/5)

## Riemannian manifolds



## Linear separability and need for embedding




2018-10-23

## Course 2: Supervised Learning


### Challenges of supervised learning (4/5)

Top part : the point here is to show an example of a dataset in 4D, which is actually much simpler because it is 1D. A nice example to explain the swiss roll is to explain how to roll the cake to make it !  
Bottom part : just explain the fact that even in very simple cases, there is no way to find a linear separator.




# Challenges of supervised learning (4/5)

## Riemannian manifolds



## Linear separability and need for embedding




2018-10-23

## Course 2: Supervised Learning

### Challenges of supervised learning (4/5)

Top part : the point here is to show an example of a dataset in 4D, which is actually much simpler because it is 1D. A nice example to explain the swiss roll is to explain how to roll the cake to make it !  
Bottom part : just explain the fact that even in very simple cases, there is no way to find a linear separator.



# Challenges of supervised learning (5/5)

## Computation time

Example on ImageNet, simply going through all images:

- $n = 10.000.000$ ,  $d \approx 1.000.000$ ,
- $\approx 10^{13}$  elementary operations,
- $\approx 2h45$  on a modern processor.

## Scalability

- Finding the best solution to a problem would be feasible with unlimited computation time,
- But searching through the space of possible functions is often untractable,
- Solutions must be computationally reasonable, which is the true challenge today.

2018-10-23

## Course 2: Supervised Learning

### └ Challenges of supervised learning (5/5)

Challenges of supervised learning (5/5)

#### Computation time

Example on ImageNet, simply going through all images:

- $n \approx 10.000.000$ ,  $d \approx 1.000.000$ ,
- $\approx 10^{13}$  elementary operations,
- $\approx 2h45$  on a modern processor.

#### Scalability

- Finding the best solution to a problem would be feasible with unlimited computation time.
- But searching through the space of possible functions is often untractable.
- Solutions must be computationally reasonable, which is the true challenge today.

This slide is pretty much self-explanatory. First, the goal is to show that just going through each image is very costly. Second, it is easy to explain why the space of possible functions quickly become so huge that it's not possible to search through it.

# Challenges of supervised learning (5/5)

## Computation time

Example on ImageNet, simply going through all images:

- $n = 10.000.000$ ,  $d \approx 1.000.000$ ,
- $\approx 10^{13}$  elementary operations,
- $\approx 2h45$  on a modern processor.

## Scalability

- Finding the best solution to a problem would be feasible with unlimited computation time,
- But searching through the space of possible functions is often untractable,
- Solutions must be computationally reasonable, which is the true challenge today.

2018-10-23

## Course 2: Supervised Learning

### └ Challenges of supervised learning (5/5)

Challenges of supervised learning (5/5)

#### Computation time

Example on ImageNet, simply going through all images:

- $n \approx 10.000.000$ ,  $d \approx 1.000.000$ ,
- $\approx 10^{13}$  elementary operations,
- $\approx 2h45$  on a modern processor.

#### Scalability

- Finding the best solution to a problem would be feasible with unlimited computation time,
- But searching through the space of possible functions is often untractable,
- Solutions must be computationally reasonable, which is the true challenge today.

This slide is pretty much self-explanatory. First, the goal is to show that just going through each image is very costly. Second, it is easy to explain why the space of possible functions quickly become so huge that it's not possible to search through it.

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

2018-10-23

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

#### Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

2018-10-23

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

x

2018-10-23

## Course 2: Supervised Learning

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

x x

2018-10-23

## Course 2: Supervised Learning

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

x x

# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

## Course 2: Supervised Learning

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

x x

# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

## Course 2: Supervised Learning

### └ Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

### └ Vapnik Chervonenki (VC) dimension


The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

## Course 2: Supervised Learning

### └ Vapnik Chervonenki (VC) dimension


The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .




# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

## Course 2: Supervised Learning

### Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .

# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

## Course 2: Supervised Learning

### Vapnik Chervonenki (VC) dimension


The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .






# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

## Course 2: Supervised Learning

### Vapnik Chervonenki (VC) dimension

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



2018-10-23

### └ Vapnik Chervonenki (VC) dimension


The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.

Vapnik Chervonenki (VC) dimension

Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



# Vapnik Chervonenki (VC) dimension

## Definition

- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



VC is 3.

2018-10-23

## Course 2: Supervised Learning


### └ Vapnik Chervonenki (VC) dimension

Vapnik Chervonenki (VC) dimension

Definition


- Let us fix  $d$ ,
- The VC dimension is a measure of the genericity of a method,
- It is the maximum cardinality of a set of vectors that the method is able to shatter in any possible way.

Consider for example lines to shatter set of points with  $d = 2$ .



VC is 3.

The goal of this slide is to show a theoretical limitation that can be easily be defined and demonstrated. Just comment through the animation.



Both players follow a deterministic greedy algorithm.  
Supervised learning - predict the outcome of a game from the start configuration.  
Expected accuracy of a random classifier ?

2018-10-23

## Course 2: Supervised Learning

## └ Non-symmetric PyRat without walls / mud



Both players follow a deterministic greedy algorithm.  
Supervised learning - predict the outcome of a game from the start configuration.  
Expected accuracy of a random classifier ?

Here, we continue the "fil rouge" that will be followed during the whole course.  
Ask the students "Can someone remind me what is the simplest deterministic greedy approach that can be taken by a player ?". The answer being "always take the closest piece of cheese".  
The start configuration is the location of the pieces of cheese.  
There are three possible outcomes : win python, win rat, and draw.  
So the chance level (expected accuracy of a random classifier) is 30 percent.

# Lab Session 2 and assignments for Session 3

## TP Supervised Learning (TP1)

- Basics of machine learning using sklearn (including new definitions / concepts)
- Generating PyRat Datasets
- Tests on PyRat datasets using a naive approach

## Project 1 (P1)

You will be assigned a supervised learning method. You have to prepare a Jupyter Notebook on this method, including:

- A brief description of the theory behind the method,
- Basic tests on simulated data to show the influence of parameters and hyperparameters
- Advanced tests and analysis on your own PyRat Datasets (including changing the dataset)

During Session 3 you will have 7 minutes to present your notebook.

2018-10-23

## Course 2: Supervised Learning

### └ Lab Session 2 and assignments for Session 3

Lab Session 2 and assignments for Session 3

TP Supervised Learning (TP1)

- Basics of machine learning using sklearn (including new definitions / concepts)
- Generating PyRat Datasets
- Tests on PyRat datasets using a naive approach

Project 1 (P1)

You will be assigned a supervised learning method. You have to prepare a Jupyter Notebook on this method, including:

- A brief description of the theory behind the method,
- Basic tests on simulated data to show the influence of parameters and hyperparameters
- Advanced tests and analysis on your own PyRat Datasets (including changing the dataset)

During Session 3 you will have 7 minutes to present your notebook.

Here, it is important to tell them that we expect them to think about interpreting the result on the pyrat datasets. In addition, there are definitions in the Lab Session (accuracy, precision, recall and f1 score) that are important to learn.

IMPORTANT : tell them to remember that they have COMPLETE CONTROL on the generation of the pyrat datasets (size of the maze, number of pieces of cheese, ...). So they can use that to explore the problem.