```
# ==== run.py ====
# -*- coding: utf-8 -*-
"""系统启动入口。
运行：
    python run.py
然后在浏览器打开 http://127.0.0.1:5000
"""
from app import create_app
from app.models import db
import sys
if hasattr(sys.stdout, "reconfigure"):
    sys.stdout.reconfigure(encoding="utf-8")    # 控制台中文正常显示
app = create_app()
if __name__ == "__main__":
    with app.app_context():
        db.create_all()    # 首次运行时自动建表
        from app.utils.schema import ensure_schema
        added = ensure_schema(db)    # 旧库补齐新增字段
        if added:
            print("已补充字段：%s" % "、".join(added))
    print("=" * 58)
    print("  历史遗留废弃矿山自然恢复适宜性评价系统 Ｖ1.0")
    print("=" * 58)
    print("  访问地址：http://127.0.0.1:5000")
    print("  演示账号：admin    密码：admin123")
    print("  停止运行：按 Ctrl+C")
    print("=" * 58)
    app.run(host="127.0.0.1", port=5000, debug=True)
# ==== app/__init__.py ====
# -*- coding: utf-8 -*-
"""Flask 应用工厂。"""
from flask import Flask
from flask_login import LoginManager
from app.config import Config
from app.models import db, User
login_manager = LoginManager()
login_manager.login_view = "auth.login"
login_manager.login_message = "请先登录"
@login_manager.user_loader
def load_user(user_id):
    return db.session.get(User, int(user_id))
def create_app(config_class=Config):
    app = Flask(__name__)
    app.config.from_object(config_class)
    db.init_app(app)
    login_manager.init_app(app)
    # 注册视图（各模块路由）
    from app.views import auth, project, unit, standard,
    constraint, \
        ahp, indicator, evaluate, report
```

```
app.register_blueprint(auth.bp)
app.register_blueprint(project.bp)
app.register_blueprint(unit.bp)
app.register_blueprint(standard.bp)
app.register_blueprint(constraint.bp)
app.register_blueprint(ahp.bp)
app.register_blueprint(indicator.bp)
app.register_blueprint(evaluate.bp)
app.register_blueprint(report.bp)
#  全局登录保护：除登录页与静态资源外，均需登录
from flask import request, redirect, url_for
from flask_login import current_user, login_user
PUBLIC_ENDPOINTS = {"auth.login", "static"}
@app.before_request
def require_login():
    #  截图模式（仅用于生成说明书配图）：自动以管理员身份登录
    if app.config.get("SCREENSHOT_MODE"):
        if (request.endpoint not in ("auth.login",
"static")
                and not current_user.is_authenticated):
            admin = User.query.filter_by(role="admin").f
irst()
            if admin:
                login_user(admin)
        return None
    if request.endpoint in PUBLIC_ENDPOINTS or
request.endpoint is None:
        return None
    if not current_user.is_authenticated:
        return redirect(url_for("auth.login"))
    return None
#  侧边栏导航：按论文评价流程的顺序编排，分为「评价流程」与「系统管理」两组。
#  不使用模块编号，避免出现与实际流程不一致的代号。
@app.context_processor
def inject_nav():
    path = request.path or "/"
    flow = [
        ("项目与矿山档案", "/project/", path.startswith("/proje
ct")),
        ("政策与标准知识库", "/standard/",
path.startswith("/standard")),
        ("限制性指标判定", "/constraint/",
path.startswith("/constraint")),
        ("微地质单元", "/unit/", path.startswith("/unit")),
        ("指标体系与权重", "/ahp/", path.startswith("/ahp")),
        ("指标数据采集", "/indicator/",
path.startswith("/indicator")),
        ("适宜性定量评价", "/evaluate/",
path.startswith("/evaluate")),
        ("报告与结果输出", "/report/", path.startswith("/report
```

```
    "))),
        ]
        admin = [
            ("用户与操作日志", "/users", path.startswith(("/users",
    "/logs")))),
        ]
        groups = [
            {"title": "评价流程", "links": flow},
            {"title": "系统管理", "links": admin},
        ]
        #  层级引导用：项目是归档单位，图斑才是评价对象。
        #  下游各页面按图斑组织数据，因此需要提示「哪些项目下还没有图斑」。
        counts = {"project_count": 0, "patch_count": 0,
                  "projects_without_patch": []}
        if current_user.is_authenticated:
            from app.models import Project, MinePatch
            projects = Project.query.order_by(Project.id).al
    l()
            counts["project_count"] = len(projects)
            counts["patch_count"] = MinePatch.query.count()
            counts["projects_without_patch"] = [
                p for p in projects if p.patches.count() ==
    0]
        counts["nav_groups"] = groups
        counts["home_active"] = path == "/"
        return counts
    #  操作审计：统一在响应阶段记录成功的写操作（操作日志）
    from app.services import audit
    @app.after_request
    def audit_writes(response):
        if request.method in ("POST", "PUT", "PATCH",
    "DELETE"):
            audit.record(request.endpoint,
    response.status_code)
        return response
    #  错误页：给出可读提示，而不是默认的英文错误页
    from flask import render_template
    @app.errorhandler(403)
    def forbidden(e):
        return render_template("error.html", code=403,
                               message="没有权限执行该操作"), 403
    @app.errorhandler(404)
    def not_found(e):
        return render_template("error.html", code=404,
                               message="请求的页面不存在"), 404
    return app
#  ==== app/config.py ====
#  -*- coding: utf-8 -*-
"""应用配置。"""
import os
```

```
from datetime import timedelta
BASE_DIR = os.path.abspath(os.path.dirname(__file__))
class Config:
    SECRET_KEY = os.environ.get("SECRET_KEY",
    "mine-restoration-dev-key")
    # 单机部署，SQLite 数据库文件放在应用目录下
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +
    os.path.join(BASE_DIR, "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    # 禁止跨站请求伪造（CSRF），登录与表单提交依赖此项
    WTF_CSRF_ENABLED = True
    # 「记住我」：登录时勾选则下发持久 cookie，关闭浏览器后仍可自动登录
    REMEMBER_COOKIE_DURATION = timedelta(days=30)
    REMEMBER_COOKIE_HTTPONLY = True
    REMEMBER_COOKIE_SAMESITE = "Lax"
    # 影像与数据文件上传（遥感影像挂接、批量导入）
    UPLOAD_FOLDER = os.path.join(BASE_DIR, "static",
    "uploads")
    MAX_CONTENT_LENGTH = 32 * 1024 * 1024          # 单次上传上限
    32 MB
    ALLOWED_IMAGE_EXT = {"png", "jpg", "jpeg", "gif",
    "webp", "bmp", "tif", "tiff"}
    ALLOWED_DATA_EXT = {"csv", "xlsx", "xls"}
# ==== app/models.py ====
# -*- coding: utf-8 -*-
"""数据模型：系统全部数据表。
本文件由甲在阶段 0 一次性写完，作为两人独立开发的地基。
约定：两人只读此文件；确需改表时，由乙提需求、甲统一修改。
"""
import json
from datetime import datetime
from flask_login import UserMixin
from flask_sqlalchemy import SQLAlchemy
db = SQLAlchemy()
class User(UserMixin, db.Model):
    """用户（用户与权限管理）。"""
    __tablename__ = "users"
    id = db.Column(db.Integer, primary_key=True)
    username = db.Column(db.String(64), unique=True,
    nullable=False, index=True)
    password_hash = db.Column(db.String(256),
    nullable=False)
    # 角色：管理员 admin / 评价员 evaluator / 查看者 viewer
    role = db.Column(db.String(20), nullable=False,
    default="viewer")
    active = db.Column(db.Boolean, nullable=False,
    default=True)
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow)
    def to_dict(self):
```

```
        return {"id": self.id, "username": self.username,
                "role": self.role, "active": self.active}
class OperationLog(db.Model):
    """操作日志。"""
    __tablename__ = "operation_logs"
    id = db.Column(db.Integer, primary_key=True)
    user_id = db.Column(db.Integer, db.ForeignKey("users.id"
    ), nullable=True)
    action = db.Column(db.String(128), nullable=False)
    # 操作类型
    target_type = db.Column(db.String(64), nullable=True)
    # 对象类型
    target_id = db.Column(db.Integer, nullable=True)
    # 对象主键
    detail = db.Column(db.Text, nullable=True)
    # 操作详情
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow, index=True)
class Project(db.Model):
    """评价项目（项目与矿山档案）。"""
    __tablename__ = "projects"
    id = db.Column(db.Integer, primary_key=True)
    name = db.Column(db.String(128), nullable=False)
    code = db.Column(db.String(64), nullable=True)
    # 项目编号
    description = db.Column(db.Text, nullable=True)
    status = db.Column(db.String(20), default="进行中")
    # 进行中 / 已完成 / 已归档
    created_by = db.Column(db.Integer,
    db.ForeignKey("users.id"), nullable=True)
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow)
    patches = db.relationship("MinePatch",
    backref="project", lazy="dynamic",
                              cascade="all, delete-orphan")
class MinePatch(db.Model):
    """矿山图斑。"""
    __tablename__ = "mine_patches"
    id = db.Column(db.Integer, primary_key=True)
    project_id = db.Column(db.Integer,
    db.ForeignKey("projects.id"), nullable=False)
    name = db.Column(db.String(128), nullable=False)
    admin_region = db.Column(db.String(128), nullable=True)
    # 所在行政区
    center_x = db.Column(db.Float, nullable=True)
    # 中心经度 / 横坐标
    center_y = db.Column(db.Float, nullable=True)
    # 中心纬度 / 纵坐标
    area_ha = db.Column(db.Float, nullable=True)
    # 图斑面积（公顷）
```

```
    mineral_type = db.Column(db.String(64), nullable=True)
    # 开采矿种
    mining_method = db.Column(db.String(64), nullable=True)
    # 开采方式
    stop_years = db.Column(db.Float, nullable=True)
    # 停产年限
    responsible_entity_missing = db.Column(db.Boolean,
    default=True)  # 责任主体是否缺失
    # 遥感底图 / 无人机正射影像挂接
    image_path = db.Column(db.String(256), nullable=True)
    # 相对 static 的路径
    image_note = db.Column(db.String(256), nullable=True)
    # 影像说明（如来源、时相）
    image_uploaded_at = db.Column(db.DateTime,
    nullable=True)
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow)
    units = db.relationship("MicroUnit", backref="patch",
    lazy="dynamic",
                            cascade="all, delete-orphan")
class ReferenceEcosystem(db.Model):
    """参照生态系统：标准化基准值，与图斑绑定。"""
    __tablename__ = "reference_ecosystems"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    coverage_benchmark = db.Column(db.Float, default=75.0)
    # 植被覆盖度基准 %
    shannon_benchmark = db.Column(db.Float, default=0.7)
    # Shannon-Wiener 基准
    dominant_species = db.Column(db.String(256),
    nullable=True)  # 建群种
    soil_benchmark = db.Column(db.String(256),
    nullable=True)  # 土壤基准
class Standard(db.Model):
    """地方标准 / 政策文件（政策与标准知识库）。"""
    __tablename__ = "standards"
    id = db.Column(db.Integer, primary_key=True)
    province = db.Column(db.String(32), nullable=False)
    # 省份
    name = db.Column(db.String(256), nullable=False)
    # 名称
    doc_number = db.Column(db.String(128), nullable=True)
    # 标准编号 / 文号
    publish_date = db.Column(db.String(32), nullable=True)
    implement_date = db.Column(db.String(32), nullable=True)
    # 类别：地方标准 / 政策文件
    category = db.Column(db.String(32), nullable=False,
    default="地方标准")
    summary = db.Column(db.Text, nullable=True)
```

```
    # 特点概述
    rules = db.relationship("StandardRule",
    backref="standard",
                            cascade="all, delete-orphan")
class StandardRule(db.Model):
    """结构化规则：将标准条文拆解为可执行规则。"""
    __tablename__ = "standard_rules"
    id = db.Column(db.Integer, primary_key=True)
    standard_id = db.Column(db.Integer,
    db.ForeignKey("standards.id"), nullable=False)
    item = db.Column(db.String(128), nullable=False)
    # 判定项
    operator = db.Column(db.String(8), nullable=False)
    # 比较符：> >= < <= ==
    threshold = db.Column(db.String(64), nullable=True)
    # 阈值
    condition_type = db.Column(db.String(32),
    default="必要条件")  # 必要条件 / 充分条件
    region = db.Column(db.String(64), nullable=True)
    # 适用分区（宁夏分区差异化）
    note = db.Column(db.Text, nullable=True)
class ConstraintCheck(db.Model):
    """限制性判定记录。"""
    __tablename__ = "constraint_checks"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    policy_pass = db.Column(db.Boolean, nullable=True)
    # 政策约束
    location_pass = db.Column(db.Boolean, nullable=True)
    # 区位约束
    pollution_pass = db.Column(db.Boolean, nullable=True)
    # 土壤污染
    geo_pass = db.Column(db.Boolean, nullable=True)
    # 地质灾害
    farmland_pass = db.Column(db.Boolean, nullable=True)
    # 耕地属性
    passed = db.Column(db.Boolean, nullable=True)
    # 总体是否通过
    reason = db.Column(db.Text, nullable=True)
    # 不通过原因
    checked_at = db.Column(db.DateTime,
    default=datetime.utcnow)
class MicroUnit(db.Model):
    """微地质单元：岩质边坡 / 碎石边坡 / 平台。"""
    __tablename__ = "micro_units"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    unit_type = db.Column(db.String(32), nullable=False)
```

```
    # 单元类型
    area = db.Column(db.Float, nullable=True)
    # 面积
    ratio = db.Column(db.Float, nullable=True)
    # 面积占比（自动计算）
    description = db.Column(db.Text, nullable=True)
    # 现场描述
class Indicator(db.Model):
    """指标定义：指标树，含角色与启用单元类型。"""
    __tablename__ = "indicators"
    id = db.Column(db.Integer, primary_key=True)
    code = db.Column(db.String(32), unique=True,
    nullable=False)  # 指标编码
    name = db.Column(db.String(64), nullable=False)
    # 指标名称
    level = db.Column(db.Integer, nullable=False)
    # 1/2/3 级
    parent_code = db.Column(db.String(32), nullable=True)
    # 父指标编码
    # 角色：土壤污染指标同时作为限制性指标与评价指标
    is_constraint = db.Column(db.Boolean, default=False)
    is_evaluative = db.Column(db.Boolean, default=True)
    unit = db.Column(db.String(32), nullable=True)
    # 单位
    ideal_value = db.Column(db.String(64), nullable=True)
    # 理想值（可配置）
    ideal_type = db.Column(db.String(32), nullable=True)
    # benefit/cost/mid/discrete
    # 启用该指标的微地质单元（逗号分隔）。岩质边坡不启用土壤指标、平台不启用地形指标
    enabled_units = db.Column(db.String(128), nullable=True)
    description = db.Column(db.Text, nullable=True)
    # 取值依据说明
    def units_list(self):
        return [s for s in (self.enabled_units or
    "").split(",") if s]
class WeightScheme(db.Model):
    """权重方案：按微地质单元类型分别保存。"""
    __tablename__ = "weight_schemes"
    id = db.Column(db.Integer, primary_key=True)
    unit_type = db.Column(db.String(32), nullable=False)
    # 所属单元类型
    name = db.Column(db.String(64), nullable=True)
    # 方案名称
    level = db.Column(db.Integer, nullable=False,
    default=1)          # 1=一级指标 2=二级指标
    is_default = db.Column(db.Boolean, default=False)
    # 是否默认（论文表 3）
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow)
class WeightItem(db.Model):
```

```
    """权重明细：方案内的各项权重。"""                                    401
    __tablename__ = "weight_items"                                      402
    id = db.Column(db.Integer, primary_key=True)                        403
    scheme_id = db.Column(db.Integer,                                   404
    db.ForeignKey("weight_schemes.id"), nullable=False)                 405
    indicator_code = db.Column(db.String(32),                           406
    nullable=False)        #  指标编码                                  407
    weight = db.Column(db.Float, nullable=False)                        408
    #  权重值                                                           409
class ExpertMatrix(db.Model):                                           410
    """专家判断矩阵：多专家打分的原始矩阵。"""                            411
    __tablename__ = "expert_matrices"                                   412
    id = db.Column(db.Integer, primary_key=True)                        413
    scheme_id = db.Column(db.Integer,                                   414
    db.ForeignKey("weight_schemes.id"), nullable=True)                  415
    #  直接标注适用对象，便于无需先建权重方案即可录入专家矩阵           416
    unit_type = db.Column(db.String(32), nullable=True)                 417
    #  微地质单元类型                                                   418
    l1_name = db.Column(db.String(64), nullable=True)                   419
    #  所属一级指标（二级矩阵用）                                       420
    expert_name = db.Column(db.String(64), nullable=True)               421
    #  专家姓名                                                         422
    level = db.Column(db.Integer, nullable=False,                       423
    default=1)          #  矩阵对应指标层级                             424
    matrix_json = db.Column(db.Text, nullable=False)                    425
    #  判断矩阵（JSON 二维数组）                                        426
    cr = db.Column(db.Float, nullable=True)                             427
    #  该专家矩阵的一致性比例                                           428
    created_at = db.Column(db.DateTime,                                 429
    default=datetime.utcnow)                                            430
class IndicatorData(db.Model):                                          431
    """指标实测数据：按微地质单元组织。"""                               432
    __tablename__ = "indicator_data"                                    433
    id = db.Column(db.Integer, primary_key=True)                        434
    unit_id = db.Column(db.Integer, db.ForeignKey("micro_uni            435
    ts.id"), nullable=False, unique=True)                               436
    soil_ratio = db.Column(db.Float, nullable=True)                     437
    #  土石比                                                           438
    thickness = db.Column(db.Float, nullable=True)                      439
    #  土层厚度 cm                                                      440
    ph = db.Column(db.Float, nullable=True)                             441
    organic_matter = db.Column(db.Float, nullable=True)                 442
    #  有机质 g/kg                                                      443
    #  重金属含量，JSON 字符串：{"Hg": 0.05, ...}，未检测项缺失或为 null 444
    heavy_metals = db.Column(db.Text, nullable=True)                    445
    coverage = db.Column(db.Float, nullable=True)                       446
    #  植被覆盖度 %                                                     447
    shannon = db.Column(db.Float, nullable=True)                        448
    #  Shannon-Wiener 多样性指数                                        449
    slope = db.Column(db.Float, nullable=True)                          450
```

```
    # 坡度 °
    aspect = db.Column(db.String(16), nullable=True)
    # 坡向：阳坡 / 阴阳坡 / 阴坡
    def heavy_metals_dict(self):
        return json.loads(self.heavy_metals) if
    self.heavy_metals else {}
class EvaluationResult(db.Model):
    """评价结果。"""
    __tablename__ = "evaluation_results"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    final_score = db.Column(db.Float, nullable=True)
    # 最终评价因子 F
    grade = db.Column(db.String(32), nullable=True)
    # 适宜性等级
    measures = db.Column(db.Text, nullable=True)
    # 推荐措施
    unit_scores = db.Column(db.Text, nullable=True)
    # 各单元得分 JSON
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow)
class ScoreDetail(db.Model):
    """得分明细：每一层指标的权重、标准化值、加权贡献，供追溯与复核。"""
    __tablename__ = "score_details"
    id = db.Column(db.Integer, primary_key=True)
    result_id = db.Column(db.Integer,
    db.ForeignKey("evaluation_results.id"), nullable=False)
    unit_id = db.Column(db.Integer, nullable=True)
    l1_name = db.Column(db.String(64), nullable=True)
    # 一级指标
    l2_name = db.Column(db.String(64), nullable=True)
    # 二级指标
    raw_value = db.Column(db.String(64), nullable=True)
    # 实测值
    std_value = db.Column(db.Float, nullable=True)
    # 标准化值
    weight = db.Column(db.Float, nullable=True)
    # 权重
    contribution = db.Column(db.Float, nullable=True)
    # 加权贡献
# ==== app/forms.py ====
# -*- coding: utf-8 -*-
"""表单定义（共享，由甲统一维护）。
各模块的 Flask-WTF 表单集中于此。
"""
from flask_wtf import FlaskForm
from wtforms import SelectField, SubmitField, StringField,
    PasswordField, BooleanField
from wtforms.validators import DataRequired, Length
```

```
from app.utils.constants import UNIT_TYPES, ASPECT_TYPES
class AHPSelectForm(FlaskForm):
    """选择微地质单元类型与指标层级，以确定判断矩阵规模。"""
    unit_type = SelectField("微地质单元类型",
    validators=[DataRequired()])
    level = SelectField("指标层级",
                        choices=[("1", "一级指标"), ("2",
    "二级指标")],
                        validators=[DataRequired()])
    l1 = SelectField("一级指标", validators=[],
    validate_choice=False)  # 动态填充，层级=2 时使用
    submit = SubmitField("生成判断矩阵")
    def __init__(self, *args, **kwargs):
        super().__init__(*args, **kwargs)
        self.unit_type.choices = [(t, t) for t in
    UNIT_TYPES]
class EmptyForm(FlaskForm):
    """仅用于承载 CSRF 令牌的空表单（矩阵录入等自定义表单使用）。"""
    pass
class LoginForm(FlaskForm):
    """登录表单。支持「记住我」以在关闭浏览器后保持登录状态。"""
    username = StringField("用户名", validators=[DataRequired()
    , Length(max=64)])
    password = PasswordField("密码", validators=[DataRequired(
    )])
    remember = BooleanField("记住我")
    submit = SubmitField("登录")
# ==== app/utils/constants.py ====
# -*- coding: utf-8 -*-
"""评价指标常量表。
全部数值取自论文，作为系统计算的唯一基准：
- 论文 4.2.2 节：指标标准化理想极值与取值依据
- 论文 4.2.3 节 / 表 4：适宜性等级划分
- 论文表 3：按微地质单元分别确定的一级、二级指标权重
- 论文 4.2.1 节：平均随机一致性指标 RI
"""
# ------------------------------------------------------------------
    ------------------
# 一、微地质单元类型
# ------------------------------------------------------------------
    ------------------
# 论文 4.1 节："按照地形地貌划分，将其划分为平台、碎石边坡和岩质边坡
# 三种地质微单元类型"
UNIT_TYPES = ("岩质边坡", "碎石边坡", "平台")
# 每个单元类型启用的指标类别（论文表 3 隐含：岩质边坡无土壤指标，平台无地形指标）
# 供数据录入界面与评价引擎判断"该单元是否需要某类指标"
UNIT_ENABLED_INDICATORS = {
    "岩质边坡": ("植被指标", "地形指标"),                  # 不设土壤指标
    "碎石边坡": ("土壤指标", "植被指标", "地形指标"),
    "平台": ("土壤指标", "植被指标"),                      # 不设地形指标
```

```
}
# ----------------------------------------------------------------------
    ------------------
# 二、指标标准化理想极值（论文 4.2.2 节）
# ----------------------------------------------------------------------
    ------------------
IDEAL_SOIL_RATIO = 0.8          # 土石比理想值
IDEAL_THICKNESS = 20.0          # 土层厚度理想值 （cm）
IDEAL_PH_RANGE = （5.0, 9.0）    # pH 理想区间（适中型指标）
IDEAL_ORGANIC = 30.0            # 有机质理想值
    （g/kg），全国第二次土壤普查养分等级划分标准二等最低值
IDEAL_COVERAGE = 75.0           # 植被覆盖度参照生态系统 （%）
IDEAL_SHANNON = 0.7             # Shannon-Wiener 多样性指数参照生态系统
# 重金属极值 （mg/kg），《绿化种植土壤》CJ/T 340—2016 土壤重金属含量 IV 级最高值
# 论文原文：镉、汞、铅、铬、砷、镍、铜、锌分别为 2、2、530、400、45、220、600、800
HEAVY_METALS = （"Cd", "Hg", "Pb", "Cr", "As", "Ni", "Cu",
    "Zn"）
HEAVY_METAL_LIMIT = {
    "Cd": 2.0, "Hg": 2.0, "Pb": 530.0, "Cr": 400.0,
    "As": 45.0, "Ni": 220.0, "Cu": 600.0, "Zn": 800.0,
}
# 污染指标下 8 种重金属"重要性相当，权重平均分配"（论文 4.2.1 节）
HEAVY_METAL_EQUAL_WEIGHT = 1.0 / 8.0
# 坡度分界，论文 4.2.2 节引《新一轮退耕还林还草总体方案》发改西部〔2014〕1772 号
SLOPE_BREAK = 25.0
# 坡向离散赋值，论文 4.2.2 节："阳坡、阴阳坡、阴坡分别赋值 0.2、0.6、1"
ASPECT_SCORES = {"阳坡": 0.2, "阴阳坡": 0.6, "阴坡": 1.0}
ASPECT_TYPES = （"阳坡", "阴阳坡", "阴坡"）
# pH 适中型标准化的容差边界（区间外线性衰减，避免得分突变）
PH_TOL_LOW = 4.0
PH_TOL_HIGH = 10.0
# ----------------------------------------------------------------------
    ------------------
# 三、适宜性等级划分（论文表 4）
# ----------------------------------------------------------------------
    ------------------
GRADE_LEVELS = (
    {"grade": "不适宜", "min": None, "max": 0.3,
     "meaning": "存在限制性条件或区域生态本底较差，自然恢复影响因子严重制约自然恢复",
     "measure": "生态重建、人工辅助"},
    {"grade": "基本适宜", "min": 0.3, "max": 0.7,
     "meaning": "生态本底良好，核心自然恢复影响因子基本满足自然恢复需求",
     "measure": "自然恢复为主，可辅以封闭场地和少量补种、补植、飞播等"},
    {"grade": "适宜", "min": 0.7, "max": None,
     "meaning": "各自然恢复影响因子均能满足自然恢复需求，自然演替速度快",
     "measure": "自然恢复"},
)
def grade_of(score):
    """按论文表 4 判定适宜性等级。"""
    for g in GRADE_LEVELS:
```

```
            lo, hi = g["min"], g["max"]
            if lo is None and score < hi:
                return g
            if hi is None and score >= lo:
                return g
            if lo is not None and hi is not None and lo <=
      score < hi:
                return g
      # score 恰好等于 0.7 时落入"适宜"
      return GRADE_LEVELS[-1]
# ------------------------------------------------------------------
      ------------------
# 四、平均随机一致性指标 RI（论文 4.2.1 节给出 n=2,3,4,5，其余为常用扩展值）
# ------------------------------------------------------------------
      ------------------
RI_TABLE = {1: 0.0, 2: 0.0, 3: 0.58, 4: 0.90, 5: 1.12, 6:
      1.24,
                7: 1.32, 8: 1.41, 9: 1.45, 10: 1.49}
# 一致性比例阈值（论文：当 CR<0.1 时，判断矩阵满足一致性要求）
CR_THRESHOLD = 0.1
# ------------------------------------------------------------------
      ------------------
# 五、默认权重方案（论文表 3）
# ------------------------------------------------------------------
      ------------------
# 论文明确："划分岩质边坡、碎石土边坡、平台三类微地质单元开展独立评价，
# 分别计算评价指标权重"。权重由 10 位专家打分后经 AHP 方法确定。
# 下表为论文表 3 所载的归一化权重，作为系统默认方案。
DEFAULT_WEIGHTS = {
      "岩质边坡": {
            "l1": {"植被指标": 0.45, "地形指标": 0.55},
            "l2": {
                "植被指标": {"植被覆盖度": 0.67, "生物多样性": 0.33},
                "地形指标": {"坡度": 0.64, "坡向": 0.36},
            },
      },
      "碎石边坡": {
            "l1": {"土壤指标": 0.44, "植被指标": 0.31, "地形指标": 0.25},
            "l2": {
                "土壤指标": {"土石比": 0.25, "土层厚度": 0.25, "pH": 0.17,
                                "有机质": 0.17, "污染指标": 0.17},
                "植被指标": {"植被覆盖度": 0.64, "生物多样性": 0.36},
                "地形指标": {"坡度": 0.67, "坡向": 0.33},
            },
      },
      "平台": {
            "l1": {"土壤指标": 0.54, "植被指标": 0.46},
            "l2": {
                "土壤指标": {"土石比": 0.25, "土层厚度": 0.25, "pH": 0.17,
                                "有机质": 0.17, "污染指标": 0.17},
```

```
                "植被指标": {"植被覆盖度": 0.61, "生物多样性": 0.39},
            },
        },
}
# ------------------------------------------------------------------------
    ------------------
# 六、限制性指标（论文表 2 + 4.1 节流程）
# ------------------------------------------------------------------------
    ------------------
# 论文摘要与 4.1 节：四项限制性指标；流程段另明确"是否为耕地"为约束条件
CONSTRAINT_ITEMS = ("政策", "区位约束", "土壤污染", "地质灾害", "耕地属性")
# ==== app/utils/schema.py ====
# -*- coding: utf-8 -*-
"""轻量结构迁移。
SQLite 下 `db.create_all()` 只建缺失的表，不会给已有表补列。
本模块在启动时检查目标列是否存在，缺失则 ALTER TABLE 补上，
使旧数据库无需重建即可用上新字段。
"""
from sqlalchemy import text
# (表名, 列名, 列定义)
REQUIRED_COLUMNS = [
    # 遥感影像挂接
    ("mine_patches", "image_path", "VARCHAR(256)"),
    ("mine_patches", "image_note", "VARCHAR(256)"),
    ("mine_patches", "image_uploaded_at", "DATETIME"),
    # 指标维护
    ("indicators", "enabled_units", "VARCHAR(128)"),
    ("indicators", "description", "TEXT"),
    # 多专家矩阵
    ("expert_matrices", "unit_type", "VARCHAR(32)"),
    ("expert_matrices", "l1_name", "VARCHAR(64)"),
    ("expert_matrices", "cr", "FLOAT"),
]
def ensure_schema(db):
    """为已有表补齐缺失列。返回补列清单。"""
    added = []
    try:
        with db.engine.connect() as conn:
            for table, column, ddl in REQUIRED_COLUMNS:
                rows = conn.execute(text("PRAGMA
    table_info(%s)" % table)).fetchall()
                if not rows:
                    continue                                #
    表还不存在，create_all 会建
                existing = {r[1] for r in rows}
                if column in existing:
                    continue
                conn.execute(text(
                    "ALTER TABLE %s ADD COLUMN %s %s" %
    (table, column, ddl)))
```

```
                    conn.commit()                                          701
                    added.append("%s.%s" % (table, column))                702
        except Exception as e:                                  #          703
        迁移失败不应阻断启动                                                 704
            print("[schema] 结构检查跳过：%s" % e)                          705
        return added                                                       706
# ==== app/utils/uploads.py ====                                           707
# -*- coding: utf-8 -*-                                                    708
"""上传文件处理（遥感影像、批量导入）。"""                                    709
import os                                                                  710
import re                                                                  711
import uuid                                                                712
from datetime import datetime                                              713
from werkzeug.utils import secure_filename                                 714
def _safe_ext(filename):                                                   715
    return os.path.splitext(filename)[1].lower().lstrip(".")               716
def ext_allowed(filename, allowed):                                        717
    return _safe_ext(filename) in allowed                                  718
def save_upload(file_storage, subdir, allowed_ext,                         719
    upload_root):                                                          720
    """保存上传文件，返回相对 static 的路径（如 uploads/patches/xxx.png）。    721
    文件名重命名为「时间戳_随机串.扩展名」，避免中文名与重名问题。                 722
    """                                                                    723
    if file_storage is None or not file_storage.filename:                  724
        return None, "未选择文件"                                          725
    ext = _safe_ext(file_storage.filename)                                 726
    if ext not in allowed_ext:                                             727
        return None, "不支持的文件类型：.%s" % ext                          728
    target_dir = os.path.join(upload_root, subdir)                         729
    os.makedirs(target_dir, exist_ok=True)                                 730
    # 仅保留安全字符，并加时间戳与随机串防重名                                  731
    base = secure_filename(os.path.splitext(file_storage.fil               732
    ename)[0]) or "file"                                                   733
    base = re.sub(r"[^A-Za-z0-9_\-]", "", base)[:40] or                    734
    "file"                                                                 735
    name = "%s_%s.%s" % (datetime.now().strftime("%Y%m%d%H%M               736
    %S"),                                                                  737
                         uuid.uuid4().hex[:6], ext)                        738
    abs_path = os.path.join(target_dir, name)                              739
    file_storage.save(abs_path)                                            740
    rel = os.path.join("uploads", subdir,                                  741
    name).replace("\\", "/")                                               742
    return rel, None                                                       743
def remove_upload(rel_path, upload_root):                                  744
    """删除已保存的上传文件（相对 static 的路径）。"""                          745
    if not rel_path:                                                       746
        return                                                             747
    abs_path = os.path.join(upload_root,                                   748
    rel_path.replace("uploads/", "", 1))                                   749
    try:                                                                   750
```

```
            if os.path.isfile(abs_path):
                os.remove(abs_path)
        except OSError:
            pass
# ==== app/utils/charts.py ====
# -*- coding: utf-8 -*-
"""轻量图表。
用纯 SVG 输出，不依赖任何绘图库或前端脚本：
- 服务端渲染，页面与打印（PDF）中都能稳定显示
- 每个图元都带数值标签，黑白打印时仍可读（不单靠颜色区分）
- 单色方案，符合界面「一个视图一个强调色」的约定
"""
from html import escape
ACCENT = "#1f3a5f"
ACCENT_SOFT = "#7f93ad"
INK = "#23262b"
MUTED = "#6b7280"
LINE = "#dfe3e8"
# 灰度梯度：黑白打印时相邻扇区 / 条柱仍可区分
GRAYS = ["#1f3a5f", "#456188", "#6d86a8", "#96a9c4",
         "#bcc9da", "#dbe3ec"]
def _fmt(v, digits=4):
    try:
        return ("%%.%df" % digits) % float(v)
    except (TypeError, ValueError):
        return str(v)
def hbars(items, width=620, bar_h=22, gap=12, label_w=150,
          value_w=76):
    """水平条形图。items: [(标签, 数值, 显示文本)]"""
    if not items:
        return '<p class="muted">暂无数据</p>'
    n = len(items)
    height = n * (bar_h + gap) + 10
    max_v = max((abs(float(v)) for _, v, _ in items),
                default=1) or 1
    body_w = width - label_w - value_w
    parts = ['<svg viewBox="0 0 %d %d" width="100%%"
             'height="%d" '
             'role="img" aria-label="条形图" '
             'style="max-width:%dpx;font-family:inherit;">'
            % (width, height, height, width)]
    for i, (label, value, disp) in enumerate(items):
        y = i * (bar_h + gap) + 5
        frac = (abs(float(value)) / max_v) if max_v else 0
        w = max(2.0, body_w * frac)
        fill = GRAYS[i % len(GRAYS)]
        parts.append(
            '<text x="%d" y="%d" text-anchor="end"
            'font-size="12" fill="%s">%s</text>'
            % (label_w - 10, y + bar_h * 0.72, INK,
```

```
    escape(str(label))))                                                    801
        parts.append(                                                       802
            '<rect x="%d" y="%d" width="%.1f" height="%d"                   803
    rx="3" fill="%s"/>'                                                     804
            % (label_w, y, w, bar_h, fill))                                 805
        parts.append(                                                       806
            '<text x="%d" y="%d" font-size="12" fill="%s" '                 807
            'style="font-variant-numeric:tabular-nums;">%s</               808
    text>'                                                                  809
            % (label_w + w + 8, y + bar_h * 0.72, MUTED,                    810
    escape(str(disp))))                                                     811
    parts.append('</svg>')                                                  812
    return "".join(parts)                                                   813
def donut(items, size=210, thickness=34):                                   814
    """环形图（权重分布）。items: [(标签, 数值, 显示文本)]                  815
    图例中给出数值与占比，黑白打印时靠图例与灰度深浅区分。                  816
    """                                                                     817
    vals = [(l, float(v), d) for l, v, d in items if                        818
    float(v) > 0]                                                           819
    if not vals:                                                            820
        return '<p class="muted">暂无数据</p>'                              821
    total = sum(v for _, v, _ in vals) or 1                                 822
    r = (size - thickness) / 2                                              823
    cx = cy = size / 2                                                      824
    import math                                                             825
    parts = ['<svg viewBox="0 0 %d %d" width="%d"                           826
    height="%d" role="img" '                                                827
             'aria-label="权重分布环形图">' % (size, size, size,            828
    size)]                                                                  829
    angle = -math.pi / 2                                                    830
    for i, (label, v, disp) in enumerate(vals):                             831
        sweep = 2 * math.pi * (v / total)                                   832
        a0, a1 = angle, angle + sweep                                       833
        x0, y0 = cx + r * math.cos(a0), cy + r *                            834
    math.sin(a0)                                                            835
        x1, y1 = cx + r * math.cos(a1), cy + r *                            836
    math.sin(a1)                                                            837
        large = 1 if sweep > math.pi else 0                                 838
        parts.append(                                                       839
            '<path d="M %.2f %.2f A %.2f %.2f 0 %d 1 %.2f                   840
    %.2f" '                                                                 841
            'fill="none" stroke="%s" stroke-width="%d"/>'                   842
            % (x0, y0, r, r, large, x1, y1, GRAYS[i %                       843
    len(GRAYS)], thickness))                                                844
        angle = a1                                                          845
    parts.append('<text x="%d" y="%d" text-anchor="middle"                  846
    font-size="12" '                                                        847
                 'fill="%s">合计</text>' % (cx, cy - 2,                     848
    MUTED))                                                                 849
    parts.append('<text x="%d" y="%d" text-anchor="middle"                  850
```

```
    font-size="15" '                                                    851
                   'fill="%s" style="font-variant-numeric:tabu          852
    lar-nums;">%s</text>'                                               853
                   % (cx, cy + 18, INK, _fmt(total, 4)))                854
    parts.append('</svg>')                                              855
    legend = ['<table style="width:auto;margin-top:10px;"><t            856
    head><tr>'                                                          857
              '<th scope="col">项目</th><th                             858
    scope="col">数值</th>'                                              859
              '<th scope="col">占比</th></tr></thead><tbody>']          860
    for i, (label, v, disp) in enumerate(vals):                         861
        legend.append(                                                  862
            '<tr><td style="text-align:left;">'                         863
            '<span style="display:inline-block;width:10px;he            864
    ight:10px;'                                                         865
            'border-radius:2px;background:%s;margin-right:6p            866
    x;"></span>%s</td>'                                                 867
            '<td class="mono">%s</td><td                                868
    class="mono">%.1f%%</td></tr>'                                      869
          % (GRAYS[i % len(GRAYS)], escape(str(label)),                 870
    escape(str(disp)),                                                  871
             100.0 * v / total))                                        872
    legend.append('</tbody></table>')                                   873
    return ('<div style="display:flex;flex-wrap:wrap;gap:20p            874
    x;align-items:center;">'                                            875
            + "".join(parts) + "".join(legend) + '</div>')              876
# ==== app/utils/browser.py ====                                        877
# -*- coding: utf-8 -*-                                                 878
"""HTML 转 PDF（报告导出）。                                            879
复用本机已安装的 Chrome/Edge 无头模式打印，避免引入 reportlab、          880
weasyprint 等额外依赖。生成过程使用系统临时目录中的 ASCII 文件名，       881
避免中文路径在 file:// URL 下出问题。                                   882
"""                                                                     883
import os                                                               884
import shutil                                                           885
import subprocess                                                       886
import tempfile                                                         887
import uuid                                                             888
CANDIDATES = [                                                          889
    r"C:\Program Files\Google\Chrome\Application\chrome.exe"            890
    ,                                                                   891
    r"C:\Program Files (x86)\Google\Chrome\Application\chrom            892
    e.exe",                                                             893
    r"C:\Program Files (x86)\Microsoft\Edge\Application\msed            894
    ge.exe",                                                            895
    r"C:\Program Files\Microsoft\Edge\Application\msedge.exe            896
    ",                                                                  897
]                                                                       898
# 允许通过环境变量覆盖，便于在其他机器上指定浏览器                      899
ENV_KEY = "DSH_BROWSER_PATH"                                            900
```

```
def browser_path():
    """定位可用的浏览器可执行文件，找不到返回 None。"""
    override = os.environ.get(ENV_KEY)
    if override and os.path.isfile(override):
        return override
    for p in CANDIDATES:
        if os.path.isfile(p):
            return p
    for name in ("chrome", "msedge", "chromium"):
        found = shutil.which(name)
        if found:
            return found
    return None
def html_to_pdf(html, timeout=90):
    """把 HTML 字符串渲染为 PDF，返回字节；失败返回 (None, 原因)。"""
    exe = browser_path()
    if exe is None:
        return None, ("未找到可用的浏览器（Chrome/Edge），无法生成 PDF。"
                      "可设置环境变量 %s 指向浏览器可执行文件。" % ENV_KEY)
    tmpdir = tempfile.mkdtemp(prefix="dshpdf_")
    tag = uuid.uuid4().hex[:8]
    html_path = os.path.join(tmpdir, "r_%s.html" % tag)
    pdf_path = os.path.join(tmpdir, "r_%s.pdf" % tag)
    try:
        with open(html_path, "w", encoding="utf-8") as f:
            f.write(html)
        cmd = [
            exe, "--headless=new", "--disable-gpu",
    "--no-sandbox",
            "--no-first-run", "--no-default-browser-check",
            "--no-pdf-header-footer",
            "--virtual-time-budget=4000",
            "--print-to-pdf=%s" % pdf_path,
            "file:///" + html_path.replace("\\", "/"),
        ]
        p = subprocess.run(cmd, capture_output=True,
    text=True,
                           timeout=timeout,
    encoding="utf-8", errors="replace")
        if not os.path.isfile(pdf_path) or
    os.path.getsize(pdf_path) < 800:
            return None, "浏览器未能生成 PDF（%s）" % (p.stderr or
    "").strip()[:200]
        with open(pdf_path, "rb") as f:
            return f.read(), None
    except subprocess.TimeoutExpired:
        return None, "生成 PDF 超时，请稍后重试"
    except Exception as e:
        return None, "生成 PDF 失败：%s" % e
    finally:
```

```
            shutil.rmtree(tmpdir, ignore_errors=True)
# ==== app/services/ahp_service.py ====
# -*- coding: utf-8 -*-
"""AHP 权重引擎。
严格按论文 4.2.1 节实现：
- 式(2)(3)(4)：特征根法求权重（行元素乘积 → n 次方根 → 归一化）
- 式(5)(6)(7)：一致性检验（λmax、CI、CR）
- 论文要求 CR < 0.1；RI 按阶数查表
"""
import numpy as np
from app.utils.constants import RI_TABLE, CR_THRESHOLD
def matrix_from_upper(upper):
    """由判断矩阵上三角构造完整互反矩阵。
    参数
    ----
    upper : list[list[float]] 或 np.ndarray，上三角元素（不含对角线）。
        例：3 阶时传入 [[a12, a13], [a23]]。
        对角线为 1，下三角取倒数（a_ji = 1/a_ij）。
    """
    upper = np.asarray(upper, dtype=float)
    k = upper.shape[0]
    n = int(round((1 + (1 + 8 * k) ** 0.5) / 2))
    A = np.ones((n, n), dtype=float)
    idx = 0
    for i in range(n):
        for j in range(i + 1, n):
            A[i, j] = upper[idx]
            A[j, i] = 1.0 / upper[idx]
            idx += 1
    return A
def weights_and_consistency(A):
    """由判断矩阵 A 计算权重与一致性指标。
    返回
    ----
    dict：{weights: np.ndarray, lambda_max, ci, cr, n,
    consistent: bool}
    """
    A = np.asarray(A, dtype=float)
    n = A.shape[0]
    # 式(2) 行元素乘积
    row_prod = np.prod(A, axis=1)
    # 式(3) 开 n 次方根
    root = row_prod ** (1.0 / n)
    # 式(4) 归一化
    weights = root / root.sum()
    # 式(5) 最大特征值 λmax = (1/n) Σ (A·W)_i / W_i
    aw = A.dot(weights)
    lambda_max = float(np.sum(aw / weights) / n)
    # 式(6) 一致性指标 CI
    ci = (lambda_max - n) / (n - 1) if n > 1 else 0.0
```

```
    # 式(7) 一致性比例 CR = CI / RI
    ri = RI_TABLE.get(n, 1.49)
    cr = ci / ri if ri else 0.0
    return {
        "weights": weights,
        "lambda_max": lambda_max,
        "ci": ci,
        "cr": cr,
        "n": n,
        "consistent": cr < CR_THRESHOLD,
    }
def find_most_inconsistent(A):
    """定位判断矩阵中最不一致的一对比较。
    依据：完全一致矩阵应满足 a_ij = w_i / w_j。
    计算每个上三角元素与其理想值的相对偏差，返回偏差最大者。
    返回
    ----
    dict：{i, j, value, expected, deviation}，偏差最大的 (i, j)
    及对应取值。
    """
    A = np.asarray(A, dtype=float)
    r = weights_and_consistency(A)
    w = r["weights"]
    n = A.shape[0]
    best = None
    for i in range(n):
        for j in range(i + 1, n):
            expected = w[i] / w[j]
            if expected == 0:
                continue
            deviation = abs(A[i, j] - expected) / expected
            if best is None or deviation >
    best["deviation"]:
                best = {"i": i, "j": j, "value": A[i, j],
                        "expected": expected, "deviation":
    deviation}
    return best
def aggregate_matrices(matrices):
    """多专家判断矩阵聚合：几何平均（保持互反性）。
    参数
    ----
    matrices : list[np.ndarray]，多个同阶判断矩阵。
    """
    stack = np.stack([np.asarray(m, dtype=float) for m in
    matrices])
    return np.prod(stack, axis=0) ** (1.0 / len(stack))
def judge_from_weights(weights):
    """由权重向量构造完全一致判断矩阵并检验。
    用途：验证给定权重向量能否作为某个完全一致判断矩阵的主特征向量
    （A_ij = w_i / w_j 时 λmax = n、CR = 0）。
```

```
    """
    w = np.asarray(weights, dtype=float)
    n = w.shape[0]
    A = np.outer(w, 1.0 / w)
    r = weights_and_consistency(A)
    r["matrix"] = A
    return r
# ==== app/services/standardization.py ====
# -*- coding: utf-8 -*-
"""指标标准化（的一部分）。
按论文 4.2.2 节式(8) 实现：
    x' = (x - x_min) / (x_max - x_min)
按指标性质分为四类：越大越优 / 越小越优 / 适中 / 离散赋值。
所有理想极值取自 app.utils.constants，可配置。
"""
from app.utils.constants import (
    IDEAL_SOIL_RATIO, IDEAL_THICKNESS, IDEAL_PH_RANGE,
    IDEAL_ORGANIC,
    IDEAL_COVERAGE, IDEAL_SHANNON, HEAVY_METAL_LIMIT,
    HEAVY_METAL_EQUAL_WEIGHT, SLOPE_BREAK, ASPECT_SCORES,
    PH_TOL_LOW, PH_TOL_HIGH,
)
def std_benefit(value, ideal):
    """越大越优指标标准化：以理想值为上限，按比例给分，饱和于 [0,1]。"""
    if value is None:
        return None
    return max(0.0, min(1.0, value / ideal))
def std_cost(value, extreme):
    """越小越优指标标准化：以极值为参考，线性折减至 [0,1]。"""
    if value is None:
        return None
    return max(0.0, min(1.0, 1.0 - value / extreme))
def std_mid_ph(value, lo, hi, tol_lo=PH_TOL_LOW,
    tol_hi=PH_TOL_HIGH):
    """适中型指标标准化（pH）：理想区间内取 1，区间外线性衰减。"""
    if value is None:
        return None
    if lo <= value <= hi:
        return 1.0
    if value > hi:
        return max(0.0, (tol_hi - value) / (tol_hi - hi))
    return max(0.0, (value - tol_lo) / (lo - tol_lo))
def std_slope(value, break_point=SLOPE_BREAK, upper=90.0):
    """坡度标准化。
    论文 4.2.2 节：以 25° 为陡坡重要分界。25° 及以下记满分 1，
    超过 25° 线性折减，90° 记 0。
    """
    if value is None:
        return None
    if value <= break_point:
```

```
        return 1.0                                                    1101
    return max(0.0, (upper - value) / (upper - break_point))         1102
def aspect_score(aspect):                                             1103
    """坡向离散赋值：阳坡 0.2 / 阴阳坡 0.6 / 阴坡 1.0（论文 4.2.2 节）。"""  1104
    if aspect is None:                                                1105
        return None                                                   1106
    return ASPECT_SCORES.get(aspect)                                  1107
def pollution_score(heavy_metals):                                    1108
    """污染指标：8 种重金属等权（各 0.125）合成。                          1109
    论文注：未检测 Cr、Zn 的，从矿山类型看未受污染，按无污染（=1）处理。          1110
    heavy_metals : dict，键为金属名，值为含量 mg/kg；缺失键视为未检测。          1111
    """                                                               1112
    total = 0.0                                                       1113
    for metal, extreme in HEAVY_METAL_LIMIT.items():                  1114
        value = heavy_metals.get(metal)                               1115
        total += std_cost(value, extreme) if value is not             1116
    None else 1.0                                                     1117
    return total / len(HEAVY_METAL_LIMIT)                             1118
def standardize_unit(unit_type, data, weights=None):                  1119
    """对单个微地质单元的全部指标做标准化。                                 1120
    参数                                                              1121
    ----                                                              1122
    unit_type : str，岩质边坡 / 碎石边坡 / 平台                           1123
    data : dict，实测数据，字段见接口契约：                                 1124
        soil_ratio, thickness, ph, organic_matter,                    1125
    heavy_metals(dict),                                               1126
        coverage, shannon, slope, aspect                              1127
    weights : dict，该单元类型的权重（app.utils.constants.DEFAULT_WEIG  1128
    HTS 结构），                                                        1129
                未提供时用默认值。                                          1130
    返回                                                              1131
    ----                                                              1132
    dict：{ 一级指标： { 二级指标： （实测值， 标准化值， 权重， 贡献） } }          1133
    标准化值可能为 None，表示该指标不适用或方法待定。                          1134
    """                                                               1135
    from app.utils.constants import DEFAULT_WEIGHTS                   1136
    if weights is None:                                               1137
        weights = DEFAULT_WEIGHTS[unit_type]                          1138
    l1_enabled = weights["l1"].keys()                                 1139
    l2w = weights["l2"]                                               1140
    result = {}                                                       1141
    # ---- 土壤指标 ----                                              1142
    if "土壤指标" in l1_enabled:                                        1143
        result["土壤指标"] = {                                          1144
            "土石比": (data.get("soil_ratio"),                        1145
                       std_benefit(data.get("soil_ratio"),            1146
    IDEAL_SOIL_RATIO),                                                1147
                       l2w["土壤指标"]["土石比"]),                        1148
            "土层厚度": (data.get("thickness"),                       1149
                         std_benefit(data.get("thickness"),           1150
```

```
        IDEAL_THICKNESS),                                                    1151
                                l2w["土壤指标"]["土层厚度"]),                1152
                "pH": (data.get("ph"),                                       1153
                       std_mid_ph(data.get("ph"),                            1154
        *IDEAL_PH_RANGE),                                                    1155
                       l2w["土壤指标"]["pH"]),                               1156
                "有机质": (data.get("organic_matter"),                       1157
                           std_benefit(data.get("organic_matter")            1158
        , IDEAL_ORGANIC),                                                    1159
                           l2w["土壤指标"]["有机质"]),                       1160
                "污染指标": (data.get("heavy_metals") or {},                 1161
                             pollution_score(data.get("heavy_meta            1162
        ls") or {}),                                                         1163
                             l2w["土壤指标"]["污染指标"]),                   1164
            }                                                                1165
        # ---- 植被指标 ----                                                 1166
        if "植被指标" in l1_enabled:                                         1167
            result["植被指标"] = {                                           1168
                "植被覆盖度": (data.get("coverage"),                         1169
                               std_benefit(data.get("coverage"),             1170
        IDEAL_COVERAGE),                                                     1171
                               l2w["植被指标"]["植被覆盖度"]),               1172
                "生物多样性": (data.get("shannon"),                          1173
                               std_benefit(data.get("shannon"),              1174
        IDEAL_SHANNON),                                                      1175
                               l2w["植被指标"]["生物多样性"]),               1176
            }                                                                1177
        # ---- 地形指标 ----                                                 1178
        if "地形指标" in l1_enabled:                                         1179
            result["地形指标"] = {                                           1180
                "坡度": (data.get("slope"),                                  1181
                         std_slope(data.get("slope")),                       1182
                         l2w["地形指标"]["坡度"]),                           1183
                "坡向": (data.get("aspect"),                                 1184
                         aspect_score(data.get("aspect")),                   1185
                         l2w["地形指标"]["坡向"]),                           1186
            }                                                                1187
        return result                                                        1188
# ==== app/services/weight_service.py ====                                   1189
# -*- coding: utf-8 -*-                                                      1190
"""权重方案的存取与生效权重解析。                                            1191
系统有两套权重来源：                                                        1192
1. 论文表 3 给出的默认权重（app.utils.constants.DEFAULT_WEIGHTS），         1193
   是**权威取值来源**，案例复算与报告结论以此为准；                         1194
2. 通过层次分析法在本系统中实际算出的权重，保存在                           1195
   weight_schemes / weight_items 两张表中，可标记为「生效」。               1196
本模块负责把这两者合成为计算引擎直接可用的嵌套权重结构：                   1197
以论文表 3 为底，用生效方案中已保存的条目覆盖。                             1198
没有任何生效方案时，即完全使用论文表 3 的权重。                             1199
这样既保证默认行为与论文一致，又使 AHP 计算结果真正参与评价，               1200
```

```
而不是算完即弃。
"""
import copy
from app.models import db, WeightScheme, WeightItem
from app.utils.constants import DEFAULT_WEIGHTS
from app.services.indicator_service import TREE
#  方案名称：每个微地质单元类型固定一个可生效的方案
ACTIVE_NAME = "自定义权重方案（AHP 计算结果）"
def _code_maps():
    """由指标树导出 编码 → 名称 的映射，避免名称在两处各写一遍。"""
    l1, l2 = {}, {}
    for row in TREE:
        code, name, level, parent = row[0], row[1], row[2],
    row[3]
        if level == 1:
            l1[code] = name
        elif level == 2:
            l2[code] = (l1.get(parent, parent), name)
    return l1, l2
def effective_weights(unit_type):
    """返回该单元类型当前生效的权重。
    返回 (weights, source_label, scheme)
        weights       嵌套权重结构，可直接交给标准化与评价引擎
        source_label  权重来源说明，用于界面与报告标注
        scheme        生效的权重方案对象，无自定义方案时为 None
    """
    base = DEFAULT_WEIGHTS.get(unit_type)
    if base is None:
        return None, "未定义该微地质单元类型的权重", None
    scheme = WeightScheme.query.filter_by(unit_type=unit_typ
    e,

    name=ACTIVE_NAME).first()
    if scheme is None:
        return copy.deepcopy(base), "论文表 3 默认权重", None
    merged = copy.deepcopy(base)
    l1_map, l2_map = _code_maps()
    applied = 0
    for item in WeightItem.query.filter_by(scheme_id=scheme.
    id).all():
        code, w = item.indicator_code, item.weight
        if w is None or w <= 0:
            continue
        if code in l1_map and l1_map[code] in merged["l1"]:
            merged["l1"][l1_map[code]] = w
            applied += 1
        elif code in l2_map:
            l1_name, l2_name = l2_map[code]
            if l1_name in merged["l2"] and l2_name in
    merged["l2"][l1_name]:
```

```
                merged["l2"][l1_name][l2_name] = w                  1251
                applied += 1                                        1252
    if applied == 0:                                                1253
        return copy.deepcopy(base), "论文表 3 默认权重", None          1254
    return merged, "自定义方案（%d 项覆盖论文表 3）" % applied, scheme    1255
def save_weights(unit_type, code_weight_pairs, note=None):          1256
    """把一组「指标编码 → 权重」写入生效方案（已存在则更新对应条目）。          1257
    仅覆盖本次传入的条目，其余条目保留，便于分层次（一级 / 二级）              1258
    分次录入而无需一次填完。                                              1259
    """                                                             1260
    scheme = WeightScheme.query.filter_by(unit_type=unit_typ        1261
    e,                                                              1262
                                                                    1263
    name=ACTIVE_NAME).first()                                       1264
    if scheme is None:                                              1265
        scheme = WeightScheme(unit_type=unit_type,                  1266
    name=ACTIVE_NAME,                                               1267
                                  level=1, is_default=True)         1268
        db.session.add(scheme)                                      1269
        db.session.flush()                                          1270
    if note:                                                        1271
        scheme.level = scheme.level or 1                            1272
    if not scheme.is_default:                                       1273
        scheme.is_default = True                                    1274
    written = 0                                                     1275
    for code, w in code_weight_pairs:                               1276
        if w is None or w <= 0:                                     1277
            continue                                                1278
        item = WeightItem.query.filter_by(scheme_id=scheme.i        1279
    d,                                                              1280
                                                                    1281
    indicator_code=code).first()                                    1282
        if item is None:                                            1283
            item = WeightItem(scheme_id=scheme.id,                  1284
    indicator_code=code)                                            1285
            db.session.add(item)                                    1286
        item.weight = float(w)                                      1287
        written += 1                                                1288
    db.session.commit()                                             1289
    return scheme, written                                          1290
def reset_weights(unit_type):                                       1291
    """删除该单元类型的自定义方案，恢复为论文表 3 的默认权重。"""                1292
    schemes = WeightScheme.query.filter_by(unit_type=unit_ty        1293
    pe,                                                             1294
                                                                    1295
    name=ACTIVE_NAME).all()                                         1296
    n = 0                                                           1297
    for s in schemes:                                               1298
        WeightItem.query.filter_by(scheme_id=s.id).delete(          1299
            synchronize_session=False)                              1300
```

```
            db.session.delete(s)                                                1301
            n += 1                                                              1302
        db.session.commit()                                                     1303
        return n                                                                1304
def scheme_items(unit_type):                                                    1305
    """返回该单元类型已保存的自定义权重条目 {指标编码: 权重}。"""                    1306
    scheme = WeightScheme.query.filter_by(unit_type=unit_typ                    1307
    e,                                                                          1308
                                                                                1309
    name=ACTIVE_NAME).first()                                                   1310
    if scheme is None:                                                          1311
        return {}, None                                                         1312
    items = {i.indicator_code: i.weight                                         1313
             for i in WeightItem.query.filter_by(scheme_id=s                    1314
    cheme.id).all()}                                                            1315
    return items, scheme                                                        1316
def summary():                                                                  1317
    """各单元类型的权重来源概览，供权重首页展示。"""                              1318
    rows = []                                                                   1319
    for unit_type in DEFAULT_WEIGHTS:                                           1320
        weights, label, scheme = effective_weights(unit_type                    1321
    )                                                                           1322
        rows.append({                                                           1323
            "unit_type": unit_type,                                             1324
            "label": label,                                                     1325
            "custom": scheme is not None,                                       1326
        })                                                                      1327
    return rows                                                                 1328
# ==== app/services/evaluation_service.py ====                                  1329
# -*- coding: utf-8 -*-                                                         1330
"""适宜性评价引擎。                                                             1331
按论文式（9） 实现：                                                            1332
- 单元级：F' = Σ（二级指标权重 × 该二级指标下三级指标标准化值）                  1333
- 矿山级：F = Σ（Si × F'i），Si 为各微地质单元面积占比                          1334
- 等级判定按论文表 4。                                                          1335
"""                                                                             1336
from app.utils.constants import DEFAULT_WEIGHTS, grade_of                       1337
from app.services import standardization as std                                 1338
def score_unit(unit_type, data, weights=None):                                  1339
    """计算单个微地质单元的评价因子 F'。                                        1340
    返回                                                                        1341
    ----                                                                        1342
    dict：{ l1_scores: {一级指标: 得分}, unit_score: F', details:               1343
    [...] }                                                                     1344
    若某一级指标下存在"不适用"（标准化值为 None）的二级指标，                   1345
    则按其余项权重归一化后计算，保证单元得分始终有定义。                        1346
    """                                                                         1347
    if weights is None:                                                         1348
        weights = DEFAULT_WEIGHTS[unit_type]                                    1349
    std_result = std.standardize_unit(unit_type, data,                          1350
```

```
    weights)                                                              1351
    l1_weights = weights["l1"]                                            1352
    l1_scores = {}                                                        1353
    details = []                                                          1354
    for l1_name, items in std_result.items():                             1355
        wsum = 0.0                                                        1356
        acc = 0.0                                                         1357
        for l2_name, (raw, std_value, w2) in items.items():               1358
            if std_value is None:                                         1359
                # 不适用项：不计入                                        1360
                details.append({                                          1361
                    "l1": l1_name, "l2": l2_name, "raw":                  1362
raw,                                                                      1363
                    "std_value": None, "weight": w2,                      1364
"contribution": None,                                                     1365
                })                                                        1366
                continue                                                  1367
            contribution = std_value * w2                                 1368
            acc += contribution                                           1369
            wsum += w2                                                    1370
            details.append({                                              1371
                "l1": l1_name, "l2": l2_name, "raw": raw,                 1372
                "std_value": std_value, "weight": w2,                     1373
                "contribution": contribution,                             1374
            })                                                            1375
        l1_scores[l1_name] = acc / wsum if wsum > 0 else 0.0              1376
    # 一级指标权重按实际参与计算的指标归一化。                            1377
    # 论文表 3 的权重本身已归一（和为 1），此处为恒等变换；               1378
    # 若某层指标缺失或自定义权重不完整，可避免单元得分被整体压低。        1379
    lw_sum = sum(l1_weights[k] for k in l1_scores if k in                 1380
l1_weights)                                                               1381
    if lw_sum > 0:                                                        1382
        unit_score = sum(l1_weights[k] * l1_scores[k]                     1383
                         for k in l1_scores if k in                       1384
l1_weights) / lw_sum                                                      1385
    else:                                                                 1386
        unit_score = 0.0                                                  1387
    return {"l1_scores": l1_scores, "unit_score":                         1388
unit_score, "details": details}                                           1389
def score_mine(units, weights_map=None):                                  1390
    """计算整个矿山的评价因子 F 与适宜性等级。                            1391
    参数                                                                  1392
    ----                                                                  1393
    units : list[dict]，每个元素：                                        1394
        {unit_type, ratio, data}                                          1395
        ratio 为该单元面积占比（0~1），data 为实测数据 dict。             1396
    weights_map : dict，{单元类型： 权重结构}。未提供的单元类型           1397
        使用论文表 3 的默认权重。权重可来自 AHP 计算并经                  1398
        weight_service 保存生效，从而真正参与评价。                       1399
    返回                                                                  1400
```

```
    ----                                                                    1401
    dict:{ final_score, grade, grade_info, unit_results }                  1402
    """                                                                     1403
    weights_map = weights_map or {}                                         1404
    total = 0.0                                                             1405
    unit_results = []                                                       1406
    for u in units:                                                         1407
        r = score_unit(u["unit_type"], u["data"],                           1408
                       weights_map.get(u["unit_type"]))                     1409
        weighted = u["ratio"] * r["unit_score"]                             1410
        total += weighted                                                   1411
        unit_results.append({                                               1412
            "unit_type": u["unit_type"],                                    1413
            "ratio": u["ratio"],                                            1414
            "unit_score": r["unit_score"],                                  1415
            "weighted": weighted,                                           1416
            "l1_scores": r["l1_scores"],                                    1417
            "details": r["details"],                                        1418
        })                                                                  1419
    grade_info = grade_of(total)                                            1420
    return {                                                                1421
        "final_score": total,                                               1422
        "grade": grade_info["grade"],                                       1423
        "grade_info": grade_info,                                           1424
        "unit_results": unit_results,                                       1425
    }                                                                       1426
# ==== app/services/report_service.py ====                                  1427
# -*- coding: utf-8 -*-                                                     1428
"""报告生成：生成 Word 评价报告。                                            1429
依赖 python-docx。报告结构：                                                1430
标题 → 图斑信息 → 评价结论 → 各微地质单元得分 → 完整得分明细 → 生成时间。    1431
"""                                                                         1432
import io                                                                   1433
from datetime import datetime                                               1434
from docx import Document                                                   1435
from docx.shared import Pt, Cm                                              1436
from docx.oxml.ns import qn                                                 1437
from docx.enum.text import WD_ALIGN_PARAGRAPH                               1438
def _set_run(run, text=None, size=12, bold=False):                          1439
    if text is not None:                                                    1440
        run.text = text                                                     1441
    run.font.name = "Times New Roman"                                       1442
    run.font.size = Pt(size)                                                1443
    run.font.bold = bold                                                    1444
    # 中文字体                                                              1445
    run._element.rPr.rFonts.set(qn("w:eastAsia"), "宋体")                   1446
    return run                                                              1447
def _para(doc, text, size=12, bold=False, align=None,                       1448
    space_after=6):                                                         1449
    p = doc.add_paragraph()                                                 1450
```

```
    if align is not None:
        p.alignment = align
    p.paragraph_format.space_after = Pt(space_after)
    _set_run(p.add_run(), text, size, bold)
    return p
def _heading(doc, text, level=1):
    h = doc.add_heading(text, level=level)
    for run in h.runs:
        run.font.name = "Times New Roman"
        run._element.rPr.rFonts.set(qn("w:eastAsia"), "黑体")
    return h
def _table(doc, headers, rows, widths=None):
    t = doc.add_table(rows=1, cols=len(headers))
    t.style = "Table Grid"
    hdr = t.rows[0].cells
    for i, htext in enumerate(headers):
        _set_run(hdr[i].paragraphs[0].add_run(), htext,
    10.5, bold=True)
    for row in rows:
        cells = t.add_row().cells
        for i, val in enumerate(row):
            _set_run(cells[i].paragraphs[0].add_run(),
    str(val), 10.5)
    return t
def build_report(patch, mine_result):
    """生成评价报告 Word 文档，返回 BytesIO。
    参数
    ----
    patch : MinePatch，图斑对象
    mine_result : evaluation_service.score_mine 的返回 dict
    """
    doc = Document()
    # 页边距
    for section in doc.sections:
        section.top_margin = Cm(2.5)
        section.bottom_margin = Cm(2.5)
        section.left_margin = Cm(2.5)
        section.right_margin = Cm(2.5)
    _heading(doc, "历史遗留废弃矿山自然恢复适宜性评价报告", 0)
    _para(doc, "软件：历史遗留废弃矿山自然恢复适宜性评价系统 V1.0",
            size=10.5, align=WD_ALIGN_PARAGRAPH.CENTER)
    _para(doc, "生成时间：%s" % datetime.now().strftime("%Y-%m-%d
    %H:%M:%S"),
            size=10.5, align=WD_ALIGN_PARAGRAPH.CENTER,
    space_after=12)
    # 图斑信息
    _heading(doc, "一、图斑基本信息", 1)
    info = [
        ("图斑名称", patch.name),
        ("所在行政区", patch.admin_region or "—"),
```

```
    tables = sorted(db.metadata.tables.keys())
print("  已创建 %d 张表：" % len(tables))
for t in tables:
    print("    -", t)
print()
print(LINE)
print("全部测试通过 √")
print(LINE)
#  ==== 测试/test_evaluate.py ====
#  -*- coding: utf-8 -*-
"""评价引擎自检：用论文玉田县案例跑通完整计算链。"""
import sys
sys.stdout.reconfigure(encoding="utf-8")
import os
#  本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
#  使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app.services import evaluation_service as ev
from app.services import standardization as std
LINE = "=" * 70
#  ------------------------------------------------------------------
#  论文第 5 节案例数据（表 5，逐字抄录）
#  ------------------------------------------------------------------
#  三类单元面积占比：岩质边坡 13.86%、碎石边坡 62.95%、平台 23.19%
#  注：岩质边坡无土壤指标、平台无地形指标，对应"不适用"。
case = [
    {
        "unit_type": "岩质边坡",
        "ratio": 0.1386,
        "data": {
            "coverage": 68.88, "shannon": 0.00,
            "slope": 63.33, "aspect": "阴阳坡",
        },
    },
    {
        "unit_type": "碎石边坡",
        "ratio": 0.6295,
        "data": {
            "soil_ratio": 0.34, "thickness": 10, "ph":
9.24, "organic_matter": 4.89,
            "heavy_metals": {"Hg": 0.05, "As": 5.17, "Ni":
12.60,
                             "Cu": 11.70, "Cd": 0.04, "Pb":
6.50},
            "coverage": 87.92, "shannon": 0.60,
```

```
                "slope": 28.75, "aspect": "阳坡",
            },
        },
        {
            "unit_type": "平台",
            "ratio": 0.2319,
            "data": {
                "soil_ratio": 0.56, "thickness": 30, "ph":
    8.72, "organic_matter": 10.92,
                "heavy_metals": {"Hg": 0.02, "As": 3.13, "Ni":
    12.33,
                                 "Cu": 11.14, "Cd": 0.09, "Pb":
    9.98},
                "coverage": 58.42, "shannon": 0.72,
            },
        },
]
# ------------------------------------------------------------------
    ----------------
# 逐单元输出标准化与得分
# ------------------------------------------------------------------
    ----------------
print(LINE)
print("玉田县案例 · 评价引擎完整计算")
print(LINE)
for u in case:
    r = ev.score_unit(u["unit_type"], u["data"])
    print()
    print("  【%s】  (面积占比 %.2f%%)" % (u["unit_type"],
    u["ratio"] * 100))
    print("  " + "-" * 60)
    for l1, score in r["l1_scores"].items():
        print("    %s 得分 = %.4f" % (l1, score))
    print("    单元评价因子 F' = %.4f" % r["unit_score"])
print()
print(LINE)
print("面积加权合成（式(9)）")
print(LINE)
res = ev.score_mine(case)
total = res["final_score"]
print()
for ur in res["unit_results"]:
    print("  %s  %.2f%% × %.4f = %.4f"
          % (ur["unit_type"], ur["ratio"] * 100,
    ur["unit_score"], ur["weighted"]))
print("  " + "-" * 60)
print("  最终评价因子 F = %.4f" % total)
print()
print("  适宜性等级：%s" % res["grade"])
print("  判定依据  ：%s" % res["grade_info"]["meaning"])
```

```
print("   推荐措施   ：%s" % res["grade_info"]["measure"])
print()
print(LINE)
print("结论")
print(LINE)
print("   - 评价引擎按论文式（8）（9） 与表 3 权重完整跑通")
print("   - 坡度标准化采用论文 25° 分界的线性折减默认值（见 standardization.py）")
print("   - 最终 F ≈ %.2f，判定为「%s」，与论文「最终适宜自然恢复」的结论一致"
      % (total, res["grade"]))
print("   - 论文表 5 所载最终得分为 0.76；差异集中在坡度、坡向的标准化口径，")
print("     该口径在 standardization.std_slope / aspect_score
      中集中定义、可配置")
print(LINE)
# ==== 测试/test_web_ahp.py ====
# -*- coding: utf-8 -*-
"""AHP 网页界面自检：走通选择→录入→计算 全流程。"""
import sys
sys.stdout.reconfigure(encoding="utf-8")
import os
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file
    __)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
# 测试配置：关闭 CSRF 以简化测试客户端（真实运行仍开启 CSRF）
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///:memory:"
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
# 建立表并创建测试用户，登录后再访问业务页面
with app.app_context():
    from app.models import db, User
    from werkzeug.security import generate_password_hash
    db.create_all()
    if not User.query.filter_by(username="admin").first():
        db.session.add(User(username="admin",
                            password_hash=generate_password_
    hash("admin123"),
                            role="admin"))
        db.session.commit()
client.post("/login", data={"username": "admin",
    "password": "admin123"})
print(LINE)
```

```
print("测试 1  首页与 AHP 入口")
print(LINE)
r = client.get("/")
print("  首页状态码：", r.status_code, "（应 200）")
assert r.status_code == 200
r = client.get("/ahp/")
print("  AHP 入口状态码：", r.status_code, "（应 200）")
assert r.status_code == 200
assert "微地质单元类型" in r.get_data(as_text=True)
print()
print(LINE)
print("测试 2  选择碎石边坡一级指标 → 跳转矩阵页")
print(LINE)
r = client.post("/ahp/", data={
    "unit_type": "碎石边坡", "level": "1", "submit": "生成判断矩阵",
}, follow_redirects=True)
body = r.get_data(as_text=True)
print("  跳转后页面含「判断矩阵录入」：", "判断矩阵录入" in body)
print("  含三个一级指标（土壤/植被/地形）：", all(n in body for n in
    ("土壤指标", "植被指标", "地形指标")))
assert "判断矩阵录入" in body
assert all(n in body for n in ("土壤指标", "植被指标", "地形指标"))
print()
print(LINE)
print("测试 3  提交论文表 3 一致矩阵 → 还原权重")
print(LINE)
# 碎石边坡一级权重 (0.44, 0.31, 0.25) 对应的完全一致矩阵上三角：
# a12 = 0.44/0.31 = 1.4194, a13 = 0.44/0.25 = 1.76, a23 =
    0.31/0.25 = 1.24
r = client.post("/ahp/matrix?unit_type=碎石边坡&level=1", data={
    "m_0_1": "1.4194", "m_0_2": "1.76", "m_1_2": "1.24",
}, follow_redirects=True)
body = r.get_data(as_text=True)
print("  结果页含「计算结果」：", "计算结果" in body)
print("  含权重 0.44：", "0.44" in body, " 含 0.31：", "0.31" in
    body, " 含 0.25：", "0.25" in body)
print("  含一致性检验通过：", "通过" in body)
assert "计算结果" in body
assert "0.44" in body and "0.31" in body and "0.25" in body
print()
print(LINE)
print("测试 4  不一致矩阵应提示不通过并定位")
print(LINE)
# 明显不一致：a12=9, a13=1, a23=9
r = client.post("/ahp/matrix?unit_type=碎石边坡&level=1", data={
    "m_0_1": "9", "m_0_2": "1", "m_1_2": "9",
}, follow_redirects=True)
body = r.get_data(as_text=True)
print("  含「不通过」：", "不通过" in body)
print("  含「建议优先调整」：", "建议优先调整" in body)
```

```
assert "不通过" in body
assert "建议优先调整" in body
print()
print(LINE)
print("网页界面全部测试通过 √")
print(LINE)
# ==== 测试/test_web_modules.py ====
# -*- coding: utf-8 -*-
"""模块自检：登录、项目档案、微地质单元、标准库、限制性判定。"""
import os
import sys
sys.stdout.reconfigure(encoding="utf-8")
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(
        ROOT, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
print(LINE)
print("测试 1  未登录应被重定向到登录页")
print(LINE)
r = client.get("/project/")
print("  /project/ 状态码:", r.status_code, " 重定向到:",
    r.headers.get("Location"))
assert r.status_code == 302 and "login" in
    r.headers.get("Location", "")
print()
print(LINE)
print("测试 2  登录")
print(LINE)
r = client.post("/login", data={"username": "admin",
    "password": "admin123"},
                follow_redirects=True)
body = r.get_data(as_text=True)
print("  登录后含「系统功能」:", "系统功能" in body)
print("  含用户名 admin:", "admin" in body)
assert "系统功能" in body
print()
print(LINE)
```

```
print("测试 3  项目与矿山档案")
print(LINE)
r = client.get("/project/")
body = r.get_data(as_text=True)
print("  项目列表状态码：", r.status_code)
print("  含案例项目：", "玉田县典型历史遗留废弃矿山案例" in body)
assert "玉田县典型历史遗留废弃矿山案例" in body
# 新建项目
client.post("/project/add", data={"name": "测试项目A", "code":
    "T-001"})
r = client.get("/project/")
print("  新建项目后含「测试项目A」：", "测试项目A" in r.get_data(as_text=True
    ))
assert "测试项目A" in r.get_data(as_text=True)
# 清理测试数据，避免污染演示库
with app.app_context():
    from app.models import db, Project
    for p in Project.query.filter_by(name="测试项目A").all():
        db.session.delete(p)
    db.session.commit()
print("  已清理测试项目")
print()
print(LINE)
print("测试 4  微地质单元（面积占比自动计算）")
print(LINE)
from app.models import MinePatch
with app.app_context():
    patch = MinePatch.query.filter_by(name="玉田县孤树镇白云岩采石场").f
    irst()
    pid = patch.id
r = client.get("/unit/%d" % pid)
body = r.get_data(as_text=True)
print("  单元列表含三类单元：", all(t in body for t in ("岩质边坡",
    "碎石边坡", "平台")))
print("  含占比合计：", "占比合计" in body)
assert "岩质边坡" in body and "占比合计" in body
print()
print(LINE)
print("测试 5  标准知识库与省际口径比对")
print(LINE)
r = client.get("/standard/")
body = r.get_data(as_text=True)
print("  含辽宁/湖南/新疆标准：", all(p in body for p in ("辽宁", "湖南",
    "新疆")))
assert "辽宁" in body
r = client.get("/standard/compare")
body = r.get_data(as_text=True)
print("  口径比对页含「植被覆盖度」分组：", "植被覆盖度" in body)
print("  含多省份并列：", "湖南" in body and "新疆" in body)
assert "植被覆盖度" in body
```

```
print()
print(LINE)
print("测试 6  限制性指标判定（一票否决）")
print(LINE)
r = client.get("/constraint/%d" % pid)
body = r.get_data(as_text=True)
print("  含五项条件:", all(x in body for x in ("政策约束", "区位约束",
    "土壤污染", "地质灾害", "耕地属性")))
assert all(x in body for x in ("政策约束", "区位约束", "土壤污染",
    "地质灾害", "耕地属性"))
# 全部通过
client.post("/constraint/%d" % pid, data={
    "policy_pass": "1", "location_pass": "1",
    "pollution_pass": "1",
    "geo_pass": "1", "farmland_pass": "1"})
r = client.get("/constraint/%d" % pid)
body = r.get_data(as_text=True)
print("  全通过后显示「通过，可进入定量评价」:", "可进入定量评价" in body)
assert "可进入定量评价" in body
# 一项不通过
client.post("/constraint/%d" % pid, data={
    "policy_pass": "1", "location_pass": "0",
    "pollution_pass": "1",
    "geo_pass": "1", "farmland_pass": "1"})
r = client.get("/constraint/%d" % pid)
body = r.get_data(as_text=True)
print("  一项不通过后显示「不通过」:", "不通过" in body)
print("  含失败项「区位约束」:", "区位约束" in body)
assert "不通过" in body
# 恢复为全部通过，避免把演示数据留在「不通过」状态影响后续步骤
client.post("/constraint/%d" % pid, data={
    "policy_pass": "1", "location_pass": "1",
    "pollution_pass": "1",
    "geo_pass": "1", "farmland_pass": "1"})
r = client.get("/constraint/%d" % pid)
print("  已恢复为全部通过:", "可进入定量评价" in r.get_data(as_text=True))
print()
print(LINE)
print("全部测试通过 √")
print(LINE)
# ==== 测试/test_web_evaluate.py ====
# -*- coding: utf-8 -*-
"""端到端自检：录数据 → 执行评价 → 查看结果。"""
import os
import sys
sys.stdout.reconfigure(encoding="utf-8")
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
```

```
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
# 与真实配置共用同一个 app.db，但关闭 CSRF 便于测试客户端
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(
        ROOT, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
# 登录（案例种子已创建 admin 用户）
client.post("/login", data={"username": "admin",
    "password": "admin123"})
print(LINE)
print("测试 1  指标数据列表")
print(LINE)
r = client.get("/indicator/")
body = r.get_data(as_text=True)
print("  状态码：", r.status_code)
print("  含案例图斑：", "玉田县孤树镇白云岩采石场" in body)
print("  含三个单元：", all(n in body for n in ("岩质边坡", "碎石边坡",
    "平台")))
assert r.status_code == 200
assert "岩质边坡" in body and "碎石边坡" in body and "平台" in body
print()
print(LINE)
print("测试 2  指标数据录入页（按单元类型显示字段）")
print(LINE)
from app.models import MicroUnit, MinePatch
with app.app_context():
    unit_rock = MicroUnit.query.filter_by(unit_type="岩质边坡").
    first()
    unit_gravel = MicroUnit.query.filter_by(unit_type="碎石边坡"
    ).first()
r = client.get("/indicator/%d" % unit_rock.id)
b_rock = r.get_data(as_text=True)
print("  岩质边坡页：无「土石比」字段：", "土石比" not in b_rock, "（应 True）")
print("  岩质边坡页：含「植被覆盖度」：", "植被覆盖度" in b_rock)
assert "土石比" not in b_rock and "植被覆盖度" in b_rock
r = client.get("/indicator/%d" % unit_gravel.id)
b_gravel = r.get_data(as_text=True)
print("  碎石边坡页：含「土石比」字段：", "土石比" in b_gravel)
print("  碎石边坡页：含 8 种重金属：", all(m in b_gravel for m in
    ("Cd", "Hg", "Pb", "Cr", "As", "Ni", "Cu", "Zn")))
assert "土石比" in b_gravel and all(m in b_gravel for m in
    ("Cd", "Hg", "Pb", "Cr", "As", "Ni", "Cu", "Zn"))
```

```
print()
print(LINE)
print("测试 3  执行评价")
print(LINE)
with app.app_context():
    patch = MinePatch.query.first()
r = client.post("/evaluate/%d" % patch.id, data={},
    follow_redirects=True)
body = r.get_data(as_text=True)
print("  跳转至结果页：", "适宜性评价结果" in body)
print("  含最终评价因子 F：", "最终评价因子 F" in body)
print("  含等级「适宜」：", "适宜" in body)
print("  含推荐措施「自然恢复」：", "自然恢复" in body)
assert "最终评价因子 F" in body and "自然恢复" in body
print()
print(LINE)
print("测试 4  结果持久化")
print(LINE)
from app.models import EvaluationResult
with app.app_context():
    res = EvaluationResult.query.order_by(EvaluationResult.id.desc()).first()
    print("  最终得分 F =", res.final_score)
    print("  等级 =", res.grade)
    assert res.grade == "适宜"
    assert 0.7 <= res.final_score < 1.0
print()
print(LINE)
print("端到端全部测试通过 √")
print(LINE)
# ==== 测试/test_web_report.py ====
# -*- coding: utf-8 -*-
"""报告输出自检：得分明细页 + Word 导出。"""
import os
import sys
import io
sys.stdout.reconfigure(encoding="utf-8")
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(
        ROOT, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
```

```
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
# 登录（案例种子已创建 admin 用户）
client.post("/login", data={"username": "admin",
    "password": "admin123"})
from app.models import MinePatch, EvaluationResult
with app.app_context():
    patch = MinePatch.query.first()
    pid = patch.id
# 报告取自已保存的评价记录，因此先按网页路径真实执行一次评价
from app.views.evaluate import load_patch_input,
    save_evaluation
with app.app_context():
    units = load_patch_input(pid)
    rec = save_evaluation(pid, units)
    rid = rec.id
    print("前置：已执行评价并保存记录 id=%d，F=%.4f（%s）"
          % (rid, rec.final_score, rec.grade))
    from app.models import ScoreDetail
    n_detail = ScoreDetail.query.filter_by(result_id=rid).co
    unt()
    print("        逐层得分明细已落库：%d 条" % n_detail)
print()
print(LINE)
print("测试 1  报告列表")
print(LINE)
r = client.get("/report/")
print("  状态码：", r.status_code)
body = r.get_data(as_text=True)
print("  含「所属项目」列：", "所属项目" in body)
assert r.status_code == 200
print()
print(LINE)
print("测试 2  得分明细页")
print(LINE)
r = client.get("/report/%d" % pid)
body = r.get_data(as_text=True)
print("  状态码：", r.status_code)
print("  含「得分明细」：", "得分明细" in body)
print("  含「最终评价因子 F」：", "最终评价因子 F" in body)
print("  含二级指标明细（植被覆盖度 / 坡度 / 坡向）：", all(n in body for n in
    ("植被覆盖度", "坡度", "坡向")))
print("  含权重 / 标准化值列：", "标准化值" in body and "贡献" in body)
assert r.status_code == 200
assert "植被覆盖度" in body and "标准化值" in body
print()
print(LINE)
print("测试 3  Word 报告导出")
```

```
print(LINE)
r = client.get("/report/%d/word" % pid)
print("   状态码：", r.status_code)
print("   Content-Type:", r.headers.get("Content-Type",
    "")[:60])
data = r.data
print("   文件大小：", len(data), "字节")
print("   是否为有效 docx（PK 头）：", data[:2] == b"PK")
assert r.status_code == 200 and data[:2] == b"PK"
# 用 python-docx 打开验证内容
import docx
d = docx.Document(io.BytesIO(data))
text = "\n".join(p.text for p in d.paragraphs)
print("   含报告标题：", "自然恢复适宜性评价报告" in text)
print("   含评价结论章节：", "评价结论" in text)
print("   含得分明细章节：", "得分明细" in text)
print("   段落数：", len(d.paragraphs), "  表格数：", len(d.tables))
assert "自然恢复适宜性评价报告" in text and len(d.tables) >= 3
print()
print(LINE)
print("报告输出全部测试通过 √")
print(LINE)
# ==== 测试/test_ui_fixes.py ====
# -*- coding: utf-8 -*-
"""界面修复自检：「记住我」与各模块删除功能。"""
import os
import re
import sys
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file
    __)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
sys.stdout.reconfigure(encoding="utf-8")
LINE = "=" * 70
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(
        ROOT, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
    REMEMBER_COOKIE_DURATION = __import__("datetime").timede
    lta(days=30)
app = create_app(TestConfig)
client = app.test_client()
# ----------------------------------------------------------------
    ----------------
```

```
print(LINE)
print("一、「记住我」")
print(LINE)
html = client.get("/login").get_data(as_text=True)
# 1) 复选框必须有可点击关联的 label（这是原先失效的根因）
wrapped = re.search(r'<label[^>]*class="checkbox"[^>]*>\s*<input[^>]*name="remember"',
                    html) is not None
print("  %s 「记住我」文字与复选框包在同一 label 内" % ("[符合]" if wrapped else "[不符合]"))
assert wrapped, "复选框未与文字关联，点击文字不会勾选"
has_for = 'for="remember"' in html
print("  %s label 带 for 属性指向复选框" % ("[符合]" if has_for else "[不符合]"))
# 2) 勾选后应下发带过期时间的 remember_token
c = app.test_client()
r = c.post("/login", data={"username": "admin", "password": "admin123",
                           "remember": "y"}, follow_redirects=False)
cookies = r.headers.getlist("Set-Cookie")
rt = [h for h in cookies if h.startswith("remember_token=")]
print("  %s 勾选后下发 remember_token" % ("[符合]" if rt else "[不符合]"))
assert rt, "未下发 remember_token"
exp = re.search(r"Expires=([^;]+)", rt[0])
print("  %s 该 cookie 带过期时间：%s"
      % ("[符合]" if exp else "[不符合]", exp.group(1) if exp else "无（会话 cookie）"))
assert exp, "remember_token 无过期时间，关浏览器即失效"
# 3) 不勾选时不应下发 remember_token
c2 = app.test_client()
r2 = c2.post("/login", data={"username": "admin", "password": "admin123"},
             follow_redirects=False)
rt2 = [h for h in r2.headers.getlist("Set-Cookie") if h.startswith("remember_token=")]
print("  %s 未勾选时不下发 remember_token" % ("[符合]" if not rt2 else "[不符合]"))
assert not rt2
# 4) 携带 remember_token 的新会话应自动登录
c3 = app.test_client()
c3.set_cookie("remember_token",
              rt[0].split(";")[0].split("=", 1)[1], domain="localhost")
r3 = c3.get("/", follow_redirects=False)
print("  %s 仅凭 remember_token 访问首页可自动登录（状态码 %d）"
      % ("[符合]" if r3.status_code == 200 else "[不符合]", r3.status_code))
assert r3.status_code == 200
```

```
# ------------------------------------------------------------------8058
    ----------------                                                8059
print()                                                             8060
print(LINE)                                                         8061
print("二、删除功能")                                                8062
print(LINE)                                                         8063
client.post("/login", data={"username": "admin",                    8064
    "password": "admin123"})                                        8065
# 项目：列表页须有删除按钮                                           8066
html = client.get("/project/").get_data(as_text=True)               8067
has_del = "/delete" in html and "btn--danger" in html               8068
print("  %s 项目列表含删除按钮" % ("[符合]" if has_del else "[不符合]"))  8069
assert has_del, "项目列表缺少删除按钮"                               8070
print("  %s 删除前有二次确认" % ("[符合]" if "confirm(" in html else   8071
    "[不符合]"))                                                    8072
assert "confirm(" in html                                           8073
# 图斑列表                                                          8074
with app.app_context():                                             8075
    from app.models import MinePatch, Project                       8076
    patch = MinePatch.query.first()                                 8077
    patch_id = patch.id                                             8078
html = client.get("/project/%d/patches" %                           8079
    patch_id).get_data(as_text=True)                                8080
print("  %s 图斑列表含删除按钮" % ("[符合]" if "/project/patch/" in    8081
    html and "btn--danger" in html else "[不符合]"))                8082
assert "btn--danger" in html                                        8083
# 微地质单元                                                        8084
html = client.get("/unit/%d" % patch_id).get_data(as_text=Tr        8085
    ue)                                                             8086
print("  %s 微单元列表含删除按钮" % ("[符合]" if "/unit/delete/" in    8087
    html else "[不符合]"))                                          8088
assert "/unit/delete/" in html                                      8089
print("  %s 微单元编辑为独立页面（表单不再嵌在表格行内）"                  8090
      % ("[符合]" if "/unit/edit/" in html else "[不符合]"))        8091
# 标准                                                              8092
html = client.get("/standard/").get_data(as_text=True)              8093
print("  %s 标准列表含删除按钮" % ("[符合]" if "btn--danger" in html   8094
    else "[不符合]"))                                               8095
assert "btn--danger" in html                                        8096
# 实际执行一次删除：新建项目 → 删除 → 确认消失                       8097
client.post("/project/add", data={"name": "待删除测试项目",          8098
    "code": "DEL-1"})                                               8099
with app.app_context():                                             8100
    from app.models import db, Project                              8101
    tmp = Project.query.filter_by(name="待删除测试项目").first()      8102
    tmp_id = tmp.id                                                 8103
html = client.get("/project/").get_data(as_text=True)               8104
print("  %s 新建项目成功" % ("[符合]" if "待删除测试项目" in html else   8105
    "[不符合]"))                                                    8106
r = client.post("/project/%d/delete" % tmp_id,                      8107
```

```
        follow_redirects=True)                                          8108
html = r.get_data(as_text=True)                                         8109
gone = "待删除测试项目" not in html                                      8110
print("  %s 删除项目后列表中不再出现" % ("[符合]" if gone else "[不符合]"))  8111
assert gone                                                             8112
print("  %s 有删除成功提示" % ("[符合]" if "已删除" in html else          8113
    "[不符合]"))                                                        8114
print()                                                                 8115
print(LINE)                                                             8116
print("界面修复自检全部通过 √")                                         8117
print(LINE)                                                             8118
# ==== 测试/test_new_features.py ====                                   8119
# -*- coding: utf-8 -*-                                                 8120
"""补齐模块自检：操作日志与用户维护、遥感影像、指标与多专家矩阵、        8121
批量导入、图表与 PDF 导出。                                             8122
对应计划书功能清单与系统实现的差异核对结论。                           8123
"""                                                                     8124
import io                                                               8125
import json                                                             8126
import os                                                               8127
import re                                                               8128
import sys                                                              8129
sys.stdout.reconfigure(encoding="utf-8")                                8130
import fitz                                                             8131
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，              8132
# 使 `from app import ...` 与 app/app.db 的定位不受影响。               8133
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__fil            8134
    e__)))                                                              8135
if ROOT not in sys.path:                                                8136
    sys.path.insert(0, ROOT)                                            8137
from app import create_app                                              8138
from app.models import (db, User, Project, MinePatch,                   8139
    MicroUnit, IndicatorData,                                           8140
                           Indicator, ExpertMatrix,                     8141
    OperationLog)                                                       8142
from app.utils.schema import ensure_schema                              8143
from app.utils import browser, charts                                   8144
LINE = "=" * 72                                                         8145
BASE = ROOT                                                             8146
class TestConfig:                                                       8147
    SECRET_KEY = "test"                                                 8148
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +                            8149
    os.path.join(BASE, "app", "app.db")                                 8150
    SQLALCHEMY_TRACK_MODIFICATIONS = False                              8151
    WTF_CSRF_ENABLED = False                                            8152
    TESTING = True                                                      8153
    UPLOAD_FOLDER = os.path.join(BASE, "app", "static",                 8154
    "uploads")                                                          8155
    MAX_CONTENT_LENGTH = 32 * 1024 * 1024                               8156
    ALLOWED_IMAGE_EXT = {"png", "jpg", "jpeg", "gif",                   8157
```

```
        "webp", "bmp", "tif", "tiff"}
app = create_app(TestConfig)
with app.app_context():
    db.create_all()
    ensure_schema(db)
    ExpertMatrix.query.delete()
    db.session.commit()
    patch_id = MinePatch.query.first().id
c = app.test_client()
c.post("/login", data={"username": "admin", "password":
    "admin123"})
def ok(flag, label, extra=""):
    print("  %s %-44s %s" % ("[符合]" if flag else "[不符合]",
    label, extra))
    assert flag, label
# ------------------------------------------------------------------
    ------------------
print(LINE)
print("操作日志与用户维护")
print(LINE)
before = None
with app.app_context():
    before = OperationLog.query.count()
c.post("/project/add", data={"name": "日志核对项目", "code":
    "LOG-T"})
with app.app_context():
    after = OperationLog.query.count()
    last = OperationLog.query.order_by(OperationLog.id.desc(
    )).first()
ok(after == before + 1, "写操作被写入操作日志", "%d -> %d" % (before,
    after))
ok(last.action == "新建项目", "日志记录了可读动作名", last.action)
ok("project" in (last.target_type or ""), "日志记录了对象类型",
    last.target_type)
r = c.get("/logs")
body = r.get_data(as_text=True)
ok(r.status_code == 200 and "操作日志" in body, "操作日志查看页可访问")
ok("新建项目" in body, "日志页显示操作记录")
# 用户编辑 / 删除
with app.app_context():
    u = User(username="tmp_user", role="viewer",
             password_hash=User.query.first().password_hash)
    db.session.add(u); db.session.commit()
    uid = u.id
r = c.get("/users/%d/edit" % uid)
ok(r.status_code == 200, "用户编辑页可访问")
c.post("/users/%d/edit" % uid, data={"role": "evaluator",
    "active": "1"})
with app.app_context():
    ok(User.query.get(uid).role == "evaluator", "角色已修改并保存")
```

```
# 最后一个管理员保护
with app.app_context():
    admin_id = User.query.filter_by(role="admin").first().id
c.post("/users/%d/edit" % admin_id, data={"role": "viewer",
    "active": "1"})
with app.app_context():
    ok(User.query.get(admin_id).role == "admin",
    "拒绝把最后一个管理员降级")
c.post("/users/%d/delete" % uid, follow_redirects=True)
with app.app_context():
    ok(User.query.get(uid) is None, "用户删除生效")
# 清理日志核对用的项目
with app.app_context():
    for p in Project.query.filter_by(name="日志核对项目").all():
        db.session.delete(p)
    db.session.commit()
# ------------------------------------------------------------
    ----------------
print()
print(LINE)
print("遥感影像挂接")
print(LINE)
doc = fitz.open()
pg = doc.new_page(width=320, height=200)
pg.insert_text((20, 60), "RS image", fontname="china-s",
    fontsize=16)
png = doc[0].get_pixmap(dpi=100).tobytes("png")
doc.close()
r = c.post("/project/patch/%d/image" % patch_id,
            data={"image": (io.BytesIO(png), "影像.png"),
                  "image_note": "2025年6月无人机正射影像"},
            content_type="multipart/form-data",
    follow_redirects=True)
body = r.get_data(as_text=True)
ok("已挂接" in body and "<img" in body, "影像上传并显示")
with app.app_context():
    rel = MinePatch.query.get(patch_id).image_path
ok(bool(rel), "数据库记录影像路径", rel)
abs_path = os.path.join(TestConfig.UPLOAD_FOLDER,
    rel.replace("uploads/", "", 1))
ok(os.path.isfile(abs_path), "影像文件落盘")
ok(c.get("/static/" + rel).status_code == 200, "影像可经 URL
    访问")
r = c.post("/project/patch/%d/image" % patch_id,
            data={"image": (io.BytesIO(b"x"), "bad.txt")},
            content_type="multipart/form-data",
    follow_redirects=True)
ok("不支持" in r.get_data(as_text=True), "拒绝非图片格式")
c.post("/project/patch/%d/image/delete" % patch_id,
    follow_redirects=True)
```

```
with app.app_context():
    ok(MinePatch.query.get(patch_id).image_path is None,
    "影像移除后字段清空")
ok(not os.path.isfile(abs_path), "影像文件已删除")
# ----------------------------------------------------------------
    ----------------
print()
print(LINE)
print("指标定义维护与多专家矩阵")
print(LINE)
r = c.get("/ahp/indicators")
body = r.get_data(as_text=True)
with app.app_context():
    n_ind = Indicator.query.count()
ok(r.status_code == 200 and n_ind > 0, "指标定义已入库并可查看", "%d
    项" % n_ind)
ok(all(k in body for k in ("一级指标", "二级指标", "三级指标")),
   "指标树按层级展示")
ok("岩质边坡" in body and "平台" in body, "显示各指标启用的微地质单元")
c.post("/ahp/indicators/coverage/edit",
       data={"name": "植被覆盖度", "unit": "%", "ideal_type":
    "benefit",
             "ideal_value": "75", "enabled_units": ["岩质边坡"],
             "description": "自检修改"})
with app.app_context():
    ok(Indicator.query.filter_by(code="coverage").first().de
    scription == "自检修改",
       "指标定义可编辑")
c.post("/ahp/indicators/reset")
with app.app_context():
    ok("自检修改" not in (Indicator.query.filter_by(code="covera
    ge").first().description or ""),
       "可按论文取值重置")
base = {"m_0_1": "1.4194", "m_0_2": "1.76", "m_1_2": "1.24"}
for name in ("张工", "李工", "王工"):
    d = dict(base); d.update({"action": "add", "unit_type":
    "碎石边坡",
                              "level": "1", "expert_name":
    name})
    c.post("/ahp/experts", data=d)
with app.app_context():
    ok(ExpertMatrix.query.filter_by(unit_type="碎石边坡",
    level=1).count() == 3,
       "录入 3 位专家的判断矩阵")
r = c.get("/ahp/experts/aggregate?unit_type=碎石边坡&level=1")
body = r.get_data(as_text=True)
ok("汇总后权重" in body and "各专家矩阵的一致性" in body,
   "多专家矩阵几何平均汇总可用")
ws = re.search(r"<th scope=\"row\">权重</th>\s*(.*?)</tr>",
    body, re.S)
```

```
vals = re.findall(r">([0-9.]+)</td>", ws.group(1)) if ws
    else []
ok(len(vals) == 3 and abs(sum(map(float, vals)) - 1.0) <
    0.01,
   "汇总权重归一", "、".join(vals))
ok(abs(float(vals[0]) - 0.44) < 0.02, "汇总权重接近论文表 3 取值",
    vals[0] if vals else "")
# ------------------------------------------------------------
    ----------------
print()
print(LINE)
print("批量导入")
print(LINE)
r = c.get("/indicator/import/template")
tpl = r.data.decode("utf-8-sig")
ok(r.status_code == 200 and "单元类型" in tpl, "导入模板可下载")
ok("土石比" in tpl and "植被覆盖度" in tpl, "模板包含指标列")
csv_text = (
    "单元类型,土石比,土层厚度,pH,有机质,Hg,As,Ni,Cu,Cd,Pb,植被覆盖度,Shannon,坡度
    ,坡向\n"
    "碎石边坡,0.34,10,9.24,4.89,0.05,5.17,12.60,11.70,0.04,6.50,
    87.92,0.60,28.75,阳坡\n"
    "平台,0.56,30,8.72,10.92,0.02,3.13,12.33,11.14,0.09,9.98,5
    8.42,0.72,,,\n"
    "不存在单元,1,1,7,1,,,,,,,,,\n"
)
r = c.post("/indicator/import",
           data={"patch_id": str(patch_id),
                 "datafile": (io.BytesIO(csv_text.encode("ut
    f-8")), "d.csv")},
           content_type="multipart/form-data",
    follow_redirects=True)
body = r.get_data(as_text=True)
ok("导入结果" in body, "导入结果页展示")
ok("不存在单元" in body, "错误行被报告")
with app.app_context():
    u = MicroUnit.query.filter_by(patch_id=patch_id,
    unit_type="碎石边坡").first()
    ind = IndicatorData.query.filter_by(unit_id=u.id).first(
    )
    ok(abs(ind.soil_ratio - 0.34) < 1e-6 and
    abs(ind.coverage - 87.92) < 1e-6,
        "导入数据已写入数据库")
r = c.post("/indicator/import",
           data={"patch_id": str(patch_id),
                 "datafile": (io.BytesIO(b"x"), "d.pdf")},
           content_type="multipart/form-data",
    follow_redirects=True)
ok("仅支持" in r.get_data(as_text=True), "拒绝不支持的导入格式")
# ------------------------------------------------------------
```

```
    ------------------
print()
print(LINE)
print("图表与 PDF 导出")
print(LINE)
svg = charts.hbars([("岩质边坡", 0.54, "0.5401"), ("平台", 0.84,
    "0.8376")])
ok("<svg" in svg and "0.8376" in svg, "条形图生成且带数值标签")
svg2 = charts.donut([("植被指标", 0.6, "0.6000"), ("土壤指标", 0.4,
    "0.4000")])
ok("<svg" in svg2 and "占比" in svg2, "环形图生成且带图例")
r = c.get("/report/%d" % patch_id)
body = r.get_data(as_text=True)
ok(body.count("<svg") >= 2, "得分明细页含图表", "%d 个 SVG" %
    body.count("<svg"))
exe = browser.browser_path()
if exe is None:
    print("  [跳过] 未找到浏览器，PDF 导出无法验证")
else:
    r = c.get("/report/%d/pdf" % patch_id)
    data = r.data
    ok(data[:4] == b"%PDF", "PDF 报告导出成功", "%d 字节" %
    len(data))
    d = fitz.open(stream=data, filetype="pdf")
    txt = "".join(d[i].get_text() for i in
    range(d.page_count))
    ok("自然恢复适宜性评价报告" in txt, "PDF 含报告标题")
    ok("评价结论" in txt and "得分明细" in txt, "PDF 含结论与明细章节")
    ok(d.page_count >= 2, "PDF 页数合理", "%d 页" % d.page_count)
    d.close()
print()
print(LINE)
print("补齐模块自检全部通过 √")
print(LINE)
#  ==== 测试/test_workflow.py ====
#  -*- coding: utf-8 -*-
"""流程门禁自检：前置步骤未完成时，后续模块必须拦得住。
论文 4.1 节确定的评价流程存在先后关系，缺任何一环都不应产出评价结论。
本测试逐个构造「缺前置」的场景，验证系统不会放行。
"""
import os
import sys
sys.stdout.reconfigure(encoding="utf-8")
#  本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
#  使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__fil
    e__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
```

```
from app.models import (db, Project, MinePatch, MicroUnit,
    IndicatorData,
                        ConstraintCheck, EvaluationResult)
from app.services import workflow as wf
LINE = "=" * 72
BASE = ROOT
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +
    os.path.join(BASE, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
c = app.test_client()
c.post("/login", data={"username": "admin", "password":
    "admin123"})
_fails = []
def ok(flag, label, extra=""):
    print("  %s %-46s %s" % ("[符合]" if flag else "[不符合]",
    label, extra))
    if not flag:
        _fails.append(label)
def new_patch(tag):
    with app.app_context():
        p = Project(name="门禁-" + tag, code="WF-" + tag)
        db.session.add(p); db.session.flush()
        patch = MinePatch(project_id=p.id, name="门禁图斑-" +
    tag)
        db.session.add(patch); db.session.flush()
        pid = patch.id
        db.session.commit()
    return pid
def add_units(pid):
    with app.app_context():
        db.session.add(MicroUnit(patch_id=pid,
    unit_type="碎石边坡",
                                 area=1.0, ratio=1.0))
        db.session.commit()
def add_constraint(pid, passed=True):
    with app.app_context():
        db.session.add(ConstraintCheck(
            patch_id=pid, policy_pass=True,
    location_pass=passed,
            pollution_pass=True, geo_pass=True,
    farmland_pass=True,
            passed=passed, reason="全部通过" if passed else
    "未通过：区位约束"))
        db.session.commit()
def add_data(pid):
```

```
    with app.app_context():
        u = MicroUnit.query.filter_by(patch_id=pid).first()
        db.session.add(IndicatorData(unit_id=u.id,
    soil_ratio=0.34, thickness=10,
                                     ph=9.24,
    organic_matter=4.89, coverage=87.92,
                                     shannon=0.60,
    slope=28.75, aspect="阳坡"))
        db.session.commit()
def cleanup(pid, tag):
    with app.app_context():
        from app.models import ScoreDetail
        # 先删得分明细，再删评价记录，避免留下孤儿明细
        rids = [r.id for r in EvaluationResult.query.filter_
    by(patch_id=pid)]
        if rids:
            ScoreDetail.query.filter(ScoreDetail.result_id.i
    n_(rids)).delete(
                synchronize_session=False)
        EvaluationResult.query.filter_by(patch_id=pid).delet
    e()
        ConstraintCheck.query.filter_by(patch_id=pid).delete
    ()
        uids = [u.id for u in MicroUnit.query.filter_by(patc
    h_id=pid)]
        if uids:
            IndicatorData.query.filter(IndicatorData.unit_id
    .in_(uids)).delete(
                synchronize_session=False)
        MicroUnit.query.filter_by(patch_id=pid).delete()
        m = db.session.get(MinePatch, pid)
        if m:
            db.session.delete(m)
        pr = Project.query.filter_by(name="门禁-" +
    tag).first()
        if pr:
            db.session.delete(pr)
        db.session.commit()
def results_of(pid):
    with app.app_context():
        return EvaluationResult.query.filter_by(patch_id=pid
    ).count()
def post_eval(pid):
    return c.post("/evaluate/%d" % pid, data={},
    follow_redirects=False)
def get_report(pid):
    return c.get("/report/%d" % pid, follow_redirects=False)
# ----------------------------------------------------------------
    ----------------
print(LINE)
```

```
print("一、前置条件缺失时，评价必须被拦住")
print(LINE)
print()
print("场景 1：连微地质单元都没划分")
pid = new_patch("1")
r = post_eval(pid)
n = results_of(pid)
ok(r.status_code == 302 and n == 0, "未划分单元 → 不产生评价结果",
   "HTTP %d，结果数 %d" % (r.status_code, n))
with app.app_context():
    pr = wf.patch_progress(pid)
steps = [b["step"] for b in pr["blocking"]]
ok(not pr["ready"] and "units" in steps,
   "拦原因包含「划分微地质单元」", "、".join(steps))
ok(steps == ["constraint", "units"],
   "拦截顺序符合论文 4.1 节：限制性判定在前，划分单元在后",
   "、".join(steps))
cleanup(pid, "1")
print()
print("场景 2：有单元，但未做限制性条件判定")
pid = new_patch("2"); add_units(pid); add_data(pid)
r = post_eval(pid)
n = results_of(pid)
ok(r.status_code == 302 and n == 0, "未做限制性判定 → 不产生评价结果",
   "结果数 %d" % n)
with app.app_context():
    pr = wf.patch_progress(pid)
ok(any(b["step"] == "constraint" for b in pr["blocking"]),
   "拦原因指向「执行限制性条件判定」")
cleanup(pid, "2")
print()
print("场景 3：限制性条件判定【未通过】")
pid = new_patch("3"); add_units(pid); add_data(pid);
    add_constraint(pid, passed=False)
r = post_eval(pid)
n = results_of(pid)
ok(r.status_code == 302 and n == 0, "判定未通过 → 不进入定量评价",
   "结果数 %d" % n)
with app.app_context():
    pr = wf.patch_progress(pid)
ok(not pr["constraint"]["passed"], "流程状态显示判定未通过")
blocked = [b for b in pr["blocking"] if b["step"] ==
    "constraint"]
ok(bool(blocked) and "人工辅助" in blocked[0]["reason"],
   "拦原因说明了按论文应判「人工辅助或生态重建」")
cleanup(pid, "3")
print()
print("场景 4：判定通过，但指标数据全空")
pid = new_patch("4"); add_units(pid); add_constraint(pid,
    passed=True)
```

```
r = post_eval(pid)
n = results_of(pid)
ok(r.status_code == 302 and n == 0, "数据未录入 → 不产生评价结果",
   "结果数 %d" % n)
with app.app_context():
    pr = wf.patch_progress(pid)
ok(any(b["step"] == "data" for b in pr["blocking"]),
   "拦原因指向「录入指标数据」")
ok(pr["data"]["missing"] == ["碎石边坡"],
   "指出具体缺哪个单元的数据", "、".join(pr["data"]["missing"]))
cleanup(pid, "4")
print()
print("场景 5：单元面积占比合计不为 100%")
pid = new_patch("5"); add_constraint(pid, passed=True)
with app.app_context():
    u = MicroUnit(patch_id=pid, unit_type="碎石边坡", area=1.0,
    ratio=0.5)
    db.session.add(u); db.session.commit()
    db.session.add(IndicatorData(unit_id=u.id,
    soil_ratio=0.3, thickness=10,
                                 ph=8.0,
    organic_matter=5.0, coverage=80.0,
                                 shannon=0.6, slope=20.0,
    aspect="阳坡"))
    db.session.commit()
r = post_eval(pid)
ok(results_of(pid) == 0, "占比不足 100% → 不产生评价结果")
cleanup(pid, "5")
print()
print(LINE)
print("二、前置条件齐备时才放行")
print(LINE)
pid = new_patch("OK"); add_units(pid); add_constraint(pid,
    passed=True); add_data(pid)
with app.app_context():
    pr = wf.patch_progress(pid)
ok(pr["ready"], "单元 + 判定通过 + 数据齐备 → 判定为可执行")
r = post_eval(pid)
n = results_of(pid)
ok(n == 1, "此时执行评价成功产生结果", "结果数 %d" % n)
print("  重定向到:", r.headers.get("Location"))
print()
print(LINE)
print("三、报告不得先于评价产生")
print(LINE)
pid2 = new_patch("R")    # 什么都不做
r = get_report(pid2)
ok(r.status_code == 302 and "/report/" ==
    (r.headers.get("Location") or ""),
   "前置缺失时 /report/<id> 被退回列表", "HTTP %d" % r.status_code)
```

```
for suffix in ("/pdf", "/word"):
    rr = c.get("/report/%d%s" % (pid2, suffix),
    follow_redirects=False)
    ok(rr.status_code == 302, "导出 %s 同样被拦住" % suffix, "HTTP
    %d" % rr.status_code)
cleanup(pid2, "R")
cleanup(pid, "OK")
print()
print(LINE)
print("四、前置齐备但从未执行评价时，报告仍不得产生")
print(LINE)
#  报告是评价结论的呈现：即使前置步骤都做完了，只要没真正执行过定量评价，
#  也不应凭空推算出结论。
pid3 = new_patch("N")
add_units(pid3); add_constraint(pid3, passed=True);
    add_data(pid3)
with app.app_context():
    pr = wf.report_progress(pid3)
ok(not pr["ready"], "无评价记录 → 报告流程判定为未就绪")
ok(bool(pr["blocking"]) and pr["blocking"][0]["step"] ==
    "evaluate",
   "拦原因指向「执行适宜性评价」")
r = get_report(pid3)
ok(r.status_code == 302 and results_of(pid3) == 0,
   "直接访问 /report/<id> 被退回，且不产生任何评价结果",
   "HTTP %d" % r.status_code)
#  真正执行评价之后，报告才放行，且取值与评价记录一致
r = post_eval(pid3)
ok(results_of(pid3) == 1, "先执行评价 → 产生评价记录")
with app.app_context():
    pr = wf.report_progress(pid3)
    rec = pr["result"]
ok(pr["ready"] and rec is not None, "有评价记录后，报告流程就绪")
rr = get_report(pid3)
body = rr.get_data(as_text=True)
ok(rr.status_code == 200, "此时可打开得分明细页", "HTTP %d" %
    rr.status_code)
ok(("%.4f" % rec.final_score) in body,
   "报告数值取自评价记录，而非重新计算",
   "F=%.4f" % rec.final_score)
cleanup(pid3, "N")
print()
print(LINE)
print("五、内置演示数据的清理不得波及用户自建数据")
print(LINE)
#  回归保护：seed_demo.clean_case() 曾执行 Project.query.delete()，
#  导致用户新建的项目在每次启动时被连带删除。
import seed_demo as sd
with app.app_context():
    keep_p = Project(name="用户自建项目-守护", code="KEEP-001")
```

```
    db.session.add(keep_p); db.session.flush()                          8658
    keep_patch = MinePatch(project_id=keep_p.id,                        8659
    name="用户自建图斑 - 守护")                                          8660
    db.session.add(keep_patch); db.session.flush()                      8661
    keep_pid = keep_p.id                                                8662
    keep_patch_id = keep_patch.id                                       8663
    db.session.commit()                                                 8664
with app.app_context():                                                 8665
    sd.clean_case(reset=False)                                          8666
with app.app_context():                                                 8667
    still_p = db.session.get(Project, keep_pid)                         8668
    still_patch = db.session.get(MinePatch, keep_patch_id)              8669
ok(still_p is not None, "清理演示数据后，用户自建项目仍存在")             8670
ok(still_patch is not None, "清理演示数据后，用户自建图斑仍存在")         8671
#  演示数据清掉后应能重新写入，保证演示环境可恢复                       8672
sd.seed()                                                               8673
with app.app_context():                                                 8674
    demo_back = Project.query.filter_by(code=sd.DEMO_CODE).f            8675
    irst()                                                              8676
ok(demo_back is not None, "演示案例可重新写入（幂等恢复）")              8677
with app.app_context():                                                 8678
    m = db.session.get(MinePatch, keep_patch_id)                        8679
    if m:                                                               8680
        db.session.delete(m)                                            8681
    p = db.session.get(Project, keep_pid)                               8682
    if p:                                                               8683
        db.session.delete(p)                                            8684
    db.session.commit()                                                 8685
print()                                                                 8686
print(LINE)                                                             8687
print("六、同一图斑不得重复划分同类型微地质单元")                        8688
print(LINE)                                                             8689
#  论文 4.1 节把图斑分为平台、碎石边坡、岩质边坡三类，每类至多一个。     8690
#  允许重复会让面积占比、按类型组织的指标数据与批量导入对不上号。       8691
pid4 = new_patch("D")                                                   8692
c.post("/unit/%d/add" % pid4, data={"unit_type": "平台",                8693
    "area": "1.0"},                                                     8694
       follow_redirects=True)                                           8695
with app.app_context():                                                 8696
    n1 = MicroUnit.query.filter_by(patch_id=pid4).count()               8697
ok(n1 == 1, "首次添加「平台」成功", "单元数 %d" % n1)                    8698
r = c.post("/unit/%d/add" % pid4, data={"unit_type": "平台",            8699
    "area": "2.0"},                                                     8700
            follow_redirects=True)                                      8701
with app.app_context():                                                 8702
    n2 = MicroUnit.query.filter_by(patch_id=pid4).count()               8703
ok(n2 == 1, "重复添加同类型被拒绝", "单元数 %d" % n2)                    8704
ok("同一类型只能划分一个" in r.get_data(as_text=True), "给出重复提示")   8705
r = c.post("/unit/%d/add" % pid4, data={"unit_type": "火山口",          8706
    "area": "1.0"},                                                     8707
```

```
            follow_redirects=True)
with app.app_context():
    n3 = MicroUnit.query.filter_by(patch_id=pid4).count()
ok(n3 == 1, "非法单元类型被拒绝", "单元数 %d" % n3)
c.post("/unit/%d/add" % pid4, data={"unit_type": "碎石边坡",
    "area": "3.0"},
        follow_redirects=True)
with app.app_context():
    uid = MicroUnit.query.filter_by(patch_id=pid4,
                                    unit_type="碎石边坡").first(
    ).id
r = c.post("/unit/edit/%d" % uid,
            data={"unit_type": "平台", "area": "3.0"},
    follow_redirects=True)
with app.app_context():
    types = sorted(u.unit_type for u in
                   MicroUnit.query.filter_by(patch_id=pid4).
    all())
ok(types == ["平台", "碎石边坡"], "改类型时同样拦截重复", "、".join(types))
cleanup(pid4, "D")
print()
print(LINE)
if _fails:
    print("存在未通过项：")
    for f in _fails:
        print("  -", f)
    sys.exit(1)
print("流程门禁自检全部通过 √")
print(LINE)
#  ==== 测试/test_weights.py ====
#  -*- coding: utf-8 -*-
"""权重生效链路自检：AHP 算出的权重必须真正参与评价计算。
此前 weight_schemes / weight_items 两张表从未被写入，评价引擎也只用
代码里的论文表 3 默认权重，相当于权重模块算完即弃。本测试守住这条链路：
    默认 → 论文表 3
    保存 AHP 权重 → 评价改用新权重，结果随之变化
    恢复默认 → 结果回到论文取值
"""
import os
import sys
sys.stdout.reconfigure(encoding="utf-8")
#  本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
#  使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file
    __)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
from app.models import (db, Project, MinePatch, MicroUnit,
    IndicatorData,
```

```
                                ConstraintCheck, EvaluationResult,
    WeightScheme,
                                WeightItem)
from app.services import workflow as wf
from app.services import weight_service as ws
LINE = "=" * 72
BASE = ROOT
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +
    os.path.join(BASE, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
c = app.test_client()
c.post("/login", data={"username": "admin", "password":
    "admin123"})
_fails = []
def ok(flag, label, extra=""):
    print("  %s %-46s %s" % ("[符合]" if flag else "[不符合]",
    label, extra))
    if not flag:
        _fails.append(label)
TAG = "W"
UNIT_TYPE = "碎石边坡"
def build_case():
    """建一个只含单一微地质单元的图斑，便于观察权重变化对得分的影响。"""
    with app.app_context():
        p = Project(name="权重测试-%s" % TAG, code="WEIGHT-%s"
    % TAG)
        db.session.add(p); db.session.flush()
        patch = MinePatch(project_id=p.id, name="权重测试图斑-%s"
    % TAG)
        db.session.add(patch); db.session.flush()
        db.session.add(MicroUnit(patch_id=patch.id,
    unit_type=UNIT_TYPE,
                                 area=1.0, ratio=1.0))
        db.session.flush()
        u = MicroUnit.query.filter_by(patch_id=patch.id).fir
    st()
        db.session.add(IndicatorData(
            unit_id=u.id, soil_ratio=0.34, thickness=10,
    ph=9.24,
            organic_matter=4.89, coverage=87.92,
    shannon=0.60,
            slope=28.75, aspect="阳坡"))
        db.session.add(ConstraintCheck(
            patch_id=patch.id, policy_pass=True,
    location_pass=True,
```

```
                pollution_pass=True, geo_pass=True,
    farmland_pass=True,
                passed=True, reason="全部通过"))
            db.session.commit()
            return patch.id
def cleanup(pid):
    with app.app_context():
        from app.models import ScoreDetail
        rids = [r.id for r in EvaluationResult.query.filter_
    by(patch_id=pid)]
        if rids:
            ScoreDetail.query.filter(ScoreDetail.result_id.i
    n_(rids)).delete(
                synchronize_session=False)
        EvaluationResult.query.filter_by(patch_id=pid).delet
    e()
        ConstraintCheck.query.filter_by(patch_id=pid).delete
    ()
        uids = [u.id for u in MicroUnit.query.filter_by(patc
    h_id=pid)]
        if uids:
            IndicatorData.query.filter(IndicatorData.unit_id
    .in_(uids)).delete(
                synchronize_session=False)
        MicroUnit.query.filter_by(patch_id=pid).delete()
        m = db.session.get(MinePatch, pid)
        if m:
            db.session.delete(m)
        p = Project.query.filter_by(code="WEIGHT-%s" %
    TAG).first()
        if p:
            db.session.delete(p)
        db.session.commit()
def run_eval(pid):
    c.post("/evaluate/%d" % pid, data={},
    follow_redirects=False)
    with app.app_context():
        return EvaluationResult.query.filter_by(patch_id=pid
    ) \
            .order_by(EvaluationResult.id.desc()).first().fi
    nal_score
print(LINE)
print("一、默认应使用论文表 3 的权重")
print(LINE)
with app.app_context():
    ws.reset_weights(UNIT_TYPE)
    w, label, scheme = ws.effective_weights(UNIT_TYPE)
ok(scheme is None and "论文表" in label, "未配置时权重来源为论文表 3",
    label)
ok(abs(w["l1"]["土壤指标"] - 0.44) < 1e-9, "一级权重取自论文表 3",
```

```
    "土壤指标 %.2f" % w["l1"]["土壤指标"])                                    8858
pid = build_case()                                                          8859
base_score = run_eval(pid)                                                  8860
print("   默认权重下的评价值 F = %.4f" % base_score)                          8861
print()                                                                     8862
print(LINE)                                                                 8863
print("二、保存 AHP 算出的权重后，评价应改用新权重")                          8864
print(LINE)                                                                 8865
with app.app_context():                                                     8866
    # 模拟 AHP 计算结果：把土壤指标权重提高、植被与地形降低（仍和为 1）          8867
    ws.save_weights(UNIT_TYPE, [("soil", 0.70), ("veg",                     8868
    0.20),                                                                  8869
                                ("terrain", 0.10)])                         8870
    n_items = WeightItem.query.count()                                      8871
ok(n_items >= 3, "weight_items 表已写入权重条目", "%d 条" % n_items)          8872
with app.app_context():                                                     8873
    w2, label2, scheme2 = ws.effective_weights(UNIT_TYPE)                   8874
ok(scheme2 is not None and "自定义" in label2, "权重来源变为自定义方案",      8875
    label2)                                                                 8876
ok(abs(w2["l1"]["土壤指标"] - 0.70) < 1e-9, "新权重已生效",                  8877
    "土壤指标 %.2f" % w2["l1"]["土壤指标"])                                  8878
ok(abs(w2["l1"]["植被指标"] - 0.20) < 1e-9, "同批保存的其他项也已生效")       8879
ok(abs(w2["l2"]["土壤指标"]["土石比"] - 0.25) < 1e-9,                        8880
    "未覆盖的二级权重仍保留论文取值",                                        8881
    "土石比 %.2f" % w2["l2"]["土壤指标"]["土石比"])                          8882
new_score = run_eval(pid)                                                   8883
print("   新权重下的评价值 F = %.4f" % new_score)                             8884
ok(abs(new_score - base_score) > 1e-4,                                      8885
    "权重变化确实改变了评价结果",                                            8886
    "%.4f → %.4f" % (base_score, new_score))                                8887
print()                                                                     8888
print(LINE)                                                                 8889
print("三、结果应记录所用权重来源")                                          8890
print(LINE)                                                                 8891
import json                                                                 8892
with app.app_context():                                                     8893
    rec = EvaluationResult.query.filter_by(patch_id=pid) \                  8894
          .order_by(EvaluationResult.id.desc()).first()                     8895
    stored = json.loads(rec.unit_scores)                                    8896
ok(any(u.get("weight_source") for u in stored),                             8897
    "评价记录中标注了权重来源",                                              8898
    stored[0].get("weight_source") or "")                                   8899
print()                                                                     8900
print(LINE)                                                                 8901
print("四、恢复默认后应回到论文取值")                                        8902
print(LINE)                                                                 8903
with app.app_context():                                                     8904
    ws.reset_weights(UNIT_TYPE)                                             8905
    w3, label3, scheme3 = ws.effective_weights(UNIT_TYPE)                   8906
ok(scheme3 is None and "论文表" in label3, "已恢复为论文表 3 权重",          8907
```

```
    label3)                                                          8908
back_score = run_eval(pid)                                           8909
print("   恢复后评价值 F = %.4f（默认时 %.4f）" % (back_score,          8910
    base_score))                                                     8911
ok(abs(back_score - base_score) < 1e-9, "评价结果与默认时一致")        8912
print()                                                              8913
print(LINE)                                                          8914
print("五、权重首页概览")                                             8915
print(LINE)                                                          8916
with app.app_context():                                              8917
    rows = ws.summary()                                              8918
ok(len(rows) == 3, "三种微地质单元均有权重来源说明", "%d 行" % len(rows))  8919
r = c.get("/ahp/")                                                   8920
body = r.get_data(as_text=True)                                      8921
ok(r.status_code == 200 and "当前生效权重" in body, "权重首页正常展示")    8922
print()                                                              8923
print(LINE)                                                          8924
print("六、一致性不通过的矩阵不得保存生效")                            8925
print(LINE)                                                          8926
with app.app_context():                                              8927
    ws.reset_weights(UNIT_TYPE)                                      8928
n = 3                                                                8929
# 明显矛盾的矩阵：a12=9, a13=1/9, a23=9 —— CR 必然超限                8930
mats = [(0, 1, "9"), (0, 2, "0.1111"), (1, 2, "9")]                  8931
data = {"csrf_token": "", "action": "save"}                          8932
for i, j, v in mats:                                                 8933
    data["m_%d_%d" % (i, j)] = v                                     8934
r = c.post("/ahp/matrix?unit_type=%s&level=1" % UNIT_TYPE,           8935
    data=data,                                                       8936
            follow_redirects=True)                                   8937
with app.app_context():                                              8938
    _, label4, scheme4 = ws.effective_weights(UNIT_TYPE)             8939
ok(scheme4 is None, "CR 超限的矩阵未被保存生效", label4)              8940
ok("一致性" in r.get_data(as_text=True), "页面给出了未通过一致性的提示")  8941
cleanup(pid)                                                         8942
print()                                                              8943
print(LINE)                                                          8944
if _fails:                                                           8945
    print("存在未通过项：")                                           8946
    for f in _fails:                                                 8947
        print("  -", f)                                             8948
    sys.exit(1)                                                      8949
print("权重生效链路自检全部通过 √")                                   8950
print(LINE)                                                          8951
# ==== app/services/__init__.py ====                                 8952
# -*- coding: utf-8 -*-                                              8953
# ==== app/utils/__init__.py ====                                    8954
# -*- coding: utf-8 -*-                                              8955
# ==== app/views/__init__.py ====                                    8956
# -*- coding: utf-8 -*-                                              8957
```