```
# ==== run.py ====
# -*- coding: utf-8 -*-
"""系统启动入口。
运行：
    python run.py                启动并自动打开浏览器
    python run.py --no-browser   只启动服务，不打开浏览器
    python run.py --dev          开发模式（开启代码热重载与调试器）
    python run.py --port 5001    指定端口
默认以 127.0.0.1:5000 启动，就绪后自动打开浏览器。
"""
import os
import sys
import threading
import time
import webbrowser
if hasattr(sys.stdout, "reconfigure"):
    sys.stdout.reconfigure(encoding="utf-8")   # 控制台中文正常显示
from app import create_app
from app.models import db
PORT = 5000
for i, a in enumerate(sys.argv):
    if a == "--port" and i + 1 < len(sys.argv):
        PORT = int(sys.argv[i + 1])
URL = "http://127.0.0.1:%d" % PORT
NO_BROWSER = "--no-browser" in sys.argv
DEV = "--dev" in sys.argv
app = create_app()
def open_browser_later(delay=1.2):
    """等服务工作起来再打开浏览器，避免打开时页面还没就绪。
    放在后台线程里，不用 sleep 阻塞服务启动；线程设为守护线程，
    用户 Ctrl+C 停止服务时不会残留。
    """
    def run():
        time.sleep(delay)
        try:
            webbrowser.open(URL)
        except Exception:
            pass            # 打开失败不影响服务本身
    t = threading.Thread(target=run, daemon=True)
    t.start()
if __name__ == "__main__":
    with app.app_context():
        db.create_all()     # 首次运行时自动建表
        from app.utils.schema import ensure_schema
        added = ensure_schema(db)     # 旧库补齐新增字段
        if added:
            print("已补充字段：%s" % "、".join(added))
    print("=" * 58)
    print("   历史遗留废弃矿山自然恢复适宜性评价系统  Ｖ１．０")
    print("=" * 58)
```

```
    print("   访问地址：%s" % URL)
    print("   演示账号：admin      密码：admin123")
    print("   停止运行：按 Ctrl+C，或直接关闭本窗口")
    print("=" * 58)
    if not NO_BROWSER and not DEV:
        print("   正在打开浏览器……")
    print()
    #  开发模式才启用热重载（重载会二次启动进程，故此时不自动开浏览器）
    if not NO_BROWSER and not DEV:
        open_browser_later()
    app.run(host="127.0.0.1", port=PORT, debug=DEV,
    use_reloader=DEV)
#  ==== app/__init__.py ====
#  -*- coding: utf-8 -*-
"""Flask 应用工厂。"""
from datetime import date
from flask import Flask
from flask_login import LoginManager
from app.config import Config
from app.models import db, User
from app.utils.constants import ROLE_LABELS
login_manager = LoginManager()
login_manager.login_view = "auth.login"
login_manager.login_message = "请先登录"
@login_manager.user_loader
def load_user(user_id):
    return db.session.get(User, int(user_id))
def create_app(config_class=Config):
    app = Flask(__name__)
    app.config.from_object(config_class)
    db.init_app(app)
    login_manager.init_app(app)
    #  模板里展示时间统一走 localdt：库里存 UTC，展示成本地时间
    from app.utils.timefmt import to_local
    app.jinja_env.filters["localdt"] = to_local
    #  注册视图（各模块路由）
    from app.views import auth, project, unit, standard,
    constraint, \
        ahp, indicator, evaluate, report, search
    app.register_blueprint(auth.bp)
    app.register_blueprint(project.bp)
    app.register_blueprint(unit.bp)
    app.register_blueprint(standard.bp)
    app.register_blueprint(constraint.bp)
    app.register_blueprint(ahp.bp)
    app.register_blueprint(indicator.bp)
    app.register_blueprint(evaluate.bp)
    app.register_blueprint(report.bp)
    app.register_blueprint(search.bp)
    #  全局登录保护：除登录页与静态资源外，均需登录
```

```
from flask import request, redirect, url_for,                    101
send_from_directory                                              102
from flask_login import current_user, login_user                 103
PUBLIC_ENDPOINTS = {"auth.login", "auth.register",               104
"static", "favicon"}                                             105
#  浏览器默认会请求根路径下的 /favicon.ico。                      106
#  页面里虽已用 <link rel="icon"> 指向 static 目录，但出错页等场景仍会  107
#  回退到这个路径，补一条路由免得日志里一直刷 404。               108
@app.route("/favicon.ico")                                       109
def favicon():                                                   110
    return send_from_directory(app.static_folder,                111
"favicon.ico",                                                   112
                                       mimetype="image/vnd.micro 113
soft.icon")                                                      114
@app.before_request                                              115
def require_login():                                             116
    #  截图模式（仅用于生成说明书配图）：自动以管理员身份登录    117
    if app.config.get("SCREENSHOT_MODE"):                        118
        if (request.endpoint not in ("auth.login",               119
"auth.register", "static")                                       120
                and not current_user.is_authenticated):          121
            admin = User.query.filter_by(role="admin").f         122
irst()                                                           123
            if admin:                                            124
                login_user(admin)                                125
        return None                                              126
    if request.endpoint in PUBLIC_ENDPOINTS or                   127
request.endpoint is None:                                        128
        return None                                              129
    if not current_user.is_authenticated:                        130
        return redirect(url_for("auth.login"))                   131
    return None                                                  132
#  侧边栏导航：按论文评价流程的顺序编排，分为「评价流程」与「系统管理」两组。  133
#  不使用模块编号，避免出现与实际流程不一致的代号。              134
#  每项带图标名（内联 SVG，见 templates/_macros.html 的 ICONS）  135
#  与可选的待办角标（该步骤还没做完的图斑数）。                  136
FLOW_LINKS = [                                                   137
    ("项目与矿山档案", "/project/", "folder"),                   138
    ("政策与标准知识库", "/standard/", "book"),                  139
    ("限制性指标判定", "/constraint/", "shield"),                140
    ("微地质单元", "/unit/", "layers"),                          141
    ("指标体系与权重", "/ahp/", "sliders"),                      142
    ("指标数据采集", "/indicator/", "database"),                 143
    ("适宜性定量评价", "/evaluate/", "target"),                  144
    ("报告与结果输出", "/report/", "file"),                      145
]                                                                146
#  「用户与操作日志」已并入「个人设置」，不再是独立菜单，        147
#  因此系统管理组只留一个入口。                                  148
ADMIN_LINKS = [                                                  149
    ("个人设置", "/profile", "user"),                            150
```

```
]
@app.context_processor
def inject_nav():
    path = request.path or "/"
    def hit(prefix):
        """当前路径是否属于某个入口（/unit/ 也匹配 /unit/3）。"""
        return path.startswith(prefix.rstrip("/"))
    badges = {}
    if current_user.is_authenticated:
        from app.services import dashboard as dash
        badges = dash.nav_badges()
    def build(links):
        return [{"label": label, "href": href, "icon": icon,
                 "active": hit(href), "badge": badges.get(href, 0)}
                for label, href, icon in links]
    groups = [
        {"title": "评价流程", "links": build(FLOW_LINKS)},
        {"title": "系统管理", "links": build(ADMIN_LINKS)},
    ]
    # 面包屑用的当前页名：按路径命中的入口取，未命中时给个通用名
    if path == "/":
        page_title = "工作台"
    elif path.startswith("/profile"):
        page_title = "个人设置"
    elif path.startswith(("/users", "/logs")):
        page_title = "账号与日志"
    elif path.startswith("/search"):
        page_title = "搜索结果"
    else:
        page_title = "工作台"
        for label, href, _icon in FLOW_LINKS:
            if hit(href):
                page_title = label
                break
    # 层级引导用：项目是归档单位，图斑才是评价对象。
    # 下游各页面按图斑组织数据，因此需要提示「哪些项目下还没有图斑」。
    from app.models import Project, MinePatch
    projects = Project.query.order_by(Project.id).all()
    return {
        "nav_groups": groups,
        "home_active": path == "/",
        "page_title": page_title,
        "today": date.today().strftime("%Y-%m-%d"),
        "search_q": request.args.get("q", ""),
        "role_labels": ROLE_LABELS,
        "project_count": len(projects),
        "patch_count": MinePatch.query.count(),
        "projects_without_patch": [p for p in projects
```

```
                                                    if p.patches.count()
    == 0],
        }
    # 操作审计：统一在响应阶段记录成功的写操作（操作日志）
    from app.services import audit
    @app.after_request
    def audit_writes(response):
        if request.method in ("POST", "PUT", "PATCH",
    "DELETE"):
            audit.record(request.endpoint,
    response.status_code)
        return response
    # 错误页：给出可读提示，而不是默认的英文错误页
    from flask import render_template
    @app.errorhandler(403)
    def forbidden(e):
        return render_template("error.html", code=403,
                               message="没有权限执行该操作"), 403
    @app.errorhandler(404)
    def not_found(e):
        return render_template("error.html", code=404,
                               message="请求的页面不存在"), 404
    return app
# ==== app/config.py ====
# -*- coding: utf-8 -*-
"""应用配置。"""
import os
from datetime import timedelta
BASE_DIR = os.path.abspath(os.path.dirname(__file__))
class Config:
    SECRET_KEY = os.environ.get("SECRET_KEY",
    "mine-restoration-dev-key")
    # 单机部署，SQLite 数据库文件放在应用目录下
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +
    os.path.join(BASE_DIR, "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    # 禁止跨站请求伪造（CSRF），登录与表单提交依赖此项
    WTF_CSRF_ENABLED = True
    # 模板改动立即生效，不必重启服务。
    # Flask 在非 debug 下默认把模板缓存到进程里，改完模板刷新浏览器还是旧页面，
    # 容易被误当成「改了没生效」。本系统只在本机运行，这点开销可以忽略。
    TEMPLATES_AUTO_RELOAD = True
    # 「记住我」：登录时勾选则下发持久 cookie，关闭浏览器后仍可自动登录
    REMEMBER_COOKIE_DURATION = timedelta(days=30)
    REMEMBER_COOKIE_HTTPONLY = True
    REMEMBER_COOKIE_SAMESITE = "Lax"
    # 影像与数据文件上传（遥感影像挂接、批量导入）
    UPLOAD_FOLDER = os.path.join(BASE_DIR, "static",
    "uploads")
    MAX_CONTENT_LENGTH = 32 * 1024 * 1024          # 单次上传上限
```

```
    32 MB                                                                  251
    ALLOWED_IMAGE_EXT = {"png", "jpg", "jpeg", "gif",                      252
    "webp", "bmp", "tif", "tiff"}                                          253
    ALLOWED_DATA_EXT = {"csv", "xlsx", "xls"}                              254
    # 头像只用浏览器能直接显示的格式（不含 bmp / tif），并单独限制体积                  255
    ALLOWED_AVATAR_EXT = {"png", "jpg", "jpeg", "gif",                     256
    "webp"}                                                                257
    MAX_AVATAR_LENGTH = 4 * 1024 * 1024          # 4 MB                    258
# ==== app/models.py ====                                                  259
# -*- coding: utf-8 -*-                                                    260
"""数据模型：系统全部数据表。                                                  261
本文件由甲在阶段 0 一次性写完，作为两人独立开发的地基。                          262
约定：两人只读此文件；确需改表时，由乙提需求、甲统一修改。                       263
"""                                                                        264
import json                                                                265
from datetime import datetime                                              266
from flask_login import UserMixin                                          267
from flask_sqlalchemy import SQLAlchemy                                    268
db = SQLAlchemy()                                                          269
class User(UserMixin, db.Model):                                           270
    """用户（账户与权限）。"""                                                 271
    __tablename__ = "users"                                                272
    id = db.Column(db.Integer, primary_key=True)                           273
    username = db.Column(db.String(64), unique=True,                       274
    nullable=False, index=True)                                            275
    password_hash = db.Column(db.String(256),                              276
    nullable=False)                                                        277
    # 职务只有两种：管理员 admin（可管理账号与他人的职务） / 操作员 operator          278
    role = db.Column(db.String(20), nullable=False,                        279
    default="operator")                                                    280
    active = db.Column(db.Boolean, nullable=False,                         281
    default=True)                                                          282
    created_at = db.Column(db.DateTime,                                    283
    default=datetime.utcnow)                                               284
    # ---- 个人资料（用户可在「个人设置」里自行维护）----                        285
    display_name = db.Column(db.String(64), nullable=True)                 286
    # 昵称                                                                 287
    email = db.Column(db.String(128), nullable=True)                       288
    phone = db.Column(db.String(32), nullable=True)                        289
    gender = db.Column(db.String(8), nullable=True)                        290
    # 男 / 女 / 保密                                                       291
    avatar = db.Column(db.String(256), nullable=True)                      292
    # 头像，相对 static 的路径                                             293
    @property                                                              294
    def is_admin(self):                                                    295
        return self.role == "admin"                                        296
    @property                                                              297
    def shown_name(self):                                                  298
        """界面上显示的名字：优先用昵称，没填就用账号名。"""                      299
        return self.display_name or self.username                          300
```

```
    @property                                                          301
    def initial(self):                                                 302
        """没有头像时用首字占位。"""                                    303
        return (self.shown_name or "?")[0].upper()                     304
    def to_dict(self):                                                 305
        return {"id": self.id, "username": self.username,              306
                "display_name": self.display_name,                     307
    "gender": self.gender,                                             308
                "role": self.role, "active": self.active}              309
class OperationLog(db.Model):                                          310
    """操作日志。"""                                                   311
    __tablename__ = "operation_logs"                                   312
    id = db.Column(db.Integer, primary_key=True)                       313
    user_id = db.Column(db.Integer, db.ForeignKey("users.id"           314
    ), nullable=True)                                                  315
    action = db.Column(db.String(128), nullable=False)                 316
    # 操作类型                                                         317
    target_type = db.Column(db.String(64), nullable=True)              318
    # 对象类型                                                         319
    target_id = db.Column(db.Integer, nullable=True)                   320
    # 对象主键                                                         321
    detail = db.Column(db.Text, nullable=True)                         322
    # 操作详情                                                         323
    created_at = db.Column(db.DateTime,                                324
    default=datetime.utcnow, index=True)                               325
class Project(db.Model):                                               326
    """评价项目（项目与矿山档案）。"""                                 327
    __tablename__ = "projects"                                         328
    id = db.Column(db.Integer, primary_key=True)                       329
    name = db.Column(db.String(128), nullable=False)                   330
    code = db.Column(db.String(64), nullable=True)                     331
    # 项目编号                                                         332
    description = db.Column(db.Text, nullable=True)                    333
    status = db.Column(db.String(20), default="进行中")                334
    # 进行中 / 已完成 / 已归档                                         335
    created_by = db.Column(db.Integer,                                 336
    db.ForeignKey("users.id"), nullable=True)                          337
    created_at = db.Column(db.DateTime,                                338
    default=datetime.utcnow)                                           339
    patches = db.relationship("MinePatch",                             340
    backref="project", lazy="dynamic",                                 341
                                  cascade="all, delete-orphan")        342
class MinePatch(db.Model):                                             343
    """矿山图斑。"""                                                   344
    __tablename__ = "mine_patches"                                     345
    id = db.Column(db.Integer, primary_key=True)                       346
    project_id = db.Column(db.Integer,                                 347
    db.ForeignKey("projects.id"), nullable=False)                      348
    name = db.Column(db.String(128), nullable=False)                   349
    admin_region = db.Column(db.String(128), nullable=True)            350
```

```
    # 所在行政区                                                    351
    center_x = db.Column(db.Float, nullable=True)                   352
    # 中心经度 / 横坐标                                             353
    center_y = db.Column(db.Float, nullable=True)                   354
    # 中心纬度 / 纵坐标                                             355
    area_ha = db.Column(db.Float, nullable=True)                    356
    # 图斑面积（公顷）                                              357
    mineral_type = db.Column(db.String(64), nullable=True)          358
    # 开采矿种                                                      359
    mining_method = db.Column(db.String(64), nullable=True)         360
    # 开采方式                                                      361
    stop_years = db.Column(db.Float, nullable=True)                 362
    # 停产年限                                                      363
    responsible_entity_missing = db.Column(db.Boolean,              364
    default=True)  # 责任主体是否缺失                               365
    # 遥感底图 / 无人机正射影像挂接                                 366
    image_path = db.Column(db.String(256), nullable=True)           367
    # 相对 static 的路径                                            368
    image_note = db.Column(db.String(256), nullable=True)           369
    # 影像说明（如来源、时相）                                      370
    image_uploaded_at = db.Column(db.DateTime,                      371
    nullable=True)                                                  372
    created_at = db.Column(db.DateTime,                             373
    default=datetime.utcnow)                                        374
    units = db.relationship("MicroUnit", backref="patch",           375
    lazy="dynamic",                                                 376
                                cascade="all, delete-orphan")       377
class ReferenceEcosystem(db.Model):                                 378
    """参照生态系统：标准化基准值，与图斑绑定。"""                  379
    __tablename__ = "reference_ecosystems"                          380
    id = db.Column(db.Integer, primary_key=True)                    381
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat        382
    ches.id"), nullable=False)                                      383
    coverage_benchmark = db.Column(db.Float, default=75.0)          384
    # 植被覆盖度基准 %                                              385
    shannon_benchmark = db.Column(db.Float, default=0.7)            386
    # Shannon-Wiener 基准                                           387
    dominant_species = db.Column(db.String(256),                    388
    nullable=True)  # 建群种                                       389
    soil_benchmark = db.Column(db.String(256),                      390
    nullable=True)     # 土壤基准                                   391
class Standard(db.Model):                                           392
    """地方标准 / 政策文件（政策与标准知识库）。"""                 393
    __tablename__ = "standards"                                     394
    id = db.Column(db.Integer, primary_key=True)                    395
    province = db.Column(db.String(32), nullable=False)             396
    # 省份                                                          397
    name = db.Column(db.String(256), nullable=False)                398
    # 名称                                                          399
    doc_number = db.Column(db.String(128), nullable=True)           400
```

```
    # 标准编号 / 文号
    publish_date = db.Column(db.String(32), nullable=True)
    implement_date = db.Column(db.String(32), nullable=True)
    # 类别：地方标准 / 政策文件
    category = db.Column(db.String(32), nullable=False,
    default="地方标准")
    summary = db.Column(db.Text, nullable=True)
    # 特点概述
    rules = db.relationship("StandardRule",
    backref="standard",
                            cascade="all, delete-orphan")
class StandardRule(db.Model):
    """结构化规则：将标准条文拆解为可执行规则。"""
    __tablename__ = "standard_rules"
    id = db.Column(db.Integer, primary_key=True)
    standard_id = db.Column(db.Integer,
    db.ForeignKey("standards.id"), nullable=False)
    item = db.Column(db.String(128), nullable=False)
    # 判定项
    operator = db.Column(db.String(8), nullable=False)
    # 比较符：> >= < <= ==
    threshold = db.Column(db.String(64), nullable=True)
    # 阈值
    condition_type = db.Column(db.String(32),
    default="必要条件")  # 必要条件 / 充分条件
    region = db.Column(db.String(64), nullable=True)
    # 适用分区（宁夏分区差异化）
    note = db.Column(db.Text, nullable=True)
class ConstraintCheck(db.Model):
    """限制性判定记录。"""
    __tablename__ = "constraint_checks"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    policy_pass = db.Column(db.Boolean, nullable=True)
    # 政策约束
    location_pass = db.Column(db.Boolean, nullable=True)
    # 区位约束
    pollution_pass = db.Column(db.Boolean, nullable=True)
    # 土壤污染
    geo_pass = db.Column(db.Boolean, nullable=True)
    # 地质灾害
    farmland_pass = db.Column(db.Boolean, nullable=True)
    # 耕地属性
    passed = db.Column(db.Boolean, nullable=True)
    # 总体是否通过
    reason = db.Column(db.Text, nullable=True)
    # 不通过原因
    checked_at = db.Column(db.DateTime,
    default=datetime.utcnow)
```

```
class MicroUnit(db.Model):
    """微地质单元：岩质边坡 / 碎石边坡 / 平台。"""
    __tablename__ = "micro_units"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    unit_type = db.Column(db.String(32), nullable=False)
    # 单元类型
    area = db.Column(db.Float, nullable=True)
    # 面积
    ratio = db.Column(db.Float, nullable=True)
    # 面积占比（自动计算）
    description = db.Column(db.Text, nullable=True)
    # 现场描述
class Indicator(db.Model):
    """指标定义：指标树，含角色与启用单元类型。"""
    __tablename__ = "indicators"
    id = db.Column(db.Integer, primary_key=True)
    code = db.Column(db.String(32), unique=True,
    nullable=False)  # 指标编码
    name = db.Column(db.String(64), nullable=False)
    # 指标名称
    level = db.Column(db.Integer, nullable=False)
    # 1/2/3 级
    parent_code = db.Column(db.String(32), nullable=True)
    # 父指标编码
    # 角色：土壤污染指标同时作为限制性指标与评价指标
    is_constraint = db.Column(db.Boolean, default=False)
    is_evaluative = db.Column(db.Boolean, default=True)
    unit = db.Column(db.String(32), nullable=True)
    # 单位
    ideal_value = db.Column(db.String(64), nullable=True)
    # 理想值（可配置）
    ideal_type = db.Column(db.String(32), nullable=True)
    # benefit/cost/mid/discrete
    # 启用该指标的微地质单元（逗号分隔）。岩质边坡不启用土壤指标、平台不启用地形指标
    enabled_units = db.Column(db.String(128), nullable=True)
    description = db.Column(db.Text, nullable=True)
    # 取值依据说明
    def units_list(self):
        return [s for s in (self.enabled_units or
    "").split(",") if s]
class WeightScheme(db.Model):
    """权重方案：按微地质单元类型分别保存。"""
    __tablename__ = "weight_schemes"
    id = db.Column(db.Integer, primary_key=True)
    unit_type = db.Column(db.String(32), nullable=False)
    # 所属单元类型
    name = db.Column(db.String(64), nullable=True)
    # 方案名称
```

```
    level = db.Column(db.Integer, nullable=False,                    501
    default=1)          #  1=一级指标  2=二级指标                    502
    is_default = db.Column(db.Boolean, default=False)                503
    #  是否默认（论文表 3）                                          504
    created_at = db.Column(db.DateTime,                              505
    default=datetime.utcnow)                                         506
class WeightItem(db.Model):                                          507
    """权重明细：方案内的各项权重。"""                              508
    __tablename__ = "weight_items"                                   509
    id = db.Column(db.Integer, primary_key=True)                     510
    scheme_id = db.Column(db.Integer,                                511
    db.ForeignKey("weight_schemes.id"), nullable=False)              512
    indicator_code = db.Column(db.String(32),                        513
    nullable=False)         #  指标编码                             514
    weight = db.Column(db.Float, nullable=False)                     515
    #  权重值                                                        516
class ExpertMatrix(db.Model):                                        517
    """专家判断矩阵：多专家打分的原始矩阵。"""                      518
    __tablename__ = "expert_matrices"                                519
    id = db.Column(db.Integer, primary_key=True)                     520
    scheme_id = db.Column(db.Integer,                                521
    db.ForeignKey("weight_schemes.id"), nullable=True)               522
    #  直接标注适用对象，便于无需先建权重方案即可录入专家矩阵      523
    unit_type = db.Column(db.String(32), nullable=True)              524
    #  微地质单元类型                                                525
    l1_name = db.Column(db.String(64), nullable=True)                526
    #  所属一级指标（二级矩阵用）                                    527
    expert_name = db.Column(db.String(64), nullable=True)            528
    #  专家姓名                                                      529
    level = db.Column(db.Integer, nullable=False,                    530
    default=1)          #  矩阵对应指标层级                          531
    matrix_json = db.Column(db.Text, nullable=False)                 532
    #  判断矩阵（JSON 二维数组）                                     533
    cr = db.Column(db.Float, nullable=True)                          534
    #  该专家矩阵的一致性比例                                        535
    created_at = db.Column(db.DateTime,                              536
    default=datetime.utcnow)                                         537
class IndicatorData(db.Model):                                       538
    """指标实测数据：按微地质单元组织。"""                          539
    __tablename__ = "indicator_data"                                 540
    id = db.Column(db.Integer, primary_key=True)                     541
    unit_id = db.Column(db.Integer, db.ForeignKey("micro_uni         542
    ts.id"), nullable=False, unique=True)                            543
    soil_ratio = db.Column(db.Float, nullable=True)                  544
    #  土石比                                                        545
    thickness = db.Column(db.Float, nullable=True)                   546
    #  土层厚度 cm                                                   547
    ph = db.Column(db.Float, nullable=True)                          548
    organic_matter = db.Column(db.Float, nullable=True)              549
    #  有机质 g/kg                                                   550
```

```
    # 重金属含量，JSON 字符串：{"Hg": 0.05, ...}，未检测项缺失或为 null
    heavy_metals = db.Column(db.Text, nullable=True)
    coverage = db.Column(db.Float, nullable=True)
    # 植被覆盖度 %
    shannon = db.Column(db.Float, nullable=True)
    # Shannon-Wiener 多样性指数
    slope = db.Column(db.Float, nullable=True)
    # 坡度 °
    aspect = db.Column(db.String(16), nullable=True)
    # 坡向：阳坡 / 阴阳坡 / 阴坡
    def heavy_metals_dict(self):
        return json.loads(self.heavy_metals) if
    self.heavy_metals else {}
class EvaluationResult(db.Model):
    """评价结果。"""
    __tablename__ = "evaluation_results"
    id = db.Column(db.Integer, primary_key=True)
    patch_id = db.Column(db.Integer, db.ForeignKey("mine_pat
    ches.id"), nullable=False)
    final_score = db.Column(db.Float, nullable=True)
    # 最终评价因子 F
    grade = db.Column(db.String(32), nullable=True)
    # 适宜性等级
    measures = db.Column(db.Text, nullable=True)
    # 推荐措施
    unit_scores = db.Column(db.Text, nullable=True)
    # 各单元得分 JSON
    created_at = db.Column(db.DateTime,
    default=datetime.utcnow)
class ScoreDetail(db.Model):
    """得分明细：每一层指标的权重、标准化值、加权贡献，供追溯与复核。"""
    __tablename__ = "score_details"
    id = db.Column(db.Integer, primary_key=True)
    result_id = db.Column(db.Integer,
    db.ForeignKey("evaluation_results.id"), nullable=False)
    unit_id = db.Column(db.Integer, nullable=True)
    l1_name = db.Column(db.String(64), nullable=True)
    # 一级指标
    l2_name = db.Column(db.String(64), nullable=True)
    # 二级指标
    raw_value = db.Column(db.String(64), nullable=True)
    # 实测值
    std_value = db.Column(db.Float, nullable=True)
    # 标准化值
    weight = db.Column(db.Float, nullable=True)
    # 权重
    contribution = db.Column(db.Float, nullable=True)
    # 加权贡献
# ==== app/forms.py ====
# -*- coding: utf-8 -*-
```

```
"""表单定义（共享，由甲统一维护）。
各模块的 Flask-WTF 表单集中于此。
"""
import re
from flask_wtf import FlaskForm
from wtforms import SelectField, SubmitField, StringField,
    PasswordField, BooleanField
from wtforms.validators import (DataRequired, Length,
    Optional, EqualTo,
                                ValidationError)
from app.utils.constants import UNIT_TYPES, ASPECT_TYPES,
    GENDERS
#  邮箱格式：够用的轻量校验。
#  WTForms 自带的 Email() 需要额外安装 email_validator，
#  为一个字段引入依赖不划算，这里自己用正则判断。
EMAIL_RE = re.compile(r"^[^@\s]+@[^@\s]+\.[A-Za-z]{2,}$")
def email_format(form, field):
    v = (field.data or "").strip()
    if v and not EMAIL_RE.match(v):
        raise ValidationError("邮箱格式不正确")
def email_ok(value):
    """邮箱格式判断，供不用 WTForms 的表单复用（如管理员编辑用户）。"""
    v = (value or "").strip()
    return (not v) or bool(EMAIL_RE.match(v))
class AHPSelectForm(FlaskForm):
    """选择微地质单元类型与指标层级，以确定判断矩阵规模。"""
    unit_type = SelectField("微地质单元类型",
    validators=[DataRequired()])
    level = SelectField("指标层级",
                        choices=[("1", "一级指标"), ("2",
    "二级指标")],
                        validators=[DataRequired()])
    l1 = SelectField("一级指标", validators=[],
    validate_choice=False)  #  动态填充，层级=2 时使用
    submit = SubmitField("生成判断矩阵")
    def __init__(self, *args, **kwargs):
        super().__init__(*args, **kwargs)
        self.unit_type.choices = [(t, t) for t in
    UNIT_TYPES]
class EmptyForm(FlaskForm):
    """仅用于承载 CSRF 令牌的空表单（矩阵录入等自定义表单使用）。"""
    pass
class LoginForm(FlaskForm):
    """登录表单。支持「记住我」以在关闭浏览器后保持登录状态。
    校验消息用中文写明：登录框带 novalidate，浏览器不会代填提示，
    字段为空时若不自己给消息，用户点了「登录」会以为没反应。
    """
    username = StringField("账户名称",
                           validators=[DataRequired(message=
    "请输入账户名称"),
```

```
                                                    Length(max=64,
    message="账户名称不能超过 64 个字符")])
    password = PasswordField("密码",
                                validators=[DataRequired(messag
    e="请输入密码")])
    remember = BooleanField("记住我")
    submit = SubmitField("登录")
GENDER_CHOICES = [("", "不填")] + [(g, g) for g in GENDERS]
class ProfileForm(FlaskForm):
    """个人资料：昵称、性别与联系方式。字段都可留空。
    职务不在这里 —— 只能由管理员在「个人设置 · 账号」里改。
    """
    display_name = StringField("昵称", validators=[Optional(),
    Length(max=64)])
    gender = SelectField("性别", choices=GENDER_CHOICES,
    validators=[Optional()])
    email = StringField("邮箱", validators=[Optional(),
    email_format,
                                            Length(max=128)])
    phone = StringField("手机号", validators=[Optional(),
    Length(max=32)])
    submit_info = SubmitField("保存资料")
class RegisterForm(FlaskForm):
    """注册：账号与密码必填，其余选填。注册后默认是操作员。"""
    username = StringField("账号名称",
                           validators=[DataRequired("请填写账号名称
    "),
                                                    Length(min=2, max=64,
                                                           message="账号名称
    2–64 个字符")])
    password = PasswordField("密码",
                                validators=[DataRequired("请设置密码
    "),
                                                      Length(min=6,
    max=64,

    message="密码至少 6 位")])
    confirm = PasswordField("确认密码",
                            validators=[DataRequired(),
                                                      EqualTo("password",

    message="两次输入的密码不一致")])
    display_name = StringField("昵称", validators=[Optional(),
    Length(max=64)])
    gender = SelectField("性别", choices=GENDER_CHOICES,
    validators=[Optional()])
    email = StringField("邮箱", validators=[Optional(),
    email_format,
                                            Length(max=128)])
```

```
    phone = StringField("手机号", validators=[Optional(),
    Length(max=32)])
    submit_reg = SubmitField("注册并登录")
class PasswordForm(FlaskForm):
    """修改密码：需要先验证当前密码。"""
    old_password = PasswordField("当前密码",
    validators=[DataRequired()])
    new_password = PasswordField("新密码",
                                 validators=[DataRequired(),
    Length(min=6, max=64,

    message="新密码至少 6 位")])
    confirm = PasswordField("确认新密码",
                            validators=[DataRequired(),

    EqualTo("new_password",

    message="两次输入的新密码不一致")])
    submit_pwd = SubmitField("修改密码")
#  ==== app/utils/constants.py ====
#  -*- coding: utf-8 -*-
"""评价指标常量表。
全部数值取自论文，作为系统计算的唯一基准：
- 论文 ４．２．２ 节：指标标准化理想极值与取值依据
- 论文 ４．２．３ 节 / 表 ４：适宜性等级划分
- 论文表 ３：按微地质单元分别确定的一级、二级指标权重
- 论文 ４．２．１ 节：平均随机一致性指标 ＲＩ
"""
#  ------------------------------------------------------------------
    ------------------
#  一、微地质单元类型
#  ------------------------------------------------------------------
    ------------------
#  论文 ４．１ 节："按照地形地貌划分，将其划分为平台、碎石边坡和岩质边坡
#  三种地质微单元类型"
UNIT_TYPES = ("岩质边坡", "碎石边坡", "平台")
#  每个单元类型启用的指标类别（论文表 ３ 隐含：岩质边坡无土壤指标，平台无地形指标）
#  供数据录入界面与评价引擎判断"该单元是否需要某类指标"
UNIT_ENABLED_INDICATORS = {
    "岩质边坡": ("植被指标", "地形指标"),                # 不设土壤指标
    "碎石边坡": ("土壤指标", "植被指标", "地形指标"),
    "平台": ("土壤指标", "植被指标"),                    # 不设地形指标
}
#  ------------------------------------------------------------------
    ------------------
#  二、指标标准化理想极值（论文 ４．２．２ 节）
#  ------------------------------------------------------------------
    ------------------
IDEAL_SOIL_RATIO = 0.8          # 土石比理想值
IDEAL_THICKNESS = 20.0          # 土层厚度理想值 （cm）
```

```
IDEAL_PH_RANGE = (5.0, 9.0)      # pH 理想区间（适中型指标）
IDEAL_ORGANIC = 30.0             # 有机质理想值
    (g/kg)，全国第二次土壤普查养分等级划分标准二等最低值
IDEAL_COVERAGE = 75.0            # 植被覆盖度参照生态系统 (%)
IDEAL_SHANNON = 0.7              # Shannon-Wiener 多样性指数参照生态系统
# 重金属极值 (mg/kg)，《绿化种植土壤》CJ/T 340—2016 土壤重金属含量 IV 级最高值
# 论文原文：镉、汞、铅、铬、砷、镍、铜、锌分别为 2、2、530、400、45、220、600、800
HEAVY_METALS = ("Cd", "Hg", "Pb", "Cr", "As", "Ni", "Cu",
    "Zn")
HEAVY_METAL_LIMIT = {
    "Cd": 2.0, "Hg": 2.0, "Pb": 530.0, "Cr": 400.0,
    "As": 45.0, "Ni": 220.0, "Cu": 600.0, "Zn": 800.0,
}
# 污染指标下 8 种重金属"重要性相当，权重平均分配"（论文 4.2.1 节）
HEAVY_METAL_EQUAL_WEIGHT = 1.0 / 8.0
# 坡度分界，论文 4.2.2 节引《新一轮退耕还林还草总体方案》发改西部〔2014〕1772 号
SLOPE_BREAK = 25.0
# 坡向离散赋值，论文 4.2.2 节："阳坡、阴阳坡、阴坡分别赋值 0.2、0.6、1"
ASPECT_SCORES = {"阳坡": 0.2, "阴阳坡": 0.6, "阴坡": 1.0}
ASPECT_TYPES = ("阳坡", "阴阳坡", "阴坡")
# pH 适中型标准化的容差边界（区间外线性衰减，避免得分突变）
PH_TOL_LOW = 4.0
PH_TOL_HIGH = 10.0
# ---------------------------------------------------------------
    ----------------
# 三、适宜性等级划分（论文表 4）
# ---------------------------------------------------------------
    ----------------
GRADE_LEVELS = (
    {"grade": "不适宜", "min": None, "max": 0.3,
     "meaning": "存在限制性条件或区域生态本底较差，自然恢复影响因子严重制约自然恢复",
     "measure": "生态重建、人工辅助"},
    {"grade": "基本适宜", "min": 0.3, "max": 0.7,
     "meaning": "生态本底良好，核心自然恢复影响因子基本满足自然恢复需求",
     "measure": "自然恢复为主，可辅以封闭场地和少量补种、补植、飞播等"},
    {"grade": "适宜", "min": 0.7, "max": None,
     "meaning": "各自然恢复影响因子均能满足自然恢复需求，自然演替速度快",
     "measure": "自然恢复"},
)
def grade_of(score):
    """按论文表 4 判定适宜性等级。"""
    for g in GRADE_LEVELS:
        lo, hi = g["min"], g["max"]
        if lo is None and score < hi:
            return g
        if hi is None and score >= lo:
            return g
        if lo is not None and hi is not None and lo <=
    score < hi:
            return g
```

```
        #  s c o r e  恰好等于  0 . 7  时落入 " 适宜 "                                  801
        r e t u r n  G R A D E _ L E V E L S [ - 1 ]                                  802
#  - - -
```

```
#  ----------------------------------------------------------------------  851
    ------------------                                                      852
#  论文摘要与  4．1  节：四项限制性指标；流程段另明确＂是否为耕地＂为约束条件  853
CONSTRAINT_ITEMS  =  （＂政策＂，  ＂区位约束＂，  ＂土壤污染＂，  ＂地质灾害＂，  ＂耕地属性＂）  854
#  ----------------------------------------------------------------------  855
    ------------------                                                      856
#  七、账号职务                                                             857
#  ----------------------------------------------------------------------  858
    ------------------                                                      859
#  只分两种：管理员可管理账号、维护基础数据并查看操作日志，操作员用业务功能。  860
ROLE_LABELS  =  {＂admin＂:  ＂管理员＂，  ＂operator＂:  ＂操作员＂}        861
ROLE_CODES  =  （＂admin＂，  ＂operator＂）                                 862
DEFAULT_ROLE  =  ＂operator＂                #  新注册账号的默认职务         863
ROLE_ORDER  =  （＂admin＂，  ＂operator＂）    #  列表排序用：管理员在前     864
#  性别（注册与个人资料中选填）                                             865
GENDERS  =  （＂男＂，  ＂女＂，  ＂保密＂）                                 866
#  ====  app/utils/schema.py  ====                                         867
#  -*-  coding:  utf-8  -*-                                                868
＂＂＂轻量结构迁移。                                                        869
SQLite  下  `db.create_all()`  只建缺失的表，不会给已有表补列。             870
本模块在启动时检查目标列是否存在，缺失则  ALTER  TABLE  补上，               871
使旧数据库无需重建即可用上新字段。                                          872
＂＂＂                                                                      873
from  sqlalchemy  import  text                                              874
#  （表名，  列名，  列定义）                                               875
REQUIRED_COLUMNS  =  [                                                      876
    #  遥感影像挂接                                                         877
    （＂mine_patches＂，  ＂image_path＂，  ＂VARCHAR(256)＂），             878
    （＂mine_patches＂，  ＂image_note＂，  ＂VARCHAR(256)＂），             879
    （＂mine_patches＂，  ＂image_uploaded_at＂，  ＂DATETIME＂），          880
    #  指标维护                                                             881
    （＂indicators＂，  ＂enabled_units＂，  ＂VARCHAR(128)＂），            882
    （＂indicators＂，  ＂description＂，  ＂TEXT＂），                      883
    #  多专家矩阵                                                           884
    （＂expert_matrices＂，  ＂unit_type＂，  ＂VARCHAR(32)＂），           885
    （＂expert_matrices＂，  ＂l1_name＂，  ＂VARCHAR(64)＂），             886
    （＂expert_matrices＂，  ＂cr＂，  ＂FLOAT＂），                         887
    #  用户个人资料（账户页）                                               888
    （＂users＂，  ＂display_name＂，  ＂VARCHAR(64)＂），                   889
    （＂users＂，  ＂email＂，  ＂VARCHAR(128)＂），                         890
    （＂users＂，  ＂phone＂，  ＂VARCHAR(32)＂），                          891
    （＂users＂，  ＂gender＂，  ＂VARCHAR(8)＂），                          892
    （＂users＂，  ＂avatar＂，  ＂VARCHAR(256)＂），                        893
]                                                                           894
#  职务体系由「管理员  /  评价员  /  查看者」三种收敛为「管理员  /  操作员」两种，  895
#  旧数据里的后两种统一归为操作员。                                         896
ROLE_MIGRATION  =  {＂evaluator＂:  ＂operator＂，  ＂viewer＂:             897
    ＂operator＂}                                                           898
def  _add_columns(db):                                                      899
    added  =  []                                                            900
```

```
    with db.engine.connect() as conn:
        for table, column, ddl in REQUIRED_COLUMNS:
            rows = conn.execute(text("PRAGMA
    table_info(%s)" % table)).fetchall()
            if not rows:
                continue                                #
    表还不存在，create_all 会建
            existing = {r[1] for r in rows}
            if column in existing:
                continue
            conn.execute(text(
                "ALTER TABLE %s ADD COLUMN %s %s" % (table,
    column, ddl)))
            conn.commit()
            added.append("%s.%s" % (table, column))
    return added
def _migrate_roles(db):
    """把旧角色名统一为新的两种，返回改动的行数。"""
    changed = 0
    with db.engine.connect() as conn:
        rows = conn.execute(text("PRAGMA
    table_info(users)")).fetchall()
        if not rows:
            return 0
        for old, new in ROLE_MIGRATION.items():
            r = conn.execute(text("UPDATE users SET role =
    :new "
                                  "WHERE role = :old"),
                                 {"new": new, "old": old})
            changed += r.rowcount or 0
        conn.commit()
    return changed
def ensure_schema(db):
    """为已有表补齐缺失列，并做必要的数据迁移。返回变更清单。"""
    try:
        changed = _add_columns(db)
        n = _migrate_roles(db)
        if n:
            changed.append("用户角色归一为管理员 / 操作员 %d 条" % n)
        return changed
    except Exception as e:                              #
    迁移失败不应阻断启动
        print("[schema] 结构检查跳过：%s" % e)
        return []
# ==== app/utils/uploads.py ====
# -*- coding: utf-8 -*-
"""上传文件处理（遥感影像、批量导入）。"""
import os
import re
import uuid
```

```
from datetime import datetime
from werkzeug.utils import secure_filename
def _safe_ext(filename):
    return os.path.splitext(filename)[1].lower().lstrip(".")
def ext_allowed(filename, allowed):
    return _safe_ext(filename) in allowed
def save_upload(file_storage, subdir, allowed_ext,
    upload_root):
    """保存上传文件，返回相对 static 的路径（如 uploads/patches/xxx.png）。
    文件名重命名为「时间戳_随机串.扩展名」，避免中文名与重名问题。
    """
    if file_storage is None or not file_storage.filename:
        return None, "未选择文件"
    ext = _safe_ext(file_storage.filename)
    if ext not in allowed_ext:
        return None, "不支持的文件类型：.%s" % ext
    target_dir = os.path.join(upload_root, subdir)
    os.makedirs(target_dir, exist_ok=True)
    # 仅保留安全字符，并加时间戳与随机串防重名
    base = secure_filename(os.path.splitext(file_storage.fil
    ename)[0]) or "file"
    base = re.sub(r"[^A-Za-z0-9_\-]", "", base)[:40] or
    "file"
    name = "%s_%s.%s" % (datetime.now().strftime("%Y%m%d%H%M
    %S"),
                         uuid.uuid4().hex[:6], ext)
    abs_path = os.path.join(target_dir, name)
    file_storage.save(abs_path)
    rel = os.path.join("uploads", subdir,
    name).replace("\\", "/")
    return rel, None
def remove_upload(rel_path, upload_root):
    """删除已保存的上传文件（相对 static 的路径）。"""
    if not rel_path:
        return
    abs_path = os.path.join(upload_root,
    rel_path.replace("uploads/", "", 1))
    try:
        if os.path.isfile(abs_path):
            os.remove(abs_path)
    except OSError:
        pass
# ==== app/utils/charts.py ====
# -*- coding: utf-8 -*-
"""轻量图表。
用纯 SVG 输出，不依赖任何绘图库或前端脚本：
- 服务端渲染，页面与打印（PDF）中都能稳定显示
- 每个图元都带数值标签，黑白打印时仍可读（不单靠颜色区分）
- 单色方案，符合界面「一个视图一个强调色」的约定
"""
```

```
from html import escape
ACCENT = "#1f3a5f"
ACCENT_SOFT = "#7f93ad"
INK = "#23262b"
MUTED = "#6b7280"
LINE = "#dfe3e8"
#  灰度梯度：黑白打印时相邻扇区 / 条柱仍可区分
GRAYS = ["#1f3a5f", "#456188", "#6d86a8", "#96a9c4",
    "#bcc9da", "#dbe3ec"]
def _fmt(v, digits=4):
    try:
        return ("%%.%df" % digits) % float(v)
    except (TypeError, ValueError):
        return str(v)
def hbars(items, width=620, bar_h=22, gap=12, label_w=150,
    value_w=76):
    """水平条形图。items: [(标签, 数值, 显示文本)]"""
    if not items:
        return '<p class="muted">暂无数据</p>'
    n = len(items)
    height = n * (bar_h + gap) + 10
    max_v = max((abs(float(v)) for _, v, _ in items),
    default=1) or 1
    body_w = width - label_w - value_w
    parts = ['<svg viewBox="0 0 %d %d" width="100%%"
    height="%d" '
             'role="img" aria-label="条形图" '
             'style="max-width:%dpx;font-family:inherit;">'
    % (width, height, height, width)]
    for i, (label, value, disp) in enumerate(items):
        y = i * (bar_h + gap) + 5
        frac = (abs(float(value)) / max_v) if max_v else 0
        w = max(2.0, body_w * frac)
        fill = GRAYS[i % len(GRAYS)]
        parts.append(
            '<text x="%d" y="%d" text-anchor="end"
    font-size="12" fill="%s">%s</text>'
            % (label_w - 10, y + bar_h * 0.72, INK,
    escape(str(label))))
        parts.append(
            '<rect x="%d" y="%d" width="%.1f" height="%d"
    rx="3" fill="%s"/>'
            % (label_w, y, w, bar_h, fill))
        parts.append(
            '<text x="%d" y="%d" font-size="12" fill="%s" '
            'style="font-variant-numeric:tabular-nums;">%s</
    text>'
            % (label_w + w + 8, y + bar_h * 0.72, MUTED,
    escape(str(disp))))
    parts.append('</svg>')
```

```
    return "".join(parts)                                                1051
def donut(items, size=210, thickness=34):                                1052
    """环形图（权重分布）。items: [(标签, 数值, 显示文本)]                1053
    图例中给出数值与占比，黑白打印时靠图例与灰度深浅区分。                1054
    """                                                                  1055
    vals = [(l, float(v), d) for l, v, d in items if                     1056
    float(v) > 0]                                                        1057
    if not vals:                                                         1058
        return '<p class="muted">暂无数据</p>'                           1059
    total = sum(v for _, v, _ in vals) or 1                              1060
    r = (size - thickness) / 2                                           1061
    cx = cy = size / 2                                                   1062
    import math                                                          1063
    parts = ['<svg viewBox="0 0 %d %d" width="%d"                        1064
    height="%d" role="img" '                                             1065
             'aria-label="权重分布环形图">' % (size, size, size,         1066
    size)]                                                               1067
    angle = -math.pi / 2                                                 1068
    for i, (label, v, disp) in enumerate(vals):                          1069
        sweep = 2 * math.pi * (v / total)                                1070
        a0, a1 = angle, angle + sweep                                    1071
        x0, y0 = cx + r * math.cos(a0), cy + r *                         1072
    math.sin(a0)                                                         1073
        x1, y1 = cx + r * math.cos(a1), cy + r *                         1074
    math.sin(a1)                                                         1075
        large = 1 if sweep > math.pi else 0                              1076
        parts.append(                                                    1077
            '<path d="M %.2f %.2f A %.2f %.2f 0 %d 1 %.2f                1078
    %.2f" '                                                              1079
            'fill="none" stroke="%s" stroke-width="%d"/>'                1080
           % (x0, y0, r, r, large, x1, y1, GRAYS[i %                     1081
    len(GRAYS)], thickness))                                             1082
        angle = a1                                                       1083
    parts.append('<text x="%d" y="%d" text-anchor="middle"               1084
    font-size="12" '                                                     1085
                 'fill="%s">合计</text>' % (cx, cy - 2,                  1086
    MUTED))                                                              1087
    parts.append('<text x="%d" y="%d" text-anchor="middle"               1088
    font-size="15" '                                                     1089
                 'fill="%s" style="font-variant-numeric:tabu             1090
    lar-nums;">%s</text>'                                                1091
                 % (cx, cy + 18, INK, _fmt(total, 4)))                   1092
    parts.append('</svg>')                                               1093
    legend = ['<table style="width:auto;margin-top:10px;"><t             1094
    head><tr>'                                                           1095
              '<th scope="col">项目</th><th                              1096
    scope="col">数值</th>'                                               1097
              '<th scope="col">占比</th></tr></thead><tbody>']           1098
    for i, (label, v, disp) in enumerate(vals):                          1099
        legend.append(                                                   1100
```

```
                '<tr><td style="text-align:left;">'                    1101
                '<span style="display:inline-block;width:10px;he       1102
    ight:10px;'                                                        1103
                'border-radius:2px;background:%s;margin-right:6p       1104
    x;"></span>%s</td>'                                                1105
                '<td class="mono">%s</td><td                           1106
    class="mono">%.1f%%</td></tr>'                                     1107
                % (GRAYS[i % len(GRAYS)], escape(str(label)),          1108
    escape(str(disp)),                                                 1109
                    100.0 * v / total))                                1110
    legend.append('</tbody></table>')                                  1111
    return ('<div style="display:flex;flex-wrap:wrap;gap:20p           1112
    x;align-items:center;">'                                           1113
                + "".join(parts) + "".join(legend) + '</div>')         1114
# ==== app/utils/browser.py ====                                       1115
# -*- coding: utf-8 -*-                                                1116
"""HTML 转 PDF（报告导出）。                                           1117
复用本机已安装的 Chrome/Edge 无头模式打印，避免引入 reportlab、        1118
weasyprint 等额外依赖。生成过程使用系统临时目录中的 ASCII 文件名，     1119
避免中文路径在 file:// URL 下出问题。                                  1120
"""                                                                    1121
import os                                                              1122
import shutil                                                          1123
import subprocess                                                      1124
import tempfile                                                        1125
import uuid                                                            1126
CANDIDATES = [                                                         1127
    r"C:\Program Files\Google\Chrome\Application\chrome.exe"           1128
    ,                                                                  1129
    r"C:\Program Files (x86)\Google\Chrome\Application\chrom           1130
    e.exe",                                                            1131
    r"C:\Program Files (x86)\Microsoft\Edge\Application\msed           1132
    ge.exe",                                                           1133
    r"C:\Program Files\Microsoft\Edge\Application\msedge.exe           1134
    ",                                                                 1135
]                                                                      1136
# 允许通过环境变量覆盖，便于在其他机器上指定浏览器                     1137
ENV_KEY = "DSH_BROWSER_PATH"                                           1138
def browser_path():                                                    1139
    """定位可用的浏览器可执行文件，找不到返回 None。"""               1140
    override = os.environ.get(ENV_KEY)                                 1141
    if override and os.path.isfile(override):                          1142
        return override                                                1143
    for p in CANDIDATES:                                               1144
        if os.path.isfile(p):                                          1145
            return p                                                   1146
    for name in ("chrome", "msedge", "chromium"):                      1147
        found = shutil.which(name)                                     1148
        if found:                                                      1149
            return found                                               1150
```

```
    return None
def html_to_pdf(html, timeout=90):
    """把 HTML 字符串渲染为 PDF，返回字节；失败返回 (None, 原因)。"""
    exe = browser_path()
    if exe is None:
        return None, ("未找到可用的浏览器（Chrome/Edge），无法生成 PDF。"
                      "可设置环境变量 %s 指向浏览器可执行文件。" % ENV_KEY)
    tmpdir = tempfile.mkdtemp(prefix="dshpdf_")
    tag = uuid.uuid4().hex[:8]
    html_path = os.path.join(tmpdir, "r_%s.html" % tag)
    pdf_path = os.path.join(tmpdir, "r_%s.pdf" % tag)
    try:
        with open(html_path, "w", encoding="utf-8") as f:
            f.write(html)
        cmd = [
            exe, "--headless=new", "--disable-gpu",
    "--no-sandbox",
            "--no-first-run", "--no-default-browser-check",
            "--no-pdf-header-footer",
            "--virtual-time-budget=4000",
            "--print-to-pdf=%s" % pdf_path,
            "file:///" + html_path.replace("\\", "/"),
        ]
        p = subprocess.run(cmd, capture_output=True,
    text=True,
                           timeout=timeout,
    encoding="utf-8", errors="replace")
        if not os.path.isfile(pdf_path) or
    os.path.getsize(pdf_path) < 800:
            return None, "浏览器未能生成 PDF（%s）" % (p.stderr or
    "").strip()[:200]
        with open(pdf_path, "rb") as f:
            return f.read(), None
    except subprocess.TimeoutExpired:
        return None, "生成 PDF 超时，请稍后重试"
    except Exception as e:
        return None, "生成 PDF 失败：%s" % e
    finally:
        shutil.rmtree(tmpdir, ignore_errors=True)
# ==== app/services/ahp_service.py ====
# -*- coding: utf-8 -*-
"""AHP 权重引擎。
严格按论文 4.2.1 节实现：
- 式(2)(3)(4)：特征根法求权重（行元素乘积 → n 次方根 → 归一化）
- 式(5)(6)(7)：一致性检验（λmax、CI、CR）
- 论文要求 CR < 0.1；RI 按阶数查表
"""
import numpy as np
from app.utils.constants import RI_TABLE, CR_THRESHOLD
def matrix_from_upper(upper):
```

```
    """由判断矩阵上三角构造完整互反矩阵。
    参数
    ----
    upper : list[list[float]] 或 np.ndarray，上三角元素（不含对角线）。
        例：3 阶时传入 [[a12, a13], [a23]]。
        对角线为 1，下三角取倒数（a_ji = 1/a_ij）。
    """
    upper = np.asarray(upper, dtype=float)
    k = upper.shape[0]
    n = int(round((1 + (1 + 8 * k) ** 0.5) / 2))
    A = np.ones((n, n), dtype=float)
    idx = 0
    for i in range(n):
        for j in range(i + 1, n):
            A[i, j] = upper[idx]
            A[j, i] = 1.0 / upper[idx]
            idx += 1
    return A
def weights_and_consistency(A):
    """由判断矩阵 A 计算权重与一致性指标。
    返回
    ----
    dict：{weights: np.ndarray, lambda_max, ci, cr, n,
    consistent: bool}
    """
    A = np.asarray(A, dtype=float)
    n = A.shape[0]
    # 式(2) 行元素乘积
    row_prod = np.prod(A, axis=1)
    # 式(3) 开 n 次方根
    root = row_prod ** (1.0 / n)
    # 式(4) 归一化
    weights = root / root.sum()
    # 式(5) 最大特征值 λmax = (1/n) Σ (A·W)_i / W_i
    aw = A.dot(weights)
    lambda_max = float(np.sum(aw / weights) / n)
    # 式(6) 一致性指标 CI
    ci = (lambda_max - n) / (n - 1) if n > 1 else 0.0
    # 式(7) 一致性比例 CR = CI / RI
    ri = RI_TABLE.get(n, 1.49)
    cr = ci / ri if ri else 0.0
    return {
        "weights": weights,
        "lambda_max": lambda_max,
        "ci": ci,
        "cr": cr,
        "n": n,
        "consistent": cr < CR_THRESHOLD,
    }
def find_most_inconsistent(A):
```

```
    """定位判断矩阵中最不一致的一对比较。
    依据：完全一致矩阵应满足 a_ij = w_i / w_j。
    计算每个上三角元素与其理想值的相对偏差，返回偏差最大者。
    返回
    ----
    dict：{i, j, value, expected, deviation}，偏差最大的 (i, j)
    及对应取值。
    """
    A = np.asarray(A, dtype=float)
    r = weights_and_consistency(A)
    w = r["weights"]
    n = A.shape[0]
    best = None
    for i in range(n):
        for j in range(i + 1, n):
            expected = w[i] / w[j]
            if expected == 0:
                continue
            deviation = abs(A[i, j] - expected) / expected
            if best is None or deviation >
    best["deviation"]:
                best = {"i": i, "j": j, "value": A[i, j],
                        "expected": expected, "deviation":
    deviation}
    return best
def aggregate_matrices(matrices):
    """多专家判断矩阵聚合：几何平均（保持互反性）。
    参数
    ----
    matrices : list[np.ndarray]，多个同阶判断矩阵。
    """
    stack = np.stack([np.asarray(m, dtype=float) for m in
    matrices])
    return np.prod(stack, axis=0) ** (1.0 / len(stack))
def judge_from_weights(weights):
    """由权重向量构造完全一致判断矩阵并检验。
    用途：验证给定权重向量能否作为某个完全一致判断矩阵的主特征向量
    （A_ij = w_i / w_j 时 λmax = n、CR = 0）。
    """
    w = np.asarray(weights, dtype=float)
    n = w.shape[0]
    A = np.outer(w, 1.0 / w)
    r = weights_and_consistency(A)
    r["matrix"] = A
    return r
# ==== app/services/standardization.py ====
# -*- coding: utf-8 -*-
"""指标标准化（的一部分）。
按论文 4.2.2 节式(8) 实现：
    x' = (x - x_min) / (x_max - x_min)
```

```
按指标性质分为四类：越大越优 / 越小越优 / 适中 / 离散赋值。
所有理想极值取自 app.utils.constants，可配置。
"""
from app.utils.constants import (
    IDEAL_SOIL_RATIO, IDEAL_THICKNESS, IDEAL_PH_RANGE,
    IDEAL_ORGANIC,
    IDEAL_COVERAGE, IDEAL_SHANNON, HEAVY_METAL_LIMIT,
    HEAVY_METAL_EQUAL_WEIGHT, SLOPE_BREAK, ASPECT_SCORES,
    PH_TOL_LOW, PH_TOL_HIGH,
)
def std_benefit(value, ideal):
    """越大越优指标标准化：以理想值为上限，按比例给分，饱和于 [0,1]。"""
    if value is None:
        return None
    return max(0.0, min(1.0, value / ideal))
def std_cost(value, extreme):
    """越小越优指标标准化：以极值为参考，线性折减至 [0,1]。"""
    if value is None:
        return None
    return max(0.0, min(1.0, 1.0 - value / extreme))
def std_mid_ph(value, lo, hi, tol_lo=PH_TOL_LOW,
    tol_hi=PH_TOL_HIGH):
    """适中型指标标准化（pH）：理想区间内取 1，区间外线性衰减。"""
    if value is None:
        return None
    if lo <= value <= hi:
        return 1.0
    if value > hi:
        return max(0.0, (tol_hi - value) / (tol_hi - hi))
    return max(0.0, (value - tol_lo) / (lo - tol_lo))
def std_slope(value, break_point=SLOPE_BREAK, upper=90.0):
    """坡度标准化。
    论文 4.2.2 节：以 25° 为陡坡重要分界。25° 及以下记满分 1，
    超过 25° 线性折减，90° 记 0。
    """
    if value is None:
        return None
    if value <= break_point:
        return 1.0
    return max(0.0, (upper - value) / (upper - break_point))
def aspect_score(aspect):
    """坡向离散赋值：阳坡 0.2 / 阴阳坡 0.6 / 阴坡 1.0（论文 4.2.2 节）。"""
    if aspect is None:
        return None
    return ASPECT_SCORES.get(aspect)
def pollution_score(heavy_metals):
    """污染指标：8 种重金属等权（各 0.125）合成。
    论文注：未检测 Cr、Zn 的，从矿山类型看未受污染，按无污染（=1）处理。
    heavy_metals : dict，键为金属名，值为含量 mg/kg；缺失键视为未检测。
    """
```

```
    total = 0.0                                                          1351
    for metal, extreme in HEAVY_METAL_LIMIT.items():                     1352
        value = heavy_metals.get(metal)                                  1353
        total += std_cost(value, extreme) if value is not                1354
    None else 1.0                                                        1355
    return total / len(HEAVY_METAL_LIMIT)                                1356
def standardize_unit(unit_type, data, weights=None):                     1357
    """对单个微地质单元的全部指标做标准化。                                  1358
    参数                                                                 1359
    ----                                                                 1360
    unit_type : str，岩质边坡 / 碎石边坡 / 平台                            1361
    data : dict，实测数据，字段见接口契约：                                 1362
        soil_ratio, thickness, ph, organic_matter,                       1363
    heavy_metals(dict),                                                  1364
        coverage, shannon, slope, aspect                                 1365
    weights : dict，该单元类型的权重（app.utils.constants.DEFAULT_WEIG   1366
    HTS 结构），                                                         1367
                未提供时用默认值。                                        1368
    返回                                                                 1369
    ----                                                                 1370
    dict：{ 一级指标： { 二级指标： （实测值， 标准化值， 权重， 贡献） } }   1371
    标准化值可能为 None，表示该指标不适用或方法待定。                       1372
    """                                                                  1373
    from app.utils.constants import DEFAULT_WEIGHTS                      1374
    if weights is None:                                                  1375
        weights = DEFAULT_WEIGHTS[unit_type]                             1376
    l1_enabled = weights["l1"].keys()                                    1377
    l2w = weights["l2"]                                                  1378
    result = {}                                                          1379
    # ---- 土壤指标 ----                                                 1380
    if "土壤指标" in l1_enabled:                                          1381
        result["土壤指标"] = {                                            1382
            "土石比": (data.get("soil_ratio"),                           1383
                       std_benefit(data.get("soil_ratio"),               1384
    IDEAL_SOIL_RATIO),                                                   1385
                       l2w["土壤指标"]["土石比"]),                        1386
            "土层厚度": (data.get("thickness"),                          1387
                         std_benefit(data.get("thickness"),              1388
    IDEAL_THICKNESS),                                                    1389
                         l2w["土壤指标"]["土层厚度"]),                    1390
            "pH": (data.get("ph"),                                       1391
                   std_mid_ph(data.get("ph"),                            1392
    *IDEAL_PH_RANGE),                                                    1393
                   l2w["土壤指标"]["pH"]),                               1394
            "有机质": (data.get("organic_matter"),                       1395
                       std_benefit(data.get("organic_matter")            1396
    , IDEAL_ORGANIC),                                                    1397
                       l2w["土壤指标"]["有机质"]),                       1398
            "污染指标": (data.get("heavy_metals") or {},                 1399
                         pollution_score(data.get("heavy_meta            1400
```

```
        ls") or {}),                                                    1401
                                    l2w["土壤指标"]["污染指标"]),          1402
            }                                                           1403
        # ---- 植被指标 ----                                           1404
        if "植被指标" in l1_enabled:                                    1405
            result["植被指标"] = {                                      1406
                "植被覆盖度": (data.get("coverage"),                    1407
                                    std_benefit(data.get("coverage"),   1408
    IDEAL_COVERAGE),                                                    1409
                                    l2w["植被指标"]["植被覆盖度"]),      1410
                "生物多样性": (data.get("shannon"),                     1411
                                    std_benefit(data.get("shannon"),    1412
    IDEAL_SHANNON),                                                     1413
                                    l2w["植被指标"]["生物多样性"]),      1414
            }                                                           1415
        # ---- 地形指标 ----                                           1416
        if "地形指标" in l1_enabled:                                    1417
            result["地形指标"] = {                                      1418
                "坡度": (data.get("slope"),                             1419
                         std_slope(data.get("slope")),                  1420
                         l2w["地形指标"]["坡度"]),                      1421
                "坡向": (data.get("aspect"),                            1422
                         aspect_score(data.get("aspect")),              1423
                         l2w["地形指标"]["坡向"]),                      1424
            }                                                           1425
        return result                                                   1426
# ==== app/services/weight_service.py ====                            1427
# -*- coding: utf-8 -*-                                               1428
"""权重方案的存取与生效权重解析。                                       1429
系统有两套权重来源：                                                   1430
1. 论文表 3 给出的默认权重（app.utils.constants.DEFAULT_WEIGHTS），    1431
   是**权威取值来源**，案例复算与报告结论以此为准；                    1432
2. 通过层次分析法在本系统中实际算出的权重，保存在                      1433
   weight_schemes / weight_items 两张表中，可标记为「生效」。          1434
本模块负责把这两者合成为计算引擎直接可用的嵌套权重结构：               1435
以论文表 3 为底，用生效方案中已保存的条目覆盖。                        1436
没有任何生效方案时，即完全使用论文表 3 的权重。                        1437
这样既保证默认行为与论文一致，又使 AHP 计算结果真正参与评价，          1438
而不是算完即弃。                                                       1439
"""                                                                    1440
import copy                                                            1441
from app.models import db, WeightScheme, WeightItem                    1442
from app.utils.constants import DEFAULT_WEIGHTS                        1443
from app.services.indicator_service import TREE                        1444
# 方案名称：每个微地质单元类型固定一个可生效的方案                      1445
ACTIVE_NAME = "自定义权重方案（AHP 计算结果）"                          1446
def _code_maps():                                                      1447
    """由指标树导出 编码 → 名称 的映射，避免名称在两处各写一遍。"""      1448
    l1, l2 = {}, {}                                                    1449
    for row in TREE:                                                   1450
```

```
        code, name, level, parent = row[0], row[1], row[2],
    row[3]
        if level == 1:
            l1[code] = name
        elif level == 2:
            l2[code] = (l1.get(parent, parent), name)
    return l1, l2
def effective_weights(unit_type):
    """返回该单元类型当前生效的权重。
    返回 (weights, source_label, scheme)
        weights      嵌套权重结构，可直接交给标准化与评价引擎
        source_label 权重来源说明，用于界面与报告标注
        scheme       生效的权重方案对象，无自定义方案时为 None
    """
    base = DEFAULT_WEIGHTS.get(unit_type)
    if base is None:
        return None, "未定义该微地质单元类型的权重", None
    scheme = WeightScheme.query.filter_by(unit_type=unit_typ
    e,

    name=ACTIVE_NAME).first()
    if scheme is None:
        return copy.deepcopy(base), "论文表 3 默认权重", None
    merged = copy.deepcopy(base)
    l1_map, l2_map = _code_maps()
    applied = 0
    for item in WeightItem.query.filter_by(scheme_id=scheme.
    id).all():
        code, w = item.indicator_code, item.weight
        if w is None or w <= 0:
            continue
        if code in l1_map and l1_map[code] in merged["l1"]:
            merged["l1"][l1_map[code]] = w
            applied += 1
        elif code in l2_map:
            l1_name, l2_name = l2_map[code]
            if l1_name in merged["l2"] and l2_name in
    merged["l2"][l1_name]:
                merged["l2"][l1_name][l2_name] = w
                applied += 1
    if applied == 0:
        return copy.deepcopy(base), "论文表 3 默认权重", None
    return merged, "自定义方案（%d 项覆盖论文表 3）" % applied, scheme
def save_weights(unit_type, code_weight_pairs, note=None):
    """把一组「指标编码 → 权重」写入生效方案（已存在则更新对应条目）。
    仅覆盖本次传入的条目，其余条目保留，便于分层次（一级 / 二级）
    分次录入而无需一次填完。
    """
    scheme = WeightScheme.query.filter_by(unit_type=unit_typ
    e,
```

```
    },                                                                    10887
    {                                                                     10888
        "unit_type": "平台",                                              10889
        "ratio": 0.2319,                                                  10890
        "data": {                                                         10891
            "soil_ratio": 0.56, "thickness": 30, "ph":                    10892
    8.72, "organic_matter": 10.92,                                        10893
            "heavy_metals": {"Hg": 0.02, "As": 3.13, "Ni":                10894
    12.33,                                                                10895
                                "Cu": 11.14, "Cd": 0.09, "Pb":            10896
    9.98},                                                                10897
            "coverage": 58.42, "shannon": 0.72,                           10898
        },                                                                10899
    },                                                                    10900
]                                                                         10901
# ------------------------------------------------------------------------10902
    ------------------                                                    10903
# 逐单元输出标准化与得分                                                  10904
# ------------------------------------------------------------------------10905
    ------------------                                                    10906
print(LINE)                                                               10907
print("玉田县案例 · 评价引擎完整计算")                                   10908
print(LINE)                                                               10909
for u in case:                                                            10910
    r = ev.score_unit(u["unit_type"], u["data"])                          10911
    print()                                                               10912
    print("  【%s】  (面积占比 %.2f%%)" % (u["unit_type"],                10913
    u["ratio"] * 100))                                                    10914
    print("  " + "-" * 60)                                               10915
    for l1, score in r["l1_scores"].items():                              10916
        print("    %s 得分 = %.4f" % (l1, score))                        10917
    print("    单元评价因子 F' = %.4f" % r["unit_score"])                10918
print()                                                                   10919
print(LINE)                                                               10920
print("面积加权合成（式(9)）")                                           10921
print(LINE)                                                               10922
res = ev.score_mine(case)                                                 10923
total = res["final_score"]                                                10924
print()                                                                   10925
for ur in res["unit_results"]:                                            10926
    print("  %s  %.2f%% × %.4f = %.4f"                                   10927
          % (ur["unit_type"], ur["ratio"] * 100,                          10928
    ur["unit_score"], ur["weighted"]))                                    10929
print("  " + "-" * 60)                                                   10930
print("  最终评价因子 F = %.4f" % total)                                 10931
print()                                                                   10932
print("  适宜性等级：%s" % res["grade"])                                 10933
print("  判定依据  ：%s" % res["grade_info"]["meaning"])                 10934
print("  推荐措施  ：%s" % res["grade_info"]["measure"])                 10935
print()                                                                   10936
```

```
print(LINE)
print("结论")
print(LINE)
print("  - 评价引擎按论文式(8)(9) 与表 3 权重完整跑通")
print("  - 坡度标准化采用论文 25° 分界的线性折减默认值（见 standardization.py）")
print("  - 最终 F ≈ %.2f，判定为「%s」，与论文「最终适宜自然恢复」的结论一致"
      % (total, res["grade"]))
print("  - 论文表 5 所载最终得分为 0.76；差异集中在坡度、坡向的标准化口径，")
print("    该口径在 standardization.std_slope / aspect_score 中集中定义、可配置")
print(LINE)
#  ==== 测试/test_web_ahp.py ====
#  -*- coding: utf-8 -*-
"""AHP 网页界面自检：走通选择→录入→计算 全流程。"""
import sys
sys.stdout.reconfigure(encoding="utf-8")
import os
#  本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
#  使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
#  测试配置：关闭 CSRF 以简化测试客户端（真实运行仍开启 CSRF）
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///:memory:"
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
#  建立表并创建测试用户，登录后再访问业务页面
with app.app_context():
    from app.models import db, User
    from werkzeug.security import generate_password_hash
    db.create_all()
    if not User.query.filter_by(username="admin").first():
        db.session.add(User(username="admin",
                            password_hash=generate_password_hash("admin123"),
                            role="admin"))
        db.session.commit()
client.post("/login", data={"username": "admin",
    "password": "admin123"})
print(LINE)
print("测试 1  首页与 AHP 入口")
print(LINE)
```

```
r = client.get("/")
print("  首页状态码：", r.status_code, "（应 200）")
assert r.status_code == 200
r = client.get("/ahp/")
print("  AHP 入口状态码：", r.status_code, "（应 200）")
assert r.status_code == 200
assert "微地质单元类型" in r.get_data(as_text=True)
print()
print(LINE)
print("测试 2  选择碎石边坡一级指标 → 跳转矩阵页")
print(LINE)
r = client.post("/ahp/", data={
    "unit_type": "碎石边坡", "level": "1", "submit": "生成判断矩阵",
}, follow_redirects=True)
body = r.get_data(as_text=True)
print("  跳转后页面含「判断矩阵录入」：", "判断矩阵录入" in body)
print("  含三个一级指标（土壤/植被/地形）：", all(n in body for n in
    ("土壤指标", "植被指标", "地形指标")))
assert "判断矩阵录入" in body
assert all(n in body for n in ("土壤指标", "植被指标", "地形指标"))
print()
print(LINE)
print("测试 3  提交论文表 3 一致矩阵 → 还原权重")
print(LINE)
# 碎石边坡一级权重 (0.44, 0.31, 0.25) 对应的完全一致矩阵上三角：
# a12 = 0.44/0.31 = 1.4194, a13 = 0.44/0.25 = 1.76, a23 =
    0.31/0.25 = 1.24
r = client.post("/ahp/matrix?unit_type=碎石边坡&level=1", data={
    "m_0_1": "1.4194", "m_0_2": "1.76", "m_1_2": "1.24",
}, follow_redirects=True)
body = r.get_data(as_text=True)
print("  结果页含「计算结果」：", "计算结果" in body)
print("  含权重 0.44：", "0.44" in body, " 含 0.31：", "0.31" in
    body, " 含 0.25：", "0.25" in body)
print("  含一致性检验通过：", "通过" in body)
assert "计算结果" in body
assert "0.44" in body and "0.31" in body and "0.25" in body
print()
print(LINE)
print("测试 4  不一致矩阵应提示不通过并定位")
print(LINE)
# 明显不一致：a12=9, a13=1, a23=9
r = client.post("/ahp/matrix?unit_type=碎石边坡&level=1", data={
    "m_0_1": "9", "m_0_2": "1", "m_1_2": "9",
}, follow_redirects=True)
body = r.get_data(as_text=True)
print("  含「不通过」：", "不通过" in body)
print("  含「建议优先调整」：", "建议优先调整" in body)
assert "不通过" in body
assert "建议优先调整" in body
```

```
print()
print(LINE)
print("网页界面全部测试通过 √")
print(LINE)
#  ==== 测试/test_web_modules.py ====
#  -*- coding: utf-8 -*-
"""模块自检：登录、项目档案、微地质单元、标准库、限制性判定。"""
import os
import sys
sys.stdout.reconfigure(encoding="utf-8")
#  本脚本位于 测试/  子目录，先把仓库根目录加入模块搜索路径，
#  使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(
        ROOT, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
print(LINE)
print("测试 1  未登录应被重定向到登录页")
print(LINE)
r = client.get("/project/")
print("  /project/ 状态码:", r.status_code, " 重定向到:",
    r.headers.get("Location"))
assert r.status_code == 302 and "login" in
    r.headers.get("Location", "")
print()
print(LINE)
print("测试 2  登录")
print(LINE)
r = client.post("/login", data={"username": "admin",
    "password": "admin123"},
                follow_redirects=True)
body = r.get_data(as_text=True)
#  工作台：页首横幅 + 评价流程分区 + 数据概览
print("  登录后含「评价流程」:", "评价流程" in body)
print("  含账户 admin:", "admin" in body)
print("  含页首横幅:", 'class="hero"' in body)
print("  含数据概览:", 'class="stat-card"' in body)
assert "评价流程" in body and 'class="hero"' in body
print()
```

```
print(LINE)
print("测试 3  项目与矿山档案")
print(LINE)
r = client.get("/project/")
body = r.get_data(as_text=True)
print("  项目列表状态码：", r.status_code)
print("  含案例项目：", "玉田县典型历史遗留废弃矿山案例" in body)
assert "玉田县典型历史遗留废弃矿山案例" in body
# 新建项目
client.post("/project/add", data={"name": "测试项目A", "code":
    "T-001"})
r = client.get("/project/")
print("  新建项目后含「测试项目A」：", "测试项目A" in r.get_data(as_text=True
    ))
assert "测试项目A" in r.get_data(as_text=True)
# 清理测试数据，避免污染演示库
with app.app_context():
    from app.models import db, Project
    for p in Project.query.filter_by(name="测试项目A").all():
        db.session.delete(p)
    db.session.commit()
print("  已清理测试项目")
print()
print(LINE)
print("测试 4  微地质单元（面积占比自动计算）")
print(LINE)
from app.models import MinePatch
with app.app_context():
    patch = MinePatch.query.filter_by(name="玉田县孤树镇白云岩采石场").f
    irst()
    pid = patch.id
r = client.get("/unit/%d" % pid)
body = r.get_data(as_text=True)
print("  单元列表含三类单元：", all(t in body for t in ("岩质边坡",
    "碎石边坡", "平台")))
print("  含占比合计：", "占比合计" in body)
assert "岩质边坡" in body and "占比合计" in body
print()
print(LINE)
print("测试 5  标准知识库与省际口径比对")
print(LINE)
r = client.get("/standard/")
body = r.get_data(as_text=True)
print("  含辽宁/湖南/新疆标准：", all(p in body for p in ("辽宁", "湖南",
    "新疆")))
assert "辽宁" in body
r = client.get("/standard/compare")
body = r.get_data(as_text=True)
print("  口径比对页含「植被覆盖度」分组：", "植被覆盖度" in body)
print("  含多省份并列：", "湖南" in body and "新疆" in body)
```

```
assert "植被覆盖度" in body                                                    11137
print()                                                                        11138
print(LINE)                                                                    11139
print("测试 6  限制性指标判定（一票否决）")                                    11140
print(LINE)                                                                    11141
r = client.get("/constraint/%d" % pid)                                         11142
body = r.get_data(as_text=True)                                                11143
print("  含五项条件：", all(x in body for x in ("政策约束", "区位约束",        11144
    "土壤污染", "地质灾害", "耕地属性")))                                      11145
assert all(x in body for x in ("政策约束", "区位约束", "土壤污染",             11146
    "地质灾害", "耕地属性"))                                                   11147
# 全部通过                                                                     11148
client.post("/constraint/%d" % pid, data={                                     11149
    "policy_pass": "1", "location_pass": "1",                                  11150
    "pollution_pass": "1",                                                     11151
    "geo_pass": "1", "farmland_pass": "1"})                                    11152
r = client.get("/constraint/%d" % pid)                                         11153
body = r.get_data(as_text=True)                                                11154
print("  全通过后显示「通过，可进入定量评价」：", "可进入定量评价" in body)    11155
assert "可进入定量评价" in body                                                11156
# 一项不通过                                                                   11157
client.post("/constraint/%d" % pid, data={                                     11158
    "policy_pass": "1", "location_pass": "0",                                  11159
    "pollution_pass": "1",                                                     11160
    "geo_pass": "1", "farmland_pass": "1"})                                    11161
r = client.get("/constraint/%d" % pid)                                         11162
body = r.get_data(as_text=True)                                                11163
print("  一项不通过后显示「不通过」：", "不通过" in body)                      11164
print("  含失败项「区位约束」：", "区位约束" in body)                          11165
assert "不通过" in body                                                        11166
# 恢复为全部通过，避免把演示数据留在「不通过」状态影响后续步骤                 11167
client.post("/constraint/%d" % pid, data={                                     11168
    "policy_pass": "1", "location_pass": "1",                                  11169
    "pollution_pass": "1",                                                     11170
    "geo_pass": "1", "farmland_pass": "1"})                                    11171
r = client.get("/constraint/%d" % pid)                                         11172
print("  已恢复为全部通过：", "可进入定量评价" in r.get_data(as_text=True))    11173
print()                                                                        11174
print(LINE)                                                                    11175
print("全部测试通过 √")                                                       11176
print(LINE)                                                                    11177
# ==== 测试/test_web_evaluate.py ====                                          11178
# -*- coding: utf-8 -*-                                                        11179
"""端到端自检：录数据 → 执行评价 → 查看结果。"""                               11180
import os                                                                      11181
import sys                                                                     11182
sys.stdout.reconfigure(encoding="utf-8")                                       11183
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，                    11184
# 使 `from app import ...` 与 app/app.db 的定位不受影响。                      11185
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__fil                   11186
```

```
    e__)))                                                                  11187
if ROOT not in sys.path:                                                    11188
    sys.path.insert(0, ROOT)                                                11189
from app import create_app                                                  11190
LINE = "=" * 66                                                             11191
# 与真实配置共用同一个 app.db，但关闭 CSRF 便于测试客户端                   11192
class TestConfig:                                                           11193
    SECRET_KEY = "test"                                                     11194
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(                  11195
        ROOT, "app", "app.db")                                              11196
    SQLALCHEMY_TRACK_MODIFICATIONS = False                                  11197
    WTF_CSRF_ENABLED = False                                                11198
    TESTING = True                                                          11199
app = create_app(TestConfig)                                                11200
client = app.test_client()                                                  11201
# 登录（案例种子已创建 admin 用户）                                        11202
client.post("/login", data={"username": "admin",                            11203
    "password": "admin123"})                                                11204
print(LINE)                                                                 11205
print("测试 1  指标数据列表")                                              11206
print(LINE)                                                                 11207
r = client.get("/indicator/")                                               11208
body = r.get_data(as_text=True)                                             11209
print("  状态码：", r.status_code)                                         11210
print("  含案例图斑：", "玉田县孤树镇白云岩采石场" in body)                11211
print("  含三个单元：", all(n in body for n in ("岩质边坡", "碎石边坡",    11212
    "平台")))                                                               11213
assert r.status_code == 200                                                 11214
assert "岩质边坡" in body and "碎石边坡" in body and "平台" in body         11215
print()                                                                     11216
print(LINE)                                                                 11217
print("测试 2  指标数据录入页（按单元类型显示字段）")                      11218
print(LINE)                                                                 11219
from app.models import MicroUnit, MinePatch                                 11220
with app.app_context():                                                     11221
    unit_rock = MicroUnit.query.filter_by(unit_type="岩质边坡").            11222
    first()                                                                 11223
    unit_gravel = MicroUnit.query.filter_by(unit_type="碎石边坡"            11224
    ).first()                                                               11225
r = client.get("/indicator/%d" % unit_rock.id)                              11226
b_rock = r.get_data(as_text=True)                                           11227
print("  岩质边坡页：无「土石比」字段：", "土石比" not in b_rock, "（应 True）")11228
print("  岩质边坡页：含「植被覆盖度」：", "植被覆盖度" in b_rock)          11229
assert "土石比" not in b_rock and "植被覆盖度" in b_rock                    11230
r = client.get("/indicator/%d" % unit_gravel.id)                            11231
b_gravel = r.get_data(as_text=True)                                         11232
print("  碎石边坡页：含「土石比」字段：", "土石比" in b_gravel)            11233
print("  碎石边坡页：含 8 种重金属：", all(m in b_gravel for m in          11234
    ("Cd", "Hg", "Pb", "Cr", "As", "Ni", "Cu", "Zn")))                      11235
assert "土石比" in b_gravel and all(m in b_gravel for m in                  11236
```

```
    ("Cd", "Hg", "Pb", "Cr", "As", "Ni", "Cu", "Zn"))
print()
print(LINE)
print("测试 3  执行评价")
print(LINE)
with app.app_context():
    import seed_demo
    patch = seed_demo.demo_patch()
r = client.post("/evaluate/%d" % patch.id, data={},
    follow_redirects=True)
body = r.get_data(as_text=True)
print("  跳转至结果页：", "适宜性评价结果" in body)
print("  含最终评价因子 F：", "最终评价因子 F" in body)
print("  含等级「适宜」：", "适宜" in body)
print("  含推荐措施「自然恢复」：", "自然恢复" in body)
assert "最终评价因子 F" in body and "自然恢复" in body
print()
print(LINE)
print("测试 4  结果持久化")
print(LINE)
from app.models import EvaluationResult
with app.app_context():
    res = EvaluationResult.query.order_by(EvaluationResult.i
    d.desc()).first()
    print("  最终得分 F =", res.final_score)
    print("  等级 =", res.grade)
    assert res.grade == "适宜"
    assert 0.7 <= res.final_score < 1.0
print()
print(LINE)
print("端到端全部测试通过 √")
print(LINE)
# ==== 测试/test_web_report.py ====
# -*- coding: utf-8 -*-
"""报告输出自检：得分明细页 + Word 导出。"""
import os
import sys
import io
sys.stdout.reconfigure(encoding="utf-8")
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__fi
    e__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
LINE = "=" * 66
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(
```

```
        ROOT, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
client = app.test_client()
# 登录（案例种子已创建 admin 用户）
client.post("/login", data={"username": "admin",
    "password": "admin123"})
from app.models import MinePatch, EvaluationResult
with app.app_context():
    import seed_demo
    patch = seed_demo.demo_patch()
    pid = patch.id
# 报告取自已保存的评价记录，因此先按网页路径真实执行一次评价
from app.views.evaluate import load_patch_input,
    save_evaluation
with app.app_context():
    units = load_patch_input(pid)
    rec = save_evaluation(pid, units)
    rid = rec.id
    print("前置：已执行评价并保存记录 id=%d，F=%.4f（%s）"
          % (rid, rec.final_score, rec.grade))
    from app.models import ScoreDetail
    n_detail = ScoreDetail.query.filter_by(result_id=rid).co
    unt()
    print("        逐层得分明细已落库：%d 条" % n_detail)
print()
print(LINE)
print("测试 1  报告列表")
print(LINE)
r = client.get("/report/")
print("  状态码：", r.status_code)
body = r.get_data(as_text=True)
print("  含「所属项目」列：", "所属项目" in body)
assert r.status_code == 200
print()
print(LINE)
print("测试 2  得分明细页")
print(LINE)
r = client.get("/report/%d" % pid)
body = r.get_data(as_text=True)
print("  状态码：", r.status_code)
print("  含「得分明细」：", "得分明细" in body)
print("  含「最终评价因子 F」：", "最终评价因子 F" in body)
print("  含二级指标明细（植被覆盖度 / 坡度 / 坡向）：", all(n in body for n in
    ("植被覆盖度", "坡度", "坡向")))
print("  含权重 / 标准化值列：", "标准化值" in body and "贡献" in body)
assert r.status_code == 200
assert "植被覆盖度" in body and "标准化值" in body
```

```
print()                                                                 11337
print(LINE)                                                             11338
print("测试 3  Word 报告导出")                                          11339
print(LINE)                                                             11340
r = client.get("/report/%d/word" % pid)                                 11341
print("  状态码:", r.status_code)                                       11342
print("  Content-Type:", r.headers.get("Content-Type",                  11343
    "")[:60])                                                           11344
data = r.data                                                           11345
print("  文件大小:", len(data), "字节")                                 11346
print("  是否为有效 docx(PK 头):", data[:2] == b"PK")                   11347
assert r.status_code == 200 and data[:2] == b"PK"                       11348
# 用 python-docx 打开验证内容                                          11349
import docx                                                             11350
d = docx.Document(io.BytesIO(data))                                     11351
text = "\n".join(p.text for p in d.paragraphs)                          11352
print("  含报告标题:", "自然恢复适宜性评价报告" in text)                11353
print("  含评价结论章节:", "评价结论" in text)                          11354
print("  含得分明细章节:", "得分明细" in text)                          11355
print("  段落数:", len(d.paragraphs), " 表格数:", len(d.tables))        11356
assert "自然恢复适宜性评价报告" in text and len(d.tables) >= 3          11357
print()                                                                 11358
print(LINE)                                                             11359
print("报告输出全部测试通过 √")                                        11360
print(LINE)                                                             11361
# ==== 测试/test_ui_fixes.py ====                                       11362
# -*- coding: utf-8 -*-                                                 11363
"""界面修复自检:「记住我」与各模块删除功能。"""                         11364
import os                                                               11365
import re                                                               11366
import sys                                                              11367
# 本脚本位于 测试/ 子目录,先把仓库根目录加入模块搜索路径,               11368
# 使 `from app import ...` 与 app/app.db 的定位不受影响。               11369
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__fil            11370
    e__)))                                                              11371
if ROOT not in sys.path:                                                11372
    sys.path.insert(0, ROOT)                                            11373
from app import create_app                                              11374
sys.stdout.reconfigure(encoding="utf-8")                                11375
LINE = "=" * 70                                                         11376
class TestConfig:                                                       11377
    SECRET_KEY = "test"                                                 11378
    SQLALCHEMY_DATABASE_URI = "sqlite:///" + os.path.join(              11379
        ROOT, "app", "app.db")                                          11380
    SQLALCHEMY_TRACK_MODIFICATIONS = False                              11381
    WTF_CSRF_ENABLED = False                                            11382
    TESTING = True                                                      11383
    REMEMBER_COOKIE_DURATION = __import__("datetime").timede            11384
    lta(days=30)                                                        11385
app = create_app(TestConfig)                                            11386
```

```
client = app.test_client()
# ------------------------------------------------------------------------
    ----------------
print(LINE)
print("一、「记住我」")
print(LINE)
html = client.get("/login").get_data(as_text=True)
# 1） 复选框必须有可点击关联的 label（这是原先失效的根因）
#     只判断「复选框与文字是否落在同一个 <label> 内」，不绑定具体类名 ——
#     否则换个样式类就会误报，而真正的回归点其实与类名无关。
labels = re.findall(r"<label[^>]*>(.*?)</label>", html,
    re.S)
wrapped = any(('name="remember"' in b and "记住我" in b) for b
    in labels)
print("  %s 「记住我」文字与复选框包在同一 label 内" % ("[符合]" if wrapped
    else "[不符合]"))
assert wrapped, "复选框未与文字关联，点击文字不会勾选"
has_for = 'for="remember"' in html
print("  %s label 带 for 属性指向复选框" % ("[符合]" if has_for else
    "[不符合]"))
# 2） 勾选后应下发带过期时间的 remember_token
c = app.test_client()
r = c.post("/login", data={"username": "admin", "password":
    "admin123",
                           "remember": "y"},
    follow_redirects=False)
cookies = r.headers.getlist("Set-Cookie")
rt = [h for h in cookies if h.startswith("remember_token=")]
print("  %s 勾选后下发 remember_token" % ("[符合]" if rt else
    "[不符合]"))
assert rt, "未下发 remember_token"
exp = re.search(r"Expires=([^;]+)", rt[0])
print("  %s 该 cookie 带过期时间：%s"
      % ("[符合]" if exp else "[不符合]", exp.group(1) if exp
    else "无（会话 cookie）"))
assert exp, "remember_token 无过期时间，关浏览器即失效"
# 3） 不勾选时不应下发 remember_token
c2 = app.test_client()
r2 = c2.post("/login", data={"username": "admin",
    "password": "admin123"},
               follow_redirects=False)
rt2 = [h for h in r2.headers.getlist("Set-Cookie") if
    h.startswith("remember_token=")]
print("  %s 未勾选时不下发 remember_token" % ("[符合]" if not rt2
    else "[不符合]"))
assert not rt2
# 4） 携带 remember_token 的新会话应自动登录
c3 = app.test_client()
c3.set_cookie("remember_token",
              rt[0].split(";")[0].split("=", 1)[1],
```

```
        domain="localhost")                                                    11437
r3 = c3.get("/", follow_redirects=False)                                       11438
print("  %s 仅凭 remember_token 访问首页可自动登录（状态码 %d）"                    11439
      % ("[符合]" if r3.status_code == 200 else "[不符合]",                     11440
        r3.status_code))                                                       11441
assert r3.status_code == 200                                                   11442
# ------------------------------------------------------------------------11443
        ------------------                                                     11444
print()                                                                        11445
print(LINE)                                                                    11446
print("二、删除功能")                                                            11447
print(LINE)                                                                    11448
client.post("/login", data={"username": "admin",                               11449
        "password": "admin123"})                                               11450
# 项目：列表页须有删除按钮                                                        11451
html = client.get("/project/").get_data(as_text=True)                          11452
has_del = "/delete" in html and "btn--danger" in html                          11453
print("  %s 项目列表含删除按钮" % ("[符合]" if has_del else "[不符合]"))          11454
assert has_del, "项目列表缺少删除按钮"                                           11455
print("  %s 删除前有二次确认" % ("[符合]" if "confirm(" in html else            11456
        "[不符合]"))                                                           11457
assert "confirm(" in html                                                      11458
# 图斑列表：地址用的是项目主键，不是图斑主键                                      11459
with app.app_context():                                                        11460
        from app.models import MinePatch, Project                              11461
        import seed_demo                                                       11462
        patch = seed_demo.demo_patch()                                         11463
        patch_id = patch.id                                                    11464
        project_id = patch.project_id                                          11465
html = client.get("/project/%d/patches" %                                      11466
        project_id).get_data(as_text=True)                                     11467
print("  %s 图斑列表含删除按钮" % ("[符合]" if "/project/patch/" in            11468
        html and "btn--danger" in html else "[不符合]"))                       11469
assert "/project/patch/" in html and "btn--danger" in html                     11470
# 微地质单元                                                                    11471
html = client.get("/unit/%d" % patch_id).get_data(as_text=Tr11472
        ue)                                                                    11473
print("  %s 微单元列表含删除按钮" % ("[符合]" if "/unit/delete/" in            11474
        html else "[不符合]"))                                                 11475
assert "/unit/delete/" in html                                                 11476
print("  %s 微单元编辑为独立页面（表单不再嵌在表格行内）"                          11477
      % ("[符合]" if "/unit/edit/" in html else "[不符合]"))                    11478
# 标准                                                                          11479
html = client.get("/standard/").get_data(as_text=True)                         11480
print("  %s 标准列表含删除按钮" % ("[符合]" if "btn--danger" in html            11481
        else "[不符合]"))                                                      11482
assert "btn--danger" in html                                                   11483
# 实际执行一次删除：新建项目 → 删除 → 确认消失                                    11484
client.post("/project/add", data={"name": "待删除测试项目",                     11485
        "code": "DEL-1"})                                                      11486
```

```
with app.app_context():
    from app.models import db, Project
    tmp = Project.query.filter_by(name="待删除测试项目").first()
    tmp_id = tmp.id
html = client.get("/project/").get_data(as_text=True)
print("  %s 新建项目成功" % ("[符合]" if "待删除测试项目" in html else
    "[不符合]"))
r = client.post("/project/%d/delete" % tmp_id,
    follow_redirects=True)
html = r.get_data(as_text=True)
gone = "待删除测试项目" not in html
print("  %s 删除项目后列表中不再出现" % ("[符合]" if gone else "[不符合]"))
assert gone
print("  %s 有删除成功提示" % ("[符合]" if "已删除" in html else
    "[不符合]"))
print()
print(LINE)
print("界面修复自检全部通过 √")
print(LINE)
# ==== 测试/test_new_features.py ====
# -*- coding: utf-8 -*-
"""补齐模块自检：操作日志与用户维护、遥感影像、指标与多专家矩阵、
批量导入、图表与 PDF 导出。
对应计划书功能清单与系统实现的差异核对结论。
"""
import io
import json
import os
import re
import sys
sys.stdout.reconfigure(encoding="utf-8")
import fitz
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
from app.models import (db, User, Project, MinePatch,
    MicroUnit, IndicatorData,
                            Indicator, ExpertMatrix,
    OperationLog)
from app.utils.schema import ensure_schema
from app.utils import browser, charts
LINE = "=" * 72
BASE = ROOT
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +
```

```
    os.path.join(BASE, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
    UPLOAD_FOLDER = os.path.join(BASE, "app", "static",
    "uploads")
    MAX_CONTENT_LENGTH = 32 * 1024 * 1024
    ALLOWED_IMAGE_EXT = {"png", "jpg", "jpeg", "gif",
    "webp", "bmp", "tif", "tiff"}
app = create_app(TestConfig)
with app.app_context():
    db.create_all()
    ensure_schema(db)
    ExpertMatrix.query.delete()
    db.session.commit()
    # 固定取内置演示案例的图斑，避免受库中用户自建项目 / 验证算例的影响
    import seed_demo
    patch_id = seed_demo.demo_patch().id
c = app.test_client()
c.post("/login", data={"username": "admin", "password":
    "admin123"})
def ok(flag, label, extra=""):
    print("  %s %-44s %s" % ("[符合]" if flag else "[不符合]",
    label, extra))
    assert flag, label
# ------------------------------------------------------------
    ------------------
print(LINE)
print("操作日志与用户维护")
print(LINE)
before = None
with app.app_context():
    before = OperationLog.query.count()
c.post("/project/add", data={"name": "日志核对项目", "code":
    "LOG-T"})
with app.app_context():
    after = OperationLog.query.count()
    last = OperationLog.query.order_by(OperationLog.id.desc(
    )).first()
ok(after == before + 1, "写操作被写入操作日志", "%d -> %d" % (before,
    after))
ok(last.action == "新建项目", "日志记录了可读动作名", last.action)
ok("project" in (last.target_type or ""), "日志记录了对象类型",
    last.target_type)
r = c.get("/profile?tab=logs")
body = r.get_data(as_text=True)
ok(r.status_code == 200 and "操作日志" in body, "操作日志分类可访问")
ok("新建项目" in body, "日志页显示操作记录")
# 账号编辑 / 删除（职务只有管理员与操作员两种）
with app.app_context():
```

```
    u = User(username="tmp_user", role="operator",
             password_hash=User.query.first().password_hash)
    db.session.add(u); db.session.commit()
    uid = u.id
r = c.get("/users/%d/edit" % uid)
ok(r.status_code == 200, "账号编辑页可访问")
#  保护校验要趁系统里只有一名管理员时做：
#  先降级唯一的 admin 应被拒绝，再把临时账号提为管理员看修改是否生效
with app.app_context():
    admin_id = User.query.filter_by(role="admin").first().id
c.post("/users/%d/edit" % admin_id,
       data={"role": "operator", "active": "1"})
with app.app_context():
    ok(db.session.get(User, admin_id).role == "admin",
    "拒绝把最后一个管理员降级")
c.post("/users/%d/edit" % uid, data={"role": "admin",
    "active": "1"})
with app.app_context():
    ok(db.session.get(User, uid).role == "admin",
    "职务已修改并保存")
c.post("/users/%d/delete" % uid, follow_redirects=True)
with app.app_context():
    ok(db.session.get(User, uid) is None, "账号删除生效")
#  清理日志核对用的项目
with app.app_context():
    for p in Project.query.filter_by(name="日志核对项目").all():
        db.session.delete(p)
    db.session.commit()
# ------------------------------------------------------------
    ------------------
print()
print(LINE)
print("遥感影像挂接")
print(LINE)
doc = fitz.open()
pg = doc.new_page(width=320, height=200)
pg.insert_text((20, 60), "RS image", fontname="china-s",
    fontsize=16)
png = doc[0].get_pixmap(dpi=100).tobytes("png")
doc.close()
r = c.post("/project/patch/%d/image" % patch_id,
           data={"image": (io.BytesIO(png), "影像.png"),
                 "image_note": "2025年6月无人机正射影像"},
           content_type="multipart/form-data",
    follow_redirects=True)
body = r.get_data(as_text=True)
ok("已挂接" in body and "<img" in body, "影像上传并显示")
with app.app_context():
    rel = db.session.get(MinePatch, patch_id).image_path
ok(bool(rel), "数据库记录影像路径", rel)
```

```
abs_path = os.path.join(TestConfig.UPLOAD_FOLDER,
    rel.replace("uploads/", "", 1))
ok(os.path.isfile(abs_path), "影像文件落盘")
ok(c.get("/static/" + rel).status_code == 200, "影像可经 URL
    访问")
r = c.post("/project/patch/%d/image" % patch_id,
           data={"image": (io.BytesIO(b"x"), "bad.txt")},
           content_type="multipart/form-data",
    follow_redirects=True)
ok("不支持" in r.get_data(as_text=True), "拒绝非图片格式")
c.post("/project/patch/%d/image/delete" % patch_id,
    follow_redirects=True)
with app.app_context():
    ok(db.session.get(MinePatch, patch_id).image_path is
    None, "影像移除后字段清空")
ok(not os.path.isfile(abs_path), "影像文件已删除")
# ----------------------------------------------------------------
    ----------------
print()
print(LINE)
print("指标定义维护与多专家矩阵")
print(LINE)
r = c.get("/ahp/indicators")
body = r.get_data(as_text=True)
with app.app_context():
    n_ind = Indicator.query.count()
ok(r.status_code == 200 and n_ind > 0, "指标定义已入库并可查看", "%d
    项" % n_ind)
ok(all(k in body for k in ("一级指标", "二级指标", "三级指标")),
   "指标树按层级展示")
ok("岩质边坡" in body and "平台" in body, "显示各指标启用的微地质单元")
c.post("/ahp/indicators/coverage/edit",
       data={"name": "植被覆盖度", "unit": "%", "ideal_type":
    "benefit",
             "ideal_value": "75", "enabled_units": ["岩质边坡"],
             "description": "自检修改"})
with app.app_context():
    ok(Indicator.query.filter_by(code="coverage").first().de
    scription == "自检修改",
       "指标定义可编辑")
c.post("/ahp/indicators/reset")
with app.app_context():
    ok("自检修改" not in (Indicator.query.filter_by(code="cover
    ge").first().description or ""),
       "可按论文取值重置")
base = {"m_0_1": "1.4194", "m_0_2": "1.76", "m_1_2": "1.24"}
for name in ("张工", "李工", "王工"):
    d = dict(base); d.update({"action": "add", "unit_type":
    "碎石边坡",
                              "level": "1", "expert_name":
```

```
        name})                                                          11687
        c.post("/ahp/experts", data=d)                                  11688
with app.app_context():                                                 11689
        ok(ExpertMatrix.query.filter_by(unit_type="碎石边坡",           11690
        level=1).count() == 3,                                          11691
            "录入 3 位专家的判断矩阵")                                  11692
r = c.get("/ahp/experts/aggregate?unit_type=碎石边坡&level=1")          11693
body = r.get_data(as_text=True)                                         11694
ok("汇总后权重" in body and "各专家矩阵的一致性" in body,               11695
    "多专家矩阵几何平均汇总可用")                                       11696
ws = re.search(r"<th scope=\"row\">权重</th>\s*(.*?)</tr>",             11697
        body, re.S)                                                     11698
vals = re.findall(r">([0-9.]+)</td>", ws.group(1)) if ws                11699
        else []                                                         11700
ok(len(vals) == 3 and abs(sum(map(float, vals)) - 1.0) <                11701
        0.01,                                                           11702
    "汇总权重归一", "、".join(vals))                                    11703
ok(abs(float(vals[0]) - 0.44) < 0.02, "汇总权重接近论文表 3 取值",      11704
        vals[0] if vals else "")                                        11705
# ------------------------------------------------------------------    11706
        ----------------                                                11707
print()                                                                 11708
print(LINE)                                                             11709
print("批量导入")                                                       11710
print(LINE)                                                             11711
r = c.get("/indicator/import/template")                                 11712
tpl = r.data.decode("utf-8-sig")                                        11713
ok(r.status_code == 200 and "单元类型" in tpl, "导入模板可下载")        11714
ok("土石比" in tpl and "植被覆盖度" in tpl, "模板包含指标列")           11715
csv_text = (                                                            11716
        "单元类型,土石比,土层厚度,pH,有机质,Hg,As,Ni,Cu,Cd,Pb,植被覆盖度,Shannon,坡度11717
        ,坡向\n"                                                        11718
        "碎石边坡,0.34,10,9.24,4.89,0.05,5.17,12.60,11.70,0.04,6.50,11719
        87.92,0.60,28.75,阳坡\n"                                        11720
        "平台,0.56,30,8.72,10.92,0.02,3.13,12.33,11.14,0.09,9.98,51721
        8.42,0.72,,,\n"                                                 11722
        "不存在单元,1,1,7,1,,,,,,,,,\n"                                11723
)                                                                       11724
r = c.post("/indicator/import",                                         11725
                data={"patch_id": str(patch_id),                        11726
                      "datafile": (io.BytesIO(csv_text.encode("ut11727
        f-8")), "d.csv")},                                              11728
                content_type="multipart/form-data",                     11729
        follow_redirects=True)                                          11730
body = r.get_data(as_text=True)                                         11731
ok("导入结果" in body, "导入结果页展示")                                11732
ok("不存在单元" in body, "错误行被报告")                                11733
with app.app_context():                                                 11734
        u = MicroUnit.query.filter_by(patch_id=patch_id,                11735
        unit_type="碎石边坡").first()                                   11736
```

```
        ind = IndicatorData.query.filter_by(unit_id=u.id).first(
        )
        ok(abs(ind.soil_ratio - 0.34) < 1e-6 and
        abs(ind.coverage - 87.92) < 1e-6,
            "导入数据已写入数据库")
    r = c.post("/indicator/import",
               data={"patch_id": str(patch_id),
                     "datafile": (io.BytesIO(b"x"), "d.pdf")},
               content_type="multipart/form-data",
        follow_redirects=True)
    ok("仅支持" in r.get_data(as_text=True), "拒绝不支持的导入格式")
    # ------------------------------------------------------------
        ------------------
    print()
    print(LINE)
    print("图表与 PDF 导出")
    print(LINE)
    svg = charts.hbars([("岩质边坡", 0.54, "0.5401"), ("平台", 0.84,
        "0.8376")])
    ok("<svg" in svg and "0.8376" in svg, "条形图生成且带数值标签")
    svg2 = charts.donut([("植被指标", 0.6, "0.6000"), ("土壤指标", 0.4,
        "0.4000")])
    ok("<svg" in svg2 and "占比" in svg2, "环形图生成且带图例")
    #  报告是评价结论的呈现，需先真实执行一次评价才能打开
    with app.app_context():
        from app.views.evaluate import load_patch_input,
        save_evaluation
        save_evaluation(patch_id, load_patch_input(patch_id))
    r = c.get("/report/%d" % patch_id)
    body = r.get_data(as_text=True)
    ok(body.count("<svg") >= 2, "得分明细页含图表", "%d 个 SVG" %
        body.count("<svg"))
    exe = browser.browser_path()
    if exe is None:
        print("  [跳过] 未找到浏览器，PDF 导出无法验证")
    else:
        r = c.get("/report/%d/pdf" % patch_id)
        data = r.data
        ok(data[:4] == b"%PDF", "PDF 报告导出成功", "%d 字节" %
        len(data))
        d = fitz.open(stream=data, filetype="pdf")
        txt = "".join(d[i].get_text() for i in
        range(d.page_count))
        ok("自然恢复适宜性评价报告" in txt, "PDF 含报告标题")
        ok("评价结论" in txt and "得分明细" in txt, "PDF 含结论与明细章节")
        ok(d.page_count >= 2, "PDF 页数合理", "%d 页" % d.page_count)
        d.close()
    print()
    print(LINE)
    print("补齐模块自检全部通过 √")
```

```
print(LINE)
# ==== 测试/test_workflow.py ====
# -*- coding: utf-8 -*-
"""流程门禁自检：前置步骤未完成时，后续模块必须拦得住。
论文 4.1 节确定的评价流程存在先后关系，缺任何一环都不应产出评价结论。
本测试逐个构造「缺前置」的场景，验证系统不会放行。
"""
import os
import sys
sys.stdout.reconfigure(encoding="utf-8")
# 本脚本位于 测试/ 子目录，先把仓库根目录加入模块搜索路径，
# 使 `from app import ...` 与 app/app.db 的定位不受影响。
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
from app import create_app
from app.models import (db, Project, MinePatch, MicroUnit,
    IndicatorData,
                        ConstraintCheck, EvaluationResult)
from app.services import workflow as wf
LINE = "=" * 72
BASE = ROOT
class TestConfig:
    SECRET_KEY = "test"
    SQLALCHEMY_DATABASE_URI = "sqlite:///" +
    os.path.join(BASE, "app", "app.db")
    SQLALCHEMY_TRACK_MODIFICATIONS = False
    WTF_CSRF_ENABLED = False
    TESTING = True
app = create_app(TestConfig)
c = app.test_client()
c.post("/login", data={"username": "admin", "password":
    "admin123"})
_fails = []
def ok(flag, label, extra=""):
    print("  %s %-46s %s" % ("[符合]" if flag else "[不符合]",
    label, extra))
    if not flag:
        _fails.append(label)
def new_patch(tag):
    with app.app_context():
        p = Project(name="门禁-" + tag, code="WF-" + tag)
        db.session.add(p); db.session.flush()
        patch = MinePatch(project_id=p.id, name="门禁图斑-" +
    tag)
        db.session.add(patch); db.session.flush()
        pid = patch.id
        db.session.commit()
    return pid
```

```
def add_units(pid):
    with app.app_context():
        db.session.add(MicroUnit(patch_id=pid,
    unit_type="碎石边坡",
                                 area=1.0, ratio=1.0))
        db.session.commit()
def add_constraint(pid, passed=True):
    with app.app_context():
        db.session.add(ConstraintCheck(
            patch_id=pid, policy_pass=True,
    location_pass=passed,
            pollution_pass=True, geo_pass=True,
    farmland_pass=True,
            passed=passed, reason="全部通过" if passed else
    "未通过：区位约束"))
        db.session.commit()
def add_data(pid):
    with app.app_context():
        u = MicroUnit.query.filter_by(patch_id=pid).first()
        db.session.add(IndicatorData(unit_id=u.id,
    soil_ratio=0.34, thickness=10,
                                     ph=9.24,
    organic_matter=4.89, coverage=87.92,
                                     shannon=0.60,
    slope=28.75, aspect="阳坡"))
        db.session.commit()
def cleanup(pid, tag):
    with app.app_context():
        from app.models import ScoreDetail
        # 先删得分明细，再删评价记录，避免留下孤儿明细
        rids = [r.id for r in EvaluationResult.query.filter_
    by(patch_id=pid)]
        if rids:
            ScoreDetail.query.filter(ScoreDetail.result_id.i
    n_(rids)).delete(
                synchronize_session=False)
        EvaluationResult.query.filter_by(patch_id=pid).delet
    e()
        ConstraintCheck.query.filter_by(patch_id=pid).delete
    ()
        uids = [u.id for u in MicroUnit.query.filter_by(pat
    h_id=pid)]
        if uids:
            IndicatorData.query.filter(IndicatorData.unit_id
    .in_(uids)).delete(
                synchronize_session=False)
        MicroUnit.query.filter_by(patch_id=pid).delete()
        m = db.session.get(MinePatch, pid)
        if m:
            db.session.delete(m)
```

```
            pr = Project.query.filter_by(name="门禁-" +
        tag).first()
            if pr:
                db.session.delete(pr)
            db.session.commit()
def results_of(pid):
        with app.app_context():
            return EvaluationResult.query.filter_by(patch_id=pid
        ).count()
def post_eval(pid):
        return c.post("/evaluate/%d" % pid, data={},
        follow_redirects=False)
def get_report(pid):
        return c.get("/report/%d" % pid, follow_redirects=False)
# ------------------------------------------------------------
        ------------------
print(LINE)
print("一、前置条件缺失时，评价必须被拦住")
print(LINE)
print()
print("场景 1：连微地质单元都没划分")
pid = new_patch("1")
r = post_eval(pid)
n = results_of(pid)
ok(r.status_code == 302 and n == 0, "未划分单元 → 不产生评价结果",
    "HTTP %d，结果数 %d" % (r.status_code, n))
with app.app_context():
    pr = wf.patch_progress(pid)
steps = [b["step"] for b in pr["blocking"]]
ok(not pr["ready"] and "units" in steps,
    "拦原因包含「划分微地质单元」", "、".join(steps))
ok(steps == ["constraint", "units"],
    "拦截顺序符合论文 4.1 节：限制性判定在前，划分单元在后",
    "、".join(steps))
cleanup(pid, "1")
print()
print("场景 2：有单元，但未做限制性条件判定")
pid = new_patch("2"); add_units(pid); add_data(pid)
r = post_eval(pid)
n = results_of(pid)
ok(r.status_code == 302 and n == 0, "未做限制性判定 → 不产生评价结果",
    "结果数 %d" % n)
with app.app_context():
    pr = wf.patch_progress(pid)
ok(any(b["step"] == "constraint" for b in pr["blocking"]),
    "拦原因指向「执行限制性条件判定」")
cleanup(pid, "2")
print()
print("场景 3：限制性条件判定【未通过】")
pid = new_patch("3"); add_units(pid); add_data(pid);
```

```
        add_constraint(pid, passed=False)                                  11937
    r = post_eval(pid)                                                     11938
    n = results_of(pid)                                                    11939
    ok(r.status_code == 302 and n == 0, "判定未通过 → 不进入定量评价",          11940
       "结果数 %d" % n)                                                    11941
    with app.app_context():                                                11942
        pr = wf.patch_progress(pid)                                        11943
    ok(not pr["constraint"]["passed"], "流程状态显示判定未通过")              11944
    blocked = [b for b in pr["blocking"] if b["step"] ==                    11945
        "constraint"]                                                      11946
    # 提示只写「缺什么」：label 说明未通过，reason 直接引用判定记录里没过的项    11947
    ok(bool(blocked) and "未通过" in blocked[0]["label"],                    11948
       "拦提示指明限制性条件判定未通过", blocked[0]["label"] if blocked else  11949
        "")                                                                11950
    ok(bool(blocked) and "区位约束" in (blocked[0]["reason"] or ""),          11951
       "并把具体没通过的条件带出来", blocked[0]["reason"] if blocked else "")  11952
    cleanup(pid, "3")                                                      11953
    print()                                                                11954
    print("场景 4：判定通过，但指标数据全空")                                  11955
    pid = new_patch("4"); add_units(pid); add_constraint(pid,              11956
        passed=True)                                                       11957
    r = post_eval(pid)                                                     11958
    n = results_of(pid)                                                    11959
    ok(r.status_code == 302 and n == 0, "数据未录入 → 不产生评价结果",          11960
       "结果数 %d" % n)                                                    11961
    with app.app_context():                                                11962
        pr = wf.patch_progress(pid)                                        11963
    ok(any(b["step"] == "data" for b in pr["blocking"]),                   11964
       "拦原因指向「录入指标数据」")                                        11965
    ok(pr["data"]["missing"] == ["碎石边坡"],                                11966
       "指出具体缺哪个单元的数据", "、".join(pr["data"]["missing"]))         11967
    cleanup(pid, "4")                                                      11968
    print()                                                                11969
    print("场景 5：单元面积占比合计不为 100%")                                 11970
    pid = new_patch("5"); add_constraint(pid, passed=True)                 11971
    with app.app_context():                                                11972
        u = MicroUnit(patch_id=pid, unit_type="碎石边坡", area=1.0,         11973
        ratio=0.5)                                                         11974
        db.session.add(u); db.session.commit()                             11975
        db.session.add(IndicatorData(unit_id=u.id,                         11976
        soil_ratio=0.3, thickness=10,                                      11977
                                             ph=8.0,                       11978
        organic_matter=5.0, coverage=80.0,                                 11979
                                             shannon=0.6, slope=20.0,      11980
        aspect="阳坡"))                                                     11981
        db.session.commit()                                                11982
    r = post_eval(pid)                                                     11983
    ok(results_of(pid) == 0, "占比不足 100% → 不产生评价结果")               11984
    cleanup(pid, "5")                                                      11985
    print()                                                                11986
```

```
print(LINE)
print("二、前置条件齐备时才放行")
print(LINE)
pid = new_patch("OK"); add_units(pid); add_constraint(pid,
    passed=True); add_data(pid)
with app.app_context():
    pr = wf.patch_progress(pid)
ok(pr["ready"], "单元 + 判定通过 + 数据齐备 → 判定为可执行")
r = post_eval(pid)
n = results_of(pid)
ok(n == 1, "此时执行评价成功产生结果", "结果数 %d" % n)
print("  重定向到:", r.headers.get("Location"))
print()
print(LINE)
print("三、报告不得先于评价产生")
print(LINE)
pid2 = new_patch("R")    # 什么都不做
r = get_report(pid2)
ok(r.status_code == 302 and "/report/" ==
    (r.headers.get("Location") or ""),
   "前置缺失时 /report/<id> 被退回列表", "HTTP %d" % r.status_code)
for suffix in ("/pdf", "/word"):
    rr = c.get("/report/%d%s" % (pid2, suffix),
    follow_redirects=False)
    ok(rr.status_code == 302, "导出 %s 同样被拦住" % suffix, "HTTP
    %d" % rr.status_code)
cleanup(pid2, "R")
cleanup(pid, "OK")
print()
print(LINE)
print("四、前置齐备但从未执行评价时，报告仍不得产生")
print(LINE)
# 报告是评价结论的呈现：即使前置步骤都做完了，只要没真正执行过定量评价，
# 也不应凭空推算出结论。
pid3 = new_patch("N")
add_units(pid3); add_constraint(pid3, passed=True);
    add_data(pid3)
with app.app_context():
    pr = wf.report_progress(pid3)
ok(not pr["ready"], "无评价记录 → 报告流程判定为未就绪")
ok(bool(pr["blocking"]) and pr["blocking"][0]["step"] ==
    "evaluate",
   "拦原因指向「执行适宜性评价」")
r = get_report(pid3)
ok(r.status_code == 302 and results_of(pid3) == 0,
   "直接访问 /report/<id> 被退回，且不产生任何评价结果",
   "HTTP %d" % r.status_code)
# 真正执行评价之后，报告才放行，且取值与评价记录一致
r = post_eval(pid3)
ok(results_of(pid3) == 1, "先执行评价 → 产生评价记录")
```

```
with app.app_context():
    pr = wf.report_progress(pid3)
    rec = pr["result"]
ok(pr["ready"] and rec is not None, "有评价记录后，报告流程就绪")
rr = get_report(pid3)
body = rr.get_data(as_text=True)
ok(rr.status_code == 200, "此时可打开得分明细页", "HTTP %d" %
    rr.status_code)
ok(("%.4f" % rec.final_score) in body,
   "报告数值取自评价记录，而非重新计算",
   "F=%.4f" % rec.final_score)
cleanup(pid3, "N")
print()
print(LINE)
print("五、内置演示数据的清理不得波及用户自建数据")
print(LINE)
# 回归保护：seed_demo.clean_case() 曾执行 Project.query.delete()，
# 导致用户新建的项目在每次启动时被连带删除。
import seed_demo as sd
with app.app_context():
    keep_p = Project(name="用户自建项目-守护", code="KEEP-001")
    db.session.add(keep_p); db.session.flush()
    keep_patch = MinePatch(project_id=keep_p.id,
    name="用户自建图斑-守护")
    db.session.add(keep_patch); db.session.flush()
    keep_pid = keep_p.id
    keep_patch_id = keep_patch.id
    db.session.commit()
with app.app_context():
    sd.clean_case(reset=False)
with app.app_context():
    still_p = db.session.get(Project, keep_pid)
    still_patch = db.session.get(MinePatch, keep_patch_id)
ok(still_p is not None, "清理演示数据后，用户自建项目仍存在")
ok(still_patch is not None, "清理演示数据后，用户自建图斑仍存在")
# 演示数据清掉后应能重新写入，保证演示环境可恢复
sd.seed()
with app.app_context():
    demo_back = Project.query.filter_by(code=sd.DEMO_CODE).f
    irst()
ok(demo_back is not None, "演示案例可重新写入（幂等恢复）")
with app.app_context():
    m = db.session.get(MinePatch, keep_patch_id)
    if m:
        db.session.delete(m)
    p = db.session.get(Project, keep_pid)
    if p:
        db.session.delete(p)
    db.session.commit()
print()
```

```
print(LINE)
print("六、同一图斑不得重复划分同类型微地质单元")
print(LINE)
#  论文 4.1 节把图斑分为平台、碎石边坡、岩质边坡三类，每类至多一个。
#  允许重复会让面积占比、按类型组织的指标数据与批量导入对不上号。
pid4 = new_patch("D")
c.post("/unit/%d/add" % pid4, data={"unit_type": "平台",
    "area": "1.0"},
       follow_redirects=True)
with app.app_context():
    n1 = MicroUnit.query.filter_by(patch_id=pid4).count()
ok(n1 == 1, "首次添加「平台」成功", "单元数 %d" % n1)
r = c.post("/unit/%d/add" % pid4, data={"unit_type": "平台",
    "area": "2.0"},
            follow_redirects=True)
with app.app_context():
    n2 = MicroUnit.query.filter_by(patch_id=pid4).count()
ok(n2 == 1, "重复添加同类型被拒绝", "单元数 %d" % n2)
ok("同一类型只能划分一个" in r.get_data(as_text=True), "给出重复提示")
r = c.post("/unit/%d/add" % pid4, data={"unit_type": "火山口",
    "area": "1.0"},
            follow_redirects=True)
with app.app_context():
    n3 = MicroUnit.query.filter_by(patch_id=pid4).count()
ok(n3 == 1, "非法单元类型被拒绝", "单元数 %d" % n3)
c.post("/unit/%d/add" % pid4, data={"unit_type": "碎石边坡",
    "area": "3.0"},
       follow_redirects=True)
with app.app_context():
    uid = MicroUnit.query.filter_by(patch_id=pid4,
                                    unit_type="碎石边坡").first()
    ).id
r = c.post("/unit/edit/%d" % uid,
           data={"unit_type": "平台", "area": "3.0"},
    follow_redirects=True)
with app.app_context():
    types = sorted(u.unit_type for u in
                   MicroUnit.query.filter_by(patch_id=pid4)
    all())
ok(types == ["平台", "碎石边坡"], "改类型时同样拦截重复", "、".join(types))
cleanup(pid4, "D")
print()
print(LINE)
if _fails:
    print("存在未通过项：")
    for f in _fails:
        print("  -", f)
    sys.exit(1)
print("流程门禁自检全部通过 √")
print(LINE)
```

```
#  ====  测试/test_weights.py  ====
#  -*-  coding:  utf-8  -*-
"""权重生效链路自检：AHP  算出的权重必须真正参与评价计算。
此前  weight_schemes  /  weight_items  两张表从未被写入，评价引擎也只用
代码里的论文表  3  默认权重，相当于权重模块算完即弃。本测试守住这条链路：
      默认  →  论文表  3
      保存  AHP  权重  →  评价改用新权重，结果随之变化
      恢复默认  →  结果回到论文取值
"""
import  os
import  sys
sys.stdout.reconfigure(encoding="utf-8")
#  本脚本位于  测试/  子目录，先把仓库根目录加入模块搜索路径，
#  使  `from  app  import  ...`  与  app/app.db  的定位不受影响。
ROOT  =  os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if  ROOT  not  in  sys.path:
      sys.path.insert(0,  ROOT)
from  app  import  create_app
from  app.models  import  (db,  Project,  MinePatch,  MicroUnit,
      IndicatorData,
                              ConstraintCheck,  EvaluationResult,
      WeightScheme,
                              WeightItem)
from  app.services  import  workflow  as  wf
from  app.services  import  weight_service  as  ws
LINE  =  "="  *  72
BASE  =  ROOT
class  TestConfig:
      SECRET_KEY  =  "test"
      SQLALCHEMY_DATABASE_URI  =  "sqlite:///"  +
      os.path.join(BASE,  "app",  "app.db")
      SQLALCHEMY_TRACK_MODIFICATIONS  =  False
      WTF_CSRF_ENABLED  =  False
      TESTING  =  True
app  =  create_app(TestConfig)
c  =  app.test_client()
c.post("/login",  data={"username":  "admin",  "password":
      "admin123"})
_fails  =  []
def  ok(flag,  label,  extra=""):
      print("  %s  %-46s  %s"  %  ("[符合]"  if  flag  else  "[不符合]",
      label,  extra))
      if  not  flag:
            _fails.append(label)
TAG  =  "W"
UNIT_TYPE  =  "碎石边坡"
def  build_case():
      """建一个只含单一微地质单元的图斑，便于观察权重变化对得分的影响。"""
      with  app.app_context():
```

```
        p = Project(name="权重测试-%s" % TAG, code="WEIGHT-%s"
    % TAG)
        db.session.add(p); db.session.flush()
        patch = MinePatch(project_id=p.id, name="权重测试图斑-%s"
    % TAG)
        db.session.add(patch); db.session.flush()
        db.session.add(MicroUnit(patch_id=patch.id,
    unit_type=UNIT_TYPE,
                                 area=1.0, ratio=1.0))
        db.session.flush()
        u = MicroUnit.query.filter_by(patch_id=patch.id).fir
    st()
        db.session.add(IndicatorData(
            unit_id=u.id, soil_ratio=0.34, thickness=10,
    ph=9.24,
            organic_matter=4.89, coverage=87.92,
    shannon=0.60,
            slope=28.75, aspect="阳坡"))
        db.session.add(ConstraintCheck(
            patch_id=patch.id, policy_pass=True,
    location_pass=True,
            pollution_pass=True, geo_pass=True,
    farmland_pass=True,
            passed=True, reason="全部通过"))
        db.session.commit()
        return patch.id
def cleanup(pid):
    with app.app_context():
        from app.models import ScoreDetail
        rids = [r.id for r in EvaluationResult.query.filter_
    by(patch_id=pid)]
        if rids:
            ScoreDetail.query.filter(ScoreDetail.result_id.i
    n_(rids)).delete(
                synchronize_session=False)
        EvaluationResult.query.filter_by(patch_id=pid).delet
    e()
        ConstraintCheck.query.filter_by(patch_id=pid).delete
    ()
        uids = [u.id for u in MicroUnit.query.filter_by(patc
    h_id=pid)]
        if uids:
            IndicatorData.query.filter(IndicatorData.unit_id
    .in_(uids)).delete(
                synchronize_session=False)
        MicroUnit.query.filter_by(patch_id=pid).delete()
        m = db.session.get(MinePatch, pid)
        if m:
            db.session.delete(m)
        p = Project.query.filter_by(code="WEIGHT-%s" %
```

```
    TAG).first()
        if p:
            db.session.delete(p)
        db.session.commit()
def run_eval(pid):
    c.post("/evaluate/%d" % pid, data={},
    follow_redirects=False)
    with app.app_context():
        return EvaluationResult.query.filter_by(patch_id=pid
    ) \
            .order_by(EvaluationResult.id.desc()).first().fi
    nal_score
print(LINE)
print("一、默认应使用论文表 3 的权重")
print(LINE)
with app.app_context():
    ws.reset_weights(UNIT_TYPE)
    w, label, scheme = ws.effective_weights(UNIT_TYPE)
ok(scheme is None and "论文表" in label, "未配置时权重来源为论文表 3",
    label)
ok(abs(w["l1"]["土壤指标"] - 0.44) < 1e-9, "一级权重取自论文表 3",
   "土壤指标 %.2f" % w["l1"]["土壤指标"])
pid = build_case()
base_score = run_eval(pid)
print("  默认权重下的评价值 F = %.4f" % base_score)
print()
print(LINE)
print("二、保存 AHP 算出的权重后，评价应改用新权重")
print(LINE)
with app.app_context():
    # 模拟 AHP 计算结果：把土壤指标权重提高、植被与地形降低（仍和为 1）
    ws.save_weights(UNIT_TYPE, [("soil", 0.70), ("veg",
    0.20),
                                ("terrain", 0.10)])
    n_items = WeightItem.query.count()
ok(n_items >= 3, "weight_items 表已写入权重条目", "%d 条" % n_items)
with app.app_context():
    w2, label2, scheme2 = ws.effective_weights(UNIT_TYPE)
ok(scheme2 is not None and "自定义" in label2, "权重来源变为自定义方案",
    label2)
ok(abs(w2["l1"]["土壤指标"] - 0.70) < 1e-9, "新权重已生效",
   "土壤指标 %.2f" % w2["l1"]["土壤指标"])
ok(abs(w2["l1"]["植被指标"] - 0.20) < 1e-9, "同批保存的其他项也已生效")
ok(abs(w2["l2"]["土壤指标"]["土石比"] - 0.25) < 1e-9,
   "未覆盖的二级权重仍保留论文取值",
   "土石比 %.2f" % w2["l2"]["土壤指标"]["土石比"])
new_score = run_eval(pid)
print("  新权重下的评价值 F = %.4f" % new_score)
ok(abs(new_score - base_score) > 1e-4,
   "权重变化确实改变了评价结果",
```

```
    "%.4f → %.4f" % (base_score, new_score))
print()
print(LINE)
print("三、结果应记录所用权重来源")
print(LINE)
import json
with app.app_context():
    rec = EvaluationResult.query.filter_by(patch_id=pid) \
        .order_by(EvaluationResult.id.desc()).first()
    stored = json.loads(rec.unit_scores)
ok(any(u.get("weight_source") for u in stored),
   "评价记录中标注了权重来源",
   stored[0].get("weight_source") or "")
print()
print(LINE)
print("四、恢复默认后应回到论文取值")
print(LINE)
with app.app_context():
    ws.reset_weights(UNIT_TYPE)
    w3, label3, scheme3 = ws.effective_weights(UNIT_TYPE)
ok(scheme3 is None and "论文表" in label3, "已恢复为论文表 3 权重",
   label3)
back_score = run_eval(pid)
print("  恢复后评价值 F = %.4f（默认时 %.4f）" % (back_score,
   base_score))
ok(abs(back_score - base_score) < 1e-9, "评价结果与默认时一致")
print()
print(LINE)
print("五、权重首页概览")
print(LINE)
with app.app_context():
    rows = ws.summary()
ok(len(rows) == 3, "三种微地质单元均有权重来源说明", "%d 行" % len(rows))
r = c.get("/ahp/")
body = r.get_data(as_text=True)
ok(r.status_code == 200 and "当前生效权重" in body, "权重首页正常展示")
print()
print(LINE)
print("六、一致性不通过的矩阵不得保存生效")
print(LINE)
with app.app_context():
    ws.reset_weights(UNIT_TYPE)
n = 3
# 明显矛盾的矩阵：a12=9, a13=1/9, a23=9 —— CR 必然超限
mats = [(0, 1, "9"), (0, 2, "0.1111"), (1, 2, "9")]
data = {"csrf_token": "", "action": "save"}
for i, j, v in mats:
    data["m_%d_%d" % (i, j)] = v
r = c.post("/ahp/matrix?unit_type=%s&level=1" % UNIT_TYPE,
    data=data,
```

```
            follow_redirects=True)                                  12337
with app.app_context():                                             12338
    _, label4, scheme4 = ws.effective_weights(UNIT_TYPE)            12339
ok(scheme4 is None, "CR 超限的矩阵未被保存生效", label4)              12340
ok("一致性" in r.get_data(as_text=True), "页面给出了未通过一致性的提示")  12341
cleanup(pid)                                                        12342
print()                                                             12343
print(LINE)                                                         12344
if _fails:                                                          12345
    print("存在未通过项：")                                          12346
    for f in _fails:                                                12347
        print("  -", f)                                             12348
    sys.exit(1)                                                     12349
print("权重生效链路自检全部通过 √")                                  12350
print(LINE)                                                         12351
#  ==== app/services/__init__.py ====                               12352
#  -*- coding: utf-8 -*-                                            12353
#  ==== app/utils/__init__.py ====                                  12354
#  -*- coding: utf-8 -*-                                            12355
#  ==== app/utils/timefmt.py ====                                   12356
#  -*- coding: utf-8 -*-                                            12357
"""时间显示：库里一律存 UTC，展示时换成服务器本地时间。                  12358
为什么不在写库时直接用本地时间：一个系统里时间基准只能有一个。          12359
`app/models.py` 里所有 `created_at` / `checked_at` 都用              12360
    `datetime.utcnow`，                                             12361
存的是 UTC；如果写库改成本地时间，已经存进库的几千条记录会新旧混着差 8 小时。  12362
所以统一在「展示」这一层换算，老数据不用动。                          12363
用法（Jinja）：                                                      12364
    {{ row.created_at | localdt }}                          →       12365
    2026-09-26 23:33                                                12366
    {{ row.created_at | localdt("%Y-%m-%d %H:%M:%S") }} →           12367
    2026-09-26 23:33:28                                             12368
"""                                                                 12369
from datetime import datetime, timezone                             12370
DEFAULT_FORMAT = "%Y-%m-%d %H:%M"                                   12371
def to_local(value, fmt=DEFAULT_FORMAT, empty="—"):                 12372
    """把 UTC 时间换算成服务器本地时间并格式化。                      12373
    传进来的值按「无时区即 UTC」处理；带时区的原样换算，便于以后改用  12374
    带时区的时间戳。空值返回占位符，免得页面上出现 None。            12375
    """                                                             12376
    if value is None:                                               12377
        return empty                                                12378
    if value.tzinfo is None:                                        12379
        value = value.replace(tzinfo=timezone.utc)                  12380
    return value.astimezone().strftime(fmt)                         12381
def now_utc():                                                      12382
    """取当前 UTC 时间（带时区），用于只作展示、不落库的时间戳。"""    12383
    return datetime.now(timezone.utc)                               12384
#  ==== app/views/__init__.py ====                                  12385
#  -*- coding: utf-8 -*-                                            12386
```