

Further Approximation Algorithms

MA428, Dr Katerina Papadaki

I. EXERCISE 1

Sketch the proofs of the following:

- (a) The greedy algorithm for the k -center problem is a 2-approximation algorithm.
- (b) There does not exist an α -approximation algorithm for the TSP (non-metric), for $\alpha > 1$, unless $P = NP$.
- (c) Christofides algorithm is a $\frac{3}{2}$ -approximation algorithm.

II. EXERCISE 2

Suppose we have $n = 3$ boolean variables, and $m = 3$ clauses where:

$$C_1 = \bar{x}_1 \vee \bar{x}_2 \vee x_3,$$

$$C_2 = \bar{x}_1 \vee x_2 \vee x_3 \text{ and}$$

$$C_3 = x_1 \vee x_2 \vee \bar{x}_3,$$

with weights $w_1 = 3$, $w_2 = 2$ and $w_3 = 1$. Suppose we want to maximize the value of $\sum_{j=1}^m w_j C_j$, where the variables C_j , take the value 1 when the clause is satisfied.

(i) Find an optimal solution by inspection and give the value of the x variables and the objective value.

(ii) Approximate the solution using randomized rounding, using the random 0 – 1 sequence 001110100... to generate random boolean variables. What is the approximate objective value

K. Papadaki is with the Department of Management, Operational Research Group at London School of Economics, United Kingdom

E-mail: k.p.papadaki@lse.ac.uk

and the value of the x variables.

(iii) The randomized algorithm used in (ii) is a $\frac{1}{2}$ -approximation. Could we get a value in (ii) which is less than $\frac{1}{2}$ times the optimal value OPT ?

III. EXERCISE 3

Prove that a vertex cover heuristic that adds both of an uncovered edge's endpoints to a cover yields a 2-approximation. (Hint: compare the vertices added by the algorithm with those in an optimal cover.)

IV. EXERCISE 4

Consider the complete graph $G = (V, E)$, where $V = \{1, 2, 3, 4, 5\}$ and $c_{ij} = \frac{i+j}{2}$. Approximate an optimal tour for the TSP on G using:

- (a) Show that the triangle inequality holds.
- (b) The nearest addition algorithm.
- (c) The double tree algorithm.
- (d) Christofides algorithm.
- (e) For each one of the above α -approximation algorithms, give the value of α and verify that the approximate solutions found is within α of OPT .