

# Lockers Integration API Documentation

## Overview

The Lockers Integration API provides functionality for managing smart locker reservations and availability. This microservice enables partners to search for nearby lockers, create reservations, and manage the complete locker lifecycle.

**Base URL:** `https://dev-api.motions.space/api/v1/lockers-service`

**Contact Support:** [api-support@motions.space](mailto:api-support@motions.space)

## Authentication

All API endpoints require authentication using an API key passed in the request header.

```
http
api-key: your_api_key_here
```

## Response Format

All API responses follow a consistent JSON structure:

```
json
{
  "status": "success|error|completed",
  "message": "Human readable message",
  "data": "Response data or null"
}
```

# Endpoints

## 1. Search Nearby Lockers

**Endpoint:** `GET /integration/lockers/nearby`

**Description:** Returns a list of lockers near a given location. If no query parameters are provided, all lockers are returned.

### Query Parameters

| Parameter           | Type    | Required | Description                             |
|---------------------|---------|----------|-----------------------------------------|
| <code>lat</code>    | string  | No       | Latitude coordinate                     |
| <code>lng</code>    | string  | No       | Longitude coordinate                    |
| <code>radius</code> | integer | No       | Search radius in meters (default: 1000) |

### Request Headers

| Header               | Value            | Required | Description     |
|----------------------|------------------|----------|-----------------|
| <code>api-key</code> | string           | Yes      | Your API key    |
| <code>Accept</code>  | application/json | No       | Response format |

### Example Request

http

GET /integration/lockers/nearby?lat=6.627683580910164&lng=3.3659057347491776&radius=1000

**Host:** dev-api.motions.space

**api-key:** your\_api\_key\_here

**Accept:** application/json

## Example Response (200 OK)

```
json
{
  "data": [
    {
      "address": "12 Admiralty Way, Lekki",
      "available_slots": {
        "large": 2,
        "medium": 3,
        "small": 5
      },
      "distance_km": 1.2,
      "locker_id": "locker_lekki_001",
      "name": "Lekki Phase 1 Hub"
    }
  ],
  "message": "Locker created",
  "status": "success"
}
```

## Response Fields

| Field                               | Type    | Description                                    |
|-------------------------------------|---------|------------------------------------------------|
| <code>address</code>                | string  | Physical address of the locker location        |
| <code>available_slots</code>        | object  | Available compartments by size                 |
| <code>available_slots.large</code>  | integer | Number of available large compartments         |
| <code>available_slots.medium</code> | integer | Number of available medium compartments        |
| <code>available_slots.small</code>  | integer | Number of available small compartments         |
| <code>distance_km</code>            | number  | Distance from search coordinates in kilometers |
| <code>locker_id</code>              | string  | Unique identifier for the locker               |
| <code>name</code>                   | string  | Display name of the locker location            |

## 2. Reserve a Locker

**Endpoint:** `POST /integration/reservations`

**Description:** Creates a new locker reservation for a specified duration and compartment size.

### Request Headers

| Header                    | Value            | Required | Description         |
|---------------------------|------------------|----------|---------------------|
| <code>api-key</code>      | string           | Yes      | Your API key        |
| <code>Content-Type</code> | application/json | Yes      | Request body format |
| <code>Accept</code>       | application/json | No       | Response format     |

### Request Body

```
json
```

```
{
  "locker_id": "d78259e2-5793-4050-b4f9-b89af7d84834",
  "size": "large",
  "recipient_phone": "string",
  "duration_hours": 3
}
```

## Request Body Parameters

| Parameter       | Type    | Required | Description                             |
|-----------------|---------|----------|-----------------------------------------|
| locker_id       | string  | Yes      | ID of the locker to reserve             |
| size            | string  | Yes      | Compartment size (small, medium, large) |
| recipient_phone | string  | Yes      | Phone number of the recipient           |
| duration_hours  | integer | Yes      | Reservation duration in hours           |

## Example Request

```
http
POST /integration/reservations
Host: dev-api.motions.space
api-key: your_api_key_here
Content-Type: application/json

{
  "locker_id": "d78259e2-5793-4050-b4f9-b89af7d84834",
  "size": "large",
  "recipient_phone": "+234123456789",
  "duration_hours": 3
}
```

## Response Examples

### Success (201 Created)

```
json

{
  "data": {
    "access_code": 4821,
    "compartment": "M-12",
    "expires_at": "Fri, 15 Aug 2025 14:00:00 GMT",
    "id": "res_abc123",
    "status": "active"
  },
  "message": "Locker reserved",
  "status": "success"
}
```

### Bad Request (400)

```
json

{
  "data": null,
  "message": "Bad data sent.",
  "status": "error"
}
```

### Not Found (404)

```
json
```

```
{
  "data": null,
  "message": "Resource not found.",
  "status": "error"
}
```

## Internal Server Error (500)

```
json
{
  "data": null,
  "message": "Internal server error.",
  "status": "error"
}
```

## Success Response Fields

| Field       | Type    | Description                            |
|-------------|---------|----------------------------------------|
| access_code | integer | 4-digit code to access the compartment |
| compartment | string  | Assigned compartment identifier        |
| expires_at  | string  | Reservation expiration timestamp (GMT) |
| id          | string  | Unique reservation identifier          |
| status      | string  | Current status of the reservation      |

## 3. Get Locker Reservation

**Endpoint:** GET /integration/reservations/{id}

**Description:** Retrieves details of a specific reservation by its ID.

### Path Parameters

| Parameter | Type   | Required | Description    |
|-----------|--------|----------|----------------|
| id        | string | Yes      | Reservation ID |

### Request Headers

| Header  | Value            | Required | Description     |
|---------|------------------|----------|-----------------|
| api-key | string           | Yes      | Your API key    |
| Accept  | application/json | No       | Response format |

### Example Request

```
http

GET /integration/reservations/res_rem1wu
Host: dev-api.motions.space
api-key: your_api_key_here
Accept: application/json
```

### Example Response (200 OK)

```
json
```

```
{
  "data": {
    "compartment": "M-12",
    "expires_at": "Fri, 15 Aug 2025 14:00:00 GMT",
    "id": "res_abc123",
    "status": "active"
  },
  "message": "Locker created",
  "status": "success"
}
```

### Response Fields

| Field       | Type   | Description                            |
|-------------|--------|----------------------------------------|
| compartment | string | Assigned compartment identifier        |
| expires_at  | string | Reservation expiration timestamp (GMT) |
| id          | string | Unique reservation identifier          |
| status      | string | Current status of the reservation      |

## 4. Complete Reservation

**Endpoint:** POST /integration/reservations/{id}/complete

**Description:** Marks a reservation as complete and releases the locker compartment.

### Path Parameters

| Parameter | Type   | Required | Description    |
|-----------|--------|----------|----------------|
| id        | string | Yes      | Reservation ID |

## Request Headers

| Header  | Value            | Required | Description     |
|---------|------------------|----------|-----------------|
| api-key | string           | Yes      | Your API key    |
| Accept  | application/json | No       | Response format |

## Example Request

```
http
POST /integration/reservations/res_rem1wu/complete
Host: dev-api.motions.space
api-key: your_api_key_here
Accept: application/json
```

## Example Response (200 OK)

```
json
{
  "data": null,
  "message": "Locker released successfully",
  "status": "completed"
}
```

## Error Handling

The API uses conventional HTTP response codes to indicate success or failure:

- **200 OK** - Request successful
- **201 Created** - Resource created successfully

- **400 Bad Request** - Invalid request data
- **404 Not Found** - Resource not found
- **500 Internal Server Error** - Server error

All error responses include a descriptive message in the response body.

## Rate Limiting

Please contact support for information about rate limits and usage quotas.

## SDK and Examples

### cURL Examples

#### Search Nearby Lockers:

```
bash

curl -X GET "https://dev-api.motions.space/api/v1/lockers-service/integration/lockers/nearby?lat=6.627683" \
-H "api-key: your_api_key_here" \
-H "Accept: application/json"
```

#### Reserve a Locker:

```
bash
```

```
curl -X POST "https://dev-api.motions.space/api/v1/lockers-service/integration/reservations" \  
-H "api-key: your_api_key_here" \  
-H "Content-Type: application/json" \  
-d '{  
  "locker_id": "d78259e2-5793-4050-b4f9-b89af7d84834",  
  "size": "large",  
  "recipient_phone": "+234123456789",  
  "duration_hours": 3  
'
```

### Get Reservation:

```
bash  
  
curl -X GET "https://dev-api.motions.space/api/v1/lockers-service/integration/reservations/res_abc123" \  
-H "api-key: your_api_key_here" \  
-H "Accept: application/json"
```

### Complete Reservation:

```
bash  
  
curl -X POST "https://dev-api.motions.space/api/v1/lockers-service/integration/reservations/res_abc123/co  
-H "api-key: your_api_key_here" \  
-H "Accept: application/json"
```

## Support

For technical support, questions, or API key requests, please contact:

**Email:** [api-support@motions.space](mailto:api-support@motions.space)

---

*This documentation is generated from the Lockers Integration Postman Collection*