

These are the commands for the follow-along exercises in Lesson 3.2.

3.202: Adding CSS when serving your document

header.html

```
<link rel="stylesheet" type="text/css"
href="../static/css/genedata.css">
```

```
<h1 id="application_title">Gene Browser</h2>
```

```

```

genedata.css

```
body {
    font-family: Sans-Serif;
    margin: 0px;
    border: 0px;
    padding: 0px;
}

#application_title
{
    display: inline;
}

#logo{
    height: 50px;
    width: 50px
}

#header{
    width: 100%;
    background-color: #3caea3;
}

#navigation{
    width: 100%;
    background-color: #20639b;
    color: #ffffff;
    padding: 2px;
}

#footer{
    width: 100%;
    background-color: #92cdc7;
}

#application_title
{
    display: inline;
    vertical-align: middle;
```

```

}

#logo{
    vertical-align: middle;
    height: 50px;
    width: 50px
}

#header{
    vertical-align: middle;
    width: 100%;
    background-color: #3caea3;
}

a {
    text-decoration: none;
}
.nav_link {
    color: white;
}
#content{
    padding-left: 10px;
}

title.html
<a class="nav_link" href="/">Home</a>&nbsp;
<a class="nav_link" href="https://www.ebi.ac.uk/">EBI</a>&nbsp;
<a class="nav_link" href="https://www.uniprot.org/">Uniprot</a>

```

3.204: Restyling the website

gene.html, list.html

```

{% extends "./base.html" %}
{% block content %}
...
{% endblock %}

```

views.py

```

def index(request):
    master_genes = Gene.objects.all()
    return render(request, 'genedata/index.html', {'master_genes':
master_genes})

def gene(request, pk):
    gene = Gene.objects.get(pk=pk)
    gene.access += 1
    print("Gene record:", pk, "access count:", str(gene.access))
    gene.save()

    master_genes = Gene.objects.all()

```

```

    return render(request, 'genedata/gene.html', {'gene': gene,
'master_genes': master_genes})

def list(request, type):
    genes = Gene.objects.filter(entity__exact=type)

    master_genes = Gene.objects.all()
    return render(request, 'genedata/list.html', {'genes': genes,
'type': type, 'master_genes': master_genes})

def poslist(request):
    genes =
Gene.objects.filter(entity__exact='Chromosome').filter(sense__star
tswith='+')
    master_genes = Gene.objects.all()
    return render(request, 'genedata/list.html', {'genes': genes,
'type': 'PosList', 'master_genes': master_genes})

def delete(request, pk):
    GeneAttributeLink.objects.filter(gene_id=pk).delete()
    Gene.objects.filter(pk=pk).delete()
    return HttpResponseRedirect("/")

```

index.html

```

{% for gene in master_genes %}

{% block geneList %}
<div id="gene_list">
<h1>D.Bucha Genes</h1>
<table>
    <tr><th>Gene ID</th></tr>
    {% for gene in master_genes %}
        <tr><td><a href="/gene/{{gene.pk}}">{{gene}}</a></td></tr>
    {% endfor %}
</table>
</div>
{% endblock%}

```

genedata.css

```

#content{
    padding-left: 10px;
    float: left;
}

#gene_list{
    padding-left: 10px;
    padding-right: 20px;
    float: left;
    border-right: 2px dashed black;
}

#footer{

```

```
padding-left: 10px;  
width: 100%;  
float: left;  
}
```