Chapter 7. Convolutional Neural Networks and Architectures

Convolution, stride, padding, pooling, equivariance; AlexNet, LRN, ZFNet, VGG, GoogLeNet/Inception, ResNet, saliency maps

Contents

1 Why a New Layer **2**

2 Convolution as a Local Dot Product **2**

2.1 A fixed filter: moving average 2

2.2 Single and multiple channels 2

2.3 Parameter counts 3

3 Stride, Padding and Output Size **3**

4 Learning Filters **4**

5 Shift Equivariance **4**

6 1×1 Convolution, Pooling and Global Average Pooling **4**

7 Algebraic Facts from Past Exams **5**

8 Vocabulary and Costs **5**

9 AlexNet **6**

10 ZFNet and VGG **6**

11 GoogLeNet and the Inception Module **6**

11.1 Naive module 6

11.2 Bottleneck module 7

11.3 Split–transform–merge (2021 midterm Q5) 7

12 Network in Network: Exact versus Approximate Invariance (2022 midterm Q7) **7**

13 Why Depth Can Fail, and Residual Networks **8**

14 Saliency Maps **8**

1 Why a New Layer

An image $X \in \mathbb{R}^{H\times W\times C}$ fed to a fully connected layer is flattened, and $z = A\mathbf{x} + \mathbf{b}$ with $A \in \mathbb{R}^{M\times HWC}$ has $M(HWC+1)$ parameters: for $32\times 32\times 3$ input and $M = 1000$, already 3,073,000. Flattening loses no numbers, but an unrestricted matrix does not encode which pixels are neighbors or that a pattern can appear anywhere. Two assumptions about images motivate convolution:

- **Locality**: nearby pixels jointly form edges, corners and textures, so a unit can look at a small patch (local connectivity).
- **Stationarity**: the same pattern may occur at any position, so the same detector should be used everywhere (weight sharing).

Definition 7.1: equivariance and invariance

Let $T_{\boldsymbol{\tau}}$ shift an image, $(T_{\boldsymbol{\tau}}X)_{i,j,c} = X_{i-\tau_1,j-\tau_2,c}$. A feature extractor F is shift *equivariant* if $F(T_{\boldsymbol{\tau}}X) = T_{\boldsymbol{\tau}}F(X)$ (the output moves with the input) and a classifier G is shift *invariant* if $G(T_{\boldsymbol{\tau}}X) = G(X)$ (the output does not change). More generally, for a group acting by $\rho_{\text{in}}(g)$, $\rho_{\text{out}}(g)$, f is equivariant if $f(\rho_{\text{in}}(g)x) = \rho_{\text{out}}(g)f(x)$; invariance is the case $\rho_{\text{out}} = \text{id}$.

2 Convolution as a Local Dot Product

2.1 A fixed filter: moving average

With the 3×3 averaging kernel (1/9 everywhere), $Y_{i,j} = \frac{1}{9}\sum_{u,v=0}^{2} X_{i+u,j+v}$: on an image of 0s and 90s a window with r bright pixels outputs $10r$. Averaging suppresses isolated pixels but blurs edges; a 5×5 average smooths more. A CNN *learns* the kernel; learned weights may be negative and need not sum to one.

2.2 Single and multiple channels

Definition 7.2: convolutional layer

With D filters $W \in \mathbb{R}^{D\times K\times K\times C}$, biases $\mathbf{b} \in \mathbb{R}^D$, stride S, padding P,

$$Z_{i,j,d} = b_d + \sum_{u=0}^{K-1}\sum_{v=0}^{K-1}\sum_{c=1}^{C} W_{d,u,v,c}\,\tilde{X}_{Si+u,\,Sj+v,\,c},$$


where $\tilde{X}$ is the padded input. Each output is a dot product of a $K\times K\times C$ patch with a filter spanning *all* input channels, plus a bias. The array $Z_{\cdot,\cdot,d}$ is the feature map of filter d; stacking the D maps gives D output channels. This operation is cross-correlation (no kernel flip); since kernels are learned, the distinction does not matter for expressiveness.

Example 7.3: one channel, 2×2 filter

$X = \begin{pmatrix} 1 & 2 & 0 \\ 0 & 1 & 3 \\ 2 & 1 & 0 \end{pmatrix}$, $W = \begin{pmatrix} 1 & 0 \\ -1 & 2 \end{pmatrix}$, $b = 1$, $S = 1$, $P = 0$: $Z = \begin{pmatrix} 4 & 8 \\ 1 & 1 \end{pmatrix}$. The same four weights and bias are reused at the four positions.

Example 7.4: a 5×5 example

With a 5×5 image and $W = \begin{pmatrix} 1 & 2 & 3 \\ -4 & 7 & 4 \\ 2 & -5 & 1 \end{pmatrix}$ ($b = 0$): unpadded $Z = \begin{pmatrix} 51 & 66 & 20 \\ 31 & 49 & 101 \\ 15 & 53 & -2 \end{pmatrix}$; with $P = 1$ the output is 5×5 and its central 3×3 block equals the unpadded output (those windows contain the same pixels).



A filter spans the full depth of the input; sliding it over all spatial positions gives one 28×28 activation map.

2.3 Parameter counts

One $5 \times 5 \times 3$ filter has 75 weights and one bias; six filters on $32 \times 32 \times 3$ give a $28 \times 28 \times 6$ output with $6(75 + 1) = 456$ parameters. For the same input and output shape:

Layer	Parameters
Fully connected	$4704(3072 + 1) = 14{,}455{,}392$
Locally connected, unshared	$28^2 \cdot 6(75 + 1) = 357{,}504$
Convolution (shared)	$6(75 + 1) = 456$

Locality removes long-range connections; sharing removes independent copies. As a matrix acting on the flattened input, convolution is sparse with repeated entries (a 1D length-2 filter (a, b) on $(x_1, \dots, x_4)$ gives a banded matrix with only two free numbers).

3 Stride, Padding and Output Size

Theorem 7.5: output size

For input length N, kernel K, stride S, padding P (symmetric), the number of output positions is

$$N' = \left\lfloor \frac{N + 2P - K}{S} \right\rfloor + 1, \qquad C' = D.$$

Proof. The padded length is $N + 2P$. A window starting at tS ends at $tS + K - 1$, which must be $\le N + 2P - 1$, i.e. $t \le (N + 2P - K)/S$. The admissible integers are $t = 0, \dots, \lfloor (N + 2P - K)/S \rfloor$. ■

$N = 7$, $K = 3$: $S = 1 \Rightarrow 5$, $S = 2 \Rightarrow 3$, $S = 3 \Rightarrow 2$ (the last does not "fit" exactly; a border is left unused). For $S = 1$ and odd K, $P = (K - 1)/2$ preserves the size (padding $1, 2, 3$ for $K = 3, 5, 7$). Zero padding is an explicit boundary assumption, not recovered information.

Example 7.6: further examples

Input $52 \times 52 \times 128$, $D = 256$.
(1) $K = 3, S = 1, P = 1$: output $52 \times 52 \times 256$, parameters $256(9 \cdot 128 + 1) = 295{,}168$; each filter is $3 \times 3 \times 128$.
(2) $K = 4, S = 2, P = 1$: $\lfloor (52 + 2 - 4)/2 \rfloor + 1 = 26$, output $26 \times 26 \times 256$, parameters $256(16 \cdot 128 + 1) = 524{,}544$. Parameters, activations (HWD) and multiply–accumulates ($\approx HWDK^2C$) are different costs.

Stacking: $32 \times 32 \times 3 \to 28 \times 28 \times 6 \to 24 \times 24 \times 10$ with ten $5 \times 5 \times 6$ filters ($10(150 + 1) = 1510$ parameters). Two stacked stride-1 5×5 layers see a 9×9 patch (receptive field $5 + 4$). With strides, $r_\ell = r_{\ell-1} + (K_\ell - 1) j_{\ell-1}$ and $j_\ell = S_\ell j_{\ell-1}$, starting from $r_0 = j_0 = 1$.

4 Learning Filters

For an unpadded stride-1 layer with upstream $G_{i,j,d} = \partial L / \partial Z_{i,j,d}$,

$$\frac{\partial L}{\partial W_{d,u,v,c}} = \sum_{i,j} G_{i,j,d} X_{i+u,j+v,c}, \qquad \frac{\partial L}{\partial b_d} = \sum_{i,j} G_{i,j,d} :$$

every position contributes to the update of the shared weight (the backward counterpart of weight sharing).

5 Shift Equivariance

Theorem 7.7: convolution commutes with shifts

On an infinite grid (or with circular indices), stride-1 convolution satisfies $C_W(T_{\boldsymbol{\tau}} X) = T_{\boldsymbol{\tau}} C_W(X)$, and pointwise nonlinearities also commute with shifts. Global average pooling of a circularly shifted map is unchanged, so GAP $\circ$ (convolutions, ReLUs) is shift invariant.

Proof. $[C_W(T_{\boldsymbol{\tau}} X)]_{i,j,d} = b_d + \sum_{u,v,c} W_{d,u,v,c} X_{i+u-\tau_1, j+v-\tau_2, c} = [C_W X]_{i-\tau_1, j-\tau_2, d}$; the coefficients do not depend on the absolute position (i, j). A circular shift permutes positions, and an average is invariant under permutations. ■

Remark 7.8: when exactness fails

With zero padding, content shifted across the border is lost and zeros enter, so equality holds only away from the boundary. A stride-S layer (or pooling) is compatible only with shifts that are multiples of S: for width-2, stride-2 max pooling M, $M(T_2 x) = T_1 M(x)$ but $M(T_1 x)$ need not be a shift of $M(x)$ (e.g. $x = (0, 1, 2, 0)$, $M(x) = (1, 2)$, $M(T_1 x) = (0, 2)$).

6 1×1 Convolution, Pooling and Global Average Pooling

1×1 convolution. At each position $\mathbf{y}_{i,j} = A\mathbf{x}_{i,j} + \mathbf{b}$ with $A \in \mathbb{R}^{D \times C}$ shared across positions: it mixes channels, not neighbors. $56 \times 56 \times 64 \to 56 \times 56 \times 32$ costs $32(64 + 1) = 2080$ parameters.

Pooling. Channelwise, no parameters: $Y^{\max}_{i,j,c} = \max_{u,v} X_{iS+u, jS+v, c}$ or the average. For $X = \begin{pmatrix} 5 & 10 & 6 & 7 \\ 4 & 0 & 4 & 3 \\ 2 & 4 & 3 & 4 \\ 0 & 8 & 1 & 6 \end{pmatrix}$ and 2×2, stride 2: average $\begin{pmatrix} 4.75 & 5 \\ 3.5 & 3.5 \end{pmatrix}$, max $\begin{pmatrix} 10 & 7 \\ 8 & 6 \end{pmatrix}$. Pooling reduces resolution

and gives limited robustness to small shifts within a window. Backward: max pooling routes the gradient to the maximizer; average pooling spreads g/K^2.

Global average pooling. $g_c = \frac{1}{HW}\sum_{i,j} X_{i,j,c}$ maps $H \times W \times C \to C$; a classifier on top needs $Q(C+1)$ instead of $Q(HWC+1)$ parameters. It discards spatial arrangement entirely.

7 Algebraic Facts from Past Exams

Theorem 7.9: positive homogeneity (2024 midterm Q6)

A network built only from bias-free convolutions and linear layers, ReLU, max pooling, reshaping and dropout satisfies $f(\lambda X) = \lambda f(X)$ for all $\lambda \geq 0$.

Proof. Each component is positively homogeneous: linear maps for all λ; $\max(0, \lambda t) = \lambda \max(0, t)$ and $\max_i \lambda x_i = \lambda \max_i x_i$ for $\lambda \geq 0$ (scaling by $\lambda > 0$ preserves order and signs; $\lambda = 0$ is trivial); dropout multiplies by a fixed mask. Compositions of positively homogeneous maps are positively homogeneous: $g_1(g_2(\lambda X)) = g_1(\lambda g_2(X)) = \lambda g_1(g_2(X))$. Biases break the property, e.g. $\mathrm{ReLU}(x+1)$ at $x = 0$. ■

Theorem 7.10: conv–MP–ReLU orders coincide (2022 midterm Q2)

conv→MaxPool→ReLU, conv→ReLU→MaxPool and conv→ReLU→MaxPool→ReLU are the same function.

Proof. For nondecreasing ϕ, $\max_i \phi(x_i) = \phi(\max_i x_i)$: $\phi(x_i) \leq \phi(\max x)$ for all i with equality at the maximizer. ReLU is nondecreasing and elementwise, and max pooling is a windowwise max, so $\mathrm{ReLU} \circ \mathrm{MP} = \mathrm{MP} \circ \mathrm{ReLU}$; finally $\mathrm{ReLU} \circ \mathrm{ReLU} = \mathrm{ReLU}$. (For average pooling only avg ReLU $\geq$ ReLU avg holds, by convexity.) ■

Theorem 7.11: convolutions that implement given maps (2021 midterm Q1, 2022 midterm Q3)

With PyTorch's convention $Y_{o,i,j} = b_o + \sum_c \sum_{k,l=1}^{3} w_{o,c,k,l} \tilde{X}_{c,i+k-2,j+l-2}$ (3×3, padding 1), reading the value at offset $(\Delta i, \Delta j)$ requires a 1 at $(k, l) = (2 + \Delta i, 2 + \Delta j)$.

- Identity $C \to C$: $w_{c,c',k,l} = \delta_{cc'}\delta_{k2}\delta_{l2}$, $\mathbf{b} = \mathbf{0}$.
- Colorwise finite differences $Y_{2c-1} = X_{c,i+1,j} - X_{c,i,j}$, $Y_{2c} = X_{c,i,j+1} - X_{c,i,j}$: $w_{2c-1,c} = \begin{pmatrix} 0 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 1 & 0 \end{pmatrix}$, $w_{2c,c} = \begin{pmatrix} 0 & 0 & 0 \\ 0 & -1 & 1 \\ 0 & 0 & 0 \end{pmatrix}$, all other slices zero; zero padding supplies the out-of-range zeros.

8 Vocabulary and Costs

A network maps an image to class scores and then probabilities, $X \mapsto h(X) \mapsto \mathbf{s}(X) \in \mathbb{R}^Q \mapsto \mathbf{p}(X)$. For a convolution with D filters $K \times K \times C$ producing $H' \times W' \times D$:

$$N_{\text{param}} = D(K^2C + 1), \qquad N_{\text{act}} = H'W'D, \qquad N_{\text{MAC}} \approx H'W'DK^2C.$$

An FC layer $\mathbb{R}^n \to \mathbb{R}^m$ has $m(n+1)$ parameters. Top-1 error asks whether the highest score is correct; top-5 error asks whether the true label is missing from the five highest scores.

9 AlexNet

Five convolutional and three FC layers (eight weight layers):

Stage	Settings	Output
Input	RGB	$227 \times 227 \times 3$
Conv1	96, 11×11, $S = 4$, $P = 0$	$55 \times 55 \times 96$ $\quad((227 - 11)/4 + 1)$
Pool1, Norm1	3×3, $S = 2$; LRN	$27 \times 27 \times 96$
Conv2	256, 5×5, $P = 2$	$27 \times 27 \times 256$
Pool2, Norm2	3×3, $S = 2$; LRN	$13 \times 13 \times 256$
Conv3, Conv4	384, 3×3, $P = 1$	$13 \times 13 \times 384$
Conv5	256, 3×3, $P = 1$	$13 \times 13 \times 256$
Pool3	3×3, $S = 2$	$6 \times 6 \times 256 = 9216$
FC6, FC7, FC8	$9216 \to 4096 \to 4096 \to 1000$	1000 scores

The FC layers dominate: $4096 \cdot 9217 = 37{,}752{,}832$, $4096 \cdot 4097 = 16{,}781{,}312$, $1000 \cdot 4097 = 4{,}097{,}000$, together 58,631,144 parameters, whereas Conv1 has $96(11^2 \cdot 3 + 1) = 34{,}944$. Design choices:

- **ReLU**: avoids sigmoid/tanh saturation on the positive side.
- **Large first stride**: $227 \to 55$ immediately reduces memory and computation (at the cost of detail).
- **Local response normalization**: $a_{i,j,c} \mapsto a_{i,j,c}/(k + \alpha \sum_{r \in N(c)} a_{i,j,r}^2)^\beta$ normalizes across neighboring channels (not batch normalization).
- **Dropout** 0.5 in the FC layers against overfitting.


10 ZFNet and VGG

ZFNet tunes AlexNet's kernel sizes and strides. VGG uses deeper stacks of small 3×3 convolutions: two stride-1 3×3 layers have a 5×5 receptive field with $18C^2$ weights (versus $25C^2$), three have 7×7 with $27C^2$ (versus $49C^2$), and interleaved ReLUs add nonlinearity. Receptive fields obey $r_\ell = r_{\ell-1} + (K_\ell - 1)j_{\ell-1}$, $j_\ell = S_\ell j_{\ell-1}$.

11 GoogLeNet and the Inception Module

11.1 Naive module

For input $28 \times 28 \times 256$, parallel branches with padding chosen to keep 28×28: 1×1 (128), 3×3 (192), 5×5 (96), 3×3 max pool (stride 1). Channel concatenation gives $128 + 192 + 96 + 256 = 672$ channels. Weights: $256 \cdot 128 + 9 \cdot 256 \cdot 192 + 25 \cdot 256 \cdot 96 = 1{,}089{,}536$.



The naive Inception module: parallel convolutions of several sizes and a pooling branch, concatenated along the depth.

11.2 Bottleneck module

Insert 1×1 reductions to 64 channels before the 3×3 and 5×5 convolutions and after pooling: outputs $128 + 192 + 96 + 64 = 480$ channels and

$$32{,}768 + (16{,}384 + 110{,}592) + (16{,}384 + 153{,}600) + 16{,}384 = 346{,}112 \text{ weights}$$

(about 330k), a 68% reduction.

Theorem 7.12: when a bottleneck saves weights

A direct $K \times K$ map $C \to D$ costs K^2CD; reducing to R channels first costs $CR + K^2RD$. This is cheaper iff $R < \dfrac{K^2CD}{C + K^2D}$ (for $K = 5, C = 256, D = 96$ the threshold is ≈ 231).

The 1×1 convolution is a channel-mixing matrix applied at every position (see above). GoogLeNet stacks such modules (22 weight layers) and replaces the large FC stack by global average pooling plus a final classifier.

11.3 Split–transform–merge (2021 midterm Q5)

A $256 \to 128 \to 128 \to 256$ conv–ReLU block (1×1, 3×3 with padding 1, 1×1, all with biases) has $32{,}896 + 147{,}584 + 33{,}024 = 213{,}504$ parameters. Thirty-two parallel $256 \to 4 \to 4 \to 256$ paths summed at the end have $32(1028 + 148 + 1280) = 78{,}592$ parameters; the 3×3 cost drops by the group factor 32. Implementation: three `nn.ModuleLists` of 32 convolutions, ReLU inside each path, then a sum (equivalently grouped convolutions with `groups=32`).

12 Network in Network: Exact versus Approximate Invariance (2022 midterm Q7)

NiN stacks mlpconv blocks (a spatial convolution followed by 1×1 convolutions, ReLUs, 3×3 stride-2 max pooling with ceil mode, dropout) and ends with average pooling over the final $8 \times 8 \times 10$ map. Take X with a single 1 at $(j, k) = (19, 19)$ and $\tilde{X}$ the same shifted to $(23, 19)$ (0-based, no biases, eval mode). Tracking where outputs can be nonzero: bias-free layers map zeros to zeros; a $K \times K$ convolution with padding $(K-1)/2$ widens the support by $(K-1)/2$; 1×1 convolutions and ReLU keep it; pool output p sees rows $2p, 2p+1, 2p+2$.

	rows for X	rows for $\tilde{X}$
conv1 (5×5)	17–21	21–25
out1 (16×16)	8–10	10–12
conv2 (5×5)	6–12	8–14
out2 (8×8)	2–6	3–7
out3 (3×3 conv)	1–7	2–8, truncated to 2–7

Columns stay 8–10, 2–6, 1–7. The shift 4 is a multiple of the total stride 4, so out1 is exactly shifted by 2 and out2 by 1; then out3 of $\tilde{X}$ equals out3 of X shifted down one row, except that row 7 of X's map would land on row 8, outside the 8×8 map. Hence the averaged outputs differ exactly by $\frac{1}{64}\sum_k \text{out3}(X)_{c,7,k}$: approximately equal, but not exactly equal in general.


13 Why Depth Can Fail, and Residual Networks

Deeper plain networks can have *higher training error*: this is not overfitting but an optimization (degradation) problem. A deeper network that can represent identity layers contains the shallower one, so its *optimal* training loss is not worse, yet gradient methods may not find it. For $\mathbf{x}_{\ell+1} = f_\ell(\mathbf{x}_\ell)$, $\nabla_{\mathbf{x}_0} L = J_0^\top \cdots J_{L-1}^\top \nabla_{\mathbf{x}_L} L$; if every Jacobian has norm at most $\rho < 1$ the gradient shrinks like ρ^L ($0.9^{50} \approx 0.005$).

Theorem 7.13: residual block

$\mathbf{y} = \mathbf{x} + F(\mathbf{x}; \boldsymbol{\theta})$ gives $\dfrac{\partial \mathbf{y}}{\partial \mathbf{x}} = \mathbf{I} + J_F(\mathbf{x})$ and $\nabla_{\mathbf{x}} L = \mathbf{g} + J_F^\top \mathbf{g}$ with $\mathbf{g} = \nabla_{\mathbf{y}} L$.

The identity path carries the gradient even when J_F is small, and the block can represent the identity by $F = 0$: the network learns a residual $F = H - \mathrm{id}$ rather than the whole map H. This is a reparametrization, not a guarantee (e.g. $J_F = -\mathbf{I}$ cancels the gradient; a ReLU after the sum alters the identity). If shapes differ, use a projection shortcut $\mathbf{y} = P(\mathbf{x}) + F(\mathbf{x})$ (e.g. a 1×1 or strided convolution). Unlike Inception's concatenation, residual addition keeps the channel count. A bottleneck block $256 \to 64 \to 64 \to 256$ (1×1, 3×3, 1×1) has $2 \cdot 256 \cdot 64 + 9 \cdot 64^2 = 69{,}632$ weights versus $18 \cdot 256^2 = 1{,}179{,}648$ for two full-width 3×3 layers. In the CIFAR-10 plots, residual networks remove the training-error degradation seen in plain networks. The full backpropagation formulas for a residual MLP are derived in Chapter 5 (2021 midterm Q7).



A residual block learns $F(\mathbf{x}) = H(\mathbf{x}) - \mathbf{x}$; with $F = 0$ it is the identity, and gradients pass through the shortcut.

14 Saliency Maps

To see which pixels a prediction is sensitive to, differentiate the selected class score with respect to the input (not the weights):

$$G_{i,j,k} = \frac{\partial s_c(X)}{\partial X_{i,j,k}}, \qquad M_{i,j} = \max_k |G_{i,j,k}|.$$

By Taylor's theorem $s_c(X + \Delta X) \approx s_c(X) + \langle \nabla_X s_c(X), \Delta X \rangle$: a large $|G|$ means a small change of that pixel changes the score a lot, and the sign says in which direction. For $s(\mathbf{x}) = 2x_1 - 3x_2 + 0.1x_3$, the gradient $(2, -3, 0.1)$ ranks x_2 first. Saliency is local sensitivity, not a complete causal explanation.