

Assignment 8-5 Integer Subtraction 4

You are given two positive integers a and b . The problem is to subtract b from a . ($b \leq a < 10^{250}$)

Input

The input consists of t ($30 \leq t \leq 40$) test cases. The first line of the input contains only positive integer t . Then t test cases follow. Each test case consists of two lines which give the two positive integers a and b ($b \leq a < 10^{250}$), respectively.

Output

For each test case, you are to output a single line containing the difference $a - b$.

Sample Input

```
2
12345
12311
12345
12345
```

Sample Output

```
34
0
```

Part of the program

You are required to write the function subtraction to complete the following program which solves this problem. In your program, you cannot declare global variables or static arrays.

```
#include <iostream>
#include <cstring>
using namespace::std;

class HugeInt
{
public:
    int size;
    int *digit;

    // returns true if and only if hugeInt1 == hugeInt2
    bool equal( HugeInt hugeInt2 );

    // difference = minuend - subtrahend provided that minuend >= subtrahend
    void subtraction( HugeInt subtrahend, HugeInt &difference );
};
```

```

int main()
{
    char strA[ 251 ], strB[ 251 ];

    int T;
    cin >> T;
    for( int t = 0; t < T; ++t )
    {
        cin >> strA >> strB;

        HugeInt minuend;
        minuend.size = strlen( strA );
        minuend.digit = new int[ minuend.size ];
        for( int i = 0; i < minuend.size; ++i )
            minuend.digit[ i ] = strA[ minuend.size - 1 - i ] - '0';

        HugeInt subtrahend;
        subtrahend.size = strlen( strB );
        subtrahend.digit = new int[ subtrahend.size ];
        for( int i = 0; i < subtrahend.size; ++i )
            subtrahend.digit[ i ] = strB[ subtrahend.size - 1 - i ] - '0';

        HugeInt difference;
        minuend.subtraction( subtrahend, difference );

        for( int i = difference.size - 1; i >= 0; i-- )
            cout << difference.digit[ i ];
        cout << endl;

        delete[] minuend.digit;
        delete[] subtrahend.digit;
        delete[] difference.digit;
    }
}

// returns true if and only if hugeInt1 == hugeInt2
bool HugeInt::equal( HugeInt hugeInt2 )
{
    if( size != hugeInt2.size )
        return false;

    for( int i = 0; i < size; i++ )
        if( digit[ i ] != hugeInt2.digit[ i ] )
            return false;

    return true;
}

// difference = minuend - subtrahend provided that minuend >= subtrahend
void HugeInt::subtraction( HugeInt subtrahend, HugeInt &difference )
{
    if( equal( subtrahend ) )
    {
        difference.size = 1;
        difference.digit = new int[ 1 ];
        difference.digit[ 0 ] = 0;
        return;
    }
}

}

```