C++ IO support for various FEM exchange file formats

Berthold Höllmann

October 11, 2017

Contents

1	Sup	e formats		1		
	1.1	NAST	RAN Bull	lk Data Format (BDF)		
		1.1.1	BDF Ca	ards supported		
			1.1.1.1	Bulk Data		
			1.1.1.2	Header Data		2
	1.2	DNV	GL Seasaı	ım Input Interface File (FEM)		3
		1.2.1	FEM Ca	ards supported		3
		1.2.2	Elemen	nt Types in SESAM		2

1 Supported FEM file formats

Not all functionality defined for the exchange file formats is supported. The supported subset is currently mainly defined by the functionality supported in GLFrame rspt. the BMF file format.

More detailed information on supported functionality can be found in the according directories in the docs subdirectory.

1.1 NASTRAN Bulk Data Format (BDF)

1.1.1 BDF Cards supported

1.1.1.1 Bulk Data

	Name	Description	Read	Write
General				
	MAT1	Material definition	✓	✓
	MAT2	Shell Element Anisotropic Material Property Definition	✓	✓
	GRID	Grid nodes	✓	✓
Element	ts			
	CTRIA3	3 node shaped shell elements	✓	✓
	CQUAD4	4 node shaped shell elements	✓	✓
	CBEAM	Complex beams ¹	✓	✓
	CBAR	Simple beams	✓	✓
	CROD	Trusses	✓	✓
	CBUSH	Generalized Spring-and-Damper Connection	X	✓
Element	properties			
	PSHELL	Properties for CTRIA3, and CQUAD4	✓	✓
	PBEAM	Integral properties for CBEAM	✓	✓
	PBEAML	Properties for CBEAM describing cross section	✓	✓
	PBAR	Integral properties for CBAR	✓	✓
	PBARL	Properties for CBAR describing cross section	1	✓
	PROD	Properties for CROD	1	✓
	PBUSH	Generalized Spring-and-Damper Property	X	✓
Load		<u> </u>		
	LOAD	Load case combination	✓	✓
	FORCE	Forces on Nodes	✓	✓
	MOMENT	Moments on Nodes	1	✓
	CMASS2	Scalar Mass Property and Connection	1	1
	CMASS4	Scalar Mass Property and Connection to Scalar Points Only	1	1
	GRAV	Acceleration or Gravity Load	✓	✓
Misc				
	ENDDATA	Marker for end of input file	✓	✓
	PARAM	Specifies values for parameters used in solution sequences or user written DMAP programs.	✓	✓

1.1.1.2 Header Data

Name	Description	Read	Write
SOL	Execute a Solution Sequence	Х	✓
CEND	End of Executive Control Delimiter	X	✓
TITLE	Output Title	X	✓
ECH0	Bulk Data Echo Request	X	✓
DISPLACEMENT	Displacement Output Request	X	✓
SPCFORCES	Single-Point Forces of Constraint Output Request	X	✓
STRESS	Element Stress Output Request	X	✓
LOAD	External Static Load Set Selection	X	✓
SUBTITLE	Output Subtitle	X	✓
SUBCASE	Subcase Delimiter	X	✓
BEGIN BULK	Case Control and Bulk Data Delimiter	×	✓

 $^{^{1}}$ Twisting CBEAM cross section by using the BIT flag is not supported. Offset via OFFT is only supported for the same offset at A and B end of beam.

1.2 DNV GL Seasam Input Interface File (FEM)

1.2.1 FEM Cards supported

	Name	Description	Read	Write	Page ²
General					
	DATE	Date and Program Information	✓	✓	4-2
	GCOORD	Nodal Coordinates	✓	✓	6-56
	GNODE	Correspondence between External and Internal	1	✓	6-80
		Node Numbering, and Number of Degrees of			
	IDENT	Freedom of Each Node Identification of Superelements	/	/	4-9
	IEND	End of a Superelement	/	✓	4-3 4-4
Element		End of a superelement		· ·	4-4
Element	.s GELMNT1	Element Data Definition	/	/	6-65
	GELREF1	Reference to Element Data	/	/	6-66
Floment	properties	Reference to Element Data	•	•	0-00
Element	GBEAMG	General Beam Element Data	/	/	6-49
	GBARM	Cross Section Type Massive Bar	/	/	6-48
	GIORH	Cross Section Type I or H Beam	/	/	6-71
	GLSEC	Cross Section Type L-Section	/	/	6-76
	GPIPE	Cross Section Type Tube	/	/	6-81
	GUSYI	Cross Section Type Unsymmetrical I-Beam	/	/	6-93
	GECCEN	Eccentricities	/	/	6-61
	BELFIX	Flexible Joint/Hinge	/	/	6-8
	GELTH	Thickness of Two-dimensional Elements	/	/	6-70
Load	OLLIII	Thickness of Two-dimensional Elements	•	•	0-/0
Loau	BLDEP	Nodes with Linear Dependence	/	/	6-27
	BNBCD	Nodes with Boundary Conditions	/	/	6-30
	BNDISPL	Nodes with Prescribed Displacements and Accel-	/	/	6-31
	DNDISIE	erations	•	•	0 31
	BNLOAD	Nodes with Loads	✓	✓	6-35
	MGSPRNG	Element to Ground	✓	✓	6-103
	TDLOAD	not documented (Seems to be similar to TD-	✓	✓	
	BEUSLO	MATER or TDSETNAM) Elements with Surface Loads	/	1	6-21
Superel.					
	BSELL	Subelement Load Description	/	/	7-27
	GELMNT2	Subelement Description with Simple Correspon-	/	✓	7-31
		dence			, 0
	HSUPSTAT	Superelement Statistical Information	✓	✓	7-40
	HSUPTRAN	Superelement Transformations	✓	✓	7-41
	HIERARCH	Superelement Hierarchy Description	✓	✓	7-38
	TDSUPNAM	Name and Description of a Super-Element.	✓	✓	4-8
Misc					
	GSETMEMB	Set (group) of Nodes or Elements (Members)	✓	✓	6-84
	GUNIVEC	Specification of Local Element Coordinate System	✓	✓	6-92
	MISOSEL	Isotropy, Linear Elastic Structural Analysis	✓	✓	6-115
	MORSMEL	Anisotropy, Linear Elastic Structural Analysis, 2-	✓	✓	6-117
		D Membrane Elements and 2-D Thin Shell Ele-			
	TDCETNAM	ments Name and Description of a Set (group)	,	,	4 =
	TDSETNAM	Name and Description of a Set (group) User supplied Text	/	<i>\</i>	4-7
	TEXT	Osei supplieu text	✓	1	4-10

1.2.2 Element Types in SESAM

Conventions for use of the interface file for the elements in SESAM are defined here. Other element types may be introduced for use in other programs.

The table below contains element type numbers already reserved. (Not all of them are included in SESAM).

For ADVANCE, the element types listed are those available from the SESAM preprocessors. In addition to that ADVANCE has a lot of other element types.

Table 1: List of existing Element Types

Typ ³	Name	N.4	Table 1: List of existing El Description of Element	Ref.	5	6	7	8	9	Other ¹⁰
1	11001110		Not yet defined							
2	BEPS	2	2-D, 2 Node Beam	3, 5	/			/		
3	CSTA	3	Plane Constant Strain Trian-	2, 4		/	/	/		
3	33.7.	5	gle	-, -						
4			Not yet defined	3						
5	RPBQ	4	Rectangular Plate. Bending	3						
		_	Modes							
6	ILST	6	Plane Lin. Strain Triangle	2		/	/			
7	T00F	0	Not yet defined			,	,			
8	IQQE	8	Plane Quadrilateral Mem-	2		1	/			
9	LQUA	4	brane Element Plane Quadrilateral Mem-	2,4		1	1	/		
		'	brane Element	-, I						
10	TESS	2	Truss Element	2,4	1	1	1	1	1	
11	GMAS	1	1-Noded Mass-Matrix			1	1		X	
12	GLMA	2	2-Noded Mass-Matrix				1			
13	GLDA	2	2-Noded Damping-Matrix							
14			Not yet defined							
15	BEAS	2	3-D, 2 Node Beam	2, 4	/	/	/		1	FR, LA,
										PL, PR,
16	AXIS	2	Axial Spring		/			/ 19	X	WA FR
17	AXDA	2	Axial Damper		/	1	1		X	110
18	GSPR	1	Spring to Ground	4	1	1	1	1	X	FR
19	GDAM	1	Damper to Ground	'	1	/	/		X	
20	IHEX	20	Isoparametric Hexahedron	2		1	1	1		FR
21	LHEX	8	Linear Hexahedron	2, 4		1	/	✓		FR
22	SECB	3	Subparametric Curved Beam	2						
23	BTSS	3	General Curved Beam	2		1	1			PL, PR
24	FQUS	4	Flat Quadrilateral Thin Shell	4		✓	✓		1	PL, PR
24	FFQ	4	Free Formulation Quadrilat-	5				1		
	ETDC	_	eral Shell			,	,		,	DI
25	FTRS	3	Flat Triangular Thin Shell	4		•	•		•	PL
25	FFTR	3	Free Formulation Triangular Shell	5				•		
26	SCTS	6	Subparametric Curved Trian-	2		1	1			PL
		-	gular Thick Shell	_						
27	MCTS	6	Subparametric Curved Trian-	2^{20}		1	1			
			gular Thick Sandwich Ele-							
			ment							

Continued on next page

 $^{^2}$ References page in "Technical Report: Sesam Input Interface File, File Description", Document id: 89-7012, Revision Number 9 / 01

Continued from previous page

Гур ¹¹	nued from Name	N. ¹²	Description of Element	Ref.	13	14	15	16	17	Other ¹⁸
28	SCQS	8	Subparametric Curved	2			✓			PL, PR
_0	Jugu	Ü	Quadrilateral Thick Shell	_						1 12, 1 10
29	MCQS	8	Subparam. Curved Quadr.	2^{12}		/	/			
-/			Thick Sandwich Elem.							
30	IPRI	15	Isoparametric Triangular	2		1	✓	✓		
			Prism							
31	ITET	10	Isoparametric Tetrahedron	2			/			
32	TPRI	6	Triangular Prism	2, 4		1	1	✓		
33	TETR	4	Tetrahedron	2			✓			
34	LCTS	6	Subparam. Layered Curved	2^{12}		1	✓			
			Triangular Thick Shell							
35	LCQS	8	Subparam. Layered Curved	2^{12}		✓	✓			
			Quadrilat. Thick Shell							
36	TRS1	18	2nd Order Hexahed. Transi-	6			✓			PR
			tion Elem., Solid / Shell							
37	TRS2	15	2nd Order Hexahed. Transi-	6			/			PR
			tion Elem., Solid / Shell							
38	TRS3	12	2nd Order Hexahed. Transi-	6			/			PR
			tion Elem., Solid / Shell							
39			Not yet defined							
40	GLSH	2	General Spring / Shim Ele-	21	/		/		X	
4.4	AVCC	0	ment			,	,	,		
41	AXCS	3	Axisymmetric Constant	7, 5		•	•	/		
40	AXLQ	4	Strain Triangle			,	/	/		
42	1	4	Axisymmetric Quadrilateral	7, 5		,	,	•		
43	AXLS	6	Axisymmetric Linear Strain	7		•	•			
4.4	4400	8	Triangle	-		,	/			
44	AXQQ	0	Axisymmetric Linear Strain	7		•	•			
45	PILS	1	Quadrilateral Pile / Soil	4	/			/		
45 46	PCAB	2	Plane Cable-Bar Element	4	/			/		
46	PSPR			4	/			,		
47	PSPK	1	Plane Spring Element	4	*			,		
48		4	4-node Contact Element with	4				•		
40		0	triangular Shape 2-Noded Link Element	4				/		
49		2		4				•		
50	CTCD	0	Not yet defined							
51	CTCP	2	2-Noded Contact Element							
52	CTCL	4	4-Noded Contact Element							
53	CTAL	4	4-Noded Axisymmetric Con-							
54	стсс	6	tact Element 6-Noded Contact Element							
	CTAQ	6	6-Noded (3+3) Axisymmetric			/				
55	CIAQ	U	Contact Element			•				
56	CTLQ	8	8-Noded (4+4) Contact Ele-	8, 9						PR
0-			ment	-, ,						
57	CTCQ	16	16-Noded (8+8) Contact Ele-	8, 9		1				PR
		_	ment	-						
58	CTMQ	18	18-Noded (9+9) Contact Ele-	8, 9						PR
5 0			ment							
59			Not yet defined							
60	11000	_	Not yet defined							DD
61 62	HCQS	9	9-Noded Shell Element			/				PR
60	I		Not yet defined							

Continued on next page

Continued from previous page

Typ ¹¹	Name	N. ¹²	Description of Element	Ref.	13	14	15	16	17	Other ¹⁸
63			Not yet defined							
64			Not yet defined							
65			Not yet defined							
66	SLQS	8	Semiloof Quadrilateral							
67	SLTS	6	Curved Thin Shell (32 d.o.fs) Semiloof Triangular Curved Thin Shell (24 d.o.fs)							
68	SLCB	3	Semiloof Curved Beam (11							
69 70	MATR	n	d.o.fs) Not yet defined General Matrix Element with arbitrary no. of nodes (n)					1		SP
100	GHEX	21	General Hexahedron				1			
163	GHEX	27	General Hexahedron				1			

³ELTYP

⁴Number of nodes

⁵Indcluded in program PREFRAME

⁶Included in program PREFEM

⁷Included in program SESTRA

⁸Included in program ADVANCE

⁹Included in program Poseidon

 ¹⁰ FR = FRAMEWORK, LA = LAUNCH, PL = PLATEWORK, PR = PRETUBE, SP = SPLICE, WD = WADAM, WJ = WAJAC
 ¹¹Temporarily ADVANCE interprets Axisl Spring as link element, ignoring the material reference. The 6 matrix numbers are given in direct input to ADVANCE.

¹²The element subroutines are the same as for the subparametric curved thick shells (SCQS and SCTS).

¹³As General Spring it is just a 2-noded spring (12x12 matrix) which may be in a local coordinate system. As a shim element the preprocessor(s) will only insert stiffness in the local x- and y-direction. In the analysis program(s), shim members and general springs are treated exactly in the same manner.