Person							
Ssn	age	gender	firstName	lastName	Gld		
		1 -	-	1			
Company				1			
<u>cName</u>		cAddress	cAddress		Gld		
Guest							
<u>Gld</u>	guestT	ype OrdId	VId		status		
注:Guest 的 Gym	I union type 的	的实现方式是 surro	gate key.				
<u>FacilityId</u>			type				
ChessRoom							
<u>FacilityId</u>			size				
<u>FacilityId</u>			size				
			size				
Facility FacilityId	勺 union type F	ServiceId 的实现方式是 inhe		Session			
Facility <u>FacilityId</u> 注:Facility f	勺 union type l	的实现方式是 inhe					
Facility <u>FacilityId</u> 注:Facility É	灯 union type [Session	ne		
Facility FacilityId 注:Facility 自 Food FoodId		的实现方式是 inhe	eit the same key.	deliveredTir			
Facility FacilityId 注:Facility 自 Food FoodId		的实现方式是 inhe	eit the same key.	deliveredTir			
Facility FacilityId 注:Facility 的 Food FoodId 注:Specializ Service ServiceId	ation Food & 1	的实现方式是 inhe	走 a. Multiple R	deliveredTir			
Facility FacilityId 注:Facility 的 Food FoodId 注:Specializ Service ServiceId	ation Food & 1	的实现方式是 inhe ServiceId aculity 的实现方式	走 a. Multiple R	deliveredTir			
Facility FacilityId 注:Facility 的 Food FoodId 注:Specializ Service ServiceId	ation Food & 1	的实现方式是 inhe ServiceId aculity 的实现方式	走 a. Multiple R	deliveredTir			
Facility FacilityId 注:Facility 的 Food FoodId 注:Specializ Service ServiceId 注:Relation: RoomId	ation Food & r ship Orders 的 available ation BigRoom	的实现方式是 inhe service defined s	就是 a. Multiple R RoomId gn key. BigFlag	deliveredTir elations – supe DoubleFlag	rclass and subclas		
Facility FacilityId 注:Facility 的 Food FoodId 注:Specializ Service ServiceId 注:Relation RoomId 注:Specializ	ation Food & r ship Orders 的 available ation BigRoom attributes.	的实现方式是 inhe service described serviced service described service	就是 a. Multiple R RoomId gn key. BigFlag	deliveredTir elations – supe DoubleFlag	SingleFlag		

password

Employee <u>UserId</u> 注: Specialization User 的实现方式是 b. Multiple relations – subclass relations only.

Bill

	<u>Gld</u>	Billic	1	ResId	Eld	payDate	total	

注: weak entity 继承了 owner entity 的 primary key – Gid.

Pays

Gld BillId

注:Relationship pays 的实现方式是 Relationship relation.

Contact

<u>GId</u> <u>telNo</u>

注: telNo 是 Multivalue attribute.

Reserve

注: Reserve 是 3-ary relationship. 实现方式是 Relationship relation.