

- This lab will cover Stacks and Queues.
 - It is assumed that you have reviewed chapters 6 of the textbook. You may want to refer to the text and your lecture notes during the lab as you solve the problems.
 - When approaching the problems, think before you code. Doing so is good practice and can help you lay out possible solutions.
 - Think of any possible test cases that can potentially cause your solution to fail!
 - You must stay for the duration of the lab. If you finish early, you may help other students. If you don't finish by the end of the lab, we recommend you complete it on your own time. Ideally you should not spend more time than suggested for each problem.
 - Your TAs are available to answer questions in lab, during office hours, and on Piazza.
-

Vitamins (35 minutes)

1. What is the output of the following code?

```
s = ArrayStack()
i = 2

s.push(1)
s.push(2)
s.push(4)
s.push(8)

i += s.top()
s.push(i)
s.pop()
s.pop()
print(i)
print(s.top())
```

2. Trace the following function with different list inputs. Describe what the function does, and give a meaningful name to the function:

```
def mystery(lst):
    s = ArrayStack()
    for i in range(len(lst)):
        s.push(lst.pop())
    for i in range(len(s)):
        lst.append(s.pop())
```

3. Trace the following function, which takes in a stack of integers. Describe what the function does, and give a meaningful name to the function:

```
def mystery(s):
    if len(s) == 1:
        return s.top()
    else:
        val = s.pop()
        result = mystery(s)

        if val < result:
            result = val
        s.push(val)
        return result
```

4. Fill out the prefix, infix, postfix table below:

| Prefix | Infix | Postfix | Value |
|---------------|-----------------------|----------------|-------|
| - * 3 4 10 | 3 * 4 - 10 | | 2 |
| | (5 * 5) + (10 / 2) | 5 5 * 10 2 / + | 30 |
| | | 10 2 - 4 / 8 + | |
| + * 6 3 * 8 4 | | | |
| | (8 * 2) + 4 - (3 + 6) | | |

5. What is the output of the following code?

```
q = ArrayQueue()
i = 2

q.enqueue(1)
q.enqueue(2)
q.enqueue(4)
q.enqueue(8)

i += q.first()
q.enqueue(i)
```

```
q.dequeue()
q.dequeue()
print(i)
print(q.first())
```

6. Describe what the following function does and give it an appropriate name. Trace the function with a queue of integers.

```
def mystery(q):
    if (q.is_empty()):
        return

    else:
        val = q.dequeue()
        mystery(q)
        if val % 2 != 0:
            q.enqueue(val)
```

7. Trace the following function with different string inputs. Describe what the function does, and give a meaningful name to the function:

```
def mystery(input_str):
    s = ArrayStack()
    q = ArrayQueue()

    for char in input_str:
        s.push(char)
        q.enqueue(char)

    while not s.is_empty():
        if s.pop() != q.dequeue():
            return False

    return True
```

Coding

In this section, it is strongly recommended that you solve the problem on paper before writing code. Note that you should not access the underlying list in the ArrayStack implementation. **Treat it as a black box and only use the len, is_empty, push, top, and pop methods.**

Download the **ArrayStack.py** & **ArrayList.py** files under Resources/Labs on NYU Classes

Note: import the class like so → `from ArrayStack import *`

1. Write a **recursive function** that takes in a Stack of integers and returns the sum of all values in the stack. Do not use any helper functions or change the function signature. Note that the stack should be restored to its original state if you pop from the stack.

ex) s contains [1, -14, 5, 6, -7, 9, 10, -5, -8] from top → bottom.
stack_sum(s) returns -3

```
def stack_sum(s):  
    """  
    : s type: ArrayStack  
    : return type: int  
    """
```

Hint: See how the stack is restored in the code snippet from vitamins question 3.

2. Create an **iterative function** that evaluates a valid prefix string expression. You may only use **one ArrayStack** as an additional data structure to the given setup. Do not use any helper functions or change the function signature.

In addition, each character is separated by one white space and numbers may have more than one digit. Therefore, we will use the split function to create a new list of each substring of the string separated by a white space. You may assume all numbers will be positive.

ex) exp_str is "- + * 16 5 * 8 4 20"

exp_lst = exp.split(" ") → ["-", "+", "*", "16", "5", "*", "8", "4", "20"]

eval_prefix(exp_str) returns = 92

```
def eval_prefix(exp_str):  
    """  
    : exp type: str  
    : return type: int  
    """  
    exp_lst = exp_str.split( )
```

Hint:

To check if a string contains digits, use `.isdigit()`.

To check if a string is an operator, you may want to do `if char in "-+/*"` similarly to how you checked for vowels.

As you parse the expression lst, think about when you would push/pop the operator or number to/from the stack. Try to trace this execution on paper first before writing your code.

Test your code with the various prefix expressions from the Vitamins q4.

3. Write an **iterative function** that flattens a nested list while retaining the left to right ordering of its values using one **ArrayStack** and its defined methods. That is, you should not directly access the underlying array in the implementation. Do not use any helper functions or change the function signature.
(30 minutes)

In addition, do not create any other data structure other than the ArrayStack.

ex) `lst = [[[0]], [1, 2], 3, [4, [5, 6, [7]], 8], 9]`
`flatten_list(lst)`
`print(lst) → lst = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`

```
def flatten_list(lst):  
    """  
    : lst type: list  
    : return type: None  
    """  
    s = ArrayStack()
```

Hint: You may want to traverse the list from the end for 2 reasons: pop and append has an amortized cost of $O(1)$ and a stack reverses the collection order because of FIFO.

4. OPTIONAL

Write an **iterative function** that will sort a stack of unsorted integers. You are **only allowed to use another stack** and no other additional data structure for your solution. Do not use any helper functions or change the function signature.

A sorted stack is determined if its values are in ascending order from top to bottom. Smallest on top, largest on bottom.

The **runtime** of the function should be **quadratic**.

```
def stack_sort(s):  
    """  
    : input_str type: ArrayStack  
    : return type: None  
    """  
  
    #use this to help with sorting  
  
    helper_stack = ArrayStack( )
```