

1.

```
double longitude = -6.2546;
double latitude = 53.3438;
double radius = 1.3;
String type = "\"flood\"";
int lvl = 1;
int people = 123;
int startTime = 1581007055;
int endTime = 0;
```

```
String id=reportDisaster(longitude, latitude, radius, type, lvl, people, startTime,
endTime);
return (String)id;
```

2.

```
String id2="\"1136AFC576003000\"";
String assembly_lat = "\"53.3540786\"";
String assembly_ln = "\" -6.259978\"";
set_assemblyPoint(id2,assembly_lat,assembly_ln);
```

No return

3.

```
String all_dis=get_all_disasters();
这是个 Json 形式的 String
```

//parseJSONWithJSONObject(all\_dis); 可以以 disaster Id 为 key, disaster info 为 value  
//parseJSONWithJSONObject2(all\_dis); 细分 value 里对应的 key value

```
036      "people": 123,
037      "radius": 1.3,
038      "req_route": "",
039      "start_time": 1587597795,
040      "type": "flood"
041    },
042    "1163EB46AD802000": {
043      "assembly_lat": 0,
044      "assembly_ln": 0,
045      "end_time": 0,
046      "latitude": 53.3438,
047      "longitude": -66.2546,
048      "lvl": 1,
049      "people": 123,
050      "radius": 1.3,
051      "req_route": "",
052      "start_time": 1587598204,
053      "type": "flood"
054    },
055    "1163EBAD6A403000": {
056      "assembly_lat": 0,
057      "assembly_ln": 0,
058      "end_time": 0,
059      "latitude": 53.3438,
060      "longitude": -66.2546,
061      "lvl": 1,
062      "people": 123,
063      "radius": 1.3,
064      "req_route": "",
065      "start_time": 1587598309,
066      "type": "flood"
067    }
068  }
```

截图示例

4.  
String id\_finish="\1136AFC576003000\"";  
finsih\_disaster(id\_finish);

No return

5.  
String query\_dis=query\_disaster();  
Same as example 3

截图示例

```
1  {
2      "113649C3CA401000": {
3          "des_lat": 53.3438,
4          "des_ln": -6.2546,
5          "disaster_id": "1136AFC576003000",
6          "latitude": 0,
7          "longitude": 0,
8          "type": 2
9      },
0      "1136AD8E18802000": {
1          "des_lat": 53.3438,
2          "des_ln": -6.2546,
3          "disaster_id": "1136AFC576003000",
4          "latitude": 53.3438,
5          "longitude": 6.259978,
6          "type": 2
7      },
8      "1136ADD7EAC03000": {
9          "des_lat": 53.3438,
0          "des_ln": -6.2546,
1          "disaster_id": "1136AFC576003000",
2          "latitude": 0,
3          "longitude": 0,
4          "type": 2
5      },
6  }
```

6.  
String query\_freeVehicles=query\_free\_vehicles();  
Same as example 3

截图示例

```
1  {
2      "0": 47
3  }
```

7.  
String id\_dispatch="1136AFC576003000";  
int vehicle0=1;//vehicle type:vehicle0, vehicle1  
int vehicle2=2;  
String dispatch\_result=dispatch\_vehicles(id\_dispatch,vehicle0,vehicle2);  
Return fine(successful)