

Contents

1 Basis	1	4.7 Floyd-Warshall Algorithm	5
1.1 Default Code	1	4.8 Maximum Clique	5
1.2 Some Useful Primes	1	4.9 Kosaraju's Algorithm for SCC	6
1.3 隨機 & MT19937	1		
2 Data Structures	1	5 Tree Algorithms	6
2.1 Disjoint Set (Union-Find)	1	5.1 Lowest Common Ancestor	6
2.2 Binary Indexed Tree	1	5.2 Euler Tour for LCA	6
2.3 Segment Tree	1	5.3 DSU on Tree	7
3 Mathematics	2	6 String Algorithms	7
3.1 公式們	2	6.1 Suffix Array (SAIS)	7
3.2 階乘 & 模逆元	2	6.2 Z-algorithm	7
3.3 GCD and LCM	2	6.3 Knuth-Morris-Pratt Algorithm	8
3.4 EXGCD	2	6.4 Manacher's Algorithm	8
3.5 Fast Power	2	6.5 Minimum Rotation	8
3.6 FFT	2	6.6 Rolling Hash	8
3.7 質數表	3	7 Geometry	8
3.8 歐拉函數	3	7.1 Basic Geometry Structure	8
3.9 Miller-Rabin Algorithm	3	7.2 Circle Cover Area	9
3.10 Pollard's Rho Algorithm	3	7.3 Circles' Tangent Lines	9
3.11 約瑟夫問題	3	7.4 Circles' Intersections	10
4 Graph	3	7.5 Convex Hull	10
4.1 Topological Sort	3	7.6 Convex Hull Tricks	10
4.2 Tarjan's Algorithm for BCC	4	7.7 Pick's Theory	10
4.3 Bellmen-Ford Algorithm	4	8 Sorting	11
4.4 Dijkstra's Algorithm	4	8.1 Merge Sort	11
4.5 Dinic's Algorithm for Maximum Flow	4	8.2 Quick Sort	11
4.6 Dominator Tree	5	9 Miscellaneous	11
		9.1 Discretization	11
		9.2 Blessing	11
		9.3 Graph Paper	12

1 Basis

1.1 Default Code

```
#include <bits/stdc++.h>
#define ll long long
#define ld long double
#define pii pair<int, int>
#define D double
#define INF 0x7f7f7f7f7f7f7f7f
#define REP(i, n) for (int i = 0; i < n; i++)
#define PB push_back
#define SZ(x) (int)(x).size()
#define all(x) (x).begin(), (x).end()
using namespace std;
const int MXN = 2e6 + 5;
const int MOD = 1e9 + 7;
signed main() {
    ios_base::sync_with_stdio(0), cin.tie(0), cout.tie(0);
    return 0;
}
```

1.2 Some Useful Primes

```
/* 999983, 1097774749, 1076767633, 100102021, 999997771,
 * 1001010013, 1000512343, 987654361, 999991231,
 * 999888733, 98789101, 987777733, 999991921,
 * 1010101333, 1010102101, 1000000000039,
 * 1000000000000037, 2305843009213693951,
 * 4611686018427387847, 9223372036854775783,
 * 18446744073709551557 */
```

1.3 隨機 & MT19937

```
#include <bits/stdc++.h>
using namespace std;
mt19937 gen(/*seed*/ hash<string>("SHIKA"));
chrono::steady_clock::now().time_since_epoch().count();
int randint(int a, int b) { // [a, b]
    return uniform_int_distribution<int>(a, b)(gen);
}
```

2 Data Structures

2.1 Disjoint Set (Union-Find)

```
struct DSU {
    int n;
    vector<int> f, sz;
    DSU(int _n) { // 初始化
        n = _n;
        f.resize(n);
        sz.resize(n);
        for (int i = 0; i < n; i++) {
```

```
f[i] = i;
        sz[i] = 1;
    }
}
int find(int x) { // 返回 x 的根節點
    if (x == f[x])
        return x;
    return f[x] = find(f[x]);
}
void merge(int x, int y) { // 將 x 和 y 合併
    x = find(x), y = find(y);
    if (x == y)
        return;
    if (sz[x] < sz[y]) // 將小的併入大的
        swap(x, y);
    sz[x] += sz[y];
    f[y] = x;
}
};
```

2.2 Binary Indexed Tree

```
#define lowbit(x) (x & -x)
struct BIT {
    int n;
    vector<ll> a;
    BIT(int _n) {
        n = _n;
        a.clear();
        a.resize(n + 1, 0);
    }
    void update(int x, int v) { // 將 x 的值加上 v
        for (; x < a.size(); x += lowbit(x))
            a[x] += v;
    }
    ll query(int x) { // 查詢區間 [1, x] 的總和
        ll ret = 0;
        for (; x; x -= lowbit(x))
            ret += a[x];
        return ret;
    }
    // 查詢區間 [L, r] 的總和
    ll query(int l, int r) { // 大多呼叫這個為主
        return query(r) - query(l - 1);
    }
    int kth(int k) { // 說實話這不常用 有時可以刪掉
        int x = 0;
        for (int i = 1 << __lg(n); i; i >>= 1) {
            if (x + i <= n && k >= a[x + i - 1]) {
                x += i;
                k -= a[x - 1];
            }
        }
        return x;
    }
};
```

2.3 Segment Tree

```
#define cl (i << 1)
#define cr (i << 1 | 1)
#define NO_TAG 0
struct SegmentTree { // 1-base
    int n;
    vector<int> seg, tag;
    SegmentTree(int _n) { // 空的 SegmentTree
        n = _n;
        seg.resize(n * 4);
        tag.resize(n * 4);
    }
    SegmentTree(vector<int>& arr) { // 處理好的 SegmentTree
        n = arr.size();
        seg.resize(n * 4);
        tag.resize(n * 4);
        build(1, 0, n - 1, arr); // kk
    }
    void push(int i, int l, int r) {
        if (tag[i] != NO_TAG) {
            seg[i] += tag[i]; // update by tag
            if (l != r) {
                tag[cl] += tag[i]; // push
                tag[cr] += tag[i]; // push
            }
        }
    }
```

```

    }
    tag[i] = 0;
}
}
void pull(int i, int l, int r) {
    int mid = (l + r) >> 1;
    push(cl, l, mid);
    push(cr, mid + 1, r);
    seg[i] = max(seg[cl], seg[cr]); // pull
}
void build(int i, int l, int r, vector<int>& arr) {
    if (l == r) {
        seg[i] = arr[l]; // set value
        return;
    }
    int mid = (l + r) >> 1;
    build(cl, l, mid, arr);
    build(cr, mid + 1, r, arr);
    pull(i, l, r);
}
void update(int i, int l, int r, int ql, int qr, int v) {
    push(i, l, r);
    if (ql <= l && r <= qr) {
        tag[i] += v;
        return;
    }
    int mid = (l + r) >> 1;
    if (ql <= mid)
        update(cl, l, mid, ql, qr, v);
    if (qr > mid)
        update(cr, mid + 1, r, ql, qr, v);
    pull(i, l, r);
}
int query(int i, int l, int r, int ql, int qr) {
    push(i, l, r);
    if (ql <= l && r <= qr) {
        return seg[i];
    }
    int mid = (l + r) >> 1;
    if (ql <= mid)
        ans = max(ans, query(cl, l, mid, ql, qr));
    if (qr > mid)
        ans = max(ans, query(cr, mid + 1, r, ql, qr));
    return ans;
}
// 區間 [ql, qr] 加值 v
void update(int ql, int qr, int v) {
    update(1, 0, n - 1, ql, qr, v); // kk
}
// 查詢區間 [ql, qr]
int query(int ql, int qr) {
    return query(1, 0, n - 1, ql, qr); // kk
}
// 不知道是 [0, n-1] 還是 [1, n]
};

```

3 Mathematics

3.1 公式們

$$\sum_{k=1}^n n = \frac{n(n+1)}{2}, \quad \sum_{k=1}^n n^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{k=1}^n n^3 = \left[\frac{n(n+1)}{2} \right]^2$$

$$\sum_{k=1}^n n^4 = n(1+n)(1+2n)(-1+3n+3n^2)/30$$

$$\sum_{k=1}^n n^5 = n^2(n+1)^2(2n^2+2n-1)/12$$

$$\text{錯位排列} \quad DP_i = \begin{cases} 0 \vee 1, & i = 1 \vee 2 \\ (i-1)(DP_{i-1} \times DP_{i-2}), & i \geq 3 \\ = iDP_{i-1} + (-1)^i & \text{另一種關係式} \end{cases}$$

$$P_k^n = \frac{n!}{k!(n-k)!}, \quad C_k^n = \frac{n!}{(n-k)!}, \quad H_k^n = C_{n-1}^{n+k-1}$$

$$\pi = \arccos(-1), \quad 0 = e^{i\pi} + 1, \quad pV = nTR$$

$$a^{\varphi(m)} \equiv 1 \pmod{m}$$

$$a^b \equiv a^{b \bmod \varphi(m)-1} \pmod{m}$$

$$\varphi(m) = m - 1, \text{ When } m \text{ is Prime}$$

3.2 階乘 & 模逆元

```

ll fac[MXN], inv[MXN];
void init() {
    fac[0] = 1; // 0! = 1
    for (ll i = 1; i < MXN; i++)
        fac[i] = fac[i - 1] * i % MOD; // n! = n * (n-1)!
    inv[MXN - 1] = power(fac[MXN - 1], MOD - 2);
    for (ll i = MXN - 2; i >= 0; i--)
        inv[i] = inv[i + 1] * (i + 1) % MOD; // (n!)^(-1)
}

```

3.3 GCD and LCM

```

ll gcd(ll a, ll b) {
    if (b && a) // 輾轉先除法 -> 交叉取餘數直到不能再取
        while ((a %= b) && (b %= a)) {}
    return a + b;
}
ll lcm(ll a, ll b) { return a * b * gcd(a, b); }

```

3.4 EXGCD

$$ax + by = \gcd(a, b)$$

```

int exgcd(int a, int b, ll &x, ll &y) {
    if (b == 0) {
        x = 1, y = 0;
        return a;
    }
    int now = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return now;
}

```

3.5 Fast Power

```

ll power(ll x, ll y) {
    ll ret = 1;
    while (y) {
        if (y & 1) (ret *= x) %= MOD;
        (x *= x) %= MOD;
        y >>= 1;
    }
    return ret;
}

```

3.6 FFT

使用前要先跑過 pre_fft(); n 必須是 2^k 。

```

const int MAXN = 262144 << 1; // (must be 2^k)
// before any usage, run pre_fft() first
typedef long double ld;
typedef complex<ld> cplx; // real(), imag()
const ld PI = acos(-1);
const cplx I(0, 1);
cplx omega[MAXN + 1];
void pre_fft() {
    for (int i = 0; i <= MAXN; i++)
        omega[i] = exp(i * 2 * PI / MAXN * I);
}
void fft(int n, cplx a[], bool inv = false) {
    int basic = MAXN / n;
    int theta = basic;
    for (int m = n; m >= 2; m >>= 1) {
        int mh = m >> 1;
        for (int i = 0; i < mh; i++) {
            cplx w = omega[inv ? MAXN - (i * theta % MAXN) : i * theta % MAXN];
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                cplx x = a[j] - a[k];
                a[j] += a[k];
                a[k] = w * x;
            }
        }
        theta = (theta * 2) % MAXN;
    }
    int i = 0;
    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^ k); k >>= 1) {}
        if (j < i) swap(a[i], a[j]);
    }
    if (inv)
        for (i = 0; i < n; i++)
            a[i] /= n;
}

```

```

}
cplx arr[MAXN + 1];
inline void mul(int _n, ll a[], int _m, ll b[],
               ll ans[]) {
    int n = 1, sum = _n + _m - 1;
    while (n < sum)
        n <= 1;
    for (int i = 0; i < n; i++) {
        double x = (i < _n ? a[i] : 0),
               y = (i < _m ? b[i] : 0);
        arr[i] = complex<double>(x + y, x - y);
    }
    fft(n, arr);
    for (int i = 0; i < n; i++)
        arr[i] = arr[i] * arr[i];
    fft(n, arr, true);
    for (int i = 0; i < sum; i++)
        ans[i] = (long long int)(arr[i].real() / 4 + 0.5);
}

```

3.7 質數表

```

// isprime, 最大質因數, 質因數數量
int isPrime[MXN], fac[MXN], num[MXN];
void getPrimes() {
    isPrime[1] = 1, fac[1] = num[1];
    for (int i = 2; i < MXN; ++i) {
        if (isPrime[i]) continue;
        for (int j = i; j < MXN; j += i) {
            if (i != j) isPrime[j] = 1;
            fac[j] = i;
            num[j]++;
        }
    }
}
vector<int> ret; // 質因數分解
void div(int x) {
    for (; x > 1; x /= fac[x])
        ret.push_back(fac[x]);
}

```

3.8 歐拉函數

$\varphi(x)$ = 所有小於等於 x 且和 x 互質的數的數量

```

int phi(int n) { // O(sqrtN)
    int res = n, a = n;
    for (int i = 2; i * i <= a; i++) {
        if (a % i == 0) {
            res = res / i * (i - 1);
            while (a % i == 0)
                a /= i;
        }
    }
    if (a > 1) res = res / a * (a - 1);
    return res;
}

int phi[MXN]; // 建表 最大1e7
void phi_table(int n) {
    phi[1] = 1;
    for (int i = 2; i <= n; ++i) {
        if (phi[i]) continue;
        for (int j = i; j <= n; j += i) {
            if (phi[j] == 0) phi[j] = j;
            phi[j] = phi[j] / i * (i - 1);
        }
    }
}

```

3.9 Miller-Rabin Algorithm

$$\text{Magic} = \begin{cases} \{2, 7, 61\}, & n < 4, 759, 123, 141 \\ \{2, 13, 23, 1662803\}, & n < 1, 122, 004, 669, 633 \\ \{2, 3, 5, 7, 11, 13\}, & n < 3, 474, 749, 660, 383 \\ \{2, 325, 9375, 28178, \\ 450775, 9780504, 1795265022\} & n < 2^{64} \end{cases}$$

```

ll mul(ll x, ll y, ll mod) {
    ll ret = x * y - (ll)((long double)x / mod * y) * mod;
    return ret < 0 ? ret + mod : ret;
    // return x * y % mod; // for __int128
}

```

```

ll magic[] = {}; // 這邊填入要用於測試的數列
ll S = 3; // 測試的數列數字的數量
bool witness(ll a, ll n, ll u, int t) {
    if (!a) return 0;
    ll x = power(a, u, n);
    for (int i = 0; i < t; i++) {
        ll nx = mul(x, x, n);
        if (nx == 1 && x != 1 && x != n - 1) return 1;
        x = nx;
    }
    return x != 1;
}
bool miller_rabin(ll n) {
    int s = S; // magic number size
    // iterate s times of witness on n
    if (n < 2) return false;
    if (!(n & 1)) return (n == 2);

    // 將 n - 1 寫成 u * (2 ^ t) 的形式
    ll u = n - 1;
    int t = 0;
    while (!(u & 1))
        u >>= 1, t++;

    while (s--) {
        ll a = magic[s] % n;
        if (witness(a, n, u, t)) return false;
    }
    return true;
}

```

3.10 Pollard's Rho Algorithm

```

vector<ll> ret;
ll mul(ll x, ll y, ll mod) {
    ll ret = x * y - (ll)((long double)x / mod * y) * mod;
    return ret < 0 ? ret + mod : ret;
    // return x * y % mod; // for __int128
}
ll f(ll x, ll c, ll mod) {
    return (mul(x, x, mod) + c) % mod;
}
ll pollard_rho(ll n) {
    ll c = 1, x = 0, y = 0, p = 2, q, t = 0;
    while (t++ % 128 or gcd(p, n) == 1) {
        if (x == y) c++, y = f(x = 2, c, n);
        if (q = mul(p, abs(x - y), n)) p = q;
        x = f(x, c, n);
        y = f(f(y, c, n), c, n);
    }
    return gcd(p, n);
}
void fact(ll x) { // 透過遞迴找質數
    if (miller_rabin(x)) {
        ret.push_back(x);
        return;
    }
    ll f = pollard_rho(x);
    fact(f);
    fact(x / f);
}

```

3.11 約瑟夫問題

```

int josephus(int n, int m) { // n人每m次
    int ans = 0;
    for (int i = 1; i <= n; ++i)
        ans = (ans + m) % i;
    return ans;
}

```

4 Graph

4.1 Topological Sort

```

vector<int> edge[MAXN], ans;
int deg[MAXN]; // in degree
void topo(int n) { // 1-base
    queue<int> que;
    for (int i = 1; i <= n; i++)
        if (!deg[i])
            que.push(i);
}

```

```

while (!que.empty()) {
    int u = que.front();
    que.pop();
    ans.push_back(u);
    // 結果存 ans
    for (int v : edge[u]) {
        deg[v]--;
        if (!deg[v])
            que.push(v);
    }
}
}

```

4.2 Tarjan's Algorithm for BCC

```

struct BccVertex {
    int n, nScc, step, dfn[MXN], low[MXN];
    vector<int> E[MXN], sccv[MXN];
    int top, stk[MXN];
    void init(int _n) {
        n = _n;
        nScc = step = 0;
        for (int i = 0; i < n; i++)
            E[i].clear();
    }
    void addEdge(int u, int v) {
        E[u].PB(v);
        E[v].PB(u);
    }
    void DFS(int u, int f) {
        dfn[u] = low[u] = step++;
        stk[top++] = u;
        for (auto v : E[u]) {
            if (v == f) continue;
            if (dfn[v] == -1) {
                DFS(v, u);
                low[u] = min(low[u], low[v]);
                if (low[v] >= dfn[u]) {
                    int z;
                    sccv[nScc].clear();
                    do {
                        z = stk[--top];
                        sccv[nScc].PB(z);
                    } while (z != v);
                    sccv[nScc++].PB(u);
                }
            } else low[u] = min(low[u], dfn[v]);
        }
    }
    vector<vector<int>> solve() {
        vector<vector<int>> res;
        for (int i = 0; i < n; i++)
            dfn[i] = low[i] = -1;
        for (int i = 0; i < n; i++)
            if (dfn[i] == -1) {
                top = 0;
                DFS(i, i);
            }
        REP(i, nScc) res.PB(sccv[i]);
        return res;
    }
} graph;

```

4.3 Bellman-Ford Algorithm

```

struct Edge {
    int from, to, weight;
} edge[MAXN];
int dis[MAXN];
void bellman_ford(int n, int m) {
    dis[1] = 0; // 起點的距離一定是 0
    for (int j = 0; j < n - 1; j++) { // n 個節點要跑 n - 1 次
        for (int i = 0; i < m; i++) { // 對於所有邊都嘗試鬆弛
            if (dis[edge[i].to] > dis[edge[i].from] + edge[i].weight)
                dis[edge[i].to] = dis[edge[i].from] + edge[i].weight;
        }
    }
}

```

4.4 Dijkstra's Algorithm

```

vector<pii> vec[N]; // vec[u] = {v, w}: u 為起點 v 為終點 w 為路權
bool vis[N]; // 紀錄該節點是否走過
vector<int> dijkstra(int s) { // 起點
    vector<int> dis(N);
    for (int i = 0; i < N; i++) // 初始化
        dis[i] = INF; // 值要設為比可能的最短路徑權重還要大的值
    dis[s] = 0;
    priority_queue<pii, vector<pii>, greater<pii>> pq; // 以小到大批序
    // {w, v}: w 為路權 v 為節點
    pq.push({dis[s], s});
    while (pq.empty() == 0) {
        int u = pq.top().second;
        pq.pop();
        if (vis[u]) // 走過的不要再走
            continue;
        vis[u] = 1;
        for (auto i : vec[u]) {
            int v = i.first, w = i.second;
            if (dis[u] + w < dis[v]) { // 鬆弛
                dis[v] = dis[u] + w;
                pq.push({dis[v], v});
            }
        }
    }
    return dis;
}

```

4.5 Dinic's Algorithm for Maximum Flow

```

struct Dinic {
    struct Edge {
        int v, f, re;
    };
    int n, s, t, level[MXN];
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t) {
        n = _n;
        s = _s;
        t = _t;
        for (int i = 0; i < n; i++)
            E[i].clear();
    }
    void add_edge(int u, int v, int f) {
        E[u].PB({v, f, SZ(E[v])});
        E[v].PB({u, 0, SZ(E[u]) - 1});
    }
    bool BFS() {
        for (int i = 0; i < n; i++)
            level[i] = -1;
        queue<int> que;
        que.push(s);
        level[s] = 0;
        while (!que.empty()) {
            int u = que.front();
            que.pop();
            for (auto it : E[u]) {
                if (it.f > 0 && level[it.v] == -1) {
                    level[it.v] = level[u] + 1;
                    que.push(it.v);
                }
            }
        }
        return level[t] != -1;
    }
    int DFS(int u, int nf) {
        if (u == t) return nf;
        int res = 0;
        for (auto &it : E[u]) {
            if (it.f > 0 && level[it.v] == level[u] + 1) {
                int tf = DFS(it.v, min(nf, it.f));
                res += tf;
                nf -= tf;
                it.f -= tf;
                E[it.v][it.re].f += tf;
                if (nf == 0) return res;
            }
        }
        return 0;
    }
    if (!res) level[u] = -1;
}

```

```

    return res;
}
int flow(int res = 0) {
    while (BFS())
        res += DFS(s, 2147483647);
    return res;
}
} flow;
/*
    查找二分圖配對點:
    在 add_edge 時寫上 index[u].push_back({v,
    flow.E[u].size()});

    在 flow 完之後寫上這個
    for (int i = 1; i <= n; i++) { // 遍歷所有節點
        for (pair<int, int> j : index[i]) {
            if (flow.E[i][j].second - 1].f == 0)
                cout << i << ' ' << j.first << '\n';
        }
    }
}
*/

```

4.6 Dominator Tree

```

#define REP(i, s, e) for (int i = (s); i <= (e); i++)
#define REPD(i, s, e) for (int i = (s); i >= (e); i--)
struct DominatorTree { // O(N)
    int n, s;
    vector<int> g[MAXN], pred[MAXN];
    vector<int> cov[MAXN];
    int dfn[MAXN], nfd[MAXN], ts;
    int par[MAXN]; // idom[u] s到u的最後一個必經點
    int sdom[MAXN], idom[MAXN];
    int mom[MAXN], mn[MAXN];
    inline bool cmp(int u, int v) {
        return dfn[u] < dfn[v];
    }
    int eval(int u) {
        if (mom[u] == u)
            return u;
        int res = eval(mom[u]);
        if (cmp(sdom[mn[mom[u]]], sdom[mn[u]]))
            mn[u] = mn[mom[u]];
        return mom[u] = res;
    }
    void init(int _n, int _s) {
        ts = 0;
        n = _n;
        s = _s;
        REP(i, 1, n) g[i].clear(), pred[i].clear();
    }
    void addEdge(int u, int v) {
        g[u].push_back(v);
        pred[v].push_back(u);
    }
    void dfs(int u) {
        ts++;
        dfn[u] = ts;
        nfd[ts] = u;
        for (int v : g[u])
            if (dfn[v] == 0) {
                par[v] = u;
                dfs(v);
            }
    }
    void build() {
        REP(i, 1, n) {
            dfn[i] = nfd[i] = 0;
            cov[i].clear();
            mom[i] = mn[i] = sdom[i] = i;
        }
        dfs(s);
        REPD(i, n, 2) {
            int u = nfd[i];
            if (u == 0)
                continue;
            for (int v : pred[u])
                if (dfn[v]) {
                    eval(v);
                    if (cmp(sdom[mn[v]], sdom[u]))
                        sdom[u] = sdom[mn[v]];
                }
            cov[sdom[u]].push_back(u);
        }
    }
}

```

```

        mom[u] = par[u];
        for (int w : cov[par[u]]) {
            eval(w);
            if (cmp(sdom[mn[w]], par[u]))
                idom[w] = mn[w];
            else
                idom[w] = par[u];
        }
        cov[par[u]].clear();
    }
    REP(i, 2, n) {
        int u = nfd[i];
        if (u == 0)
            continue;
        if (idom[u] != sdom[u])
            idom[u] = idom[idom[u]];
    }
} domT;

```

4.7 Floyd-Warshall Algorithm

```

int dis[N][N];
void init(int n) {
    for (int i = 0; i <= n; i++) { // 初始化
        for (int j = 0; j <= n; j++)
            dis[i][j] = INF;
        dis[i][i] = 0;
    }
}
void floyd_warshall(int n) {
    for (int k = 0; k < n; k++) { // 窮舉中繼點 k
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) { // 窮舉點對 (i, j)
                dis[i][j] = min(dis[i][j], dis[i][k] + dis[k][j]);
            }
        }
    }
}

```

4.8 Maximum Clique

```

#define N 111 // 80 ~ 100 左右
struct MaxClique { // 0-base
    typedef bitset<N> Int;
    Int linkto[N], v[N];
    int n;
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; i++) {
            linkto[i].reset();
            v[i].reset();
        }
    }
    void addEdge(int a, int b) {
        v[a][b] = v[b][a] = 1;
    }
    int popcount(const Int& val) {
        return val.count();
    }
    int lowbit(const Int& val) {
        return val._Find_first();
    }
    int ans, stk[N];
    int id[N], di[N], deg[N];
    Int cans;
    void maxclique(int elem_num, Int candi) {
        if (elem_num > ans) {
            ans = elem_num;
            cans.reset();
            for (int i = 0; i < elem_num; i++)
                cans[id[stk[i]]] = 1;
        }
        int potential = elem_num + popcount(candi);
        if (potential <= ans)
            return;
        int pivot = lowbit(candi);
        Int smaller_candi = candi & (~linkto[pivot]);
        while (smaller_candi.count() && potential > ans) {
            int next = lowbit(smaller_candi);
            candi[next] = !candi[next];
            smaller_candi[next] = !smaller_candi[next];
        }
    }
}

```

```

        potential--;
        if (next == pivot ||
            (smaller_candi & linkto[next]).count()) {
            stk[elem_num] = next;
            maxclique(elem_num + 1, candi & linkto[
                next]);
        }
    }
}
int solve() {
    for (int i = 0; i < n; i++) {
        id[i] = i;
        deg[i] = v[i].count();
    }
    sort(id, id + n,
        [&](int id1, int id2) { return deg[id1] > deg
            [id2]; });
    for (int i = 0; i < n; i++)
        di[id[i]] = i;
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            if (v[i][j])
                linkto[di[i]][di[j]] = 1;

    Int cand;
    cand.reset();
    for (int i = 0; i < n; i++)
        cand[i] = 1;
    ans = 1;
    cans.reset();
    cans[0] = 1;
    maxclique(0, cand);
    return ans;
}
} solver;

```

4.9 Kosaraju's Algorithm for SCC

```

#define FZ(x) memset(x, 0, sizeof(x)) // fill zero
struct Scc {
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n) {
        n = _n;
        for (int i = 0; i <= n; i++)
            E[i].clear(), rE[i].clear();
    }
    void addEdge(int u, int v) {
        E[u].PB(v);
        rE[v].PB(u);
    }
    void DFS(int u) {
        vst[u] = 1;
        for (auto v : E[u])
            if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u) {
        vst[u] = 1;
        bln[u] = nScc; // 編號是 0-base
        for (auto v : rE[u])
            if (!vst[v]) rDFS(v);
    }
    void solve() {
        nScc = 0;
        vec.clear();
        fill(vst, vst + n + 1, 0);
        for (int i = 0; i < n; i++)
            if (!vst[i]) DFS(i);
        reverse(vec.begin(), vec.end());
        fill(vst, vst + n + 1, 0);
        for (auto v : vec)
            if (!vst[v]) {
                rDFS(v);
                nScc++;
            }
    }
};

```

5 Tree Algorithms

5.1 Lowest Common Ancestor

```

#include <bits/stdc++.h>
using namespace std;

```

```

const int N = 2e5 + 5, logN = 20;
vector<int> g[N];

int timing = 1, logn, n;
int in[N], out[N];
int anc[N][logN], depth[N];

// 建立倍增表
void build_table(int n) {
    logn = log2(n);
    for (int i = 1; i < logN; i++) {
        for (int now = 1; now <= n; now++) {
            anc[now][i] = anc[anc[now][i - 1]][i - 1];
        }
    }
}

// 建立時間戳記
// 跑一遍 DFS 得到誰是誰的父親
void dfs_init(int u, int pre) {
    in[u] = timing++; // 這時進入u
    anc[u][0] = pre; // now的0倍祖先是pre
    for (int nxt : g[u]) { // 跑過所有孩子
        if (pre == nxt)
            continue;
        depth[nxt] = depth[u] + 1;
        dfs_init(nxt, u);
    }
    out[u] = timing++; // 這時離開u
}

// 判斷是否是祖先
bool is_ancestor(int u, int v) {
    return (in[u] < in[v] && out[v] < out[u]);
}

// 找最低共同祖先
int getlca(int x, int y) {
    if (is_ancestor(x, y)) // 如果 u 為 v 的祖先則 lca 為
        u
        return x;
    if (is_ancestor(y, x)) // 如果 v 為 u 的祖先則 lca 為
        u
        return y;

    // 判斷 2^logN, 2^(logN-1), ..., 2^1, 2^0 倍祖先
    for (int i = logn; i >= 0; i--) {
        // cout << anc[x][i] << '\n';
        if (!is_ancestor(anc[x][i], y) &&
            anc[x][i]) // 如果 2^i 倍祖先不是 v 的祖
                先
            x = anc[x][i]; // 則往上移動
    }
    return anc[x][0]; // 回傳此點的父節點即為答案
}

// 以下是樹上差分
int tag[N], f[N], ans[N], root;
void add(int x, int y) {
    int lca = getlca(x, y);
    tag[x]++;
    tag[y]++;
    tag[lca]--;
    if (lca != root)
        tag[f[lca]]--;
}

int dfs_add(int now, int fa) {
    int diff = tag[now];
    for (auto nxt : g[now]) {
        if (nxt == fa)
            continue;
        diff += dfs_add(nxt, now);
    }
    return ans[now] = diff;
}

```

5.2 Euler Tour for LCA

```

#include <bits/stdc++.h>
using namespace std;

```

```

const int N = 1e5 + 5;

vector<int> tour, edge[N];
int timing = 0;
int in[N], out[N];

void dfs(int u, int fa) {
    tour.push_back(u); // 進入的時間點
    in[u] = tour.size() - 1;
    for (auto v : edge[u]) {
        if (v == fa) continue;
        dfs(v, u);
        tour.push_back(u); // 走完其中一個孩子 再走回自己
    }
    out[u] = tour.size() - 1;
}

void build(vector<int>& tour) { // 把tour丟進線段樹初始化
    seg.build(tour); // 除了tour, 還要建每個點的深度
}

int query(int x, int y) {
    if (is_ancestor(x, y)) return x; // LCA(x,y)=x
    if (is_ancestor(y, x)) return y; // LCA(x,y)=y;
    if (out[y] < in[x]) swap(x, y); // 如果「y的區間」在「x的區間」的左邊, 就交換
    int index = seg.query(out[x], in[y]); // 取得區間內哪個位置的深度是最低的
    return tour[index];
}

```

5.3 DSU on Tree

```

int find(int x) {
    if (f[x] == x) return x;
    else return f[x] = find(f[x]);
}

void merge(int x, int y) {
    x = find(x), y = find(y);
    if (sz[x] < sz[y]) swap(x, y);
    sz[x] += sz[y];
    f[y] = x;
}

void init() {
    // 初始化一開始大小都為1 (每群一開始都是獨立一個)
    for (int i = 1; i <= n; i++) sz[i] = 1;
    for (int i = 1; i <= n; i++) f[i] = i;
}

```

6 String Algorithms

6.1 Suffix Array (SAIS)

```

// 此為後綴陣列模板
// 用法:
// 把要處理的字串轉成整數陣列傳入suffix_array(), 會得到SA與H維結果
const int N = 500010; // 有可能要在這就寫原本字串的兩倍長
struct SA {
#define REP(i, n) for (int i = 0; i < int(n); i++)
#define REP1(i, a, b) for (int i = (a); i <= int(b); i++)
    bool _t[N * 2];
    int _s[N * 2], _sa[N * 2], _c[N * 2], x[N], _p[N], _q[N * 2],
        hei[N], r[N];
    int operator[](int i) { return _sa[i]; }
    void build(int *s, int n, int m) {
        memcpy(_s, s, sizeof(int) * n);

```

```

        sais(_s, _sa, _p, _q, _t, _c, n, m);
        mkhei(n);
    }
    void mkhei(int n) {
        REP(i, n) r[_sa[i]] = i;
        hei[0] = 0;
        REP(i, n) if (r[i]) {
            int ans = i > 0 ? max(hei[r[i] - 1] - 1, 0) : 0;
            while (_s[i + ans] == _s[_sa[r[i] - 1] + ans]) ans++;
            hei[r[i]] = ans;
        }
    }
    void sais(int *s, int *sa, int *p, int *q, bool *t, int *c, int n, int z) {
        bool uniq = t[n - 1] = true, neq;
        int nn = 0, nmzx = -1, *nsa = sa + n, *ns = s + n, lst = -1;
#define MS0(x, n) memset((x), 0, n * sizeof(*(x)))
#define MAGIC(XD) \
        MS0(sa, n); \
        memcpy(x, c, sizeof(int) * z); \
        XD; \
        memcpy(x + 1, c, sizeof(int) * (z - 1)); \
        REP(i, n) \
        if (sa[i] && !t[sa[i] - 1]) \
            sa[x[sa[i] - 1]++] = sa[i] - 1; \
        memcpy(x, c, sizeof(int) * z); \
        for (int i = n - 1; i >= 0; i--) \
            if (sa[i] && t[sa[i] - 1]) \
                sa[--x[sa[i] - 1]] = sa[i] - 1; \
        MS0(c, z); \
        REP(i, n) uniq &= ++c[s[i]] < 2; \
        REP(i, z - 1) c[i + 1] += c[i]; \
        if (uniq) { \
            REP(i, n) sa[--c[s[i]]] = i; \
            return; \
        } \
        for (int i = n - 2; i >= 0; i--) \
            t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]); \
        MAGIC(REP1(i, 1, n - 1) if (t[i] && !t[i - 1]) sa \
            [--x[s[i]]] = \
                p[q[i] = nn++] = i); \
        REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i] - 1]) \
            { \
                neq = lst < 0 || \
                    memcmp(s + sa[i], s + lst, \
                        (p[q[sa[i]] + 1] - sa[i]) * \
                            sizeof(int)); \
                ns[q[lst = sa[i]]] = nmzx += neq; \
            } \
        sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, \
            nmzx + 1); \
        MAGIC(for (int i = nn - 1; i >= 0; i--) sa[--x[s[p \
            [nsa[i]]]]) = \
                p[nsa[i]]); \
    }
    } sa;
    int H[N], SA[N]; // SA: 後綴陣列的length
                    // H[i]: SA[i]與SA[i-1]的共同子字串長
    void suffix_array(int *ip, int len) {
        // should padding a zero in the back
        // ip is int array, len is array length
        // ip[0..n-1] != 0, and ip[len] = 0
        ip[len++] = 0;
        sa.build(ip, len, 128);
        for (int i = 0; i < len; i++) {
            H[i] = sa.hei[i + 1];
            SA[i] = sa._sa[i + 1];
        }
        // resulting height, sa array \in [0, len)
    }
}

```

6.2 Z-algorithm

```

int z[MAXN];
void Z_value(const string& s) {
    // z[i] = lcp(s[1...], s[i...])
    int i, j, left, right, len = s.size();
    left = right = 0;
    z[0] = len;

```

```

    for (i = 1; i < len; i++) {
        j = max(min(z[i - left], right - i), 0);
        for (; i + j < len && s[i + j] == s[j]; j++)
            ;
        z[i] = j;
        if (i + z[i] > right) {
            right = i + z[i];
            left = i;
        }
    }
}

```

6.3 Knuth-Morris-Pratt Algorithm

```

int failure[MXN];
vector<int> KMP(string& t, string& p) {
    vector<int> ret; // 要保證長度 t > p
    for (int i = 1, j = failure[0] = -1; i < p.size(); ++i)
    {
        while (j >= 0 && p[j + 1] != p[i])
            j = failure[j];
        if (p[j + 1] == p[i]) j++;
        failure[i] = j;
    }
    for (int i = 0, j = -1; i < t.size(); ++i) {
        while (j >= 0 && p[j + 1] != t[i])
            j = failure[j];
        if (p[j + 1] == t[i]) j++;
        if (j == p.size() - 1) {
            ret.push_back(i - p.size() + 1);
            j = failure[j];
        }
    }
    return ret;
}

```

6.4 Manacher's Algorithm

```

int ans[MAXN << 1];
char s[MAXN << 1];
string ret; // 迴文字串儲存結果
void find_palindrome(char *s, int len, int *z) {
    int idx = 0, mx = -1;
    for (int i = 0; i < len; i++) { // 找迴文半徑最大值
        if (mx < ans[i]) {
            idx = i;
            mx = ans[i];
        }
    }
    for (int i = idx - mx + 1; i < idx; i++)
        if (s[i] != '@')
            ret.push_back(s[i]);
    for (int i = idx; i <= idx + mx - 1; i++)
        if (s[i] != '@')
            ret.push_back(s[i]);
    // cout << ret << '\n'; //// 直接輸出
}
void z_value_pal(char *s, int len, int *z) { // 字串，長度，輸出的陣列
    len = (len << 1) + 1;
    for (int i = len - 1; i >= 0; i--)
        s[i] = i & 1 ? s[i >> 1] : '@';
    z[0] = 1;
    for (int i = 1, l = 0, r = 0; i < len; i++) {
        z[i] = i < r ? min(z[l + l - i], r - i) : 1;
        while (i - z[i] >= 0 && i + z[i] < len &&
            s[i - z[i]] == s[i + z[i]])
            ++z[i];
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    find_palindrome(s, strlen(s), z);
}

```

6.5 Minimum Rotation

```

int min_rotation(string s) {
    int a = 0, N = s.size();
    s += s;
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++) {
            if (a + j == i || s[a + j] < s[i + j]) {
                i += max(0, j - 1);
            }
        }
    }
}

```

```

        break;
    }
    if (s[a + j] > s[i + j]) {
        a = i;
        break;
    }
}
return a;
}
// rotate(begin(s), begin(s) + minRotation(s), end(s))
// 上面註解可以直接讓一個字串做 rotate，得到字典序最小的 rotation

```

6.6 Rolling Hash

```

ll P1 = 75577, P2 = 12721, MOD = 998244353;
pii hashes[MAXN], hashes2[MAXN];
string s1, s2;
void build(string s, pii hash) {
    ll val1 = 0, val2 = 0;
    for (int i = 0; i < s.length(); i++) {
        val1 = (val1 * P1 % MOD + s[i]) % MOD;
        val2 = (val2 * P2 % MOD + s[i]) % MOD;
        hash[i] = {val1, val2};
    }
}
ll minus(ll a, ll b) {
    return (a - b + MOD) % MOD;
}
ll cnt_occur() { // 檢查
    int n = s1.size(), k = s2.size();
    ll cnt = (hashes2[k - 1].x == hashes[k - 1].x &&
        hashes2[k - 1].y == hashes[k - 1].y);
    ll val1 = 0, val2 = 0;
    for (int i = 1, j = k; j < n; j++, i++) {
        val1 = minus(hashes[j].x, hashes[i - 1].x * fpow(P1,
            j - i + 1));
        val2 = minus(hashes[j].y, hashes[i - 1].y * fpow(P2,
            j - i + 1));
        if (hashes2[k - 1].x == val1 && hashes2[k - 1].y ==
            val2)
            cnt++;
    }
}

```

7 Geometry

7.1 Basic Geometry Structure

```

int dcmp(ld x) { // 處理小數點精度的東東
    if (abs(x) < eps)
        return 0;
    else
        return x < 0 ? -1 : 1;
}
struct Pt {
    ld x, y;
    Pt(ld _x = 0, ld _y = 0) : x(_x), y(_y) {}
    Pt operator+(const Pt &a) {
        return Pt(x + a.x, y + a.y);
    }
    Pt operator-(const Pt &a) {
        return Pt(x - a.x, y - a.y);
    }
    Pt operator*(const ld &a) {
        return Pt(x * a, y * a);
    }
    Pt operator/(const ld &a) {
        return Pt(x / a, y / a);
    }
    ld operator*(const Pt &a) { // 內積
        return x * a.x + y * a.y;
    }
    ld operator^(const Pt &a) { // 行列式(叉乘)
        return x * a.y - y * a.x;
    }
    bool operator<(const Pt &a) const {
        return x < a.x || (x == a.x && y < a.y);
    }
    friend ld cross(Point a, Point b, Point o) {
        // 行列式(叉乘)，存入三個點
        Point p1 = a - o, p2 = b - o;
    }
}

```

```

    return p1.x * p2.y - p1.y * p2.x;
}
// return dcmp(x-a.x) < 0 || (dcmp(x-a.x) == 0 && dcmp
// (y-a.y) < 0);
// }
bool operator==(const Pt &a) {
    return dcmp(x - a.x) == 0 && dcmp(y - a.y) == 0;
}
};

ld norm2(const Pt &a) { // 平方
    return a * a;
}

ld norm(const Pt &a) {
    return sqrt(norm2(a));
}

Pt perp(const Pt &a) { // 與原本向量垂直的向量
    return Pt(-a.y, a.x);
}

Pt rotate(const Pt &a, ld ang) { // 旋轉矩陣
    return Pt(a.x * cos(ang) - a.y * sin(ang),
              a.x * sin(ang) + a.y * cos(ang));
}

struct Line {
    Pt s, e, v; // start, end, end-start
    ld ang;
    Line(Pt _s = Pt(0, 0), Pt _e = Pt(0, 0)) : s(_s), e(_e) {
        v = e - s;
        ang = atan2(v.y, v.x);
    }
    bool operator<(const Line &L) const {
        return ang < L.ang;
    }
};

struct Circle {
    Pt o;
    ld r;
    Circle(Pt _o = Pt(0, 0), ld _r = 0) : o(_o), r(_r) {}
};

```

7.2 Circle Cover Area

```

struct CircleCover {
    int C;
    Circle c[N]; // 填入C(圓數量),c(圓陣列)
    bool g[N][N], overlap[N][N];
    // Area[i] : area covered by at least i circles
    D Area[N];
    void init(int _C) {
        C = _C;
    }
    bool CCinter(Circle &a, Circle &b, Pt &p1, Pt &p2) {
        Pt o1 = a.o, o2 = b.o;
        D r1 = a.r, r2 = b.r;
        if (norm(o1 - o2) > r1 + r2)
            return {};
        if (norm(o1 - o2) < max(r1, r2) - min(r1, r2))
            return {};
        D d2 = (o1 - o2) * (o1 - o2);
        D d = sqrt(d2);
        if (d > r1 + r2)
            return false;
        Pt u = (o1 + o2) * 0.5 +
              (o1 - o2) * ((r2 * r2 - r1 * r1) / (2 * d2));
        D A = sqrt((r1 + r2 + d) * (r1 - r2 + d) * (r1 +
              r2 - d) * (-r1 + r2 + d));
        Pt v = Pt(o1.y - o2.y, -o1.x + o2.x) * A / (2 * d2);
        p1 = u + v;
        p2 = u - v;
        return true;
    }
    struct Teve {
        Pt p;
        D ang;
        int add;
        Teve() {}
        Teve(Pt _a, D _b, int _c) : p(_a), ang(_b), add(_c) {}
    }
};

```

```

bool operator<(const Teve &a) const {
    return ang < a.ang;
}
} eve[N * 2];
// strict: x = 0, otherwise x = -1
bool disjunct(Circle &a, Circle &b, int x) {
    return dcmp(norm(a.o - b.o) - a.r - b.r) > x;
}
bool contain(Circle &a, Circle &b, int x) {
    return dcmp(a.r - b.r - norm(a.o - b.o)) > x;
}
bool contain(int i, int j) {
    /* c[j] is non-strictly in c[i]. */
    return (dcmp(c[i].r - c[j].r) > 0 ||
            (dcmp(c[i].r - c[j].r) == 0 && i < j)) &&
            contain(c[i], c[j], -1);
}
void solve() {
    for (int i = 0; i <= C + 1; i++)
        Area[i] = 0;
    for (int i = 0; i < C; i++)
        for (int j = 0; j < C; j++)
            overlap[i][j] = contain(i, j);
    for (int i = 0; i < C; i++)
        for (int j = 0; j < C; j++)
            g[i][j] = !(overlap[i][j] || overlap[j][i] ||
                        disjunct(c[i], c[j], -1));
    for (int i = 0; i < C; i++) {
        int E = 0, cnt = 1;
        for (int j = 0; j < C; j++)
            if (j != i && overlap[j][i])
                cnt++;
        for (int j = 0; j < C; j++)
            if (i != j && g[i][j]) {
                Pt aa, bb;
                CCinter(c[i], c[j], aa, bb);
                D A = atan2(aa.y - c[i].o.y, aa.x - c[i].o.x);
                D B = atan2(bb.y - c[i].o.y, bb.x - c[i].o.x);
                eve[E++] = Teve(bb, B, 1);
                eve[E++] = Teve(aa, A, -1);
                if (B > A)
                    cnt++;
            }
        if (E == 0)
            Area[cnt] += pi * c[i].r * c[i].r;
        else {
            sort(eve, eve + E);
            eve[E] = eve[0];
            for (int j = 0; j < E; j++) {
                cnt += eve[j].add;
                Area[cnt] += (eve[j].p ^ eve[j + 1].p) * 0.5;
                D theta = eve[j + 1].ang - eve[j].ang;
                if (theta < 0)
                    theta += 2.0 * pi;
                Area[cnt] +=
                    (theta - sin(theta)) * c[i].r * c[i].r * 0.5;
            }
        }
    }
} ret;

```

7.3 Circles' Tangent Lines

```

vector<Line> go(const Circle& c1, const Circle& c2, int
    sign1) {
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;
    double d_sq = norm(c1.o - c2.o);
    if (d_sq < eps)
        return ret;
    double d = sqrt(d_sq);
    Pt v = (c2.o - c1.o) / d;
    double c = (c1.r - sign1 * c2.r) / d;
    if (c * c > 1)
        return ret;
    double h = sqrt(max(0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {

```

```

        Pt n = {v.x * c - sign2 * h * v.y, v.y * c + sign2
                * h * v.x};
        Pt p1 = c1.o + n * c1.r;
        Pt p2 = c2.o + n * (c2.r * sign1);
        if (fabs(p1.x - p2.x) < eps and fabs(p1.y - p2.y)
            < eps)
            p2 = p1 + perp(c2.o - c1.o);
        ret.push_back({p1, p2});
    }
    return ret;
}

```

7.4 Circles' Intersections

```

vector<Pt> interCircle(Pt o1, ld r1, Pt o2, ld r2) {
    if (norm(o1 - o2) > r1 + r2)
        return {};
    if (norm(o1 - o2) < max(r1, r2) - min(r1, r2))
        return {};
    ld d2 = (o1 - o2) * (o1 - o2);
    ld d = sqrt(d2);
    if (d > r1 + r2)
        return {};
    Pt u =
        (o1 + o2) * 0.5 + (o1 - o2) * ((r2 * r2 - r1 * r1)
        / (2 * d2));
    ld A = sqrt((r1 + r2 + d) * (r1 - r2 + d) * (r1 + r2 -
        d) *
        (-r1 + r2 + d));
    Pt v = Pt(o1.y - o2.y, -o1.x + o2.x) * A / (2 * d2);
    return {u + v, u - v};
}

```

7.5 Convex Hull

```

double cross(Pt o, Pt a, Pt b) {
    return (a - o) ^ (b - o);
}
vector<Pt> convex_hull(vector<Pt> pt) {
    sort(pt.begin(), pt.end());
    int top = 0;
    vector<Pt> stk(2 * pt.size());
    for (int i = 0; i < (int)pt.size(); i++) {
        while (top >= 2 &&
            cross(stk[top - 2], stk[top - 1], pt[i]) <=
                0)
            top--;
        stk[top++] = pt[i];
    }
    for (int i = pt.size() - 2, t = top + 1; i >= 0; i--)
        while (top >= t &&
            cross(stk[top - 2], stk[top - 1], pt[i]) <=
                0)
            top--;
        stk[top++] = pt[i];
    stk.resize(top - 1);
    return stk;
}

```

7.6 Convex Hull Tricks

```

struct Convex {
    int n;
    vector<Pt> A, V, L, U;
    Convex(const vector<Pt> &A) : A(A), n(A.size()) {
        // n >= 3
        rotate(A.begin(), min_element(all(A)), A.end());
        ;
        // 最左的の點排最前面 有時可以不需要這一行
        auto it = max_element(all(A));
        L.assign(A.begin(), it + 1);
        U.assign(it, A.end()), U.push_back(A[0]);
        for (int i = 0; i < n; i++) {
            V.push_back(A[(i + 1) % n] - A[i]);
        }
    }
    int PtSide(Pt p, Line L) {
        return dcmp((L.b - L.a) ^ (p - L.a));
    }
    int inside(Pt p, const vector<Pt> &h, auto f) {
        auto it = lower_bound(all(h), p, f);
        if (it == h.end())

```

```

        return 0;
    if (it == h.begin())
        return p == *it;
    return 1 - dcmp((p - *prev(it)) ^ (*it - *prev(it)
        ));
}
// 1. whether a given point is inside the CH
// ret 0: out, 1: on, 2: in
int inside(Pt p) {
    return min(inside(p, L, less{}), inside(p, U,
        greater{}));
}
static bool cmp(Pt a, Pt b) {
    return dcmp(a ^ b) > 0;
}
// 2. Find tangent points of a given vector
// ret the idx of far/closer tangent point
int tangent(Pt v, bool close = true) {
    assert(v != Pt{});
    auto l = V.begin(), r = V.begin() + L.size() - 1;
    if (v < Pt{})
        l = r, r = V.end();
    if (close)
        return (lower_bound(l, r, v, cmp) - V.begin())
            % n;
    return (upper_bound(l, r, v, cmp) - V.begin()) % n;
}
// 3. Find 2 tang pts on CH of a given outside point
// return index of tangent points
// return {-1, -1} if inside CH
array<int, 2> tangent2(Pt p) {
    array<int, 2> t{-1, -1};
    if (inside(p) == 2)
        return t;
    if (auto it = lower_bound(all(L), p);
        it != L.end() and p == *it) {
        int s = it - L.begin();
        return {(s + 1) % n, (s - 1 + n) % n};
    }
    if (auto it = lower_bound(all(U), p, greater{});
        it != U.end() and p == *it) {
        int s = it - U.begin() + L.size() - 1;
        return {(s + 1) % n, (s - 1 + n) % n};
    }
    for (int i = 0; i != t[0]; i = tangent((A[t[0] = i
        ] - p), 0))
        ;
    for (int i = 0; i != t[1]; i = tangent((p - A[t[1]
        = i]), 1))
        ;
    return t;
}
int find(int l, int r, Line L) {
    if (r < l)
        r += n;
    int s = PtSide(A[l % n], L);
    return *ranges::partition_point(views::iota(l, r),
        [&](int m) {
            return PtSide(A[m % n], L) == s;
        }) - 1;
}
// 4. Find intersection point of a given line
// intersection is on edge (i, next(i))
vector<int> intersect(Line L) {
    int l = tangent(L.a - L.b), r = tangent(L.b - L.a)
        ;
    if (PtSide(A[l], L) == 0)
        return {l};
    if (PtSide(A[r], L) == 0)
        return {r};
    if (PtSide(A[l], L) * PtSide(A[r], L) > 0)
        return {};
    return {find(l, r, L) % n, find(r, l, L) % n};
}
};

```

7.7 Pick's Theory

```

vector<Pt> p;
ll compute_area(int n) { // A * 2
    ll area = 0;
    for (int i = 1; i < n; i++)
        area += cross(p[i], p[(i + 1) % n], p[0]);
}

```


9.3 Graph Paper





