

Contents

1 Basis	1	4.9 Kosaraju's Algorithm for SCC	5
1.1 Default Code	1	5 Tree Algorithms	6
1.2 Some Useful Primes	1	5.1 Lowest Common Ancestor	6
1.3 隨機 & MT19937	1	5.2 Euler Tour for LCA	6
2 Data Structures	1	5.3 DSU on Tree	6
2.1 Disjoint Set (Union-Find)	1	6 String Algorithms	7
2.2 Binary Indexed Tree	1	6.1 Suffix Array (SAIS)	7
2.3 Segment Tree	1	6.2 Z-algorithm	7
3 Mathematics	2	6.3 Knuth-Morris-Pratt Algorithm	7
3.1 Combination with Inverse	2	6.4 Manacher's Algorithm	7
3.2 EXGCD	2	6.5 Minimum Rotation	8
3.3 FFT	2	6.6 Rolling Hash	8
3.4 Exponentiation by Squaring	2	7 Geometry	8
3.5 GCD and LCM	3	7.1 Basic Geometry Structure	8
3.6 Miller-Rabin Algorithm	3	7.2 Circle Cover Area	9
3.7 Pollard's Rho Algorithm	3	7.3 Circles' Tangent Lines	9
4 Graph	3	7.4 Circles' Intersections	9
4.1 Topological Sort	3	7.5 Convex Hull	9
4.2 Tarjan's Algorithm for BCC	3	7.6 Convex Hull Tricks	10
4.3 Bellmen-Ford Algorithm	4	7.7 Pick's Theory	10
4.4 Dijkstra's Algorithm	4	8 Sorting	10
4.5 Dinic's Algorithm for Maximum Flow	4	8.1 Merge Sort	10
4.6 Dominator Tree	4	8.2 Quick Sort	11
4.7 Floyd-Warshall Algorithm	5	9 Miscellaneous	11
4.8 Maximum Clique	5	9.1 Discretization	11
		9.2 Blessing	11
		9.3 Graph Paper	12

1 Basis

1.1 Default Code

```
#include <bits/stdc++.h>
#define ll long long
#define ld long double
#define pii pair<int, int>
#define D double
#define INF 0x7f7f7f7f7f7f7f7fLL
#define REP(i, n) for (int i = 0; i < n; i++)
#define PB push_back
#define SZ(x) (int)(x).size()
#define all(x) (x).begin(), (x).end()
using namespace std;
const int MAX_N = 2e6 + 5;
const int MOD = 1e9 + 7;
signed main() {
    ios_base::sync_with_stdio(0), cin.tie(0), cout.tie(0);
    return 0;
}
```

1.2 Some Useful Primes

```
/* 999983, 1097774749, 1076767633, 100102021, 999997771,
 * 1001010013, 1000512343, 987654361, 999991231,
 * 999888733, 98789101, 987777733, 999991921,
 * 1010101333, 1010102101, 1000000000039,
 * 1000000000000037, 2305843009213693951,
 * 4611686018427387847, 9223372036854775783,
 * 18446744073709551557 */
```

1.3 隨機 & MT19937

```
#include <bits/stdc++.h>
using namespace std;
mt19937 gen(*seed* hash<string>()("SHIKA"));
chrono::steady_clock::now().time_since_epoch().count();
int randint(int a, int b) { // [a, b]
    return uniform_int_distribution<int>(a, b)(gen);
}
```

2 Data Structures

2.1 Disjoint Set (Union-Find)

```
struct DSU {
    int n;
    vector<int> f, sz;
    DSU(int _n) { // 初始化
        n = _n;
        f.resize(n);
        sz.resize(n);
        for (int i = 0; i < n; i++) {
            f[i] = i;
        }
    }
};
```

```
sz[i] = 1;
}
}
int find(int x) { // 返回 x 的根節點
    if (x == f[x])
        return x;
    return f[x] = find(f[x]);
}
void merge(int x, int y) { // 將 x 和 y 合併
    x = find(x), y = find(y);
    if (x == y)
        return;
    if (sz[x] < sz[y]) // 將小的併入大的
        swap(x, y);
    sz[x] += sz[y];
    f[y] = x;
}
};
```

2.2 Binary Indexed Tree

```
#define lowbit(x) (x & -x)
struct BIT {
    int n;
    vector<ll> a;
    BIT(int _n) {
        n = _n;
        a.clear();
        a.resize(n + 1, 0);
    }
    void update(int x, int v) { // 將 x 的值加上 v
        for (; x < a.size(); x += lowbit(x))
            a[x] += v;
    }
    ll query(int x) { // 查詢區間 [1, x] 的總和
        ll ret = 0;
        for (; x; x -= lowbit(x))
            ret += a[x];
        return ret;
    }
    // 查詢區間 [l, r] 的總和
    ll query(int l, int r) { // 大多呼叫這個為主
        return query(r) - query(l - 1);
    }
    int kth(int k) { // 說實話這不常用 有時可以刪掉
        int x = 0;
        for (int i = 1 << __lg(n); i; i >>= 1) {
            if (x + i <= n && k >= a[x + i - 1]) {
                x += i;
                k -= a[x - 1];
            }
        }
        return x;
    }
};
```

2.3 Segment Tree

```
#define cl (i << 1)
#define cr (i << 1 | 1)
#define NO_TAG 0
struct SegmentTree { // 1-base
    int n;
    vector<int> seg, tag;
    SegmentTree(int _n) { // 空的 SegmentTree
        n = _n;
        seg.resize(n * 4);
        tag.resize(n * 4);
    }
    SegmentTree(vector<int>& arr) { // 處理好的 SegmentTree
        n = arr.size();
        seg.resize(n * 4);
        tag.resize(n * 4);
        build(1, 0, n - 1, arr); // kk
    }
    void push(int i, int l, int r) {
        if (tag[i] != NO_TAG) {
            seg[i] += tag[i]; // update by tag
            if (l != r) {
                tag[cl] += tag[i]; // push
                tag[cr] += tag[i]; // push
            }
        }
    }
};
```

```

        tag[i] = 0;
    }
}
void pull(int i, int l, int r) {
    int mid = (l + r) >> 1;
    push(cl, l, mid);
    push(cr, mid + 1, r);
    seg[i] = max(seg[cl], seg[cr]); // pull
}
void build(int i, int l, int r, vector<int>& arr) {
    if (l == r) {
        seg[i] = arr[l]; // set value
        return;
    }
    int mid = (l + r) >> 1;
    build(cl, l, mid, arr);
    build(cr, mid + 1, r, arr);
    pull(i, l, r);
}
void update(int i, int l, int r, int ql, int qr, int v) {
    push(i, l, r);
    if (ql <= l && r <= qr) {
        tag[i] += v;
        return;
    }
    int mid = (l + r) >> 1;
    if (ql <= mid)
        update(cl, l, mid, ql, qr, v);
    if (qr > mid)
        update(cr, mid + 1, r, ql, qr, v);
    pull(i, l, r);
}
int query(int i, int l, int r, int ql, int qr) {
    push(i, l, r);
    if (ql <= l && r <= qr) {
        return seg[i];
    }
    int mid = (l + r) >> 1, ans = -INF;
    if (ql <= mid)
        ans = max(ans, query(cl, l, mid, ql, qr));
    if (qr > mid)
        ans = max(ans, query(cr, mid + 1, r, ql, qr));
    return ans;
}
// 區間 [ql, qr] 加值 v
void update(int ql, int qr, int v) {
    update(1, 0, n - 1, ql, qr, v); // kk
}
// 查詢區間 [ql, qr]
int query(int ql, int qr) {
    return query(1, 0, n - 1, ql, qr); // kk
}
// 不知道是 [0, n-1] 還是 [1, n]
};

```

3 Mathematics

3.1 Combination with Inverse

```

ll fac[MAX_N], inv[MAX_N];

void init() {
    fac[0] = 1; // 0! = 1
    for (ll i = 1; i < MAX_N; i++) // factorial
        fac[i] = fac[i - 1] * i % MOD;
    // 費馬小定理(逆元) with 快速幂
    inv[MAX_N - 1] = power(fac[MAX_N - 1], MOD - 2);
    for (ll i = MAX_N - 2; i >= 0; i--) // the inverse of factorial
        inv[i] = inv[i + 1] * (i + 1) % MOD;
}

// 組合 (Combination) n 取 k
ll comb(ll n, ll k) {
    //  $C(n, k) = n! / (k! * (n - k)!)$ 
    return fac[n] * inv[k] % MOD * inv[n - k] % MOD;
}

// 排列 (Permutation) n 取 k
ll perm(ll n, ll k) {
    //  $P(n, k) = C(n, k) * k!$ 
    return fac[n] * inv[n - k] % MOD;
}

```

```

}

// 重複組合 (Combinations WITH Repetitions)
ll h(ll n, ll k) {
    //  $H(n, k) = C(n + k - 1, n - 1)$ 
    return fac[n + k - 1] * inv[k] % MOD * inv[n - 1] % MOD;
}

```

3.2 EXGCD

```

int exgcd(int a, int b, ll &x, ll &y) {
    if (b == 0) {
        x = 1, y = 0;
        return a;
    }
    int now = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return now;
}

```

3.3 FFT

```

const int MAXN = 262144 << 1;
// (must be 2^k)
// before any usage, run pre_fft() first
typedef long double ld;
typedef complex<ld> cplx; // real(), imag()
const ld PI = acos(-1);
const cplx I(0, 1);
cplx omega[MAXN + 1];
void pre_fft() {
    for (int i = 0; i <= MAXN; i++)
        omega[i] = exp(i * 2 * PI / MAXN * I);
}
// n must be 2^k
void fft(int n, cplx a[], bool inv = false) {
    int basic = MAXN / n;
    int theta = basic;
    for (int m = n; m >= 2; m >= 1) {
        int mh = m >> 1;
        for (int i = 0; i < mh; i++) {
            cplx w = omega[inv ? MAXN - (i * theta % MAXN) : i * theta % MAXN];
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                cplx x = a[j] - a[k];
                a[j] += a[k];
                a[k] = w * x;
            }
        }
        theta = (theta * 2) % MAXN;
    }
    int i = 0;
    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^= k); k >>= 1) {}
        if (j < i)
            swap(a[i], a[j]);
    }
    if (inv)
        for (i = 0; i < n; i++)
            a[i] /= n;
}

cplx arr[MAXN + 1];
inline void mul(int _n, ll a[], int _m, ll b[], ll ans[]) {
    int n = 1, sum = _n + _m - 1;
    while (n < sum)
        n <<= 1;
    for (int i = 0; i < n; i++) {
        double x = (i < _n ? a[i] : 0), y = (i < _m ? b[i] : 0);
        arr[i] = complex<double>(x + y, x - y);
    }
    fft(n, arr);
    for (int i = 0; i < n; i++)
        arr[i] = arr[i] * arr[i];
    fft(n, arr, true);
    for (int i = 0; i < sum; i++)
        ans[i] = (long long int)(arr[i].real() / 4 + 0.5);
}

```

3.4 Exponentiation by Squaring

```

11 power(ll x, ll y) {
    ll ret = 1;
    while (y) {
        if (y & 1)
            (ret *= x) %= MOD;
        (x *= x) %= MOD;
        y >>= 1;
    }
    return ret;
}

```

3.5 GCD and LCM

```

11 gcd(ll a, ll b) {
    if (b && a) // 輾轉先除法->交叉取餘數直到不能再取
        while ((a %= b) && (b %= a)) {}
    return a + b;
}

11 lcm(ll a, ll b) {
    return a * b * gcd(a, b);
}

```

3.6 Miller-Rabin Algorithm

```

11 mul(ll x, ll y, ll mod) {
    ll ret = x * y - (ll)((long double)x / mod * y) * mod;
    return ret < 0 ? ret + mod : ret;
    // return x * y % mod; // 如果數字大到需要開
    // __int128就用這
}

11 magic[] = {}; // 這邊填入要用於測試的數列
11 S = 3; // 測試的數列數字的數量
bool witness(ll a, ll n, ll u, int t) {
    if (!a)
        return 0;
    ll x = power(a, u, n);
    for (int i = 0; i < t; i++) {
        ll nx = mul(x, x, n);
        if (nx == 1 && x != 1 && x != n - 1)
            return 1;
        x = nx;
    }
    return x != 1;
}

bool miller_rabin(ll n) {
    int s = S; // magic number size
    // iterate s times of witness on n
    if (n < 2)
        return false;
    if (!(n & 1))
        return (n == 2);

    // 將 n - 1 寫成 u * (2 ^ t) 的形式
    ll u = n - 1;
    int t = 0;
    while (!(u & 1))
        u >>= 1, t++;

    while (s--) {
        ll a = magic[s] % n;
        if (witness(a, n, u, t))
            return false;
    }
    return true;
}

```

3.7 Pollard's Rho Algorithm

```

vector<ll> ret;
11 mul(ll x, ll y, ll mod) {
    ll ret = x * y - (ll)((long double)x / mod * y) * mod;
    return ret < 0 ? ret + mod : ret;
    // return x * y % mod; // for __int128
}

11 f(ll x, ll c, ll mod) {
    return (mul(x, x, mod) + c) % mod;
}

11 pollard_rho(ll n) {
    ll c = 1, x = 0, y = 0, p = 2, q, t = 0;
    while (t++ % 128 or gcd(p, n) == 1) {
        if (x == y)

```

```

        c++, y = f(x = 2, c, n);
        if (q = mul(p, abs(x - y), n))
            p = q;
        x = f(x, c, n);
        y = f(f(y, c, n), c, n);
    }
    return gcd(p, n);
}

void fact(ll x) { // 透過遞迴找質數
    if (miller_rabin(x)) {
        ret.push_back(x);
        return;
    }
    ll f = pollard_rho(x);
    fact(f);
    fact(x / f);
}

```

4 Graph

4.1 Topological Sort

```

vector<int> edge[MAXN], ans;
int deg[MAXN]; // in degree
void topo(int n) { // 1-base
    queue<int> que;
    for (int i = 1; i <= n; i++)
        if (!deg[i])
            que.push(i);
    while (!que.empty()) {
        int u = que.front();
        que.pop();
        ans.push_back(u);
        // 結果存 ans
        for (int v : edge[u]) {
            deg[v]--;
            if (!deg[v])
                que.push(v);
        }
    }
}

```

4.2 Tarjan's Algorithm for BCC

```

struct BccVertex {
    int n, nScc, step, dfn[MAX_N], low[MAX_N];
    vector<int> E[MAX_N], sccv[MAX_N];
    int top, stk[MAX_N];
    void init(int _n) {
        n = _n;
        nScc = step = 0;
        for (int i = 0; i < n; i++)
            E[i].clear();
    }

    void addEdge(int u, int v) {
        E[u].PB(v);
        E[v].PB(u);
    }

    void DFS(int u, int f) {
        dfn[u] = low[u] = step++;
        stk[top++] = u;
        for (auto v : E[u]) {
            if (v == f)
                continue;
            if (dfn[v] == -1) {
                DFS(v, u);
                low[u] = min(low[u], low[v]);
                if (low[v] >= dfn[u]) {
                    int z;
                    sccv[nScc].clear();
                    do {
                        z = stk[--top];
                        sccv[nScc].PB(z);
                    } while (z != v);
                    sccv[nScc++].PB(u);
                }
            } else
                low[u] = min(low[u], dfn[v]);
        }
    }

    vector<vector<int>> solve() {
        vector<vector<int>> res;
        for (int i = 0; i < n; i++)
            dfn[i] = low[i] = -1;
    }
}

```

```

    for (int i = 0; i < n; i++)
        if (dfn[i] == -1) {
            top = 0;
            DFS(i, i);
        }
    REP(i, nScc) res.PB(sccv[i]);
    return res;
}
} graph;

```

4.3 Bellman-Ford Algorithm

```

struct Edge {
    int from, to, weight;
} edge[MAXN];
int dis[MAXN];
void bellman_ford(int n, int m) {
    dis[1] = 0; // 起點的距離一定是0
    for (int j = 0; j < n - 1; j++) { // n 個節點要跑 n - 1 次
        for (int i = 0; i < m; i++) { // 對於所有邊都嘗試鬆弛
            if (dis[edge[i].to] > dis[edge[i].from] + edge[i].weight)
                dis[edge[i].to] = dis[edge[i].from] + edge[i].weight;
        }
    }
}

```

4.4 Dijkstra's Algorithm

```

vector<pii> vec[N]; // vec[u] = {v, w}: u 為起點 v 為終點 w 為路權
bool vis[N]; // 紀錄該節點是否走過
vector<int> dijkstra(int s) { // 起點
    vector<int> dis(N);
    for (int i = 0; i < N; i++) // 初始化
        dis[i] = INF; // 值要設為比可能的最短路徑權重還要大的值
    dis[s] = 0;
    priority_queue<pii, vector<pii>, greater<pii>> pq; // 以小到大大排序
    // {w, v}: w 為路權 v 為節點
    pq.push({dis[s], s});
    while (pq.empty() == 0) {
        int u = pq.top().second;
        pq.pop();
        if (vis[u]) // 走過的不要再走
            continue;
        vis[u] = 1;
        for (auto i : vec[u]) {
            int v = i.first, w = i.second;
            if (dis[u] + w < dis[v]) { // 鬆弛
                dis[v] = dis[u] + w;
                pq.push({dis[v], v});
            }
        }
    }
    return dis;
}

```

4.5 Dinic's Algorithm for Maximum Flow

```

struct Dinic {
    struct Edge {
        int v, f, re;
    };
    int n, s, t, level[MAX_N];
    vector<Edge> E[MAX_N];
    void init(int _n, int _s, int _t) {
        n = _n;
        s = _s;
        t = _t;
        for (int i = 0; i < n; i++)
            E[i].clear();
    }
    void add_edge(int u, int v, int f) {
        E[u].PB({v, f, SZ(E[v])});
        E[v].PB({u, 0, SZ(E[u]) - 1});
    }
}

```

```

bool BFS() {
    for (int i = 0; i < n; i++)
        level[i] = -1;
    queue<int> que;
    que.push(s);
    level[s] = 0;
    while (!que.empty()) {
        int u = que.front();
        que.pop();
        for (auto it : E[u]) {
            if (it.f > 0 && level[it.v] == -1) {
                level[it.v] = level[u] + 1;
                que.push(it.v);
            }
        }
    }
    return level[t] != -1;
}
int DFS(int u, int nf) {
    if (u == t)
        return nf;
    int res = 0;
    for (auto &it : E[u]) {
        if (it.f > 0 && level[it.v] == level[u] + 1) {
            int tf = DFS(it.v, min(nf, it.f));
            res += tf;
            nf -= tf;
            it.f -= tf;
            E[it.v][it.re].f += tf;
            if (nf == 0)
                return res;
        }
    }
    return 0;
}
if (!res)
    level[u] = -1;
return res;
}
int flow(int res = 0) {
    while (BFS())
        res += DFS(s, 2147483647);
    return res;
}
} flow;
/*
查找二分圖配對點：
在 add_edge 時寫上 index[u].push_back({v, flow.E[u].size()});

在 flow 完之後寫上這個
for (int i = 1; i <= n; i++) { // 遍歷所有節點
    for (pair<int, int> j : index[i]) {
        if (flow.E[i][j.second - 1].f == 0)
            cout << i << ' ' << j.first << '\n';
    }
}
*/

```

4.6 Dominator Tree

```

#define REP(i, s, e) for (int i = (s); i <= (e); i++)
#define REPD(i, s, e) for (int i = (s); i >= (e); i--)
struct DominatorTree { // O(N)
    int n, s;
    vector<int> g[MAXN], pred[MAXN];
    vector<int> cov[MAXN];
    int dfn[MAXN], nfd[MAXN], ts;
    int par[MAXN]; // idom[u] s到u的最後一個必經點
    int sdom[MAXN], idom[MAXN];
    int mom[MAXN], mn[MAXN];
    inline bool cmp(int u, int v) {
        return dfn[u] < dfn[v];
    }
    int eval(int u) {
        if (mom[u] == u)
            return u;
        int res = eval(mom[u]);
        if (cmp(sdom[mn[mom[u]]], sdom[mn[u]]))
            mn[u] = mn[mom[u]];
        return mom[u] = res;
    }
    void init(int _n, int _s) {
        ts = 0;
        n = _n;
    }
}

```

```

    s = _s;
    REP(i, 1, n) g[i].clear(), pred[i].clear();
}
void addEdge(int u, int v) {
    g[u].push_back(v);
    pred[v].push_back(u);
}
void dfs(int u) {
    ts++;
    dfn[u] = ts;
    nfd[ts] = u;
    for (int v : g[u])
        if (dfn[v] == 0) {
            par[v] = u;
            dfs(v);
        }
}
void build() {
    REP(i, 1, n) {
        dfn[i] = nfd[i] = 0;
        cov[i].clear();
        mom[i] = mn[i] = sdom[i] = i;
    }
    dfs(s);
    REPD(i, n, 2) {
        int u = nfd[i];
        if (u == 0)
            continue;
        for (int v : pred[u])
            if (dfn[v]) {
                eval(v);
                if (cmp(sdom[mn[v]], sdom[u]))
                    sdom[u] = sdom[mn[v]];
            }
        cov[sdom[u]].push_back(u);
        mom[u] = par[u];
        for (int w : cov[par[u]]) {
            eval(w);
            if (cmp(sdom[mn[w]], par[u]))
                idom[w] = mn[w];
            else
                idom[w] = par[u];
        }
        cov[par[u]].clear();
    }
    REP(i, 2, n) {
        int u = nfd[i];
        if (u == 0)
            continue;
        if (idom[u] != sdom[u])
            idom[u] = idom[idom[u]];
    }
}
} domT;

```

4.7 Floyd-Warshall Algorithm

```

int dis[N][N];
void init(int n) {
    for (int i = 0; i <= n; i++) { // 初始化
        for (int j = 0; j <= n; j++)
            dis[i][j] = INF;
        dis[i][i] = 0;
    }
}
void floyd_warshall(int n) {
    for (int k = 0; k < n; k++) { // 窮舉中繼點 k
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) { // 窮舉點對 (i, j)
                dis[i][j] = min(dis[i][j], dis[i][k] + dis[k][j]);
            }
        }
    }
}

```

4.8 Maximum Clique

```

#define N 111 // 80 ~ 100 左右
struct MaxClique { // 0-base
    typedef bitset<N> Int;
    Int linkto[N], v[N];
    int n;

```

```

void init(int _n) {
    n = _n;
    for (int i = 0; i < n; i++) {
        linkto[i].reset();
        v[i].reset();
    }
}
void addEdge(int a, int b) {
    v[a][b] = v[b][a] = 1;
}
int popcount(const Int& val) {
    return val.count();
}
int lowbit(const Int& val) {
    return val._Find_first();
}
int ans, stk[N];
int id[N], di[N], deg[N];
Int cans;
void maxclique(int elem_num, Int candi) {
    if (elem_num > ans) {
        ans = elem_num;
        cans.reset();
        for (int i = 0; i < elem_num; i++)
            cans[id[stk[i]]] = 1;
    }
    int potential = elem_num + popcount(candi);
    if (potential <= ans)
        return;
    int pivot = lowbit(candi);
    Int smaller_candi = candi & (~linkto[pivot]);
    while (smaller_candi.count() && potential > ans) {
        int next = lowbit(smaller_candi);
        candi[next] = !candi[next];
        smaller_candi[next] = !smaller_candi[next];
        potential--;
        if (next == pivot ||
            (smaller_candi & linkto[next]).count()) {
            stk[elem_num] = next;
            maxclique(elem_num + 1, candi & linkto[next]);
        }
    }
}
int solve() {
    for (int i = 0; i < n; i++) {
        id[i] = i;
        deg[i] = v[i].count();
    }
    sort(id, id + n,
        [&](int id1, int id2) { return deg[id1] > deg[id2]; });
    for (int i = 0; i < n; i++)
        di[id[i]] = i;
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            if (v[i][j])
                linkto[di[i]][di[j]] = 1;
    Int cand;
    cand.reset();
    for (int i = 0; i < n; i++)
        cand[i] = 1;
    ans = 1;
    cans.reset();
    cans[0] = 1;
    maxclique(0, cand);
    return ans;
}
} solver;

```

4.9 Kosaraju's Algorithm for SCC

```

#define FZ(x) memset(x, 0, sizeof(x)) // fill zero
struct Scc {
    int n, nScc, vst[MAX_N], bln[MAX_N];
    vector<int> E[MAX_N], rE[MAX_N], vec;
    void init(int _n) {
        n = _n;
        for (int i = 0; i <= n; i++)
            E[i].clear(), rE[i].clear();
    }
    void addEdge(int u, int v) {
        E[u].PB(v);
        rE[v].PB(u);
    }

```

```

}
void DFS(int u) {
    vst[u] = 1;
    for (auto v : E[u])
        if (!vst[v])
            DFS(v);
    vec.PB(u);
}
void rDFS(int u) {
    vst[u] = 1;
    bln[u] = nScc; // 編號是 0-base
    for (auto v : rE[u])
        if (!vst[v])
            rDFS(v);
}
void solve() {
    nScc = 0;
    vec.clear();
    fill(vst, vst + n + 1, 0);
    for (int i = 0; i < n; i++)
        if (!vst[i])
            DFS(i);
    reverse(vec.begin(), vec.end());
    fill(vst, vst + n + 1, 0);
    for (auto v : vec)
        if (!vst[v]) {
            rDFS(v);
            nScc++;
        }
}
};

```

5 Tree Algorithms

5.1 Lowest Common Ancestor

```

#include <bits/stdc++.h>
using namespace std;

const int N = 2e5 + 5, logN = 20;
vector<int> g[N];

int timing = 1, logn, n;
int in[N], out[N];
int anc[N][logN], depth[N];

// 建立倍增表
void build_table(int n) {
    logn = log2(n);
    for (int i = 1; i < logN; i++) {
        for (int now = 1; now <= n; now++) {
            anc[now][i] = anc[anc[now][i - 1]][i - 1];
        }
    }
}

// 建立時間戳記
// 跑一遍 DFS 得到誰是誰的父親
void dfs_init(int u, int pre) {
    in[u] = timing++; // 這時進入 u
    anc[u][0] = pre; // now 的 0 倍祖先是 pre
    for (int nxt : g[u]) { // 跑過所有孩子
        if (pre == nxt)
            continue;
        depth[nxt] = depth[u] + 1;
        dfs_init(nxt, u);
    }
    out[u] = timing++; // 這時離開 u
}

// 判斷是否是祖先
bool is_ancestor(int u, int v) {
    return (in[u] < in[v] && out[v] < out[u]);
}

// 找最低共同祖先
int getlca(int x, int y) {
    if (is_ancestor(x, y)) // 如果 u 為 v 的祖先則 lca 為 u
        return x;
    if (is_ancestor(y, x)) // 如果 v 為 u 的祖先則 lca 為 u
        return y;
}

```

```

return y;

// 判斷 2^logN, 2^(logN-1), ..., 2^1, 2^0 倍祖先
for (int i = logn; i >= 0; i--) {
    // cout << anc[x][i] << '\n';
    if (!is_ancestor(anc[x][i], y) &&
        anc[x][i]) // 如果 2^i 倍祖先不是 v 的祖先
        x = anc[x][i]; // 則往上移動
}
return anc[x][0]; // 回傳此點的父節點即為答案
}

// 以下是樹上差分
int tag[N], f[N], ans[N], root;
void add(int x, int y) {
    int lca = getlca(x, y);
    tag[x]++;
    tag[y]++;
    tag[lca]--;
    if (lca != root)
        tag[f[lca]]--;
}

int dfs_add(int now, int fa) {
    int diff = tag[now];
    for (auto nxt : g[now]) {
        if (nxt == fa)
            continue;
        diff += dfs_add(nxt, now);
    }
    return ans[now] = diff;
}

```

5.2 Euler Tour for LCA

```

#include <bits/stdc++.h>
using namespace std;

const int N = 1e5 + 5;

vector<int> tour, edge[N];
int timing = 0;
int in[N], out[N];

void dfs(int u, int fa) {
    tour.push_back(u); // 進入的時間點
    in[u] = tour.size() - 1;
    for (auto v : edge[u]) {
        if (v == fa)
            continue;
        dfs(v, u);
        tour.push_back(u); // 走完其中一個孩子 再走回自己
    }
    out[u] = tour.size() - 1;
}

void build(vector<int>& tour) { // 把 tour 丟進線段樹初始化
    seg.build(tour); // 除了 tour，還要建每個點的深度
}

int query(int x, int y) {
    if (is_ancestor(x, y))
        return x; // LCA(x, y) = x
    if (is_ancestor(y, x))
        return y; // LCA(x, y) = y;
    if (out[y] < in[x])
        swap(x, y); // 如果「y 的區間」在「x 的區間」的左邊，就交換
    int index =
        seg.query(out[x], in[y]); // 取得區間內哪個位置的深度是最低的
    return tour[index];
}

```

5.3 DSU on Tree

```

int find(int x) {
    if (f[x] == x)
        return x;
    else
        return f[x] = find(f[x]);
}

```



```

}

void merge(int x, int y) {
    x = find(x), y = find(y);
    if (sz[x] < sz[y])
        swap(x, y);
    sz[x] += sz[y];
    f[y] = x;
}

void init() {
    // 初始化一開始大小都為1 (每群一開始都是獨立一個)
    for (int i = 1; i <= n; i++)
        sz[i] = 1;
    for (int i = 1; i <= n; i++)
        f[i] = i;
}

```

6 String Algorithms

6.1 Suffix Array (SAIS)

```

// 此為後綴陣列模板
// 用法:
// 把要處理的字串轉成整數陣列傳入suffix_array(), 會得到SA
// 與H維結果
const int N = 500010; // 有可能要在這就寫原本字串的兩倍長
struct SA {
#define REP(i, n) for (int i = 0; i < int(n); i++)
#define REP1(i, a, b) for (int i = (a); i <= int(b); i++)
    bool _t[N * 2];
    int _s[N * 2], _sa[N * 2], _c[N * 2], x[N], _p[N], _q[
        N * 2],
        hei[N], r[N];
    int operator[](int i) {
        return _sa[i];
    }
    void build(int *s, int n, int m) {
        memcpy(_s, s, sizeof(int) * n);
        sais(_s, _sa, _p, _q, _t, _c, n, m);
        mkhei(n);
    }
    void mkhei(int n) {
        REP(i, n) r[_sa[i]] = i;
        hei[0] = 0;
        REP(i, n) if (r[i]) {
            int ans = i > 0 ? max(hei[r[i] - 1] - 1, 0) :
                0;
            while (_s[i + ans] == _s[_sa[r[i] - 1] + ans])
                ans++;
            hei[r[i]] = ans;
        }
    }
    void sais(int *s, int *sa, int *p, int *q, bool *t,
        int *c, int n,
        int z) {
        bool uniq = t[n - 1] = true, neq;
        int nn = 0, nmzx = -1, *nsa = sa + n, *ns = s + n,
            lst = -1;
#define MS0(x, n) memset((x), 0, n * sizeof(*(x)))
#define MAGIC(XD) \
        MS0(sa, n); \
        memcpy(x, c, sizeof(int) * z); \
        XD; \
        memcpy(x + 1, c, sizeof(int) * (z - 1)); \
        REP(i, n) \
        if (sa[i] && !t[sa[i] - 1]) \
            sa[x[s[sa[i] - 1]]++] = sa[i] - 1; \
        memcpy(x, c, sizeof(int) * z); \
        for (int i = n - 1; i >= 0; i--) \
            if (sa[i] && t[sa[i] - 1]) \
                sa[--x[s[sa[i] - 1]]] = sa[i] - 1; \
        MS0(c, z); \
        REP(i, n) uniq &= ++c[s[i]] < 2; \
        REP(i, z - 1) c[i + 1] += c[i]; \
        if (uniq) { \
            REP(i, n) sa[--c[s[i]]] = i; \
            return; \
        } \
        for (int i = n - 2; i >= 0; i--) \
            t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s \
                [i + 1]); \
        MAGIC(REP1(i, 1, n - 1) if (t[i] && !t[i - 1]) sa \
            [--x[s[i]]] =

```

```

        p[q[i] = nn++] = i);
        REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i] - 1])
            {
                neq = lst < 0 ||
                    memcmp(s + sa[i], s + lst,
                        (p[q[sa[i]] + 1] - sa[i]) *
                            sizeof(int));
                ns[q[lst = sa[i]]] = nmzx += neq;
            }
        sais(ns, nsa, p + nn, q + n, t + n, c + z, nn,
            nmzx + 1);
        MAGIC(for (int i = nn - 1; i >= 0; i--) sa[--x[s[p
            [nsa[i]]]]] =
                p[nsa[i]]);
    }
} sa;
int H[N], SA[N]; // SA: 後綴陣列的Length
// H[i]: SA[i]與SA[i - 1]的共同子字串長
void suffix_array(int *ip, int len) {
    // should padding a zero in the back
    // ip is int array, len is array length
    // ip[0..n-1] != 0, and ip[len] = 0
    ip[len++] = 0;
    sa.build(ip, len, 128);
    for (int i = 0; i < len; i++) {
        H[i] = sa.hei[i + 1];
        SA[i] = sa._sa[i + 1];
    }
    // resulting height, sa array \in [0, len)
}

```

6.2 Z-algorithm

```

int z[MAXN];
void Z_value(const string& s) {
    // z[i] = lcp(s[1...], s[i...])
    int i, j, left, right, len = s.size();
    left = right = 0;
    z[0] = len;
    for (i = 1; i < len; i++) {
        j = max(min(z[i - left], right - i), 0);
        for (; i + j < len && s[i + j] == s[j]; j++)
            ;
        z[i] = j;
        if (i + z[i] > right) {
            right = i + z[i];
            left = i;
        }
    }
}

```

6.3 Knuth-Morris-Pratt Algorithm

```

int failure[MAX_N];
vector<int> KMP(string& t, string& p) {
    vector<int> ret; // 要保證長度 t > p
    for (int i = 1, j = failure[0] = -1; i < p.size(); ++i)
        while (j >= 0 && p[j + 1] != p[i])
            j = failure[j];
        if (p[j + 1] == p[i])
            j++;
        failure[i] = j;
    }
    for (int i = 0, j = -1; i < t.size(); ++i) {
        while (j >= 0 && p[j + 1] != t[i])
            j = failure[j];
        if (p[j + 1] == t[i])
            j++;
        if (j == p.size() - 1) {
            ret.push_back(i - p.size() + 1);
            j = failure[j];
        }
    }
    return ret;
}

```

6.4 Manacher's Algorithm

```

int ans[MAXN << 1];
char s[MAXN << 1];
string ret; // 迴文字串儲存結果
void find_palindrome(char *s, int len, int *z) {
    int idx = 0, mx = -1;

```

```

for (int i = 0; i < len; i++) { // 找迴文半徑最大值
    if (mx < ans[i]) {
        idx = i;
        mx = ans[i];
    }
}
for (int i = idx - mx + 1; i < idx; i++)
    if (s[i] != '@')
        ret.push_back(s[i]);
for (int i = idx; i <= idx + mx - 1; i++)
    if (s[i] != '@')
        ret.push_back(s[i]);
// cout << ret << '\n'; ///// 直接輸出
}
void z_value_pal(char *s, int len, int *z) { // 字串，長度，輸出的陣列
    len = (len << 1) + 1;
    for (int i = len - 1; i >= 0; i--)
        s[i] = i & 1 ? s[i >> 1] : '@';
    z[0] = 1;
    for (int i = 1, l = 0, r = 0; i < len; i++) {
        z[i] = i < r ? min(z[l + l - i], r - i) : 1;
        while (i - z[i] >= 0 && i + z[i] < len &&
            s[i - z[i]] == s[i + z[i]])
            ++z[i];
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    find_palindrome(s, strlen(s), z);
}

```

6.5 Minimum Rotation

```

int min_rotation(string s) {
    int a = 0, N = s.size();
    s += s;
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++) {
            if (a + j == i || s[a + j] < s[i + j]) {
                i += max(0, j - 1);
                break;
            }
            if (s[a + j] > s[i + j]) {
                a = i;
                break;
            }
        }
    }
    return a;
}
// rotate(begin(s), begin(s) + minRotation(s), end(s))
// 上面註解可以直接讓一個字串做 rotate，得到字典序最小的 rotation

```

6.6 Rolling Hash

```

ll P1 = 75577, P2 = 12721, MOD = 998244353;
pii hashes[MAXN], hashes2[MAXN];
string s1, s2;
void build(string s, pii hash) {
    ll val1 = 0, val2 = 0;
    for (int i = 0; i < s.length(); i++) {
        val1 = (val1 * P1 % MOD + s[i]) % MOD;
        val2 = (val2 * P2 % MOD + s[i]) % MOD;
        hash[i] = {val1, val2};
    }
}
ll minus(ll a, ll b) {
    return (a - b + MOD) % MOD;
}
ll cnt_occur() { // 檢查
    int n = s1.size(), k = s2.size();
    ll cnt = (hashes2[k - 1].x == hashes[k - 1].x &&
        hashes2[k - 1].y == hashes[k - 1].y);
    ll val1 = 0, val2 = 0;
    for (int i = 1, j = k; j < n; j++, i++) {
        val1 = minus(hashes[j].x, hashes[i - 1].x * fpow(P1,
            j - i + 1));
        val2 = minus(hashes[j].y, hashes[i - 1].y * fpow(P1,
            j - i + 1));
        if (hashes2[k - 1].x == val1 && hashes2[k - 1].y ==
            val2)
            cnt++;
    }
}

```

```

}
}

```

7 Geometry

7.1 Basic Geometry Structure

```

int dcmp(ld x) { // 處理小數點精度的東東
    if (abs(x) < eps)
        return 0;
    else
        return x < 0 ? -1 : 1;
}
struct Pt {
    ld x, y;
    Pt(ld _x = 0, ld _y = 0) : x(_x), y(_y) {}
    Pt operator+(const Pt &a) {
        return Pt(x + a.x, y + a.y);
    }
    Pt operator-(const Pt &a) {
        return Pt(x - a.x, y - a.y);
    }
    Pt operator*(const ld &a) {
        return Pt(x * a, y * a);
    }
    Pt operator/(const ld &a) {
        return Pt(x / a, y / a);
    }
    ld operator*(const Pt &a) { // 內積
        return x * a.x + y * a.y;
    }
    ld operator^(const Pt &a) { // 行列式(叉乘)
        return x * a.y - y * a.x;
    }
    bool operator<(const Pt &a) const {
        return x < a.x || (x == a.x && y < a.y);
    }
    friend ld cross(Point a, Point b, Point o) {
        // 行列式(叉乘)，存入三個點
        Point p1 = a - o, p2 = b - o;
        return p1.x * p2.y - p1.y * p2.x;
    }
    // return dcmp(x-a.x) < 0 || (dcmp(x-a.x) == 0 && dcmp(
        (y-a.y) < 0);
    // }
    bool operator==(const Pt &a) {
        return dcmp(x - a.x) == 0 && dcmp(y - a.y) == 0;
    }
};

ld norm2(const Pt &a) { // 平方
    return a * a;
}
ld norm(const Pt &a) {
    return sqrt(norm2(a));
}
Pt perp(const Pt &a) { // 與原本向量垂直的向量
    return Pt(-a.y, a.x);
}
Pt rotate(const Pt &a, ld ang) { // 旋轉矩陣
    return Pt(a.x * cos(ang) - a.y * sin(ang),
        a.x * sin(ang) + a.y * cos(ang));
}

struct Line {
    Pt s, e, v; // start, end, end-start
    ld ang;
    Line(Pt _s = Pt(0, 0), Pt _e = Pt(0, 0)) : s(_s), e(_e) {
        v = e - s;
        ang = atan2(v.y, v.x);
    }
    bool operator<(const Line &L) const {
        return ang < L.ang;
    }
};

struct Circle {
    Pt o;
    ld r;
    Circle(Pt _o = Pt(0, 0), ld _r = 0) : o(_o), r(_r) {}
};

```



```
}

```

8.2 Quick Sort

```
template <typename T>
void quick_sort(T arr[], int l, int r) {
    // 陣列元素少於 1 直接結束
    if (r <= l + 1)
        return;

    // 左邊和右邊的指針
    int li = l + 1, ri = r - 1;
    // 判定的基準點
    T pivot = arr[l];

    // TODO: 左邊 <= 基準點 < 右邊
    while (li != ri) {
        // 右邊的指針往左移動，找比基準點小的值
        while (arr[ri] > pivot && li < ri)
            ri--;
        // 左邊的指針往右移動，找比基準點大的值
        while (arr[li] <= pivot && li < ri)
            li++;
        // 當左右指針沒有相遇時，表示不滿足 TODO
        if (li < ri)
            swap(arr[li], arr[ri]);
    }

    // 將基準點移到指針相遇的地方
    arr[l] = arr[li];
    arr[li] = pivot;

    quick_sort(arr, l, li);    // 處理基準點的左邊
    quick_sort(arr, li + 1, r); // 處理基準點的右邊
}
```

```
// ##          ##
// #####
//          ##
//          ##          ##
//          ##          ##
//          ##          ##
//          ##          ##
//          ##          ##
// #####
//
//          元首保佑 永無BUG

```

```
//
//          < @ \
// \_/_/_/_/ \_/_/_/_/ \_/_/_/_/
// \_/_/_/_/ \_/_/_/_/ \_/_/_/_/
// \_/_/_/_/ \_/_/_/_/ \_/_/_/_/
//          u/u/u/****/u\u\u
//          u/u/****/\u\u
//          |*|*|
//          | |
//          /+--+\\
//          || ☒ ||
//          \\=//
//
//          神獸保佑 永無BUG

```

9 Miscellaneous

9.1 Discretization

```
int arr[MAX_N], tmp[MAX_N], n;
// arr[i] 是初始陣列，長度為n，且 0-base
void discretization() {
    for (int i = 0; i < n; i++) // 將 arr 複製到 tmp
        tmp[i] = arr[i];
    sort(tmp, tmp + n);          // 排序
    int len = unique(tmp, tmp + n) - (tmp); // 把 tmp 裡
    重複的數字去掉
    for (int i = 0; i < n; i++)
        arr[i] = lower_bound(tmp, tmp + len, arr[i]) - tmp;
    ; // 二分搜
}
```

9.2 Blessing

```
//          !#####          #
//          !#####!          ##!
//          !#####!          ###
//          !#####          ####
//          #####          #####
//          !###!          !#####          #####
//          !          #####          #####!
//          !#####!          #####
//          #####          #####
//          !#####!          #####!
//          #####!          #####
//          ##          #####
//          ,#####!          !#####
//          ,###,#####!#####!
//          ,####'          #####!          #####
//          ,####'          #####          !#####!
//          #####          #####
//          ~##          #####
//
//          同志保佑 永無BUG

```

```
// ##          #####
// ##          ##
// ##          ##
// ##          ##
// ##          ##
// ##          ##
// ##          ##

```

9.3 Graph Paper



