

2.

A)

aa=(return value from fact(6))
main

aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=4*(return value from fact(3))
n=4
aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=3*(return value from fact(2))
n=3
aa=4*(return value from fact(3))
n=4
aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=2*(return value from fact(1))
n=2
aa=3*(return value from fact(2))
n=3
aa=4*(return value from fact(3))
n=4

aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

result=1
n=1
aa=2*(return value from fact(1))
n=2
aa=3*(return value from fact(2))
n=3
aa=4*(return value from fact(3))
n=4
aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=2*1=2
n=2
aa=3*(return value from fact(2))
n=3
aa=4*(return value from fact(3))
n=4
aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=3*2=6
n=3
aa=4*(return value from fact(3))
n=4
aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6

aa=(return value from fact(6))
main

aa=4*6=24
n=4
aa=5*(return value from fact(4))
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=5*24=120
n=5
aa=6*(return value from fact(5))
n=6
aa=(return value from fact(6))
main

aa=6*120=720
n=6
aa=(return value from fact(6))
main

aa=720
main

Time complexity: $O(N)$.

B)

I would use the tree structure. Moving N disks from rod A to rod B equals moving $(N-1)$ disks from rod A to rod C and move the N disk from A to B and move $(N-1)$ disks from rod C to rod B. Thus, the time taken $T(N)$ equals $2T(N-1)+1$. It is easy to know that moving one disk from a rod to another takes 1 step which means $T(1)=1$. So a recursive method could be used in Towers of Hanoi problem. The steps are shown in the Java code.

Move disk-1 from rod A to rod C

Move disk-2 from rod A to rod B

Move disk-1 from rod C to rod B

Move disk-3 from rod A to rod C

Move disk-1 from rod B to rod A

Move disk-2 from rod B to rod C

Move disk-1 from rod A to rod C

Move disk-4 from rod A to rod B

Move disk-1 from rod C to rod B
Move disk-2 from rod C to rod A
Move disk-1 from rod B to rod A
Move disk-3 from rod C to rod B
Move disk-1 from rod A to rod C
Move disk-2 from rod A to rod B
Move disk-1 from rod C to rod B
Move disk-5 from rod A to rod C
Move disk-1 from rod B to rod A
Move disk-2 from rod B to rod C
Move disk-1 from rod A to rod C
Move disk-3 from rod B to rod A
Move disk-1 from rod C to rod B
Move disk-2 from rod C to rod A
Move disk-1 from rod B to rod A
Move disk-4 from rod B to rod C
Move disk-1 from rod A to rod C
Move disk-2 from rod A to rod B
Move disk-1 from rod C to rod B
Move disk-3 from rod A to rod C
Move disk-1 from rod B to rod A
Move disk-2 from rod B to rod C
Move disk-1 from rod A to rod C
Move disk-6 from rod A to rod B
Move disk-1 from rod C to rod B
Move disk-2 from rod C to rod A
Move disk-1 from rod B to rod A
Move disk-3 from rod C to rod B
Move disk-1 from rod A to rod C
Move disk-2 from rod A to rod B
Move disk-1 from rod C to rod B
Move disk-4 from rod C to rod A
Move disk-1 from rod B to rod A
Move disk-2 from rod B to rod C
Move disk-1 from rod A to rod C
Move disk-3 from rod B to rod A
Move disk-1 from rod C to rod B
Move disk-2 from rod C to rod A
Move disk-1 from rod B to rod A
Move disk-5 from rod C to rod B
Move disk-1 from rod A to rod C
Move disk-2 from rod A to rod B
Move disk-1 from rod C to rod B
Move disk-3 from rod A to rod C

Move disk-1 from rod B to rod A
 Move disk-2 from rod B to rod C
 Move disk-1 from rod A to rod C
 Move disk-4 from rod A to rod B
 Move disk-1 from rod C to rod B
 Move disk-2 from rod C to rod A
 Move disk-1 from rod B to rod A
 Move disk-3 from rod C to rod B
 Move disk-1 from rod A to rod C
 Move disk-2 from rod A to rod B
 Move disk-1 from rod C to rod B

C)

Iterative:

For i from 0 to n=6, result=result*x.
 result is initialized as 1.

i=0	result = result * x = 1 * x = x
i=1	result = result * x = x * x = x ²
i=2	result = result * x = x ² * x = x ³
i=3	result = result * x = x ³ * x = x ⁴
i=4	result = result * x = x ⁴ * x = x ⁵
i=5	result = result * x = x ⁵ * x = x ⁶

Recursive:

If n equals 1, pow(x,n)=x

Otherwise, pow(x,n)=pow(x,(n-1))*x

aa=(return value from pow(x, 6))
main

aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
main

aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
main

aa=x*(return value from pow(x,3))

n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main

aa=x*(return value from pow(x, 2))
n=3
aa=x*(return value from pow(x, 3))
n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main

aa=x*(return value from pow(x, 1))
n=2
aa=x*(return value from pow(x, 2))
n=3
aa=x*(return value from pow(x, 3))
n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main

result=x
n=1
aa=x*(return value from pow(x, 1))
n=2
aa=x*(return value from pow(x, 2))
n=3
aa=x*(return value from pow(x, 3))
n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))

n=6
aa=(return value from pow(x, 6))
Main

aa=x*x=x ²
n=2
aa=x*(return value from pow(x, 2))
n=3
aa=x*(return value from pow(x, 3))
n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main

aa=x* x ² = x ³
n=3
aa=x*(return value from pow(x, 3))
n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main

aa=x* x ³ = x ⁴
n=4
aa=x*(return value from pow(x, 4))
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main

aa=x* x ⁴ = x ⁵
n=5
aa=x*(return value from pow(x, 5))
n=6
aa=(return value from pow(x, 6))
Main


until $n=1$ which returns the array $\{0, 1\}$.

Then we got the array of $n=2$ with the algorithm: $\{00, 01, 11, 10\}$.


Then we got the array of $n=3$ with the algorithm: $\{000, 001, 011, 010, 110, 111, 101, 100\}$.

So on and so forth until we finally get the array of $n=6$, which is: $\{000000, 000001, 000011, 000010, 000110, 000111, 000101, 000100, 001100, 001101, 001111, 001110, 001010, 001011, 001001, 001000, 011000, 011001, 011011, 011010, 011110, 011111, 011101, 011100, 010100, 010101, 010111, 010110, 010010, 010011, 010001, 010000, 110000, 110001, 110011, 110010, 110110, 110111, 110101, 110100, 111100, 111101, 111111, 111110, 111010, 111011, 111001, 111000, 101000, 101001, 101011, 101010, 101110, 101111, 101101, 101100, 100100, 100101, 100111, 100110, 100010, 100011, 100001, 100000\}$.


4.




enqueue all input data:




dequeue three elements:



enqueue two elements:



dequeue all elements:










5.




a)

h H u f m a n c o d i g s t p
1 1 1 2 3 5 3 2 4 2 4 2 3 2 1

r e l j o
2 1 1 6 1







Suppose '0' is used for left edges and '1' for right edges

Then the Huffman code is:

'f':00000 'c':00001 'd':00010 'g':00011 't':00100 'r':00101 'u':001100 'p':001101 'e':001110
'l':001111 'h':010000 'H':010001 '.':01001 'm':0101 'n':0110 's':0111 ' ':100 'a':101 'o':110 'i':111

b)

char	ASCII	Before	After
f	102	1100110	00000
c	99	1100011	00001
d	100	1100100	00010
g	103	1100111	00011
t	116	1110100	00100
r	114	1110010	00101
u	117	1110101	001100
p	112	1110000	001101
e	101	1100101	001110
l	108	1101100	001111
h	104	1101000	010000
H	72	1001000	010001
.	46	0101110	01001
m	109	1101101	0101
n	110	1101110	0110
s	115	1110011	0111
(space)	32	0100000	100
a	97	1100001	101
o	111	1101111	110
i	105	1101001	111

Before compression, 7 bits are needed for each char, but only 6 bits are needed for each char at most after compression.

Before compression, $47 \times 7 = 329$ bits are needed for the whole sentence

After compression, 194 bits are needed for the whole sentences, 135 bits, 41.0% of the space is saved.

d) The Huffman coding needs to compare the frequency of the appearance of each letter. A PriorityQueue can help identify which one has the highest frequency. The algorithm implements PriorityQueue through comparing the frequency integer in each node, and returns the node that has the lowest frequency while polling.

f)

The result of the program is:

110001101011000000000110010011110000111110110011111011100011001111101110001
010011001010110110101000011111001101101010010110000101110111111111001111000
10101010000111100010111111011110100011010100

194 bits in total which is exactly the same as that I did step-by-step. However, the Huffman code is not exactly the same:

{ =100, a=010, c=0011, d=11001, e=110000, f=0000, g=0001, H=110001, h=110100, i=1111, l=101010, m=0110, n=0111, .=10100, o=1110, p=110101, r=0010, s=1011, t=11011, u=101011}

The reason is that when I choose the nodes with the same frequency, I didn't choose them exactly the same order as that the computer did. So it results in the difference of Huffman code. However, for the reason that they have the same frequency, it won't have any influence on the final result. The space the Huffman code cost should be exactly the same.