Database coverage and recoverable concentration evidence

Frozen native records · source reconciliation 5 November · signature parser HARMONIZED-AMP-1.1.0

Database	Evidence counts and source references	Information sources
TIGER complete archive	Native records: 50,992 Measurement / safety rows: 346,095 / 36,218 Restricted MIC / toxicity signatures: 160,009 / 4,085 References: 7,610 reference keys	Original papers and supplements; independent semantic reading and structured extraction.
TIGER core subset	Native records: 37,800 Measurement / safety rows: 313,005 / 32,250 Restricted MIC / toxicity signatures: 154,931 / 3,975 References: 6,874 reference keys	Core concentration-evidence selection from the independently extracted TIGER archive.
DRAMP 5.0	Native records: 32,296 Target / host annotation entries: 9,104 / 3,996 Restricted MIC / toxicity signatures: 10,684 / 445 References: 4,538 citation identities	Papers, patents and specialized clinical / structural collections. Patent exports lack assay fields.
DBAASP v4	Native records: 25,542 Target-activity / safety rows: 197,338 / 23,692 Restricted MIC / toxicity signatures: 101,391 / 3,997 References: 4,972 citation identities	Referenced experimental studies and patents; structured native activity / host-response arrays.
dbAMP 3.0	Native records: 35,600 Target / host annotation entries: 17,810 / 7,339 Restricted MIC / toxicity signatures: 50,516 / 50 References: 5,228 citation identities	Literature-linked sequence and functional collections; target annotations and functional tags.

Source rows, annotated entries and restricted signatures are distinct units; no column gives a universal total of comparable assays.

Counting definitions and source notes

Native identities

TIGER counts literature-specific peptide entity IDs; comparator IDs follow their source resources. Canonical sequences or chemical identities are separate counting units. The fixed denominators are 50,992 / 37,800 / 32,296 / 25,542 / 35,600.

Original records and annotation coverage

TIGER rows come directly from original measurements.tsv and safety.tsv files, restricted to the current archive or core membership. DBAASP rows use main-entry targetActivities and hemoliticCytotoxicActivities arrays. These native columns include endpoint and value types beyond eligible concentration records. DRAMP and dbAMP figures count annotated or function-tagged entries; their bulk exports do not establish complete measurement totals. Host-directed activity is not automatically reassigned to toxicity.

Restricted signatures

HARMONIZED-AMP-1.1.0 retains the same microbial/host panel, MIC and selected 50%-response endpoints, directly equivalent native units, and positive scalar or one-sided-bound values. Each distinct native-entry × target/host × endpoint × unit × operator × value combination is counted once. Source-reported strain and resistance-phenotype labels remain distinct; a phenotype-only label does not establish an individual strain. Identical values repeated under other references or conditions collapse. Parser and context repairs improve recovery without changing the stated biological scope. These counts do not measure all experiments or independently validated assays.

Source references

TIGER archive and core retain 7,610 and 6,874 reference keys. The reconciled DBAASP / DRAMP / dbAMP source identities number 4,972 / 4,538 / 5,228. They include 17 / 527 / 0 patent identities and 0 / 149 / 0 other source records, respectively. DOI/PMID aliases are reconciled; citations awaiting identity review remain flagged. Patent publication IDs are not merged into patent families. The cross-resource unmatched paper/preprint union is 4,862, separate from 541 unmatched patent identities.

Version and source data

Scientific data remain DRR_20261025_TARGET_IDENTITY. This revision does not correct production source rows or silently alter the scientific release. Source-record and reference audits are dated 5 November 2026; parser revision and table assembly are dated 6 November 2026. Machine-readable table values, counting rules, input checksums and row-level audits accompany the figures.

Attribution

Comparator data originate from the official DRAMP 5.0, DBAASP v4 and dbAMP 3.0 exports and APIs. Their source papers and public interfaces are credited in the manuscript. The original version and prior comparison table remain archived.