

# 完整code

## 網頁建立

index.html(之前建立過，繼承base.html)

```
{% extends 'base.html'%}

{% block title %}{{pageTitle}}{% endblock %}

{% block main %}
<form action='' method="POST">{% csrf_token %}

    搜尋：<input type="search" name="cName" placeholder="請輸入人名"><br>

    <input type="submit" value="送出">
    <!--<h1>{{mainTitle}}</h1>-->
    <!--<p>{{mainContent}}</p>-->
</form>

    {% if unit %}
        <tr>
            <td>編號：{{unit.id}}</td><br>
            <td>姓名：{{unit.cName}}</td><br>
            <td>性別：{{unit.cSex}}</td><br>
            <td>生日：{{unit.cBirthday}}</td><br>
            <td>Email：{{unit.cEmail}}</td><br>
            <td>手機：{{unit.cPhone}}</td><br>
            <td>地址：{{unit.cAddr}}</td><br>
        </tr>
    {% else %}
    {% endif %}
    {% if cc %}
        <p>{{username}}，沒這個人</p>
    {% endif %}

{% endblock %}
```

=====

views.py

```

from django.shortcuts import render, redirect
from django.http import HttpResponse
from datetime import datetime
from myapp.models import student
from django.http import Http404
from django.contrib import auth
from django.http import HttpResponseRedirect

def main(request):
    pageTitle="子網頁繼承"
    # mainTitle="段落標題"
    # mainContent="段落內文"
    # article1={"aTitle":"人名","aContent":"資料"}
    # article2={"aTitle":"文章標題","aContent":"文章2內文"}
    # articles=[article1]

    cc = False
    if request.method == "POST":

        username = request.POST['cName']

        check = student.objects.filter(cName__exact=username)
        if check:

            unit = student.objects.get(cName=username)

        else:
            cc = True

    return render(request, 'index.html', locals())

```

=====

## urls.py

```

from django.contrib import admin
from django.urls import path,include
from myapp import views

urlpatterns = [
    path('admin/', admin.site.urls),
    path('helloworld/',views.helloworld),
    path('', views.main),
    path('hi/<username>/', views.hiname),      # 傳遞字串參數 username
    path('age/<int:year>/', views.age),        # 傳遞數值參數 year
    path('hello/', views.hello_view),
    path('getName/<username>/', views.getOneByName), # 傳遞字串參數 username
    path('getAll/', views.getAll),

```

```
# path(r'^admin/', admin.site.urls),  
# path(r'^$', sayhello),  
]
```