## ✓ Congratulations! You passed!

Next Item



1. **Red-black BST with no extra memory.** Describe how to save the memory for storing the color information when implementing a red-black BST.

1/1 point

Note: these interview questions are ungraded and purely for your own enrichment. To get a hint, submit a solution.

Save extra memory for storing the color information:

Modify the structure of the BST to encode the color information.

Your answer cannot be more than 10000 characters.

## Thank you for your response.

*Hint*: modify the structure of the BST to encode the color information.



1 / 1

point

. **Document search.** Design an algorithm that takes a sequence of n document words and a sequence of m query words and find the shortest interval in which the m query words appear in the document in the order given. The length of an interval is the number of words in that interval.

n document words and m query words.

for each word, maintain a sorted list of the indices in the document in which that word appears. Scan through the sorted lists of the query words in a judicious manner.

Your answer cannot be more than 10000 characters.

## Thank you for your response.

*Hint*: for each word, maintain a sorted list of the indices in the document in which that word appears. Scan through the sorted lists of the query words in a judicious manner.



Generalized queue. Design a generalized queue data type that supports all of the following operations in logarithmic time (or better) in the worst case.

1/1 point

- Create an empty data structure.
- Append an item to the end of the queue.
- Remove an item from the front of the queue.
- ullet Return the  $i^{th}$  item in the queue.
- ullet Remove the  $i^{th}$  item from the queue.

Generalized Queue.

Created a red-black BST where the keys are integers and the values are the items, such that the ith largest integer key in the red-black BST corresponds to the ith item in the queue.

Your answer cannot be more than 10000 characters.

## Thank you for your response.

Hint: create a red-black BST where the keys are integers and the values are the items such that the  $i^{th}$  largest integer key in the red-black BST corresponds to the  $i^{th}$  item in the queue.





