

COM SCI 188

Intro to Robotics

Lecture 6

Yuchen Cui
Winter 2026




Agenda

- Announcements
- Cameras: 2D & 3D
- Camera Calibration
- <break>
- Computer Vision Basics
 - Image Processing
 - Convolutional Neural Networks

Announcements


- **Coding Assignment 1 – ddl extended to Sunday**
- Problem Set 2 due next Friday
- Discussion
 - More on Quaternions & PID control
 - Practice problems

Recap: Cameras



Pinhole Camera


- Geometric camera
- Pinhole passes light \rightarrow dim image
- No focus plane (blur is the same at all distances)



Lens Camera

- Optical camera
- Lens refracts light \rightarrow bright image
- Perfect focus at one plane

Digital Single-Lens Reflex (DSLR) Camera




Pinhole Camera Geometry

Motivation

- Physics of real cameras are all different (too tedious to model all of them).
- But they all try their best to approximate pinhole camera.
- So in most of computer vision subjects, we model all cameras mathematically as a pinhole camera.

Field of View




$$\text{FoV: } \alpha = 2 \tan [d/(2f)]$$

Unit of FoV α is degree


*Each camera has two FoV:
Vertical & horizontal FoV*

Focal Length



How to compute the 2D pixel location (u, v) image from the 3D location X, Y, Z ?

Camera Projection:




$$p_{2d} = \begin{bmatrix} u \\ v \end{bmatrix}$$

$$p_{3d} = \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$


Camera coordinate:

Camera center is origin.

Camera Projection:



Camera Projection:



Camera Projection:

$$u = \frac{fX}{Z} \quad \leftrightarrow \quad \lambda \begin{bmatrix} u \\ v \\ f \end{bmatrix} = \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$

$\uparrow \qquad \qquad \uparrow$

Rewrite in
Homogeneous
coordinates

Cartesian
Coordinate

$(x, y) \Rightarrow$

homogeneous
coordinates


$$\begin{bmatrix} x \\ y \\ 1 \end{bmatrix} = \begin{bmatrix} wx \\ wy \\ w \end{bmatrix}$$

Equivalent
(w is non-zero scalar)

Convert from homogenous coordinate
back to 2D coordinate

$$\begin{bmatrix} a \\ b \\ c \end{bmatrix} \Rightarrow \left(\frac{a}{c}, \frac{b}{c} \right)$$

Camera Projection:



If we let f to take care transform
from word unit to image unit.
The unit of f is pixel




World Unit: e.g. Meters

Image Unit: Pixels

$$u = \frac{fX}{Z} \quad v = \frac{fY}{Z}$$

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \begin{bmatrix} f & 0 & 0 \\ 0 & f & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$

Exercise




$$p_{3d} = \begin{bmatrix} 3 \\ 1 \\ 5 \end{bmatrix} \quad f = 500$$

$$p_{2d} = \begin{bmatrix} u \\ v \end{bmatrix} \quad \text{what's } u, v?$$

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \begin{bmatrix} f & 0 & 0 \\ 0 & f & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$

Image Coordinate



Until now, we use 2D coordinate conventions that are **consistent** with the 3D Camera coordinate. **However, if your application uses a different 2D coordinate, you'll need to further transform the (u,v)**

Image Coordinate (Example1)







Image Coordinate (Example2)




Popular Camera Coordinate System



Computer Vision
Researchers




Lazy Grad Students



Graphics Guru ☺
OpenGL


Right-Handed Coordinate System



Evil Microsoft DirectX ☺
- Left-Handed Coordinate System

Camera Projection:


$$\lambda \begin{bmatrix} u \\ v \\ f \end{bmatrix} = \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$




All the points on the same ray, projected to the same pixels [u,v]
Only the point with smallest distance is observed in the image.

3D Vision

How do humans & animals perceive depth?



Binocular Vision




Structure from Motion (SfM)


How do robots perceive depth?



Stereo Camera




Time of Flight




Structured Light

Intel Realsense




2D to 3D projection




Knowing just 2D coordinate (u, v), we don't have enough information to compute the 3D point location (X, Y, Z).
However, with additional depth channel we can (RGB-D image).

RGB-D Image




Depth Image (1xHxW):
Each pixel record depth value Z
(in meter or millimeter)

Missing depth = 0



RGB-D Image Representation



3D point cloud: one pixel corresponding to one 3D point


Depth Image \rightarrow 3D Point Clouds:
A pixel with

- Image coordinate (u, v)
- Depth value $= Z$
- Focal focal length f


Its 3D location (X, Y, Z) in camera coordinate can be computed by:

$$X = \frac{u}{f} * Z, \quad Y = \frac{v}{f} * Z$$

(Z : reading from depth image)



Summary:



3D point (X,Y,Z) → 2D image coordinate (u,v)


$$u = \frac{fX}{Z} \quad v = \frac{fY}{Z}$$

Depth Image (u,v, Z) → 3D Point Clouds


$$X = \frac{u}{f} * Z, \quad Y = \frac{v}{f} * Z$$

(Z : reading from depth image)

World Coordinate to Camera Coordinate



In order to apply the camera model we described so far, the 3D point (X, Y, Z) must be expressed in camera coordinates (i.e., centered at camera origin)



However, the world coordinate can be different from the *camera coordinates*. Requires an additional transformation.


World Coordinate to Camera Coordinate

How to represent this transformation?
Remember rigid transform in previous?
? T ?


$\begin{bmatrix} X_{cam} \\ Y_{cam} \\ Z_{cam} \\ 1 \end{bmatrix} = \begin{bmatrix} \mathbf{R} & \mathbf{t} \\ \mathbf{0}^T & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$

Change coordinate frames from world frame to camera frame.

World Coordinate to Camera Coordinate




Is this the pose of camera in world frame?
Camera T_{world}




$$\begin{pmatrix} X_{cam} \\ Y_{cam} \\ Z_{cam} \\ 1 \end{pmatrix} = \begin{bmatrix} \mathbf{R} & \mathbf{t} \\ \mathbf{0}^T & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$$

World Coordinate to Camera Coordinate



$$\begin{pmatrix} X_{cam} \\ Y_{cam} \\ Z_{cam} \\ 1 \end{pmatrix} = \begin{bmatrix} \mathbf{R} & \mathbf{t} \\ \mathbf{0}^T & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$$

Camera T_{world}
No, it is inverse of camera pose
Camera pose in world Frame should be wT_c



Camera: Putting everything together

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \mathbf{K} \begin{array}{c} \text{Intrinsic} \\ \text{Matrix} \end{array} \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{array}{c} \text{translation} \\ \hline \begin{bmatrix} I & \mathbf{t} \\ \mathbf{0} & 1 \end{bmatrix} \end{array} \times \begin{array}{c} \text{rotation} \\ \hline \begin{bmatrix} R & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix} \end{array} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$$

Camera Extrinsic Matrix $[R|t]$

Camera: Putting everything together

Reduce Vector Dimension

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \text{Intrinsic Matrix } \mathbf{K} \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} I & \mathbf{t} \\ \mathbf{0} & 1 \end{bmatrix} \times \begin{bmatrix} R & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$$

translation

rotation

Camera Extrinsic Matrix $[R|t]$

$$\begin{bmatrix} u \\ v \\ w \end{bmatrix} = \begin{bmatrix} fx & 0 & u_0 \\ 0 & fy & v_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$

Transforming 2D coordinate system.

We have been assuming $fx = fy$ in the previous slides. However, in realworld camera they can be different

Camera: Putting everything together

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \mathbf{K} \begin{array}{c} \text{Intrinsic} \\ \text{Matrix} \end{array} \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{array}{c} \text{translation} \\ \hline \begin{bmatrix} I & \mathbf{t} \\ \mathbf{0} & 1 \end{bmatrix} \end{array} \times \begin{array}{c} \text{rotation} \\ \hline \begin{bmatrix} R & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix} \end{array} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$$

Camera Extrinsic Matrix $[R|t]$

Camera Parameter
Camera Projection Matrix

$$\mathbf{x} = \mathbf{P}^{\mathbf{P}} \mathbf{X}$$

Camera: Putting everything together

$$\mathbf{x} = \mathbf{K} \begin{bmatrix} \mathbf{R} | \mathbf{t} \end{bmatrix} \mathbf{X}$$

- Map a 3D point \mathbf{X} into a 2D coordinate in image \mathbf{x}
- How to describe its *pose* in the world? (extrinsic matrix)
- How to describe its internal parameters? (intrinsic matrix)



That's it for today!

Questions?