Better Graph Answers from a Small Model: Simpler Inputs and a Short Reused Trace

Yueran Wang*

October 2026

Abstract

Small local language models can become more useful if their inputs are easier to process and a short prior reasoning trace helps them answer. We investigate this approach on graph tasks, preserving every source element through reversible short node labels and reusing one brief thinking trace. In an independently frozen study of 24 new graphs, Qwen3-1.7B F1 rises from 0.6542 with compact inputs alone to 0.7703 with a front trace (difference 0.1161; descriptive 95% interval $[0.0437, 0.1914]$; paired sign-flip $p = 0.00624$). The improvement requires 39.8% more preparation-inclusive model tokens than compact direct reading. In prespecified secondary comparisons, compact direct reading itself raises F1 from original-input 0.3176 to 0.6542 while using 42.4% fewer model tokens; the combined trace package also exceeds both original-input direct baselines, including a larger-output baseline, in accuracy with fewer total model tokens. These secondary comparisons are unadjusted for multiplicity. Local reproduction of the original five-trace Trace as State intervention motivates the adaptation and identifies context, output-budget and answer-interface limits. Front-versus-back trace superiority remains uncertain, and a separate 8K practical-capacity criterion fails despite input fit. The result is a measured choice between lower-token compact reading and a more accurate short-trace package on a local small model; transfer to natural documents remains untested.

1 Introduction

Small language models running on local hardware are useful when they can answer more questions correctly with a manageable inference budget. For graph reasoning, the model must track node identities and combine edges across the supplied input. Long identifiers consume tokens without changing the graph operation. Additional reasoning may help, but its preparation also costs resources. We therefore study a practical sequence: simplify the complete input representation, then test whether a short earlier trace improves the answer enough to justify its additional model-token use.

Our starting point is Zou and Tang's Trace as State: earlier reasoning is fed back before an unchanged source, with the same trace placed afterward as a matched control [1]. This study first reproduces that intervention on locally served small models and then develops a bounded compact-input adaptation. Related work improves reasoning through intermediate steps, repeated reading and additional inference-time computation [2–4]. Prompt compression reduces input length through content selection [5, 6]. These approaches motivate input-side and reasoning-side interventions, but their results do not establish which combination is useful under our local small-model configurations. Our initial five-trace reproduction encountered context, decoding and answer-interface boundaries and did not establish the original placement advantage.

We adapt that intervention by combining reversible node recoding with one short source pass. A deterministic dictionary replaces long identifiers throughout the complete source, examples and question, without removing edges or using gold answers. The small model first reads this compact input with a short output cap; its full thinking field is then supplied to a fresh reader. Direct compact reading isolates the added value of the trace package, while a byte-identical appended trace tests placement. An inverse dictionary restores predicted node identities. The evaluated recipe requires no model training, and charges each reused answer the entire preparation pass.

*School of Artificial Intelligence, Beijing Normal University. Correspondence: wangyueran@mail.bnu.edu.cn.

An independently frozen confirmation on twenty-four previously unused graphs shows that a front trace raises Qwen3-1.7B mean F1 from 0.6542 to 0.7703, at 39.8% more preparation-inclusive model tokens than compact direct reading. In prespecified secondary comparisons, compact direct reading improves F1 over original input while using 42.4% fewer model tokens; these comparisons are unadjusted for multiplicity. Front-versus-back superiority remains uncertain, and a separate practical 8K-capacity criterion fails despite compact-input fit. These findings support a bounded choice between lower-token compact reading and a more accurate trace package, rather than a universal cost-saving claim.

Our main contributions are:

- A local reproduction of the five-trace intervention, with explicit context, output-budget and answer-interface boundaries.
- An independently confirmed small-model graph recipe that combines complete reversible inputs with one short trace, separating representation gains from the added trace-package benefit.
- Audited preparation-inclusive accounting and complete reporting of failed criteria and uncertain comparisons, enabling the observed accuracy–token trade-off to be assessed without assuming latency or monetary savings.

2 Related Work

2.1 Reasoning traces, rereading and inference-time computation

Chain-of-thought prompting uses intermediate reasoning demonstrations to improve reasoning in the evaluated sufficiently large models [2]. Self-consistency samples multiple reasoning paths and aggregates their answers [7]; Re2 repeats the question within a prompt to improve input understanding [3]. Snell et al. study verifier search and sequential revisions, finding that effective compute allocation depends on problem difficulty [4]. These results motivate careful budget allocation, but do not guarantee that more reasoning is beneficial for every small model. Our adaptation reuses one native thinking field without voting, a learned verifier or reader retraining. Reader repeats estimate variability; they are not an answer ensemble.

Trace as State is the direct methodological antecedent. Zou and Tang serialize earlier traces before the source on a fresh pass and compare against the same traces after the source [1]. We reproduce that placement intervention locally, then explicitly change its trace count and input representation in the compact extension. The confirmed prefix-versus-compact result tests the whole added trace package, including its warning wrapper; it neither isolates placement as the cause nor establishes the original theoretical memory separation in our models.

2.2 Prompt compression and complete input representations

LLMLingua combines a budget controller, iterative token-level compression and distribution alignment to shorten prompts [5]. LLMLingua-2 distills compression data and learns an extractive token classifier with bidirectional context [6]. Both address natural-language prompt compression. Our narrower transformation exploits arbitrary graph identifiers: a bijective dictionary shortens their representation while retaining the complete graph and operation. Inverse substitution restores the original prompt exactly. This is a task-specific representation control, not a general semantic summarizer or a new compression architecture. We have not run a head-to-head comparison with these compressors, and claim no superiority over them.

2.3 Effective context use and structured evaluation

Lost in the Middle shows that models can be sensitive to where relevant information appears in long inputs [8]. RULER distinguishes nominal context size from usable performance through retrieval, multi-hop tracing, aggregation and question answering [9]. These studies support separating input feasibility from successful task completion. We use OpenAI GraphWalks parent and BFS tasks [10], whose answers can be independently recomputed, and locally served Qwen variants [11, 12]. Our contribution is an audited small-model replication and bounded adaptation on this structured benchmark, with complete preparation

costs and failure reporting. It does not establish transfer to natural documents, improvements over direct CPU graph algorithms, or cross-question trace reuse.

3 Methods

Figure 1 summarizes the complete compact-input pipeline. Figure 2 shows the preserved graph structure, and Figure 3 details its reversible representation and accounting boundary.




Figure 1: Overall compact-input and single-trace method. The shaded groups are separate calls to the same small model. Reversible recoding f produces the complete compact context C. The source reads $C + Q$ and supplies its native thinking T to a fresh reader; the complete context also reaches that reader intact. Prefix assembles $T + C + Q$, and the stored inverse dictionary restores original identifiers afterward. The same operation Q is used in both calls. Only text is transferred, not hidden states; the separate source answer is excluded. Direct and append controls use the indicated orders. Every trace answer includes the full source-call cost.

3.1 Complete compact inputs and single-trace confirmation

Representation and preparation. This extension changes the original five-trace intervention. A deterministic dictionary replaces each ten-character graph node identifier with a distinct short label that is one token under the archived tokenizer. The same mapping is applied throughout the complete source, examples and question, and its inverse restores predicted nodes. All edges, directions, duplicate edges and operation wording remain available. Exact inverse substitution must reproduce the original prompt; gold answers never determine which content is retained. The label dictionary uses the archived tokenizer, sorted




Figure 2: Structure-preserving input recoding. (a) Confirmation graph 87 has 28 nodes and 112 directed edge entries. Both views share all vertex positions and edge directions, including five self-loop entries and two repeated edge entries that overlap in the display. Original identifiers are omitted from the left network for legibility; compact labels appear on the right. Positions are display geometry, not learned states. (b) The compact source generates a native thinking block for a fresh reader. Direct, prefix and append orders retain the complete compact context C and final operation Q. Prefix and append use byte-identical thinking, including errors and truncation. Inverse mapping restores original labels before scoring. Display geometry does not represent token length.

node identifiers and a seeded shuffled vocabulary of one-token uppercase labels, excluding uppercase words already in the prompt; its seed is $202610063 + \text{row_index}$. The inverse dictionary is archived for each graph. A single source pass on the compact input has a 1,024-token output cap. Its entire native thinking field, including mistakes and truncation, is retained in the original warning wrapper; the separate visible answer is excluded. Prefix supplies this block before the compact source, and append supplies the byte-identical block after the source and before the final operation.




Figure 3: Exact reversible representation and preparation-inclusive token accounting. (a) A three-vertex, two-edge excerpt of confirmation graph 87 before and after recoding; the complete graph has 28 nodes and 112 edge entries. The inverse dictionary restores original identifiers; positions are display geometry. (b) Inner-ring angles split complete mean cost into source and reader usage; outer-ring angles split input and output. Angles alone encode fractions. The total is 5,344.46 tokens per prefix answer, averaged over 24 sources and 48 readers; labels are rounded. Every answer pays full preparation. (c) Native reader input for graph 87's first seed, not population means. Dictionary storage and CPU preprocessing are separate; output caps do not imply matched realized compute.

Discovery and confirmation selection. The discovery study selected twelve previously unused graph heads whose complete original inputs exceeded an 8,192-token contract but whose compact inputs fit, and twelve short graphs in the catalogue interval $[3500, 6500)$ characters. Each block contained six parent and six BFS questions. Its 168 calls comprised one source and two readings of each of three arms per graph. The capacity block compared executed original readers at 32,768 context/8,192 output with compact readers at 8,192 context/4,096 output; compact prefix readers reserved 1,024 of that generated-token allowance for

preparation. Its predefined practical criterion required a nonempty gold graph to be answered exactly in both compact-direct repeats. Nonexecuted original-8K inputs were feasibility references and were never assigned zero accuracy.

After observing the discovery signal, we froze a separate confirmation using twenty-four new graph heads from the same short catalogue interval, sampled without replacement with twelve questions per task. All archived graph heads, including discovery heads, were excluded. The selection seed was 2026101010, source seed 2026101011 and reader seeds 2026101012–2026101013. Graph order and five-arm order within each repeat were randomized. Each graph supplied one source and ten readers, giving 264 calls. All confirmation calls used Qwen3-1.7B, the archived digest, native thinking, Ollama 0.40.0 and a 32,768-token context. Original and compact direct readers allowed 8,192 generated tokens; the contemporaneous original-long arm allowed 16,384. Prefix and append allowed 7,168 reader tokens after the 1,024-cap preparation pass. These are maximum generated-token allowances, not matched realized compute. Sampling used temperature 0.6, top-p 0.95, top-k 20, minimum-p 0 and repeat penalty 1. Requests were saved before transmission and exact response bytes before parsing. Calls were not retried. Between-call cooling triggered at 82 °C and resumed below 76 °C, with three-second call gaps and thirty-second graph-block rests. A corrected discovery cooling implementation and a GPU/reboot interruption are archived; frozen stimuli, model, seeds and budgets were unchanged, and eighteen completed requests were not resent.

Prespecified inference and accounting. The confirmation primary contrast is prefix minus compact-direct graph-mean F1. Two readings are averaged within each graph; the two task types receive equal weight. The frozen support rule requires a positive mean difference, a positive lower bound of a descriptive stratified graph-bootstrap 95% interval (20,000 draws; seed 2026101014), and a paired sign-flip Monte Carlo $p \leq 0.05$ (100,000 draws; seed 2026101015). The frozen protocol did not specify a test tail; the independent auditor uses the conservative two-sided test, implemented before complete collection and effect analysis. The sign-flip interpretation assumes exchangeability of paired differences under the null. Placement and original-baseline contrasts are secondary and unadjusted for multiple comparisons. The discovery and confirmation results are reported separately, and no outcome-dependent sample extension is used. Each reused answer is charged the entire one-source preparation plus one reader, without dividing preparation across the two reader repeats. Dictionary bytes and CPU recoding time are reported separately. Wall time covers the recorded model requests, not all workflow idle time or preprocessing. A normal-stop terminal visible answer line is required; malformed or length-terminated answers score zero, and unknown inverse labels count as false-positive nodes. Independently recomputed graph gold sets, exact payloads, model/context metadata, token counts and visible responses are audited without importing the runner or its scorer.

3.2 Reproduction scope and experimental conditions

Let x denote the graph context, q its operation, and T a serialized block of prior reasoning. Trace prefix and trace append use $[T, x, q]$ and $[x, T, q]$, respectively. Both receive the same realized T and retain the complete original graph. Direct reading uses $[x, q]$; question-first reading uses $[q, x, q]$. Following the original long-context adaptation of Re2 [1, 3], we used $[x, q, x, q]$ within one request. A separate fresh request containing $[x, q]$ is not Re2.

The original study used five source traces and five reader repeats, with each reused trace capped at its first 50,000 characters. All completed short-graph placement studies retained this trace count, repeat count and placement comparison. Their local source and reader output limits were 4,096 and 8,192 tokens, respectively. These explicit local limits differ from the original study, which requested no custom client-side output maximum; effective provider defaults were not established. Appendix B lists the retained and adapted components.

Tasks and selection. We used the archived 750-row `graphwalks_128k_and_shorter.parquet` file from OpenAI GraphWalks [10], comprising 400 parent and 350 BFS questions. This is one file of the released dataset, not its full repository. Its SHA-256 matched the publisher's current file metadata when checked on 6 October 2026. We used directed breadth-first search (BFS) and parent-retrieval tasks. Gold answers were recomputed from graph edges before scoring. Study-specific selection used catalogue length, task type and

exclusion of previously selected graph identities. Earlier selection was deterministic. A separate prospective replication randomly selected six new graphs per task from a restricted short-input population; it was not a random sample of all graph questions. Seeds supplied repeated measurements within graphs and did not increase the number of independent graph units.

Models and interfaces. The reported studies used the nominal Qwen3-1.7B and Qwen3-4B variants [11] and Qwen3.5-4B [12], with native thinking exposed separately from visible answers. The main configurations are listed in Table 1. Model digests, runtime versions, sampling settings and complete prompts are preserved in the frozen archives. Native Qwen3.5 studies used Ollama 0.35.1 and a fixed general-thinking profile. Its temperature was 1.0, top-p 0.95, top-k 20 and presence penalty 1.5. The earlier Qwen3 short-trace study used temperature 0.6, top-p 0.95 and top-k 20. These settings were not pooled as a model-size experiment.

Study	Model	Context	Source / reader cap
Initial and prospective short studies	Qwen3-1.7B	32,768	4,096 / 8,192
Same-question paired follow-up	Qwen3-4B	32,768	4,096 / 8,192
Output-budget diagnostic	Qwen3-4B	32,768	— / 28,672
Native source qualification	Qwen3.5-4B	65,536	32,768 / —
Native long five-trace trial	Qwen3.5-4B	131,072	32,768 / 32,768
Retained-case context diagnostic	Qwen3.5-4B	196,608	retained / 32,768
Early-state adaptation	Qwen3.5-4B	65,536	1,024 / budget-derived

Table 1: Token limits for the main local studies. The early-state reader cap was computed separately for each planned request from its fixed total allowance. Context is a configured serving limit, not a measured guarantee of effective reasoning capacity.

Prospective short-graph replication. Before collecting new responses, we froze a twelve-graph protocol and its complete allocation schedule. All graph heads selected in existing official-study freezes were excluded. Within the catalogue interval $[2000, 3500)$ characters, the resulting pools contained 34 parent questions and nine BFS questions with distinct graph heads. Six were sampled without replacement per task, using seed 202610060. Graph order and reader-arm order within each repetition were randomized using the same seeded generator. Five source seeds (202610061–202610065) and five matched reader seeds (202610071–202610075) supplied 240 planned calls. Model digest, original serializer, context and source/reader caps matched the initial short study. Decoding used temperature 0.6, top-p 0.95, top-k 20, minimum-p 0 and repeat penalty 1. The native server version was 0.35.1. Complete requests were saved before transmission and exact response bytes before parsing. No call was retried. Sequential calls were separated by five seconds, and graph blocks by sixty seconds. This was a locally frozen prospective protocol, not an external preregistration.

Same-question second-model follow-up. After observing the 1.7B results, we froze a separate Qwen3-4B study before collecting its 240 new responses. It retained the same twelve questions, graph and arm order, source and reader seeds, complete prompts, sampling parameters and context/output limits. The 4B package generated its own five-trace bundles. This compared local pipelines on matched questions; it did not isolate reader size or supply twelve additional independent graph units. The within-model prefix–append contrast remained primary, with the same descriptive stratified graph bootstrap.

Output-budget diagnostic. Interim 4B output truncation motivated a separately frozen follow-up on the same twelve known questions and five matched reader seeds. Sixty new direct requests used an output cap of 28,672 tokens, equal to $5 \times 4096 + 8192$, with all other recorded inputs, model and sampling settings retained. Original 8,192-cap direct responses remained the historical comparator. This matched maximum generated-token allowances, not total logical tokens, memory, time or compute. Conditions ran sequentially; the diagnostic hypothesis was chosen after interim observations. All cases were retained. The descriptive long-minus-original-direct interval used 20,000 stratified graph-bootstrap draws, seed 202610067.

Configured-context diagnostic. A separate frozen follow-up retained the original five-trace bundle for the previously declined row-506 case. With the original Qwen3.5-4B digest and sampling profile, it changed the configured context from 131,072 to 196,608 tokens. One full-prefix input probe with a one-token output cap checked accounting and residency without scoring an answer. Five paired seeds supplied prefix, append, fresh, question-first and Re2 readers, each with a 32,768-token output cap: 26 new calls in total. Five-second call gaps and sixty-second repeat-block rests were retained. Full original source preparation was charged to trace conditions; new-run usage was separately reported. This deliberately selected failure case diagnosed execution and case-specific outcomes, not a new population sample or completion of the old sixteen-graph trial.

Trace construction and controls. Source reasoning was read from the native thinking field; the separate visible answer was excluded. Incorrect and length-terminated source traces were retained according to each frozen protocol. Prefix and append used byte-identical trace blocks. The shorter-state adaptation retained the complete thinking generated under a 1,024-token cap. It did not select excerpts using gold answers. Representation recoding and thinking-mode controls were separate experiments, reported in the appendices.

3.3 Scoring, qualification and missing outcomes

For predicted and gold node sets P and G, we used

$$F_1(P,G) = \begin{cases} 1, & P = G = \varnothing, \\ \dfrac{2|P \cap G|}{|P| + |G|}, & \text{otherwise}, \end{cases} \qquad \mathrm{EM}(P,G) = \mathbf{1}\{P = G\}.$$

Set semantics remove duplicate predictions but retain incorrect nodes. Scoring used visible answers only and never extracted an answer from thinking. Known malformed or length-terminated outputs received zero under their respective protocols. Valid empty answers were scored normally, with an always-empty baseline reported where relevant.

Answer interfaces. The native source and configured-context studies accepted a valid terminal visible `Final Answer: [...]` line after a normal stop. The early-state study required that line to constitute the entire visible response. Its later relaxed parser was explicitly post hoc and did not replace the primary scores. Recoding protocols also differed in their treatment of unmapped nodes. Identity recoding invalidated such predictions, whereas indexed-source scoring counted them as false positives. Scores were not pooled across these rules.

Call qualification. Input counts, response metadata and resident model digest/context were checked against the recorded request. Qualification established compliance with the study's interface, not answer correctness. A qualified response could still be malformed or reach its output limit. A returned response that failed interface qualification remained undetermined under the applicable primary protocol.

Interrupted execution. Unknown responses were bounded over the original planned denominator, rather than scored as zero or replayed. For N planned outcomes with m unknown values, the F1 bounds were $[\sum F_1/N, (\sum F_1 + m)/N]$. Known unsent budget declines were deployment failures, not model answers. Client errors retained their protocol-defined failure scores and unknown usage. Unknown token usage made the reported cost a lower bound.

3.4 Statistical analysis and resource accounting

Reader repetitions were averaged within graphs before comparisons across graphs. Intervals condition on the archived trace bundles; independent redraws of complete five-trace bundles were not sampled. The short-trace study used 20,000 graph bootstrap resamples, seed 202610040, for descriptive 95% percentile intervals. Its four graphs did not support a broad population claim. The twelve-graph replication specified

prefix-minus-append F1 as its primary contrast and prefix-minus-direct as secondary. Each task stratum contributed equally. Its descriptive percentile intervals used 20,000 bootstrap draws of six graph units within each task stratum, seed 202610066. All twelve selected graphs and all repeated outcomes were included, without score-dependent stopping. Subsequent studies retained their own frozen analysis families and screening criteria (Appendix A). These criteria governed advancement to further research; they were not universal definitions of successful replication or formal noninferiority tests.

Deployment-token accounting included the complete source inputs and outputs plus one reader's input and output. Repeated reader calls estimated that reader cost; they did not divide the preparation bill. Research-run totals were reported separately and included calibration where performed. Token accounting did not establish latency, energy or cache-related computation savings. The prospective replication separately recorded observed request wall times, without an exclusive-hardware or comparative-latency claim. A dedicated API endpoint also did not establish exclusive hardware use.

4 Results

4.1 Compact inputs and a short trace improved accuracy on independent new graphs

All 264 confirmation calls completed and were independently audited, with no unknown responses. Of the twenty-four source passes, twenty-two ended at the 1,024-token output limit; the two normally stopped visible source answers were valid but incorrect. None of the source passes produced a correct qualified visible answer. Their unfiltered thinking was nevertheless retained, so the observed reader benefit does not require a correct source answer under this short cap. Prefix F1 increased from compact-direct 0.6542 to 0.7703: a difference of 0.1161 (descriptive 95% interval $[0.0437, 0.1914]$; two-sided sign-flip $p = 0.00624$). This met the frozen primary support rule on the twenty-four independent graph units. Exact match increased from 0.2292 to 0.3750 as a secondary descriptive outcome. The benefit belongs to the complete trace package, including its warning wrapper and preparation, rather than to placement alone.

Confirmation arm	F1	EM	Full tokens/answer	Valid/48	Length
Original direct	0.3176	0.0417	6,640.67	43	5
Original direct, 16K output	0.3668	0.0833	7,149.88	45	3
Compact direct	0.6542	0.2292	3,823.25	42	6
Compact trace prefix	0.7703	0.3750	5,344.46	47	1
Compact trace append	0.7130	0.3333	5,345.67	46	2

Table 2: Independent confirmation on twenty-four new graphs, two reader seeds per graph. F1 and EM average within graphs before aggregation. Full model tokens include complete preparation for each reused answer. Every length-terminated reader is included with zero score. "Valid" denotes answer-format validity after a normal stop, not correctness. All arms used the same 32K configured context.

4.2 The accuracy benefit incurred a cost relative to compact direct reading

Prefix used 1.398 times the complete model tokens of compact direct reading (descriptive interval $[1.170, 1.667]$). Its wall-time ratio was 0.842, but its interval $[0.630, 1.119]$ included one. Thus the primary benefit was higher accuracy with additional tokens; faster execution than compact direct was not established.

Against original direct, prefix F1 was higher by 0.4527 (interval $[0.3320, 0.5656]$) and its full-token ratio was 0.805 (interval $[0.724, 0.896]$). Against original-long, the F1 difference was 0.4034 (interval $[0.2931, 0.5087]$) and the token ratio was 0.747 (interval $[0.635, 0.877]$). These prespecified secondary comparisons include both recoding and trace reuse. Compact direct itself improved F1 over original direct by 0.3366 (interval $[0.1932, 0.4759]$), with a token ratio of 0.576 (interval $[0.466, 0.711]$). The combined improvement cannot be assigned entirely to traces.

The matched prefix-minus-append F1 difference was 0.0573 (interval $[-0.0321, 0.1705]$; $p = 0.36592$), leaving placement superiority uncertain. Append minus compact-direct was also uncertain: 0.0588 (interval $[-0.0600, 0.1695]$). Secondary intervals are descriptive and unadjusted for multiplicity. Figure 4 displays quality, preparation-inclusive model tokens and paired graph-level uncertainty.

4.3 Discovery and capacity boundaries

The discovery's short-graph prefix-minus-compact F1 difference was 0.1534, with a descriptive interval $[0.0394, 0.2769]$. This was an exploratory contrast, motivating the independent confirmation rather than serving as its evidence. The capacity block did not meet its practical criterion: no nonempty gold graph was answered exactly in both compact-direct repeats, although all twelve compact inputs fit the 8K contract (Figure 5). Input fit alone therefore did not establish successful task capacity.

4.4 Prospective replication left the placement advantage uncertain

The twelve-graph follow-up completed all 240 planned calls: sixty sources and sixty reader responses per condition. Every call passed the recorded interface checks; none was declined for context or had unknown usage. Twelve sources reached their 4,096-token limit. Prefix and append each produced sixty normal-valid visible answers, compared with 59 for direct reading; the remaining direct response reached its output limit. Incorrect and truncated source reasoning remained in the shared trace block.

Mean F1 was 0.7715 for prefix, 0.7351 for append and 0.6915 for direct reading (Figure 6). The primary prefix-minus-append difference was 3.64 percentage points, with a descriptive interval of $[-0.65, 8.33]$ points. The secondary prefix-minus-direct difference was 8.00 points, interval $[-3.00, 17.98]$ points. Both intervals included zero. EM was 0.3333, 0.3833 and 0.3333 respectively: the higher prefix F1 did not extend to exact match. Two graphs had empty gold answers; an always-empty response therefore scored 0.1667 in both metrics over this sample.

The prefix-minus-direct F1 point difference was +20.79 points for parents but −4.80 points for BFS. These six-graph strata did not establish a task-specific causal mechanism. They showed why an aggregate positive point estimate should not be described as a uniform improvement. The follow-up remained separate from the initial four graphs; their scores and intervals were not pooled.

Charging all five source calls plus one seed-averaged reading gave mean deployment costs of 34,901.15 tokens for prefix, 34,622.07 for append and 4,093.48 for direct reading. Prefix cost 8.53 times direct reading under this single-question contract. The complete research run consumed 2,308,239 model tokens. Observed request wall times summed to 4,115.32 seconds, excluding the planned idle gaps; this was neither total elapsed deployment time nor a hardware-exclusive latency comparison.

Configuration	F1	EM	Normal-valid	Tokens/answer
1.7B prefix	0.7715	0.3333	60/60	34,901
1.7B append	0.7351	0.3833	60/60	34,622
1.7B direct	0.6915	0.3333	59/60	4,093
4B prefix	1.0000	1.0000	60/60	51,751
4B append	1.0000	1.0000	60/60	51,612
4B direct	0.6967	0.6833	42/60	8,231

Table 3: Completed Qwen3 comparisons on the same twelve graphs, five reader repeats each. Trace costs charge all five sources and one reader. Normal-valid refers to termination and visible-answer format, not correctness. The same questions are not twenty-four independent graph units.

4.5 The second model reached a ceiling in both trace placements

The same-question Qwen3-4B follow-up completed all 240 planned calls and passed independent request, token-count, runtime and scoring checks. Prefix and append each gave sixty normal-valid and exact answers: mean F1 and EM were both 1.0000 (Figure 7). All sixty source calls reached the 4,096-token limit and



Figure 4: Independent single-trace confirmation across twenty-four graph units, with two reader seeds averaged within each graph. (a) All graph-mean F1 values; shaded densities are descriptive boundary-reflected estimates with bandwidth 0.08 and heights normalized within each arm. Horizontal segments show interquartile ranges and white markers show medians. (b) Prefix-minus-compact differences for every graph in fixed order within task; teal and orange denote gains and losses. The dashed horizontal line is the mean difference; the stated 95% interval is the prespecified stratified graph-bootstrap interval. Zero differences have zero-height bars. Before and after denote prefix and append; longer denotes the original-input larger-output control. (c) All 120 graph–method outcomes on a common F1 scale, using the same task-grouped order as (b). (d) Mean F1 versus complete model tokens per answer, charging the entire source preparation to each trace answer. The connecting segment identifies the primary comparison, not a continuous performance curve. Prefix improves mean F1 at 39.8% more full tokens than compact direct. Other comparisons remain secondary and unadjusted for multiplicity; placement superiority remains uncertain.




Figure 5: Discovery study, separate from confirmation. Each block retains twelve graph means, with two reader repeats averaged within graphs; circles denote parents and squares BFS. Descriptive boundary-reflected F1 densities use bandwidth 0.08 and equal peak height; all observations remain visible. Printed values give F1/EM means. Below, arrows connect original, compact and prefix arm means in that order; circles, squares and diamonds identify these arms. Score and complete-token scales are shared across blocks. Costs charge full preparation. Capacity packages have different serving allowances; complete original inputs would not fit the nonexecuted 8K reference. Input fit did not meet the predefined nonempty exact-in-both-repeats practical criterion. Short-block results are exploratory.



Figure 6: Prospective twelve-graph replication from independently rescored responses. (a) Curves track the same graph across direct, front-trace and back-trace conditions, separately for BFS and parent queries. Colours and identifiers distinguish graphs; smooth connections interpolate only between discrete conditions. F1 averages five reader seeds. Horizontal marker offsets separate coincident scores without changing F1. (b) All twelve complete-token graph means per arm with descriptive zero-reflected densities, bandwidth 2,000 and equal peak height; printed values are means. Trace answers pay all five sources and one reader, direct answers only the reader. All 240 calls completed; format and termination failures retain prescribed zero scores. Both empty-gold graph units remain in all analyses. Paired contrasts and existing descriptive intervals are reported in the text and tables.

therefore had zero visible-answer scores. Their thinking was nevertheless retained according to the frozen rule. Successful second-pass answering with supplied traces did not require a completed correct visible source answer under this budget.

Direct reading achieved F1 0.6967 and EM 0.6833. Eighteen of sixty direct responses reached the 8,192-token limit; forty-two stopped normally with valid terminal answers. Prefix minus direct F1 was 30.33 percentage points, with a descriptive interval of $[13.67, 46.67]$ points. The task-stratum differences were +0.67 points for parents and +60.00 points for BFS. This pipeline contrast included additional reasoning, warning instructions and preparation calls, and could be affected by direct-output truncation. It did not isolate a placement effect or a same-total-budget advantage.

The primary prefix–append contrast was exactly zero on every graph. Its bootstrap interval collapsed to zero because both conditions were at the observed score ceiling, not because population equivalence had been established. The supplied-trace conditions answered these questions reliably, while leaving no observed preference for front placement. This observation did not by itself establish how the reader used the traces. Cross-model differences also included separately generated trace content, rather than reader size alone.

Preparation-inclusive mean tokens per answer were 51,751.22 for prefix, 51,611.63 for append and 8,231.05 for direct reading. Prefix required 6.29 times the direct tokens. The complete research run used 3,740,754 model tokens; observed request-wall times summed to 15,435.86 seconds, excluding planned rests. These were logical usage and observed timings, not energy or hardware-exclusive latency measurements.

4.6 A larger output allowance was tested on the same questions

All sixty new direct-long calls completed and passed independent request and scoring checks. With a 28,672-token output cap, mean F1 was 1.0000, EM 1.0000, and 60/60 responses were normal-valid. There were 0 length-terminated outputs, compared with eighteen under the original cap. The paired F1 change from the original direct condition was 30.33 percentage points, with a descriptive interval of $[13.33, 46.67]$ points. These results quantify this sequential diagnostic on the known questions, rather than a fresh-case or equal-compute comparison.

Mean logical tokens for one direct-long answer were 8,763.78, compared with 8,231.05 in the original direct condition. The new diagnostic incurred 525,827 model tokens and 5,912.53 seconds of observed request time, excluding planned rests. The original trace scores and costs were not overwritten. Prefix preparation cost was 5.91 times direct-long tokens, with the same observed F1 and EM ceiling.

Among the eighteen previously length-terminated responses, 0/18 new thinking strings began with the old thinking text with trailing whitespace removed. The new runs were therefore not byte-identical continuations of the old runs despite matching seeds. This descriptive check further limits attribution of every changed answer to the output cap alone.

Output cap	F1	EM	Normal-valid	Tokens/answer
8192	0.6967	0.6833	42/60	8,231
28672	1.0000	1.0000	60/60	8,764

Table 4: Sequential Qwen3-4B diagnostic on the same known questions and seeds. The larger cap equals the five-source pipeline maximum generated-token allowance, not its total logical-token or compute budget. Original 8192-cap responses remain unchanged.

4.7 Native source qualification succeeded on the selected graphs

A separately frozen Qwen3.5-4B experiment tested source answering with a larger context and output allowance. Earlier bridge archives are retained for selection lineage but excluded from empirical claims because their transmitted-request provenance is weaker (Appendix B).

With a 65,536-token context and 32,768-token source output cap, all sixteen source calls stopped normally and met qualification. Across eight new graphs, F1 was 0.9286 and EM was 0.875. Figure 9 shows that errors remained on a long-BFS graph. The source screening criterion passed, providing a qualified starting point for the next migration trial. These calls did not test second-pass trace reuse.



Figure 7: Qwen3 packages on the same twelve questions, five reader seeds per graph, from two separately audited 240-call studies. (a,b) All graph means: circles denote parents, squares BFS. Perpendicular offsets separate observations. Shaded curves are descriptive densities (F1 reflected at both bounds, bandwidth 0.08; tokens reflected at zero, bandwidth 2,000), with common height scales within metrics. Ceiling conditions retain all twelve observations without smoothing. F1/EM means are printed; the dashed reference is always-empty F1. Costs charge all five sources and one reader. (c) Existing descriptive stratified graph-bootstrap intervals; dashed lines denote zero. The 4B zero-width placement interval reflects the observed ceiling, not population equivalence. Packages generate their own traces; this is not a size-only comparison. Eighteen length-terminated 4B direct readings retain zero scores.




Figure 8: Sequential output-cap diagnostic on the same twelve Qwen3-4B questions. (a) Each colour tracks one identified graph under direct-output caps of 8,192 and 28,672, with five seeds averaged. Curves interpolate between discrete conditions only; horizontal marker offsets expose overlapping ceiling observations without changing F1. Old length-terminated responses retain zero scores. (b) All twelve complete-token graph means per condition and descriptive zero-reflected densities (bandwidth 2,000, equal peak height); printed totals are means. Trace costs include all five sources. New direct answers and both trace placements reach the observed F1/EM ceiling. This known-question diagnostic matches maximum generated allowances, not total compute, and establishes neither population equivalence nor isolated causality.




Figure 9: Native source qualification on eight official graphs and two repeats, excluding calibration. (a) Every saved call is located by its input and generated tokens. Circles and triangles distinguish seeds; connectors join repeats of the same identified graph, not a fitted relationship. Teal denotes F1 equal to one and orange lower F1. Thin leader lines connect identifiers to pair midpoints. (b) Fourteen readings have F1 and EM equal to one; graph 504 has F1 0 and 0.857 and EM 0 for both seeds. All points have fixed size; no inferential error bars are shown. No trace reuse was tested.

4.8 Five native traces exceeded the configured reader context

The next trial planned sixteen long-BFS graphs, five sources per graph and five repeats of five reader conditions. On the first graph, prefix and append each required 144,677 input tokens. This exceeded the configured 131,072-token context before any reader output was generated (Figure 10). Both trace conditions were declined under the frozen resource rule, without shortening their trace block.

The trial subsequently stopped after a returned response failed its resident-model check. Of 480 planned formal slots, fourteen returned qualified responses, eight were budget declines, one returned response was unqualified, and 457 were unreached. These categories preserved 22 determined deployment outcomes and 458 unknown outcomes. The archive established first-graph infeasibility under the specified configuration, but not a sixteen-graph quality effect.

The frozen inputs also permitted a conditional cost calculation. Let I be one complete source input and C the direct output allowance. Five source inputs alone cost $5I$, whereas one direct prediction costs at most $I + C$. Hence

$$I > C/4 \quad \Longrightarrow \quad 5I > I + C.$$

All sixteen planned inputs satisfied $I > 8192$ with $C = 32768$. Under this single-prediction accounting contract, five complete sources could not be cheaper than direct reading. This bound did not apply to latency, caching, different output caps or preparation reused across different questions.

4.9 A larger configured context enabled the retained-case diagnostic

All twenty-six new calls passed independent request, input-count and resident-model checks at a configured 196,608-token context. The probe verified the full 144,677-token prefix input; it was not a scored answer. This established execution at the changed allocation for this case, rather than reasoning capacity throughout the context window.

Across five reader seeds, prefix F1/EM were 0.9750/0.8000, append 0.8984/0.6000, and fresh direct reading 0.9583/0.4000. Normal-valid counts were 5/5, 5/5 and 5/5 respectively. Table 5 retains all five conditions. No population interval was inferred from this deliberately selected case. The old sixteen-graph archive remained interrupted and its unknown outcomes were not replaced.

The original five-source preparation cost was 190,884 tokens. New probe and reader calls consumed 2,343,997 model tokens, with 12,135.52 seconds of observed request time. Preparation was charged once to each trace deployment estimate, never amortized over the five experimental repeats.

Reader	F1	EM	Normal-valid	Tokens/answer
prefix	0.9750	0.8000	5/5	350,021
append	0.8984	0.6000	5/5	344,816
fresh	0.9583	0.4000	5/5	36,498
question first	0.7220	0.0000	5/5	39,719
re2	0.7692	0.6000	4/5	50,578

Table 5: One previously selected overflow case, evaluated at a configured 196608-token context with the original trace bundle. Five repeats per condition describe this case only; no population interval is inferred. Prefix and append include the complete original source preparation cost.

4.10 Answer-format sensitivity limited the early-state comparison

A separately frozen adaptation used a 1,024-token source cap and seven reader conditions with a shared total-token allowance. Execution remained incomplete, with 129 of 224 planned reader outcomes known. Under a post hoc parser that accepted a valid terminal answer within surrounding prose, prefix, direct and question-first reading each produced thirteen exact answers on eighteen matched outputs. The primary strict scores were retained. This sensitivity showed that an apparent strict-score advantage could depend on format compliance; it did not establish equivalence or a placement benefit. Appendix D reports the planned-denominator bounds, failures and resource accounting.




Figure 10: Context and execution boundaries of the native five-trace trial. (a) Annular angles partition all 480 formal slots, excluding calibration, into qualified responses, budget declines, unqualified responses and unreached slots; counts are printed. Unreached slots are not failed answers. (b) Measured first-graph inputs against the input limit after output reservation (98,240) and configured context (131,072), shown by dashed thresholds. (c) Open endpoints delimit F1 identification bounds over all sixteen planned graph outcomes; numeric labels give both endpoints. These are not confidence intervals. Missing outcomes prevent a quality conclusion.

4.11 Additional controls identified separate sources of variation

The initial four-graph Qwen3-1.7B study also favored prefix in mean F1, but both paired descriptive intervals included zero. Appendix C retains its full numerical results and preparation cost; it is not pooled with the prospective twelve-graph follow-up.

Representation and decoding studies tested interventions distinct from trace placement. Reversible compact node names improved the F1 point estimate by 15.23 points and reduced tokens by 50.46%. Its eight-graph interval against original names was $[-21.15, 40.98]$ points, leaving the quality effect uncertain. Thinking-off and a fixed task route reduced tokens while lowering quality (Appendix I).

The indexed-source study saved 94 of 96 planned responses. Its primary indexed-off candidate failed the frozen criterion. A secondary compact-on comparison remained positive under worst-case missing-score bounds, but unknown usage prevented a complete cost comparison (Appendix H). Small longer-input and sampling studies also showed sensitivity to decoding and empty-answer baselines. They did not identify a single causal sampling parameter or a universal long-input failure.

5 Discussion

The studies distinguish a confirmed small-model accuracy benefit from placement superiority and universal efficiency. In the independent compact-input confirmation, a single front trace improved F1 with an additional token cost relative to compact direct reading. Secondary original-input comparisons showed a favorable quality–token trade-off, including against a contemporaneous larger-output baseline. The original five-trace reproduction did not establish that preparing and reusing reasoning lowered the token cost of one accurate answer. This deployment question must be separated from whether supplying traces improves an answer under a particular reader cap. The initial and prospective Qwen3-1.7B studies favored trace prefix in mean F1, but both descriptive placement intervals included zero. The twelve-graph study also showed lower prefix EM than append and opposing prefix-versus-direct point differences across tasks. On the same questions, Qwen3-4B reached perfect F1 and EM in both trace placements; its direct condition was substantially affected by output truncation. Thus answering with supplied traces and a front-placement advantage were different empirical questions. The native source study showed that selected graph questions could be answered reliably under a different configuration. It did not establish that a reader would benefit from those traces.

In the output-budget diagnostic, direct F1 was 1.0000 versus 0.6967 in the earlier run, with the same questions and sampling settings. The prefix preparation-inclusive token bill was 5.91 times that of the new direct condition at the same observed accuracy ceiling. Because its hypothesis was selected after truncation and conditions ran sequentially, it supports a bounded output-budget interpretation, not a pure causal estimate of the reasoning-state mechanism. The retained-case context diagnostic also separated a configured allocation failure from execution at a larger allocation; it did not fill the old trial's missing quality outcomes.

Relation to Trace as State. The original method supplies prior reasoning before an unchanged source, allowing it to guide rereading [1]. Our placement comparison retained that intervention. Differences in models, task lengths, output limits and interfaces prevented a direct comparison with the original benchmark scores. The local uncertainty therefore did not contradict the reported frontier-model result. The original paper also acknowledged additional latency and token costs; our accounting quantified a particular local configuration rather than identifying a flaw overlooked by its authors.

Separating the constraints. Source competence, reader feasibility and placement benefit are distinct questions. A successful source pass answers only the first. Conversely, an incorrect or incomplete source answer does not rule out useful intermediate reasoning: source correctness is not a prerequisite for testing reuse. Context overflow prevents the second pass from testing placement at all. Output-format sensitivity limits interpretation of a measured score difference. Treating these conditions separately prevents an execution failure or parsing difference from being mistaken for a failure of the underlying reasoning principle.

Implications for low-cost inference. In these graph configurations, the larger-output direct diagnostic achieved the same observed 4B accuracy ceiling as the trace conditions with a smaller preparation-inclusive token bill. This is a sequential, known-question diagnostic, not an equal-compute or purely causal comparison. It motivates checking whether a direct baseline has sufficient output allowance before attributing a pipeline advantage to reuse. A lower-cost trace pipeline would also need to reduce or amortize its preparation; the present traces were question-specific, and cross-question amortization was not measured. Token usage does not by itself establish latency, energy or monetary savings.

Implications for further reproduction. Further long-input reproduction should first ensure that the intended trace block and output reserve fit every selected input. It should then compare identical trace content before and after the source with paired graph measurements. Semantic correctness, strict output compliance and truncation should be specified separately before collection. Fewer traces or compressed traces change the intervention and require their own matched controls. These are prospective requirements, not additional findings of this study.

Contribution of the boundary study. The primary contribution is a local accuracy–cost assessment grounded in a reproduction of the placement intervention. The evidence identifies qualified source configurations, cases where the intended second pass was declined under its configured resource contract, and a scoring confound requiring explicit control. It narrows the conditions for a meaningful small-model test. The new compact-input confirmation adds a prespecified accuracy benefit for a single-trace package; it remains separate from the original five-trace placement evidence. Earlier source-free explorations remain outside that confirmed claim.

A usable but bounded improvement. On these graph inputs, users can preserve the complete source through reversible labels and choose between compact direct reading and a single-trace package. The former used fewer tokens; the latter offered higher confirmed F1. The confirmation therefore provides an observed accuracy–token trade-off on a locally served 1.7B model, without assuming that more preparation is always worthwhile. No trace placement advantage or document-task transfer follows from this finding.

6 Limitations

The confirmation sampled twenty-four fresh graph heads from a restricted catalogue-length interval, with twelve per task. Its primary inference is separated from unadjusted secondary comparisons and from the twelve-short-graph discovery signal. Ollama 0.40.0 differs from the earlier 0.35.1 runtime; no pooled cross-version effect is estimated. Reversible graph-label substitution relies on a structured identifier vocabulary and is not a demonstrated compressor for prose. The new experiment does not isolate the trace wrapper from its reasoning content, and the cost comparison changes representation and realized token use. The initial placement study used four graphs with deterministic selection. The prospective follow-up used twelve randomized graph units from restricted, previously unselected short-input pools, including only nine eligible BFS graph heads before sampling. Five readings of each graph did not create additional independent graph units. Most other study selections remained deterministic. The results cannot estimate general performance across tasks, models or domains. Unused graph identities were new to this workflow, not established as absent from model pretraining; public-benchmark contamination was not assessed. Native long-trace and early-state trials were interrupted, so their full-sample quality effects remained unknown. Model families, input complexity and decoding settings changed between studies, preventing architecture-only or scale-only attribution.

Graph questions admit exact conventional algorithms. They served as controlled probes of model behavior, not evidence that language models outperform graph parsers. Legacy synthetic and document experiments had different protocols and incomplete response provenance; they were excluded from the primary evidence. Local hashes and recorded runtime snapshots support consistency checks but do not prove continuous exclusive hardware use or third-party execution authenticity. Token counts alone do not establish energy, monetary or latency savings.

The source traces were prepared for each evaluated question; cross-question reuse and question-independent compression were not tested. The prefix–append contrast holds trace content and its warning wrapper fixed and tests placement. Comparisons with direct reading additionally change supplied content, instructions and preparation compute; they do not isolate a latent-state mechanism or a same-total-budget gain. The incomplete early-state controls cannot remove these ambiguities from the completed five-trace studies.

7 Conclusion

Complete compact inputs and one short reused trace improved the tested local 1.7B model's graph answers: the independent primary comparison increased F1 from 0.6542 to 0.7703, with 39.8% more model tokens than compact direct reading. Secondary comparisons favored recoding and the combined package over original-input direct baselines, while the preceding Trace as State reproduction identified context, output-budget and answer-interface boundaries. Placement superiority and the 8K practical-capacity criterion remained unestablished. The reader takeaway is a measured choice: simplify the complete input for fewer tokens, then add a short trace when the observed accuracy gain justifies its preparation cost; application to natural documents requires separate evidence.

Use of Generative AI Tools

OpenAI generative-AI tools, including Codex, were used for literature discovery, experimental-design discussion, code drafting and debugging, experiment orchestration, statistical and reproducibility checks, figure-code drafting, and language editing. Experimental observations came from archived local Ollama calls and deterministic programs. All fourteen figures were rendered deterministically in R as vector graphics, with plotting sources, audited CSV inputs and raster previews preserved. Numeric extraction and auditing use separately archived Python scripts. Older synthetic and document explorations and the weaker-provenance model bridge are excluded from this manuscript's empirical evidence. The author is responsible for the manuscript and any public submission. No generative-AI system is listed as an author.

References

[1] Xu Zou and Jie Tang. Trace as state: Reasoning traces as conditional states for long-context transformers. *arXiv preprint arXiv:2609.02702*, 2026. URL https://arxiv.org/abs/2609.02702v1.

[2] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. URL https://arxiv.org/abs/2201.11903.

[3] Xiaohan Xu, Chongyang Tao, Tao Shen, Can Xu, Hongbo Xu, Guodong Long, Jian-Guang Lou, and Shuai Ma. Re-reading improves reasoning in large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 15549–15575, 2024. doi: 10.18653/v1/2024.emnlp-main.871. URL https://aclanthology.org/2024.emnlp-main.871/.

[4] Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling LLM test-time compute optimally can be more effective than scaling parameters for reasoning. In *International Conference on Learning Representations (ICLR)*, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/hash/1b623663fd9b874366f3ce019fdfdd44-Abstract-Conference.html.

[5] Huiqiang Jiang, Qianhui Wu, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. Llmlingua: Compressing prompts for accelerated inference of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 13358–13376, 2023. doi: 10.18653/v1/2023.emnlp-main.825. URL https://aclanthology.org/2023.emnlp-main.825/.

[6] Zhuoshi Pan, Qianhui Wu, Huiqiang Jiang, Menglin Xia, Xufang Luo, Jue Zhang, Qingwei Lin, Victor Rühle, Yuqing Yang, Chin-Yew Lin, H. Vicky Zhao, Lili Qiu, and Dongmei Zhang. Llmlingua-2: Data distillation for efficient and faithful task-agnostic prompt compression. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 963–981, 2024. doi: 10.18653/v1/2024.findings-acl.57. URL https://aclanthology.org/2024.findings-acl.57/.

[7] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations (ICLR)*, 2023. URL https://arxiv.org/abs/2203.11171.

[8] Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024. URL https://aclanthology.org/2024.tacl-1.9/.

[9] Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. RULER: What's the real context size of your long-context language models? In *Conference on Language Modeling (COLM)*, 2024. URL https://arxiv.org/abs/2404.06654. arXiv:2404.06654.

[10] OpenAI. GraphWalks: A multi-hop reasoning long-context benchmark. Hugging Face dataset repository, 2025. URL https://huggingface.co/datasets/openai/graphwalks. Accessed 6 October 2026. The archived shorter-file SHA-256 matches the publisher's file metadata; local experiments use 750 rows, not the full repository.

[11] An Yang et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025. doi: 10.48550/arXiv.2505.09388. URL https://arxiv.org/abs/2505.09388.

[12] Qwen Team. Qwen3.5-4B model card. Hugging Face model repository, 2026. URL https://huggingface.co/Qwen/Qwen3.5-4B. Accessed 6 October 2026. Local quantized model tags, digests and serving settings are archived separately.

A Study-Specific Advance Gates

These gates were written in the respective protocols before their calls. They are screening rules for further research, not interchangeable definitions of successful replication or statistical confirmation. The descriptions below locate the original criteria; the frozen protocol and executable analysis govern each result. Failure does not establish impossibility for other models, budgets or tasks.

Short five-trace pilot. Under `protocol_official_graph_five_trace_20261003.md`, inputs must qualify and all readers must normally terminate. Prefix F1 must exceed both append and fresh reading by at least five percentage points, with EM no lower and at least two of four graph differences positive against each control. This gate does not require economical deployment; all five source calls are nevertheless charged in reported cost. One length-terminated fresh reader prevents a pass.

Identity recoding. Under `protocol_official_graph_identity_recode_20261003.md`, inputs must qualify and every compact response must be valid. Compact F1 must exceed original and long-alias F1 by at least ten percentage points, with EM no lower and at least four of eight positive graph differences for each comparison. Compact model-token cost must not exceed original cost. The compact arm has one length termination, so a favorable aggregate point estimate does not pass the gate.

Thinking mode. Under `protocol_official_graph_reasoning_mode_20261003.md`, qualified inputs and at least 31 of 32 normal outputs are required for the off or fixed-route candidate. Relative to always-on, F1 may decrease by at most five percentage points, EM must not decrease, and complete token cost must fall by at least 30%. A route dominated by always-off is not advanced. These are point-estimate screening tolerances, not formal noninferiority evidence. Both observed candidates fail.

Indexed source. Under `protocol_official_graph_indexed_source_20261003.md`, inputs must qualify and indexed-off must produce at least 15 of 16 normal outputs. Its F1 must exceed both original-on and original-off by ten points, with EM no lower; it must exceed compact-off by five points with at least four of eight positive graph differences. Total model tokens must not exceed original-off. The observed indexed-off comparison against original-on cannot satisfy the F1 condition, irrespective of the other missing arms. Compact-on was not this primary candidate.

Model bridge and native source qualification. The bridge's `protocol_official_graph_model_bridge_20261003.md` requires qualified inputs, at least 31 of 32 normal parseable 8B outputs, F1 at least 0.70 and EM at least 0.50. Even favorable missing-outcome bounds fail that gate. The separate native-source qualification protocol requires all sixteen outcomes and usage counts known and qualified, at least fifteen normal parseable outputs, and the same F1/EM thresholds. That study passes. These are source-competence gates, not evidence that a second-pass reader benefits from traces.

Native long five-trace intervention. Its frozen protocol specifies six primary prefix comparisons: append, fresh, question-first, Re2, set mode and node majority. A practical signal needs mean F1 improvement of at least 0.05, a positive lower descriptive paired interval and Holm-adjusted two-sided sign-test $p < 0.05$. Ordering evidence concerns append; an accuracy candidate must satisfy the signal criteria against all five non-trace controls, have EM point values no lower, at least 95% normally parsed outputs, known planned outcomes and qualified returned responses. A cost candidate additionally cannot exceed the cheapest qualified non-trace control's full logical-token cost. The interrupted archive cannot pass these gates. The all-six sign-test family must not be confused with the short-state study's five-control family.

Short native state. Its prospective criteria are given in the main text. The frozen protocol is `partial_state_protocol_20261004.md` in `recovery_bridge_20261003`. This study ended incomplete and did not pass. Seven of eighteen known prefix outputs were not normal-valid, making its threshold of 31/32 unattainable even if all fourteen missing outputs were valid. The prospective gate also required complete qualified execution, F1 gains of at least 0.05 over five controls with positive descriptive paired intervals and Holm-adjusted sign-test significance, EM point estimates no lower, and complete deployment-token cost no greater than the cheapest nonstate control. The post hoc visible-answer sensitivity does not alter these original criteria.

B Mapping the Original Method to the Local Studies

Table 6 specifies the scope of the reproduction against Zou and Tang [1]. It distinguishes a reproduced intervention from reproduction of an effect size.

Evidence checks. A separate verification program recomputed all 750 archived graph answers from directed edges. It also checked ten official-data study archives containing 590 saved call ledgers. Those ledgers included calibration, budget declines and request-only records, not 590 valid answers. Returned visible answers were rescored according to their study-specific frozen rules. Request hashes, frozen dependencies, model snapshots, graph identities, recorded usage and selected graph bootstrap intervals were checked against the archives.

The verification reproduced the reported short-trace F1 differences, source-qualification scores and matched early-state parsing sensitivity. It also retained the returned but unqualified long-trial response and the bridge's interrupted request and client error. No missing answer was generated, no prior call was replayed, and no primary score was replaced. The verification script and per-record SHA-256 manifest are preserved with the release materials.

Evidence boundary. These checks establish consistency between the preserved inputs, outputs and reported analyses. They do not recover absent historical responses or prove continuous exclusive hardware use. In particular, the model bridge retains intended requests reconstructed from frozen code, rather than separately captured complete transmitted payloads. Its provenance is weaker than that of the later request

Component	Original study	Local studies
Placement	Same T in $[T, x, q]$ and $[x, T, q]$; question last	Retained in paired trace comparisons
Source context	Complete original context remains	Complete graph retained; source-free development separate
Source traces	Five exposed reasoning traces; separate visible answers excluded	Five native thinking traces in short and long trials; one capped early trace in the adaptation
Serialization	Fixed warning, delimiters and trace order; first 50,000 characters per reused trace	Original serializer retained for five-trace studies; separate disclosed wrapper for early state
Reader repeats	Five per problem	Five in five-trace studies; two in the early-state adaptation
Models and data	Three frontier models; GraphWalks 256K, MRCRv2 and NUB-1M	Local Qwen variants; selected shorter official graph questions only
Generation limits	No custom client-side maximum requested; effective provider defaults not established	Explicit local context and output caps, recorded for every request
Prompt controls	Question first and Re2 alongside placement controls	Short pilot: direct and placement; native long trial and early state add question first and Re2
Outcome handling	Task-specific scoring and failure rules	Frozen local visible-answer rules, with missing responses and qualification failures distinguished

Table 6: Retained design components and explicit adaptations. The local studies do not reproduce the original models, input lengths, data coverage or provider generation budgets.

ledgers. A separate prospective twelve-graph replication additionally preserves all 240 raw response bodies and complete request records; its selection, allocation and scores were independently checked. It does not recover or validate missing older responses. Old synthetic and document scores were not promoted to official-data evidence.

Historical selection lineage. The earlier model bridge is retained locally to document the workflow and reconstruct graph-exclusion lists. Its intended requests were reconstructed from frozen code, rather than independently captured as complete transmitted payloads. Its quantitative scores are therefore excluded from this manuscript's empirical claims. This preserves selection provenance without relying on weaker historical observations to support the completed placement comparisons.

C Initial Short-Graph Study

The completed Qwen3-1.7B reproduction comprised four new official graphs and eighty calls. Each graph supplied five source traces and five paired repeats of each reader condition. All requests met interface qualification, although five sources and one direct reader reached their output limits.

Trace prefix achieved mean F1 0.7751, compared with 0.7064 for trace append and 0.6187 for direct reading. The prefix-minus-append difference was 6.87 percentage points, with a descriptive interval of $[-1.92, 14.33]$ points. The prefix-minus-direct difference was 15.64 points, with an interval of $[-0.39, 31.67]$ points. Both intervals included zero. Exact match was 0.15 for prefix and direct reading, and 0.05 for append. Thus the F1 point estimates favored prefix placement, but this small study did not establish a reliable placement advantage.

Charging all five source calls gave prefix approximately 8.07 times the tokens of direct reading. These costs quantified resource requirements separately from the placement comparison. The unequal source and reader caps also prevented a same-budget first-pass versus second-pass interpretation.

D Incomplete Early-State Adaptation and Answer-Format Sensitivity

A separate adaptation shortened preparation to a 1,024-token source cap. Seven reader arms retained the complete graph and shared the same total-token allowance. The comparison included direct, question-first, Re2, task cue, prefix, append and a paid neutral prefix.

The runner ended without a terminal completion record. Later inspection confirmed its absence, but not the cause or exact termination time. The archive contained 149 qualified responses, including calibration and source calls, and one request-only record. Of 224 planned reader outputs, 129 were known. Known research usage was at least 3,621,241 tokens.

All-plan prefix F1 was bounded by $[0.34375, 0.78125]$, compared with direct bounds $[0.19585, 0.63335]$ (Figure 11). These ranges represented missing outcomes, not sampling uncertainty. Seven of eighteen known prefix outputs were not normal-valid. Consequently, its required 31/32 normal-valid screening threshold was unattainable even if all remaining prefix outputs were valid.

Visible-answer sensitivity. Five prefix failures reached the output limit; two normally stopped with surrounding prose. Direct reading had two output-limit failures and nine normally stopped malformed outputs. We separately accepted one unambiguous visible `Final Answer: [...]` line within surrounding prose, while still rejecting length termination and thinking-derived answers. This parser was post hoc and left primary scores unchanged.

On eighteen matched graph–seed outputs, prefix, direct and question-first each yielded thirteen exact answers under this sensitivity analysis. Re2 yielded fifteen, while task cue and neutral prefix yielded ten, and append yielded eleven. These incomplete counts did not establish equivalence or Re2 superiority. They showed that the apparent strict exact-match advantage over direct and question-first reading depended on the answer-format rule.

E Reproducibility

Primary archives. The experiments used locally served models on a laptop RTX 5070 Ti with 12 GB GPU memory. The completed short-trace, longer-input and sampling archives are `logs/official_graph_five_trace/`, `logs/official_graph_long_boundary/` and `logs/official_graph_sampling_control/`. Representation and decoding controls retain separate archives under `logs/official_graph_identity_recode/`, `logs/official_graph_reasoning_mode/` and `logs/official_graph_indexed_source/`. Each archive preserves its frozen protocol or dependencies, selected cases and recorded calls. The new prospective replication preserves 240 complete calls under `logs/official_graph_confirmatory_20261006/`. The model bridge and later native studies are under `recovery_bridge_20261003/`. Their records distinguish completed, interrupted, unqualified and unattempted outcomes.

Independent verification. The read-only program `paper/verify_primary_evidence_20261005.py` recomputes graph labels and visible-answer scores without importing the original solver or scorer. Its output is `paper/evidence_verification_20261005/primary_reverification.json`. It records hashes for all 590 inspected earlier ledgers and study-specific results. The separate `paper/audit_confirmatory_20261006.py` independently reconstructs random selection and allocation, recomputes the twelve graph answers, rescores all 240 new raw responses and reports the prespecified descriptive intervals. Its audited CSVs and manifest are under `paper/evidence_verification_20261006/`. Historical rescoring uses preserved parsed native responses; exact transport-byte preservation is a stronger feature of the new studies, not a claim about every historical record. The full source-dataset SHA-256 digest appears in the machine-readable manifest. Local model tags are retained alongside digests because nominal variant names and serving metadata parameter counts are not interchangeable.

Completed follow-ups. The second-model study, output-budget diagnostic and retained-case context diagnostic preserve 240, 60 and 26 calls under `logs/official_graph_paired4b_20261006/`, `logs/output_budget_control_20261006/` and `logs/context_recovery_20261006/`. Their read-only



Figure 11: Early-state adaptation after interrupted execution. Annular angles show known versus unknown outcomes for each arm, with all 32 planned outputs retained in the denominator. Open endpoints delimit F1 identification bounds and printed pairs give both endpoints; these are not sampling intervals. Cost labels marked $\geq$ give known charged deployment tokens divided by 32 planned predictions; every total is incomplete. Each state prediction pays full source cost. Unknown outcomes are not assigned failure scores. The ranges do not establish a quality gain or efficiency advantage.

auditors are `paper/audit_paired4b_20261006.py`, `paper/audit_output_budget_control_20261006.py` and `paper/audit_context_recovery_20261006.py`. Each writes a separate manifest, scored-call table and complete summary. The context count includes one unscored input probe. The bounded evidence package contains the saved responses and copied R inputs; model weights are identified by hashes rather than redistributed.

Complete compact-input extension. Discovery and independent confirmation archives retain 168 and 264 complete calls under `logs/user_benefit_20261009/` and `logs/trace_benefit_confirmation_20261010/`. Frozen protocols, exact payload/response bytes, recoding dictionaries and all failed answers are retained. Separate auditors `paper/audit_user_benefit_20261009.py` and `paper/audit_trace_benefit_confirmation_20261010.py` recompute gold sets and scores without importing the runners. Reports, graph tables, R plotting scripts and preparation-inclusive costs are versioned separately. The discovery's archived cooling correction and reboot recovery preserve the original frozen stimuli and eighteen completed calls. Both extensions use Ollama 0.40.0; they are not pooled with the earlier runtime.

Pinned model packages. The three archived Qwen3-1.7B, Qwen3-4B and Qwen3.5-4B packages use Q4_K_M quantization. Their local manifest and component hashes, including the actual weight files, were checked and recorded. The two Qwen3 public registry manifests matched their frozen digests on 6 October 2026. The Qwen3.5 public tag had changed, so its current package is not the tested version. The old weight's public content-addressed endpoint remained available, while its local manifest, parameters and metadata were preserved. The release records this version difference; an unpinned download is not an exact reproduction. These checks establish package consistency and distinguish it from inference execution provenance.

Figures. Ten empirical figures and two detailed method figures were drawn in OriginPro 2027 from audited CSV inputs. The main confirmation figure was drawn in R from the frozen graph-level results, and an additional overall method schematic was generated in R from the evaluated protocol. Colors and direct labels distinguish the compared methods. The identifier-mapping example, reader input-token counts and token-cost decomposition use confirmation-study records. Figure source code and input tables are retained with editable native projects, vector PDF and high-resolution PNG/TIFF outputs. Earlier R-rendered versions remain archived for comparison. Plot generation does not rescore answers or change experimental observations.

Evidence inclusion. This manuscript reports the separately audited official-graph studies. Older synthetic and document explorations with incomplete response-level provenance, and the earlier bridge with reconstructed intended requests, are excluded from its results and empirical claims. Their archived files are retained unchanged outside the submission. New experiments are recorded prospectively and do not reconstruct missing historical outputs.

Availability. Study protocols, response-level records, scoring programs and figure source files are retained in the reproducibility materials. The experimental evidence has not yet been deposited in a public repository.

F Native Source Qualification

Design. This separately audited experiment tests full-source graph answering under a qualified native-thinking interface. It measures source performance rather than trace reuse. The subsequent five-trace trial terminated early (Appendix G).

Prospective protocol and verification. We used the fixed local `qwen3.5:4b` model digest, Ollama 0.35.1, the archived official general-thinking sampling profile, a 65,536-token context allocation and a 32,768-token output allowance. The original graph, system instruction and terminal-answer format were

retained. Eight distinct official GraphWalks graphs were selected in dataset order after excluding 58 earlier official-study graphs and 16 model-bridge graphs, including interrupted or unreached cases. Two fixed source seeds were used per graph. The catalogue character intervals were $[2000, 3500)$ and $[14000, 16000)$, with two parents and two BFS graphs per interval; catalogue and complete-prompt character counts were recorded separately. One separately logged single-output-token calibration preceded the 16 scored calls. No request was retried. An independent auditor reconstructed selection from historical frozen manifests, recomputed BFS labels using queue distances, rendered the official Jinja template independently of the runner's renderer translation, and verified intended payloads, native input counts, model identity, resident context and usage. All 17 returned records qualified; the calibration was excluded from primary task scores and retained in costs.

Table 7: Full-source qualification on eight independent official graphs, with two repeats per graph. Repeats are averaged within graphs before averaging graphs. F1 is node-set F1. Normal format requires a normal stop and a valid terminal visible answer; it does not imply correctness. No trace reuse was tested in these calls.

Task group	Graphs/calls	F1 (%)	EM (%)	Normal format
Short parents	2/4	100.00	100.00	4/4
Short BFS	2/4	100.00	100.00	4/4
Long parents	2/4	100.00	100.00	4/4
Long BFS	2/4	71.43	50.00	4/4
All planned tasks	8/16	92.86	87.50	16/16

Result and complete known cost. The frozen qualification gate—at least 15 of 16 normal-format outputs, mean F1 at least 0.70, EM at least 0.50, and complete qualified inputs and usage—passed without amendment. Always predicting the empty set yielded F1 and EM of 12.5%. Both exact-match errors were on long-BFS graph 504: its two source F1 scores were 0 and 6/7; graph 505 was answered exactly in both repeats. Thus, the long-BFS subgroup has only two independent graphs, and its 50% EM is not a reliable population-rate estimate. The 16 scored calls used 292,579 API tokens and 3,317.907 seconds of summed client request time; calibration used 117 tokens, yielding 292,696 known research tokens with no unknown usage. Recorded selection, independent label checking, token counting and metadata preparation before freeze serialization took 2.172 seconds. Server total, load, prefill and decode times are reported separately in the archived analysis; these fields need not sum exactly. This is not a measured five-trace deployment cost or an energy comparison.

Interpretive limits and next test. Model family, training, tokenizer, sampling profile, output allowance and fresh graph identities differ from earlier bridges, so cross-stage differences do not identify a parameter-size, architecture-only or budget-only causal effect. "Fresh" means unused in this research workflow; pretraining non-overlap with these public graphs has not been established. Longer cases also contain larger graphs. The result qualifies a local source configuration for further study, but establishes neither trace-reuse gains nor source-free sufficiency. A source-performance gate is not a necessary condition for studying trace rescue: the original paper also reported trace benefits from much weaker first-pass scores. The gate's own verdict remains unchanged.

A four-stratum follow-up was infeasible because only three unused short BFS graphs remained where four were required. Its implementations and failure identity were preserved. Together with the pilot's short-task and long-parents ceiling, this motivated a separately frozen study of 16 fresh long-BFS graphs, selected in dataset order with no future case-score filtering. This task focus is pilot-informed; it is not an outcome-independent task-family choice. The follow-up retains five native source traces, five repeats per reader, identical bundles in prefix and append, full-source sampling, Question First and full-prompt Re2 controls, and distinct node-wise majority and whole-set-mode source-answer controls. Its 131,072-token context requires a separate logged calibration. A single trace prediction pays for all five sources and one expected reader. A positive pilot would still require independent fresh-case confirmation.

A structural single-prediction token-cost boundary. A separate analytic check of the frozen follow-up inputs establishes a resource boundary without inspecting its solver outcomes. Let I denote the qualified full-source input-token count and C the common output allowance. A fresh full-source call costs at most $I + C$ logical API tokens, whereas a prediction paying for five sources incurs at least $5I$ source-input tokens before any source outputs or feedback reader. Hence $I > C/4$ rules out lower one-prediction total-token cost for this five-source design. All 16 follow-up cases satisfy this inequality at $C = 32{,}768$. Their mean five-source input-only lower bound is 56,303.4375 tokens, exceeding the fresh-call input-plus-maximum-output upper bound of 44,028.6875. These are conditional planned-request bounds, not measured interim performance means. Actual qualified inputs must match the independently rendered counts and returned outputs must obey the frozen allowance. The cost criterion remains unchanged, and the accuracy and same-state placement questions remain open. The bound concerns logical token accounting, not cache-adjusted computation, latency, monetary cost or all possible trace methods. Fewer source passes, cheaper evidence readout or preparation reused across genuinely different deployed questions require separate new-case experiments; repeated samples of one question do not justify dividing the source bill by five.

Archives and release status. The complete qualification payloads, raw responses, frozen dependencies, independent audit, analysis and figure inputs are in `recovery_bridge_20261003/hybrid_source_qualification/`; the bounded report is `paper/OFFICIAL_GRAPH_HYBRID_SOURCE_20261004.md`. The analytic per-case cost certificate is `hybrid_five_trace_single_prediction_cost_bound_20261004.json` under the recovery directory. The new five-trace protocol and analysis are frozen separately. The manuscript source package was compiled locally after figure replacement. This does not establish successful compilation on the arXiv server or completion of every historical response audit.

G Interrupted Native Five-Trace Trial

Terminal status and frozen denominator. The prospective follow-up fixed 16 fresh long-BFS graphs, five source calls per graph and five repeats of each of five reader arms, for 480 scored slots plus one calibration. The process terminated after ordinal 24 because the post-response residency check failed. Independent reconstruction of dataset selection, queue-based gold labels, request rendering, seed order, native trace serialization, joint input feasibility, usage and the consecutive execution prefix passed. The frozen analysis was then executed unchanged. Only the first graph's source bundle was generated. Of the 480 scored slots, 14 returned qualified responses, eight were recorded as untransmitted budget declines, one returned response was unqualified, and 457 were not reached. Thus 22 scored outcomes are determined and 458 remain undetermined under the frozen primary rules. Neither a successful audit nor a normal process exit establishes completion of the planned experiment.

Qualification failure is not a reasoning failure. Ordinal 24 returned a normal stop, the expected model name, 11,246 input tokens matching the independently rendered count, and 19,563 output tokens. Its subsequently archived `/api/ps` response contained an empty model list, so the frozen digest-and-context residency criterion failed. The response and incurred usage remain archived, but its primary score is undetermined. Later read-only metadata showed a different resident model, `qwen3:8b`, at a 32,768-token context. The surrounding server log also recorded other `/v1/chat/completions` requests, that model's loading, and GPU-discovery warnings. This temporal evidence is consistent with shared-runtime switching but does not identify a unique cause or caller. Earlier qualification snapshots do not prove continuous resource exclusivity. A later model load cannot retrospectively qualify the failed record, and no stopped primary request was replayed.

Observed context boundary. The five actual source thinking fields had 40,116, 34,511, 37,679, 36,275 and 41,308 characters. None exceeded the original-style 50,000-character threshold, so no trace was clipped. Both independently reconstructed trace reader inputs contained 144,677 tokens, already 13,605 above the frozen 131,072-token context. With the common 32,768-token output allowance and 64-token margin, the reserve was 177,509. Reducing only the output reserve cannot fit this full input. The predeclared joint policy declined prefix and append symmetrically. Eight decline records were actually reached; later

planned slots retain the frozen missing-outcome treatment. This is a deployment-feasibility observation on one graph and configuration, not proof that every remaining graph would fail or that a fitting trace would be ineffective. A character cap is not a portable token-budget guarantee.

What the frozen analysis can establish. Full-plan F1 bounds are $[0.0344, 0.9969]$ for direct sampling, $[0.0342, 0.9967]$ for Question First, $[0.0360, 0.9985]$ for Re2, and $[0, 0.95]$ for both trace arms. No complete graph pair supports the predeclared prefix contrasts. Ordering, accuracy-candidate, cost-candidate and important-progress indicators are all false. Failure to meet these evidence gates does not prove absence of every possible accuracy effect. Conditional scores from a few repeats on one graph cannot replace the prospective 16-graph comparison.

Incurred cost and release scope. All actually transmitted usage is known: 595,885 research tokens, including 117 calibration tokens and 595,768 scored-call tokens. The first graph's five sources alone cost 190,884 tokens; they remain charged to any trace-based single prediction even when the reader is declined. Summed scored-call client time was 7,777.206 seconds. These are incurred interrupted-workflow quantities, not complete-plan or average single-deployment costs. Before-freeze preparation and shared bundle/all-reader-job preparation were separately 2.266 and 3.234 seconds; the missing complete-workflow timer remains unmeasured. The analytic one-prediction logical-token boundary in Section F remains conditional on its specified configuration; actual caching, latency, energy and genuine cross-question amortization are different questions.

Original ledgers, terminal status, independent audit, frozen analysis, runtime diagnostics, figure CSVs and vector/600 dpi outputs are preserved in `recovery_bridge_20261003/hybrid_five_trace_replication/`. The bounded report is `paper/OFFICIAL_GRAPH_HYBRID_FIVE_TRACE_INTERRUPTED_20261004.md`. A future bounded-state adaptation requires a separate frozen protocol and fresh cases; selected but unreached graphs cannot be quietly recycled as independent confirmation.

H Interrupted Indexed-Source Comparison

Protocol and audit scope. This separate official-data experiment tested the local `qwen3:1.7b` reader on eight distinct graphs, two fixed seeds and six arms: original source with a common glossary, a reversible compact edge list, and a complete directed-relation index, each with thinking enabled or disabled. The allocated context was 32,768 tokens and output cap 8,192 tokens. The graph structure, including duplicate edges, self-loops and node inventory, was retained; the indexed representation uses incoming relations for parents and outgoing relations for BFS. The original-plus-glossary arm is not byte-identical to the official source baseline used in other stages. Independent response and selection audits both passed. Selection was reconstructed from eight prior frozen manifests excluding 50 graph identities, with the fixed length/task strata and interleaving order. Public-case nonoverlap with our earlier studies does not establish absence from model pretraining.

Incomplete execution and bounded outcomes. Ninety-four of 96 planned responses were saved. The final original/thinking-off call was attempted but its response and usage are unknown; the final compact/thinking-on call was not reached. Neither was replayed or replaced. All planned repetitions remain in the denominator; missing F1/EM values range from zero to one. These identification bounds are not confidence intervals. Complete response records were scored using the qualified, normally stopped visible terminal answer; unknown nodes count as false positives. Table 8 and Figure 12 retain the missingness rather than assigning unknown executions a fabricated failure score.

What the comparison establishes. The prespecified indexed/thinking-off candidate cannot meet its requirement of a 0.10 F1 increase over original/thinking-on. A secondary compact/thinking-on signal remains positive under every possible missing response: F1 is higher by 11.20–17.45 percentage points and EM by 31.25–37.50 points. This was not the primary candidate, the graph sample is small, and its cost is incomplete; it requires separate new-case confirmation before a joint accuracy–efficiency claim. Incoming-node indexing may convert parents into a lookup and must be compared with a conventional exact graph




Figure 12: Interrupted representation comparison by thinking mode. Coverage rings show known versus unknown readings out of sixteen per arm. Teal F1 and orange EM endpoint pairs give identification bounds over all planned slots; the F1 bounds are also printed. Zero-width ranges represent complete observed arms, not absence of sampling uncertainty. Costs are observed input-plus-output token sums, with $\geq$ marking incomplete lower bounds. CPU preprocessing (1.188 s) and compact-dictionary storage (36,612 bytes) remain separate. Unknown readings were not resent.

Table 8: Interrupted representation comparison. Each arm planned 16 readings of eight graphs. Token entries are observed arm sums of model input and output; an asterisk denotes an incomplete cost lower bound, not a full deployment cost.

Representation / thinking	Saved	F1 (%)	EM (%)	Tokens
Original / on	16	44.84	12.50	107,475
Original / off	15	28.39–34.64	0–6.25	53,844*
Compact / on	15	56.04–62.29	43.75–50.00	51,247*
Compact / off	16	25.80	0	36,047
Indexed / on	16	40.77	31.25	52,847
Indexed / off	16	44.50	12.50	23,032

program rather than presented as wholly model-performed reasoning. The known research token total is at least 324,492, with the attempted missing call's usage unknown.

The raw/frozen ledgers, response audit, separate selection certificate, release CSVs and R outputs are preserved under `logs/official_graph_indexed_source/`. The selection certificate verifies the study-specific graph selection. This evidence is separate from the 4B native five-trace migration study and does not establish a trace-reuse effect.

I Representation and Thinking-Mode Controls

Complete-source identity recoding. A separate eight-graph, two-seed experiment with `qwen3:1.7b` compared the original labels, reversible short aliases and a long-alias control of comparable input-token length, retaining every graph relation. All 48 saved calls qualified, with no unknown usage. Strict F1 was 0.4371, 0.5904 and 0.3232 respectively; EM was 0.250, 0.375 and 0.125. Normally stopped valid responses numbered 14/16, 15/16 and 13/16. Observed input-plus-output token sums were 114,237, 56,591 and 117,151; these sums include both seeds, rather than representing a mean single prediction. Compact labels reduced input tokens by 69.15% and total model tokens by 50.46% against the original arm, with a separate 25,156-byte dictionary and 1.034 s measured preprocessing. These quantities do not establish a complete hardware or contiguous deployment-time advantage.

The compact-minus-original mean F1 difference was +0.1523, with a descriptive graph-cluster interval $[-0.2115, 0.4098]$; six of eight graph differences were positive. The compact-minus-long-alias contrast was +0.2662, interval $[0.0109, 0.4699]$, an exploratory contrast. The prespecified follow-up gate failed. Parent questions benefited more than BFS in this small sample, so the overall point estimate is not a task-uniform effect. This intervention changes representation, not self-generated reasoning state. Label reversibility, graph equivalence, selection, strict unknown-node scoring and archived assets were independently audited. An initially over-restrictive alias parser was repaired with the original raw responses retained; its diagnostic record is preserved.

Thinking-mode control and fixed task route. Sixteen different official graphs and two matched seeds were tested with thinking enabled or disabled, holding the source, model, remaining settings and nominal output allowance fixed. All 64 calls qualified with known usage; 31/32 on and 30/32 off responses normally stopped and met the terminal format. Thinking-on scored F1 0.3784 and EM 0.09375; off scored 0.1643 and 0. The prespecified route (parents off, BFS on) is derived from the relevant saved paired calls, not a third independently generated 32-call arm; it scored 0.3191 and 0.0625. Physical token sums were 206,611 for on and 132,042 for off. The selected route calls sum to 162,993 tokens.

For one seed-averaged prediction per graph, the 16-graph cost sums are 103,305.5, 66,021 and 81,496.5 tokens, respectively. These divide physical two-seed sums by two; they are not mean single-question costs, which require a further division by 16. Off reduced model tokens by 36.09% but decreased F1 by 21.41 percentage points, descriptive interval $[-35.19, -10.10]$ points. Routing reduced tokens by 21.11% but decreased F1 by 5.93 points, interval $[-13.34, -0.61]$. Neither adaptation passed its follow-up gate. A cheap mode that gives worse answers is not a quality-preserving efficiency result. The thinking-off sampling profile was not separately optimized; this comparison does not establish the best achievable off-mode performance.




Figure 13: Identity recoding on eight graph units and two seeds per arm. (a) Each colour tracks one identified graph across original, compact and long-alias representations, separately by task. F1 averages the two seeds; curved links interpolate between discrete conditions only. Horizontal marker offsets separate coincident scores without changing F1. (b) Fixed-radius annuli encode input/output token shares by angle, not total cost by size; centres print observed totals charging both readings per graph. Mean F1 and existing descriptive 95% intervals appear below. Dictionary storage and CPU preprocessing are separate. All graph information survives reversible recoding; a positive estimate does not override the failed follow-up gate.

Release provenance. The two completed studies preserve 112 qualified calls and 626,632 observed research tokens. `consolidate_representation_releases_20261004.py` verifies the existing independent-audit asset hashes, figure CSV/summary correspondence, raw model-token sums and the route-cost denominator. Its separate release manifest adds provenance checks without rewriting the original freezes, responses or analyses. Both studies used the nominal 1.7B Qwen3 variant and must remain distinct from the new 4B native partial-state experiment. Their primary purpose is to identify confounds and boundaries, not to establish a self-state mechanism.




Figure 14: Thinking-mode and fixed-route comparison on sixteen graph units and two paired seeds. (a) Four task–length strata with four graphs each; arrows connect thinking-off circles to thinking-on diamonds in the quality–cost plane. Axes are shared, F1 averages graphs, and token totals sum seed-averaged costs within strata. Arrows do not imply a continuous response curve or causal isolation. (b) All-graph complete-token totals, F1 means and existing descriptive 95% intervals. Route reuses the prespecified parents/off and BFS/on subsets of saved calls. Lower cost accompanies lower observed quality; no trace-order mechanism is tested.