



微软亚洲研究院创研论坛

CVPR 2020 论文分享会



Supervised Raw Video Denoising with a Benchmark Dataset on Dynamic Scenes

Huanjing Yue, Cong Cao, Lei Liao, Ronghe Chu, and Jingyu Yang


Tianjin University

https://github.com/cao-cong/RViDeNet



1 研究背景

- □由于ISP过程的影响,sRGB域噪声特性复杂。
- □ Raw域数据信息更为丰富,且与曝光量成线性响应。







1 研究背景

- □ 带噪-干净图像数据集不断涌现,实际图像去噪算法取得显著进展。
- □ 带噪-干净视频数据集缺失,实际视频去噪算法研究较少。



(a) Low-ISO image




(b) High-ISO image



(c) Zoom-in of the low-ISO image (left) and the high-ISO image (right)



DND dataset



SIDD dataset



2 数据集构建


lil.

□困难

无法同步拍摄带噪-干净帧

□解决方法


定格动画拍摄法






2 数据集构建

□共拍摄55组室内数据集,包含11个场景,5种ISO设置




2 数据集构建

□ 室外数据集,仅用于测试。











The framework of proposed RViDeNet.


□ 鉴于噪声影响alignment, 借鉴BM3D两阶段去噪思想, 利用预去噪来辅助对齐运算。







2019-CVPR-DANet





□ 损失函数

$$\begin{split} \mathcal{L} = & \mathcal{L}_{\text{rec}} + \lambda \mathcal{L}_{\text{tmp}}, \\ \mathcal{L}_{\text{rec}} = & \|I_t^{\text{raw}} - O_t^{\text{raw}}\|_1 + \beta \|I_t^{\text{sRGB}} - O_t^{\text{sRGB}}\|_1, \\ \mathcal{L}_{\text{tmp}} = & \|\hat{O}_t^{\text{raw}_1} - \hat{O}_t^{\text{raw}_2}\|_1, \\ & + \gamma (\|I_t^{\text{raw}} - \hat{O}_t^{\text{raw}_1}\|_1 + \|I_t^{\text{raw}} - \hat{O}_t^{\text{raw}_2}\|_1), \end{split}$$




□ 消融实验

Ablation study for raw domain processing, packing, pre-denoising and non-local attention modules. The PSNR (or SSIM) results are the averaging results on all the testing videos under different ISO settings ranging from 1600 to 25600.


Raw dor	nain	×	\checkmark	√	√	$\overline{\hspace{1cm}}$	
Packing		×	×	\checkmark	\checkmark	\checkmark	
Pre-denoising		×	×	×	\checkmark	\checkmark	
Non-loc	al attention	×	×	×	×	\checkmark	
Raw	PSNR	-	43.84	43.84	43.88	43.97	
	SSIM	-	0.9866	0.9866	0.9871	0.9874	
sRGB	PSNR	38.58	39.69	39.69	39.80	39.95	
	SSIM	0.9703	0.9776	0.9778	0.9785	0.9792	



□ 对齐模块评测
















		Noisy	ViDeNN [11]	VBM4D [24]	TOFlow [43]	SMD [8]	SMD*	EDVR [35]	DIDN [44]	Ours ⁻	Ours
Raw	PSNR	32.01	-	-	-	-	-	-	43.25	43.37	43.97
	SSIM	0.732	-	-	-	-	-	-	0.984	0.985	0.987
sRGB	PSNR	31.79	31.48	34.16	34.81	26.26	35.87	38.97	38.83	39.19	39.95
	SSIM	0.752	0.826	0.922	0.921	0.912	0.957	0.972	0.974	0.975	0.979





Comparison on outdoor dataset.




Supervised Raw Video Denoising with a Benchmark Dataset on Dynamic Scenes









5 总结

- A benchmark video denoising dataset
- An efficient video denoising network-RViDeNet
- State-of-the-art video denoising performance





谢谢观看 THANKYOU

