Laboratory Assignment File

for

Cryptography Laboratory (CS0557)

Master of Technology

in

Computer Science & Engineering

Submitted by

Yugal

(Roll no. 25903053)

Submitted to

Dr. Harsh Kumar Verma

(Assistant Professor, NIT Jalandhar)

Department of Computer Science & Engineering

Dr. B R Ambedkar National Institute of Technology Jalandhar

Punjab, India-144008

June, 2026

Contents

Assignment 1: Basic Programs (28-01-2026) 1

1.1 Write a program to print prime numbers between 1 and 1000. 1

1.2 Write a program to perform matrix multiplication. 1

1.3 Write a program to find inverse of a matrix. 4

Assignment 2: Hill and Caesar Substitution Cipher (04-02-2026) 7

2.1 Implement Caesar substitution cipher in Python. 7

2.2 Implement Hill cipher in Python. 8

Assignment 3: Vigenere Cipher and Rail Fence Cipher (11-02-2026) 11

3.1 Implement Vigenere Cipher in Python. 11

3.2 Implement Rail Fence Cipher in Python. 12

Assignment 4: Perform encryption and decryption using Playfair cipher. (18-02-2026) 15

4.1 Implement Playfair Cipher in Python. 15

Assignment 5: Perform encryption and decryption using columnar transposition and one-time padding cipher. (25-02-2026) 19

5.1 Implement Columnar Transposition Cipher in Python. 19

5.2 Implement One-Time Pad Cipher in Python. 21

List of Figures

1 Program to print prime numbers between 1 and 1000 1
2 Program to perform matrix multiplication 4
3 Program to find inverse of a matrix 6
4 Program to implement Caesar Substitution Cipher 8
5 Program to implement Hill Cipher 10
6 Program to implement Vigenere Cipher 12
7 Program to implement Rail Fence Cipher 14
8 Program to implement Playfair Cipher 18
9 Program to implement Columnar Transposition Cipher 21
10 Program to implement One-Time Pad Cipher 23

Assignment 1: Basic Programs

1.1 Write a program to print prime numbers between 1 and 1000.

```java
import java.util.ArrayList;
import java.util.List;

public class Prime {
    public static void main(String[] args) {
        List<Integer> primes = new ArrayList<>();
        int x = 1;
        int y = 100;

        for (int i = 2; i <= y; i++) {
            boolean isPrime = true;

            for (int j = 2; j <= i / 2; j++) {
                if (i % j == 0) {
                    isPrime = false;
                    break;
                }
            }

            if (isPrime) {
                primes.add(i);
            }
        }

        System.out.println("Prime numbers between " + x + " and " + y + ":");
        System.out.println(primes);
    }
}
```

Output



Figure 1: Program to print prime numbers between 1 and 1000

1.2 Write a program to perform matrix multiplication.

```java
import java.util.Scanner;

public class Matrix_Multiplication {

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.println("Enter the number of rows for the first matrix (A):");
        int rowsA = scanner.nextInt();
        System.out.println("Enter the number of columns for the first matrix (A):");
        int colsA = scanner.nextInt();

        System.out.println("Enter the number of rows for the second matrix (B):");
        int rowsB = scanner.nextInt();
        System.out.println("Enter the number of columns for the second matrix (B):");
        int colsB = scanner.nextInt();

        if (colsA != rowsB) {
            System.out.println("\nError: Matrix multiplication is not possible.");
            System.out.println("The number of columns in the first matrix must equal the number of rows in the second matrix.");
            return;
        }

        int[][] matrixA = new int[rowsA][colsA];
        int[][] matrixB = new int[rowsB][colsB];
        int[][] resultMatrix = new int[rowsA][colsB];

        System.out.println("\nEnter elements of the first matrix (A):");
        for (int i = 0; i < rowsA; i++) {
            for (int j = 0; j < colsA; j++) {
                System.out.print("A[" + i + "][" + j + "]: ");
                matrixA[i][j] = scanner.nextInt();
            }
        }

```

```java
        System.out.println("\nEnter elements of the second matrix (B):");
        for (int i = 0; i < rowsB; i++) {
            for (int j = 0; j < colsB; j++) {
                System.out.print("B[" + i + "][" + j + "]: ");
                matrixB[i][j] = scanner.nextInt();
            }
        }

        for (int i = 0; i < rowsA; i++) {
            for (int j = 0; j < colsB; j++) {
                for (int k = 0; k < colsA; k++) {
                    resultMatrix[i][j] += matrixA[i][k] * matrixB[k][j];
                }
            }
        }

        System.out.println("\nResultant Matrix:");
        for (int i = 0; i < rowsA; i++) {
            for (int j = 0; j < colsB; j++) {
                System.out.print(resultMatrix[i][j] + " ");
            }
            System.out.println();
        }

        scanner.close();
    }
}
```

Output

```
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$  cd /home/yugal/Desktop/Semester\ 2/Labs/Crptography\
 Lab ; /usr/bin/env /usr/lib/jvm/java-11-openjdk-amd64/bin/java -cp /home/yugal/.config/Code/User/workspaceStorage/e4044ed479fc30
757aa14dfefed21415/redhat.java/jdt_ws/Crptography\ Lab_5f4dd023/bin Matrix_Multiplication
Enter the number of rows for the first matrix (A):
3
Enter the number of columns for the first matrix (A):
3
Enter the number of rows for the second matrix (B):
3
Enter the number of columns for the second matrix (B):
3

Enter elements of the first matrix (A):
A[0][0]: 1
A[0][1]: 2
A[0][2]: 3
A[1][0]: 4
A[1][1]: 5
A[1][2]: 6
A[2][0]: 7
A[2][1]: 8
A[2][2]: 9

Enter elements of the second matrix (B):
B[0][0]: 1
B[0][1]: 2
B[0][2]: 3
B[1][0]: 4
B[1][1]: 5
B[1][2]: 6
B[2][0]: 7
B[2][1]: 8
B[2][2]: 9

Resultant Matrix:
30 36 42
66 81 96
102 126 150
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$ ^C
```

Figure 2: Program to perform matrix multiplication

1.3 Write a program to find inverse of a matrix.

```java

import java.util.Scanner;

public class MatrixInverseSimple {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        double[][] a = new double[3][3];

        System.out.println("Enter elements of 3x3 matrix:");

        // Input
        for (int i = 0; i < 3; i++) {
            for (int j = 0; j < 3; j++) {
                a[i][j] = sc.nextDouble();
            }
```

```java
        }

        // Determinant
        double det =
                a[0][0] * (a[1][1]*a[2][2] - a[1][2]*a[2][1])
              - a[0][1] * (a[1][0]*a[2][2] - a[1][2]*a[2][0])
              + a[0][2] * (a[1][0]*a[2][1] - a[1][1]*a[2][0]);

        if (det == 0) {
            System.out.println("Matrix is singular. No inverse.");
            return;
        }

        // Adjoint matrix
        double[][] adj = new double[3][3];

        adj[0][0] =  (a[1][1]*a[2][2] - a[1][2]*a[2][1]);
        adj[0][1] = -(a[0][1]*a[2][2] - a[0][2]*a[2][1]);
        adj[0][2] =  (a[0][1]*a[1][2] - a[0][2]*a[1][1]);

        adj[1][0] = -(a[1][0]*a[2][2] - a[1][2]*a[2][0]);
        adj[1][1] =  (a[0][0]*a[2][2] - a[0][2]*a[2][0]);
        adj[1][2] = -(a[0][0]*a[1][2] - a[0][2]*a[1][0]);

        adj[2][0] =  (a[1][0]*a[2][1] - a[1][1]*a[2][0]);
        adj[2][1] = -(a[0][0]*a[2][1] - a[0][1]*a[2][0]);
        adj[2][2] =  (a[0][0]*a[1][1] - a[0][1]*a[1][0]);

        // Inverse = adjoint / determinant
        System.out.println("Inverse Matrix:");

        for (int i = 0; i < 3; i++) {
            for (int j = 0; j < 3; j++) {
                System.out.printf("%6.2f ", adj[i][j] / det);
            }
            System.out.println();
        }

        sc.close();
    }
}
```

Output

```
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$  cd /home/yugal/Desktop/Semester\ 2/Labs/Crptography\
 Lab ; /usr/bin/env /usr/lib/jvm/java-11-openjdk-amd64/bin/java -cp /home/yugal/.config/Code/User/workspaceStorage/e4044ed479fc30
757aa14dfefed21415/redhat.java/jdt_ws/Crptography\ Lab_5f4dd023/bin MatrixInverseSimple
Enter elements of 3x3 matrix:
2 3 5
6 7 3
4 5 9
Inverse Matrix:
 -2.40   0.10   1.30
  2.10   0.10  -1.20
 -0.10  -0.10   0.20
```

Figure 3: Program to find inverse of a matrix

Assignment 2: Hill and Caesar Substitution Cipher

2.1 Implement Caesar substitution cipher in Python.

```python
alphabet=list('abcdefghijklmnopqrstuvwxyz')

def encryption(plain_text, shift_key):
    cipher_text = ""
    plain_text = plain_text.lower()
    for char in plain_text:
        if char in alphabet:
            position = alphabet.index(char)
            new_position = (position+shift_key)%26
            cipher_text += alphabet[new_position]
        else:
            cipher_text += char
    print(f"Here is the text after encryption: {cipher_text}")

def decryption(cipher_text, shift_key):
    plain_text = ""
    cipher_text = cipher_text.lower()
    for char in cipher_text:
        if char in alphabet:
            position = alphabet.index(char)
            new_position = (position-shift_key)%26
            plain_text += alphabet[new_position]
        else:
            plain_text += char
    print(f"Here is the text after decryption: {plain_text}")

wanna_end = False
while not wanna_end:
    what_to_do = input("Type 'encrypt' for encryption, type 'decrypt' for decryption: \n")
    text = input("Type your message: ")
    shift = int(input("Encrypt shift key: "))

    if what_to_do == "encrypt":
        encryption(plain_text=text, shift_key=shift)
    elif what_to_do == "decrypt":
        decryption(cipher_text=text, shift_key=shift)
    play_again = input("Type 'yes' to continue, type 'no' to stop and exit: ")

```

```
    if play_again == 'no':
        wanna_end = True
        print("Exiting Program")
```

Output



```
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$ /home/yugal/anaconda3/bin/python "/home/yugal
/Desktop/Semester 2/Labs/Crptography Lab/Lab_2/Caesor_Substitution_Cipher.py"
Type 'encrypt' for encryption, type 'decrypt' for decryption:
encrypt
Type your message: yugal
Encrypt shift key: 3
Here is the text after encryption: bxjdo
Type 'yes' to continue, type 'no' to stop and exit: yes
Type 'encrypt' for encryption, type 'decrypt' for decryption:
decrypt
Type your message: bxjdo
Encrypt shift key: 3
Here is the text after decryption: yugal
Type 'yes' to continue, type 'no' to stop and exit: no
Exiting Program
```

Figure 4: Program to implement Caesar Substitution Cipher

2.2 Implement Hill cipher in Python.

```
alphabet = list('abcdefghijklmnopqrstuvwxyz')

print("Enter 4 numbers for the key matrix (2*2): ")
a = int(input("a: "))
b = int(input("b: "))
c = int(input("c: "))
d = int(input("d: "))

key_matrix = [[a,b],
              [c,d]]

# modular inverse of number mod 26
def mod_inverse(num):
    num = num%26
    for i in range(26):
        if(num * i) % 26 == 1:
            return i
    return -1

# inverse key matrix
def inverse_key_matrix():
    a = key_matrix[0][0]
    b = key_matrix[0][1]
    c = key_matrix[1][0]
    d = key_matrix[1][1]
```

```python

    # determinant
    det = (a*d - b*c)%26

    inv_det = mod_inverse(det)
    if inv_det == -1:
        print("Invalid key!")
        return None

    # inverse matix
    inv_a = (d*inv_det)%26
    inv_b = (-b*inv_det)%26
    inv_c = (-c*inv_det)%26
    inv_d = (a*inv_det)%26

    return [[inv_a, inv_b],
            [inv_c, inv_d]]

def encrypt(plain_text):
    plain_text = plain_text.replace(" ","").lower()

    # if odd, use x
    if len(plain_text)%2 != 0:
        plain_text += 'x'

    cipher_text = ""

    # process letter in pair
    for i in range(0, len(plain_text), 2):
        p1 = alphabet.index(plain_text[i])
        p2 = alphabet.index(plain_text[i+1])

        # matrix muliplication
        c1 = (key_matrix[0][0] * p1 + key_matrix[0][1] * p2) % 26
        c2 = (key_matrix[1][0] * p1 + key_matrix[1][1] * p2) % 26

        cipher_text += alphabet[c1] + alphabet[c2]
    print("Encrypted text : ", cipher_text)

def decrypt(cipher_text):
    inv_matix = inverse_key_matrix()
    if inv_matix is None:
        return
    plain_text = ""
```

```python

    for i in range(0, len(cipher_text), 2):
        c1 = alphabet.index(cipher_text[i])
        c2 = alphabet.index(cipher_text[i+1])

        # multiply by inverse key
        p1 = (inv_matix[0][0] * c1 + inv_matix[0][1] * c2) % 26
        p2 = (inv_matix[1][0] * c1 + inv_matix[1][1] * c2) % 26

        plain_text += alphabet[p1] + alphabet[p2]
    print("Decrypted text: ", plain_text)

choice = input("Type 'encrypt' or 'decrypt': ")
message = input("Type your message: ")

if choice == "encrypt":
    encrypt(message)
elif choice == "decrypt":
    decrypt(message)
else:
    print("Invalid option")
```

Output



Figure 5: Program to implement Hill Cipher

Assignment 3: Vigenere Cipher and Rail Fence Cipher

3.1 Implement Vigenere Cipher in Python.

```python
import string

alphabet = list('abcdefghijklmnopqrstuvwxyz')

def encrypt(plain_text, key):
    cipher_text = ""
    key = key.lower()
    key_index = 0

    for char in plain_text.lower():
        if char in alphabet:
            text_pos = alphabet.index(char)
            key_pos = alphabet.index(key[key_index % len(key)])
            new_pos = (text_pos + key_pos) % 26
            cipher_text += alphabet[new_pos]
            key_index += 1
        else:
            cipher_text += char

    return cipher_text

def decrypt(cipher_text, key):
    plain_text = ""
    key = key.lower()
    key_index = 0

    for char in cipher_text.lower():
        if char in alphabet:
            text_pos = alphabet.index(char)
            key_pos = alphabet.index(key[key_index % len(key)])
            new_pos = (text_pos - key_pos) % 26
            plain_text += alphabet[new_pos]
            key_index += 1
        else:
            plain_text += char

    return plain_text


# -------- Main Program --------
```

```python
while True:
    choice = input("Type 'encrypt' or 'decrypt': ").lower()
    text = input("Enter your message: ")
    key = input("Enter the key: ")

    if choice == "encrypt":
        result = encrypt(text, key)
        print("Encrypted text:", result)

    elif choice == "decrypt":
        result = decrypt(text, key)
        print("Decrypted text:", result)

    else:
        print("Invalid choice!")

    again = input("Continue? (yes/no): ").lower()
    if again == "no":
        print("Exiting program.")
        break
```

Output



Figure 6: Program to implement Vigenere Cipher

3.2 Implement Rail Fence Cipher in Python.

```python
def rail_fence_encrypt(text, rails):
    if rails == 1:
        return text

    result = ""
    gap = 2 * (rails - 1)

    for r in range(rails):
```

```
        i = r
        down = True
        step1 = gap - 2 * r
        step2 = 2 * r

        while i < len(text):
            result += text[i]

            if r == 0 or r == rails - 1:
                i += gap
            else:
                if down:
                    i += step1
                else:
                    i += step2
                down = not down

    return result

def rail_fence_decrypt(cipher, rails):
    if rails == 1:
        return cipher

    n = len(cipher)
    result = [''] * n
    gap = 2 * (rails - 1)
    idx = 0

    for r in range(rails):
        i = r
        down = True
        step1 = gap - 2 * r
        step2 = 2 * r

        while i < n and idx < n:
            result[i] = cipher[idx]
            idx += 1

            if r == 0 or r == rails - 1:
                i += gap
            else:
                if down:
                    i += step1
                else:
```

```python
                    i += step2
                down = not down

    return "".join(result)

# -------- Main Program --------
while True:
    choice = input("Type 'encrypt' or 'decrypt': ").lower()
    text = input("Enter your message: ")
    rails = int(input("Enter number of rails: "))

    if choice == "encrypt":
        result = rail_fence_encrypt(text, rails)
        print("Encrypted text:", result)

    elif choice == "decrypt":
        result = rail_fence_decrypt(text, rails)
        print("Decrypted text:", result)

    else:
        print("Invalid choice!")

    again = input("Continue? (yes/no): ").lower()
    if again == "no":
        print("Exiting program.")
        break
```

Output

```
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$ /home/yugal/anaconda3/bin/python "/home/yugal
/Desktop/Semester 2/Labs/Crptography Lab/Lab_3/Rail_Fence_Cipher.py"
Type 'encrypt' or 'decrypt': encrypt
Enter your message: hello my name is yugal
Enter number of rails: 3
Encrypted text: ho e ael ynm sygllmaiu
Continue? (yes/no): yes
Type 'encrypt' or 'decrypt': decrypt
Enter your message: ho e ael ynm sygllmaiu
Enter number of rails: 3
Decrypted text: hello my name is yugal
Continue? (yes/no): no
Exiting program.
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$
```

Figure 7: Program to implement Rail Fence Cipher

Assignment 4: Perform encryption and decryption using Playfair cipher.

4.1 Implement Playfair Cipher in Python.

```python
# ---------- Create Playfair Matrix ----------
def create_matrix(key):
    key = key.lower().replace("j", "i")
    seen = set()
    matrix_list = []

    # Add key letters first
    for ch in key:
        if ch.isalpha() and ch not in seen:
            seen.add(ch)
            matrix_list.append(ch)

    # Add remaining alphabets (without j)
    for ch in "abcdefghiklmnopqrstuvwxyz":
        if ch not in seen:
            matrix_list.append(ch)

    # Convert into 5x5 matrix
    matrix = [matrix_list[i:i+5] for i in range(0, 25, 5)]
    return matrix


# ---------- Prepare Text ----------
def prepare_text(text):
    text = text.lower().replace("j", "i")
    text = ''.join([c for c in text if c.isalpha()])

    pairs = []
    i = 0
    while i < len(text):
        a = text[i]
        b = ""

        if i+1 < len(text):
            b = text[i+1]

        if a == b:          # same letters - add x
            pairs.append(a + "x")
            i += 1
```

```python
        else:
            if b:
                pairs.append(a + b)
                i += 2
            else:           # odd length
                pairs.append(a + "x")
                i += 1

    return pairs


# ---------- Find Position ----------
def find_position(matrix, char):
    for row in range(5):
        for col in range(5):
            if matrix[row][col] == char:
                return row, col


# ---------- Encrypt ----------
def encrypt(plain_text, key):
    matrix = create_matrix(key)
    pairs = prepare_text(plain_text)

    cipher_text = ""

    for pair in pairs:
        a, b = pair[0], pair[1]
        r1, c1 = find_position(matrix, a)
        r2, c2 = find_position(matrix, b)

        # Same row
        if r1 == r2:
            cipher_text += matrix[r1][(c1 + 1) % 5]
            cipher_text += matrix[r2][(c2 + 1) % 5]

        # Same column
        elif c1 == c2:
            cipher_text += matrix[(r1 + 1) % 5][c1]
            cipher_text += matrix[(r2 + 1) % 5][c2]

        # Rectangle rule
        else:
            cipher_text += matrix[r1][c2]
```

```python
            cipher_text += matrix[r2][c1]

    return cipher_text


# ---------- Decrypt ----------
def decrypt(cipher_text, key):
    matrix = create_matrix(key)
    pairs = prepare_text(cipher_text)

    plain_text = ""

    for pair in pairs:
        a, b = pair[0], pair[1]
        r1, c1 = find_position(matrix, a)
        r2, c2 = find_position(matrix, b)

        # Same row
        if r1 == r2:
            plain_text += matrix[r1][(c1 - 1) % 5]
            plain_text += matrix[r2][(c2 - 1) % 5]

        # Same column
        elif c1 == c2:
            plain_text += matrix[(r1 - 1) % 5][c1]
            plain_text += matrix[(r2 - 1) % 5][c2]

        # Rectangle rule
        else:
            plain_text += matrix[r1][c2]
            plain_text += matrix[r2][c1]

    return plain_text


# ---------- Main Program ----------
while True:
    choice = input("Type 'encrypt' or 'decrypt': ").lower()
    text = input("Enter your message: ")
    key = input("Enter the key: ")

    if choice == "encrypt":
        result = encrypt(text, key)
        print("Encrypted text:", result)
```

```python

    elif choice == "decrypt":
        result = decrypt(text, key)
        print("Decrypted text:", result)

    else:
        print("Invalid choice!")

    again = input("Continue? (yes/no): ").lower()
    if again == "no":
        print("Exiting program.")
        break
```

Output



Figure 8: Program to implement Playfair Cipher

Assignment 5: Perform encryption and decryption using columnar transposition and one-time padding cipher.

5.1 Implement Columnar Transposition Cipher in Python.

```python
import math

# Create Order
def get_key_order(key):
    key_list = list(key)
    sorted_key = sorted(key_list)
    order = []

    for ch in sorted_key:
        index = key_list.index(ch)
        order.append(index)
        key_list[index] = None # Avoid duplicate issues
    return order

# Encrypt
def encrypt(plain_text,key):
    plain_text = plain_text.replace(" ", "")
    cols = len(key)
    rows = math.ceil(len(plain_text)/cols)

    # Fill matrix row-wise
    matrix = []
    index = 0
    for r in range(rows):
        row = []
        for c in range(cols):
            if index < len(plain_text):
                row.append(plain_text[index])
                index += 1
            else:
                row.append('x') #padding
        matrix.append(row)
    order = get_key_order(key)

    cipher_text = ""
    for col_index in order:
        for r in range(rows):
            cipher_text += matrix[r][col_index]
    return cipher_text
```

```python

# Decrypt
def decrypt(cipher_text, key):
    cols = len(key)
    rows = math.ceil(len(cipher_text)/cols)

    order = get_key_order(key)

    # Create empty matrix
    matrix = [['' for _ in range(cols)] for _ in range(rows)] #list comprehension
    index = 0
    for col_index in order:
        for r in range(rows):
            matrix[r][col_index] = cipher_text[index]
            index += 1

    plain_text = ""
    for r in range(rows):
        for c in range(cols):
            plain_text += matrix[r][c]

    return plain_text.rstrip('x')

# Main Program
while True:
    choice = input("Type 'encrypt' or 'decrypt': ").lower()
    text = input("Enter your message: ")
    key = input("Enter your key: ")

    if choice == "encrypt":
        result = encrypt(text,key)
        print("Encrypted Result: ",result)

    elif choice == "decrypt":
        result = decrypt(text, key)
        print("Decryted Result: ",result)

    else:
        print("Invalid choice!")

    again = input("Continue? (yes/no): ").lower()
    if again == "no":
        print("Exiting Program.")
```

```
        break
```

Output



```
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$
r 2/Labs/Crptography Lab/Lab_5/Columnar_Transposition_Cipher.py"
Type 'encrypt' or 'decrypt': encrypt
Enter your message: hello
Enter your key: hi
Encrypted Result:  hloelx
Continue? (yes/no): yes
Type 'encrypt' or 'decrypt': decrypt
Enter your message: hloelx
Enter your key: hi
Decryted Result:  hello
Continue? (yes/no): no
Exiting Program.
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$
```

Figure 9: Program to implement Columnar Transposition Cipher

5.2 Implement One-Time Pad Cipher in Python.

```python
# Prepare Text
def prepare_text(text):
    clean_text = ""
    for c in text:
        if c.isalpha():
            clean_text += c.upper()
    return clean_text

# Encryption
def encrypt(plain_text, key):
    plain_text = prepare_text(plain_text)
    key = prepare_text(key)

    if(len(plain_text) != len(key)):
        return "Error: Key length must be equal to plaintext length."
    cipher_text = ""

    for i in range(len(plain_text)):
        p = ord(plain_text[i]) - ord('A')
        k = ord(key[i]) - ord('A')

        c = (p + k) % 26
```

```
        cipher_text += chr(c + ord('A'))
    return cipher_text

# Decryption
def decrypt(cipher_text, key):
    cipher_text = prepare_text(cipher_text)
    key = prepare_text(key)

    if(len(cipher_text) != len(key)):
        return"Error: Key length must be equal to ciphertext length."
    plain_text = ""
    for i in range(len(cipher_text)):
        c = ord(cipher_text[i]) - ord('A')
        k = ord(key[i]) - ord('A')

        p = (c - k) % 26
        plain_text += chr(p + ord('A'))
    return plain_text


# Main Program
while True:
    choice = input("Type 'encrypt' or 'decrypt': ").lower()
    text = input("Enter your message: ")
    key = input("Enter the key (same length as message): ")

    if choice == "encrypt":
        result = encrypt(text, key)
        print("Encrypted Text: ",result)
    elif choice == "decrypt":
        result = decrypt(text, key)
        print("Decrypted Text: ", result)
    else:
        print("Invalid Choice!")

    again = input("Continue? (yes/no): ")
    if again == "no":
        print("Exiting Program")
        break
```

Output

```
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$
r 2/Labs/Crptography Lab/Lab_5/One_Time_Pad_Cipher.py"
Type 'encrypt' or 'decrypt': encrypt
Enter your message: hello
Enter the key (same length as message): yugal
Encrypted Text:  FYRLZ
Continue? (yes/no): yes
Type 'encrypt' or 'decrypt': decrypt
Enter your message: FYRLZ
Enter the key (same length as message): yugal
Decrypted Text:  HELLO
Continue? (yes/no): no
Exiting Program
(base) yugal@yugal-Inspiron-3583:~/Desktop/Semester 2/Labs/Crptography Lab$
```

Figure 10: Program to implement One-Time Pad Cipher