SOLR -ROUND 2

- 1. Installed Solr in my local Machine
- 2. bin/solr start

```
Microsoft Windows[Version 10.0.22631.4169]
(c) Microsoft Corporation. All rights reserved.

C:\solr-9.7.0\solr-9.7.0\bin>solr start
Java 23 detected. Enabled workaround for SOLR-16463


Java HotSpot(TM) 64-Bit Server VM warning: JVM cannot use large page memory because it does not have enough privilege to lock pages in memory.

WARNING: A command line option has enabled the Security Manager
WARNING: The Security Manager is deprecated and will be removed in a future release Failed to parse command-line arguments due to: Unrecognized option: --max-wait-secs


usage: bin/solr status [-maxWaitSecs <SECS>] [--solr-url <URL>]

List of options:
--maxWaitSecs <SECS> Wait up to the specified number of seconds to see Solr running.
--solr-url <URL> Address of the Solr Web application, defaults to: http://localhost:8983.
```

3. Solr is running on http://localhost:8983/solr/#/



4. Then click on the Core Admin to add the dataset name and directory path.



5. bin/solr create -c employee _data

```
C:\solr=9.7.0\solr=9.7.0\bin>solr create -c new_employee_data
WARNING: Using _default configset with data driven schema functionality. NOT RECOMMENDED for production use.
    To turn off: bin\solr config -c new_employee_data -p 8983 -action set-user-property -property update.autoCreate
Fields -value false
Option '-solrUrl', '--solrUrl': Deprecated for removal since 9.7: Use --solr-url instead
WARNING: URLs provided to this tool needn't include Solr's context-root (e.g. "/solr"). Such URLs are deprecated and sup
port for them will be removed in a future release. Correcting from [http://localhost:8983/solr] to [http://localhost:8983/].
Option '-confdir', '--confdir': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confdir', '--confdir': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confdir', '--confdir': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confdir', '--confname': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confname', '--confname': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confname': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confname': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confname': Deprecated for removal since 9.7: Use --conf-dir instead
Option '-confname': Deprecated for removal since 9.7: Use --conf-name instead
Created new core 'new_employee_data'
C:\solr=9.7.0\solr=9.7.0\bin>
```

6. bin/post -c employee data path/to/employee data.csv

```
C:\solr-9.7.0\solr-9.7.0\bin>solr post -c new_employee_data --solr-update-url http://localhost:8983/solr/new_employee_data ta/update "C:\Users\Yugendaran G\Employee Sample Data 1 (1).csv"

Posting files to [base] url http://localhost:8983/solr/new_employee_data/update...
Entering auto mode. File endings considered are xml,json,jsonl,csv,pdf,doc,docx,ppt,pptx,xls,xlsx,odt,odp,ods,ott,otp,ot s,rtf,htm,html,txt,log

POSTing file Employee Sample Data 1 (1).csv (text/csv) to [base]

1 files indexed.


COMMITting Solr index changes to http://localhost:8983/solr/new_employee_data/update...

WARNING: URLs provided to this tool needn't include Solr's context-root (e.g. "/solr"). Such URLs are deprecated and sup port for them will be removed in a future release. Correcting from [http://localhost:8983/solr] to [http://localhost:8983/s].


Time spent: 0:00:02.682


C:\solr-9.7.0\solr-9.7.0\bin>
```

7. New employee data is created



8. Then click on the core selector and select the new_employee_data column and then open the query icon and excute query .





Yugendaran G B.Tech IT