

# 并行与分布式计算

Parallel & Distributed Computing

陈鹏飞  
计算机学院  
[chenpf7@mail.sysu.edu.cn](mailto:chenpf7@mail.sysu.edu.cn)



中山大學  
SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING



# Lecture 11 — Parallel Computing with MapReduce

Pengfei Chen

School of Data and Computer Science

[chenpf7@mail.sysu.edu.cn](mailto:chenpf7@mail.sysu.edu.cn)



## ***Outline:***

- MapReduce Programming Model
- Typical Problems Solved by MapReduce
- MapReduce Examples
- A Brief History
- MapReduce Execution Overview
- Hadoop



## Motivation: Large Scale Data Processing

- 全社会数据产生的速度非常快

### Internet上一分钟产生的数据有多大？



### And Future Growth is Staggering







中山大學

SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)


SCHOOL OF COMPUTER SCIENCE AND ENGINEERING



# Motivation: Large Scale Data Processing

## ➤ 大数据的呈现出指数增长速度

全球数据存储量呈现爆炸式增长，企业及互联网数据以每年50%的速率在增长，据Gartner预测，到2020年，全球数据量将达到35ZB，等于80亿块4TB硬盘。





# ***Motivation: Large Scale Data Processing***

- Want to process lots of data ( >1TB)
- Want to parallelize across hundreds/thousands of CPUs
- ... Want to make this easy



# MapReduce


- A simple and powerful interface that enables automatic parallelization and distribution of large-scale computations, combined with an implementation of this interface that achieves high performance on large clusters of commodity PCs.”
- **More simply**, MapReduce is A parallel programming model and associated implementation



## *Some MapReduce Terminology*

- Job—A “full program” -an execution of a Mapper and Reducer across a data set
- Task —An execution of a Mapper or a Reducer on a slice of data
  - ▣ a.k.a. Task-In-Progress (TIP)
- **Task Attempt** —A particular instance of an attempt to execute a task on a machine





## *Terminology Example*

- Running “Word Count” across 20 files is one job
- 20 files to be mapped imply 20 map tasks+ some number of reduce tasks
- At least 20 map task attempts will be performed... more **if a machine crashes**, etc.



# Task Attempts

- A particular task will be attempted at least once, possibly more times if it crashes
  - ❑ If the same input causes crashes over and over, that input will eventually be abandoned
- Multiple attempts at one task may occur in parallel with speculative execution turned on
  - ❑ Task ID from TaskInProgress is not a unique identifier



# *MapReduce Programming Model*

- Process data using special `map()` and `reduce()` functions
  - ❑ The `map()` function is called on every item in the input and emits a series of intermediate key/value pairs
  - ❑ All values associated with a given key are grouped together
  - ❑ The `reduce()` function is called on every unique key, and its value list, and emits a value that is added to the output



# Map

- Records from the data source (lines out of files, rows of a database, etc) are fed into the map function as key\*value pairs: e.g., (filename, line)
- map() produces one or more intermediate values along with an output key from the input

```
- map (in_key, in_value) ->  
      (out_key, intermediate_value) list
```



# *reduce*

- After the map phase is over, all the intermediate values for a given output key are combined together into a list
- `reduce()` combines those intermediate values into one or more final values for that same output key


```
- reduce (out_key, intermediate_value list) ->  
  out_value list
```






# *reduce*

```
reduce (out_key, intermediate_value list) ->  
      out_value list
```






# MapReduce Architecture





# MapReduce Programming Model




□ More formally,

➤  $\text{Map}(k1, v1) \rightarrow \text{list}(k2, v2)$

➤  $\text{Reduce}(k2, \text{list}(v2)) \rightarrow \text{list}(v2)$




# MapReduce Execution Flow





# MapReduce in One Picture







# *MapReduce Runtime System*

- Partitions input data

Partition and distribute data amongst different nodes


- Schedules executions across a set of machines

**Yarn** – (Resource Manager), FIFO. (**Many Research work**)

- Handles machine failure

Reschedule tasks when the machine fails.

- Manages interprocess communication



# Parallelism

- map() functions run in parallel, creating different **intermediate values**  
from different input data sets
- reduce() functions also run in parallel, each working on a different output  
key
- All values are processed independently
- **Bottleneck**: reduce phase can't start until map phase is completely  
finished




# Locality

- Master program divides up tasks based on location of data: tries to have map() tasks on the same machine **as physical file data, or at least same rack**
- map() task inputs are divided into 64 MB blocks: same size as **Google File System** chunks



# Fault Tolerance

- Master detects worker failures
  - ❑ Re-executes completed & in-progress map() tasks
  - ❑ Re-executes in-progress reduce() tasks
- Master notices particular input key/values cause crashes in map(), and skips those values on re-execution
  - ❑ Effect: Can work around bugs in third-party libraries!




# Optimizations

- **No reduce can start until map is complete**
  - ❑ A single slow disk controller can rate-limit the whole process
- Master redundantly executes “slow-moving” map tasks; uses results of first copy to finish
- “Combiner” functions can run on same machine as a mapper
- Causes a mini-reduce phase to occur before the real reduce phase, to save bandwidth






# Combiner





# Optimizations






# *MapReduce Benefits*

- Greatly reduces parallel programming complexity
  - Reduces synchronization complexity
  - Automatically partitions data
  - Provides failure transparency
  - Handles load balancing



# Hadoop architecture from different views








中山大學  
SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING




# Typical Problems Solved by MapReduce





# MapReduce: High Level





# ***Nodes, Trackers, Tasks***

- Master node runs **JobTracker (ResourceManager)** instance, which accepts Job requests from clients
- **TaskTracker (NodeManager)** instances run on slave nodes
- TaskTracker forks separate Java process for task instances



## *Typical Problems Solved by MapReduce*

- ☐ Read a lot of data
- ☐ **Map**: extract something you care about from each record
- ☐ **Shuffle** and **Sort**
- ☐ **Reduce**: aggregate, summarize, filter, or transform
- ☐ Write the results
  
- ☐ Outline stays the same, but **map** and **reduce** change to fit the problem



中山大學  
SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING




# MapReduce Examples



# MapReduce Examples

## ➤ Word frequency





## Example: Count Word Occurrences


```
map(String input_key, String input_value):  
    // input_key: document name  
    // input_value: document contents  
    for each word w in input_value:  
        EmitIntermediate(w, "1");  
  
reduce(String output_key, Iterator  
    intermediate_values):  
    // output_key: a word  
    // output_values: a list of counts  
    int result = 0;  
    for each v in intermediate_values:  
        result += ParseInt(v);  
    Emit(AsString(result));
```





## Example: Count Word Occurrences

The overall MapReduce word count process





# MapReduce Examples

## □ Distributed grep

- Map function emits  $\langle \text{word}, \text{line\_number} \rangle$  if word matches search criteria
- Reduce function is the identity function

## □ URL access frequency

- Map function processes web logs, emits  $\langle \text{url}, 1 \rangle$
- Reduce function sums values and emits  $\langle \text{url}, \text{total} \rangle$



中山大學

SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING



## A Brief History



# *A Brief History*

MapReduce is a new use of an old idea in Computer Science

➤ **Map:** Apply a function to every object in a list


□ Each object is independent

- Order is unimportant
- Maps can be done in parallel

□ The function produces a result

➤ **Reduce:** Combine the results to produce a final result

You may have seen this in a Lisp or functional programming course




# MapReduce Execution Overview



# MapReduce Execution Overview


- The user program, via the MapReduce library, shards the input data








# Getting Data To The Mapper





# Getting Data To The Mapper

- The user program creates process copies distributed on a machine cluster. One copy will be the “master” and the others will be worker threads






# MapReduce Execution Overview


The master distributes  $M$  map and  $R$  reduce tasks to idle workers

- $M$  == number of shards
- $R$  == the intermediate key space is divided into  $R$  parts





## Partition and Shuffle





# MapReduce Execution Overview


- Each map-task worker reads assigned input shard and outputs intermediate key/value pairs
  - ▣ Output buffered in RAM





# MapReduce Execution Overview

- Each worker flushes intermediate values, partitioned into  $R$  regions, to disk and notifies the Master process.









# MapReduce Execution Overview


- Master process gives disk locations to an available reduce-task worker who reads all associated intermediate data.





# MapReduce Execution Overview

- Each reduce-task worker sorts its intermediate data. Calls the reduce function, passing in unique keys and associated key values. Reduce function output appended to reduce-task's partition output file






# MapReduce Execution Overview


- Master process wakes up user process when all tasks have completed.

Output contained in  $R$  output files





# Writing The Output





# MapReduce Execution Overview

## □ Fault Tolerance


- Master process periodically pings workers
  - Map-task failure
    - ✓ Re-execute
      - All output was stored locally
  - Reduce-task failure
    - ✓ Only re-execute partially completed tasks
      - All output stored in the global file system



中山大學  
SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING



# Hadoop





# MapReduce Execution Overview


□ Open source MapReduce implementation

➤ <http://hadoop.apache.org/core/index.html>

Google calls it	Hadoop equivalent
MapReduce	Hadoop
GFS	HDFS
Bigtable	HBase
Chubby	(nothing yet... but planned)



# HDFS Architecture






## ***Hadoop Related Projects***

- **Ambari:** A web-based tool for provisioning, managing, and monitoring Apache Hadoop clusters which includes support for Hadoop HDFS, Hadoop MapReduce, Hive, HCatalog, HBase, ZooKeeper, Oozie, Pig and Sqoop. Ambari also provides a dashboard for viewing cluster health such as heat maps and ability to view MapReduce, Pig and Hive applications visually along with features to diagnose their performance characteristics in a user-friendly manner
- **Avro:** A data serialization system
- **Cassandra:** A scalable multi-master database with no single points of failure
- **Chukwa:** A data collection system for managing large distributed systems
- **HBase:** A scalable, distributed database that supports structured data storage for large tables (NoSQL)
- **Hive:** A data warehouse infrastructure that provides data summarization and ad hoc querying
- **Mahout:** A Scalable machine learning and data mining library
- **Pig:** A high-level data-flow language and execution framework for parallel computation
- **ZooKeeper:** A high-performance coordination service for distributed applications



# Hadoop Ecosystem





# References


- Introduction to Parallel Programming and MapReduce, Google Code University
  - ❑ <http://code.google.com/edu/parallel/mapreduce-tutorial.html>
- Distributed Systems
  - ❑ <http://code.google.com/edu/parallel/index.html>
- MapReduce:SimplifiedDataProcessing onLargeClusters
  - ❑ <http://labs.google.com/papers/mapreduce.html>
- Hadoop
  - ❑ <http://hadoop.apache.org/core/>



中山大學  
SUN YAT-SEN UNIVERSITY

计算机学院 (软件学院)

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING



# Thank You !