



DD2437 – Artificial Neural Networks and Deep Architectures (annda)

Lecture 6: **Self-organising maps (SOMs)**

Pawel Herman

Computational Science and Technology (CST)

KTH Royal Institute of Technology

February 2018

- Vector Quantisation
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Lecture overview


- Vector Quantisation
- Self-organising maps (SOMs)
- Learning vector quantisation

- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Vector Quantisation

- The idea borrowed from information coding, data compression
- Represent data in terms of few (limited) typical data vectors – *code vectors*

- compression
- noise reduction





- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Vector Quantisation

- The idea borrowed from information coding, data compression
- Represent data in terms of few (limited) typical data vectors – *code vectors*

- compression
- noise reduction


- Voronoi partitioning



- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Vector Quantisation – unsupervised learning


- Network architecture for unsupervised learning



- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Vector Quantisation – unsupervised learning

- Network architecture for unsupervised learning



- Winner-take-all (WTA) mechanism
 - **ONLY ONE** output (the winner) unit gets active – hard competition
 - competition is one of the most fundamental computation in the brain via so-called *lateral inhibition*

- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Competitive learning – basic principle

The fundamental principle

Update the *winning* unit
(prototype/code vector) to make it
more specialised (“even better”).

- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning


Competitive learning – basic principle

The fundamental principle

Update the *winning* unit (prototype/code vector) to make it more specialised (“even better”).

Basic algorithm

- the normalised weight vectors, $\mathbf{w}_A, \dots, \mathbf{w}_C$ are generated randomly
- for each input vector, \mathbf{x} , calculate “proximity” to weight vectors and determine the nearest neighbour
- make an update of the nearest weight vector and normalize weights



If the **red** node \mathbf{w}_A wins, then:

$$\Delta \vec{w}_A = \eta \vec{x}$$

OR

$$\Delta \vec{w}_A = \eta (\vec{x} - \vec{w}_A)$$

- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning


Competitive learning – basic principle

The fundamental principle

Update the *winning* unit (prototype/code vector) to make it more specialised (“even better”).

Basic algorithm

- the normalised weight vectors, $\mathbf{w}_A, \dots, \mathbf{w}_C$ are generated randomly
- for each input vector, \mathbf{x} , calculate “**proximity**” to weight vectors and determine the nearest neighbour
- make an update of the nearest weight vector and normalize weights



- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning


Competitive learning – basic principle

The fundamental principle

Update the *winning* unit (prototype/code vector) to make it more specialised (“even better”).

Properties

- the algorithm finds cluster in data – purely unsupervised approach
- each node protects its “territory”
- there is also a batch version



If the **red** node w_A wins, then:

$$\Delta \vec{w}_A = \eta \vec{x}$$

OR

$$\Delta \vec{w}_A = \eta (\vec{x} - \vec{w}_A)$$

- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Competitive learning – problem with dead units

Dead unit problem

Prototype vectors far from actual data will never become better.

- **Vector Quantisation**
- Topology preserving (Kohonen) maps
- Supervised competitive learning

Competitive learning – problem with dead units

Dead unit problem


Prototype vectors far from actual data will never become better.

Methods to avoid dead units

- Initialise algorithm (the weights) with data samples
- “Leaky learning” (soft-competition) – some updates for all
- Learning with conscience – balanced update allowing losers to win
- Introduce noise to data


- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Topographic map




colours

poverty




- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Topographic map



“The spatial location of an output neuron in a topographic map corresponds to a particular domain or feature drawn from the input space”

Bullinaria, 2004



- Vector Quantisation
- Topology preserving (Kohonen) maps
- **Supervised competitive learning**

Topology preserving maps

Learning principle


Competitive learning where winning “spills over” to neighbours.

- Vector Quantisation
- Topology preserving (Kohonen) maps
- **Supervised competitive learning**

Topology preserving maps

Learning principle

Competitive learning where winning “spills over” to neighbours.



If the **red** node
 w_A wins, then:

$$\Delta \vec{w}_A = \eta \vec{x}$$

OR

$$\Delta \vec{w}_A = \eta (\vec{x} - \vec{w}_A)$$


Competitive learning

- Vector Quantisation
- Topology preserving (Kohonen) maps
- **Supervised competitive learning**


Topology preserving maps

Learning principle

Competitive learning where winning “spills over” to neighbours.



Competitive learning





SOM

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Mapping from high- to low-dimensional spaces

Low-dimensional (discrete) **OUTPUT** space ($n \leq 2$),
where output **nodes** are represented.




Multi-dimensional (often continuous) **INPUT** space ($n > 2$),
where both **inputs**, \mathbf{x} , and **weight** vectors, \mathbf{w} , are represented.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Mapping from high- to low-dimensional spaces

In the OUTPUT space the distance between the nodes (**their neighbourhood**) is defined to determine.....

....which nodes apart from the *winner* (**best matching unit**) get their weights, \mathbf{w} , updated




Multi-dimensional (often continuous) **INPUT** space ($n > 2$), where both **inputs**, \mathbf{x} , and **weight** vectors, \mathbf{w} , are represented.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Mapping from high- to low-dimensional spaces

In the OUTPUT space the distance between the nodes (their neighbourhood) is defined

The links between the nodes are commonly used to define some discrete distance measure, d , in the *discrete* OUTPUT space




Multi-dimensional (often continuous) **INPUT** space ($n > 2$), where both **inputs, x** , and **weight** vectors, **w** , are represented.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Mapping from high- to low-dimensional spaces

In the OUTPUT space the distance between the nodes (their neighbourhood) is defined

The links between the nodes are commonly used to define some discrete distance measure, d , in the *discrete* OUTPUT space




Multi-dimensional (often continuous) **INPUT** space ($n > 2$), where both **inputs, \mathbf{x}** , and **weight vectors, \mathbf{w}** , are represented.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning


Distance and neighbourhood in the *output* space

In the OUTPUT space the distance between the nodes (their neighbourhood) is defined

The links between the nodes are commonly used to define some discrete distance measure, d , in the *discrete* OUTPUT space



THEN we can use a neighbourhood function, h , based on the distance between the discrete nodes in the OUTPUT space




Multi-dimensional (often continuous) **INPUT** space ($n > 2$), where both **inputs, x** , and **weight** vectors, **w** , are represented.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning



Distance and neighbourhood in the *output* space

In the OUTPUT space the distance between the nodes (their neighbourhood) is defined

The links between the nodes are commonly used to define some discrete distance measure, d , in the *discrete* OUTPUT space



THEN we can use a neighbourhood function, h , based on the distance between the discrete nodes in the OUTPUT space




h shrinks since σ exponentially decreases over time: $\sigma(t) = \sigma_0 \exp\left(-\frac{t^2}{\tau}\right)$

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

Update of the corresponding *input* weights

In the OUTPUT space the distance between the nodes (their neighbourhood) is defined

The links between the nodes are commonly used to define some discrete distance measure, d , in the *discrete* OUTPUT space



THEN we can use a neighbourhood function, h , based on the distance between the discrete nodes in the OUTPUT space

Finally, however, the weight vectors, w , get updated (moved in the multi-dimensional input/weight space)

$$\Delta w = \eta h(x - w)$$

Multi-dimensional (often continuous) **INPUT** space ($n > 2$), where both **inputs, x** , and **weight** vectors, **w** , are represented.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM visualisation – showing lattices

In cases when the dimensionality of the INPUT space is low ($n \leq 3$)
SOMs are often visualized only in the INPUT/WEIGHT space

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM visualisation – showing lattices

In cases when the dimensionality of the INPUT space is low ($n \leq 3$)
SOMs are often visualized only in the INPUT/WEIGHT space
and then....

... it is very useful to **show links between nodes** as they illustrate
neighbourhood (topographical relationship) in the OUTPUT space



- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM visualisation – showing lattices in *input* space

... it is very useful to **show links between nodes** as they illustrate **neighbourhood** (topographical relationship) in the OUTPUT space

2 inputs – **2D** INPUT space (x_1, x_2) corresponding to **2D** WEIGHT space (w_1, w_2)

2D arrangement of nodes
(lattice) in the OUTPUT space




- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM visualisation – showing lattices in *input* space

... it is very useful to **show links between nodes** as they illustrate **neighbourhood** (topographical relationship) in the OUTPUT space

2 inputs – **2D** INPUT space (x_1, x_2) corresponding to **2D** WEIGHT space (w_1, w_2)


1D arrangement of nodes
in the OUTPUT space



- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM visualisation demo

Lower-dimensional manifold



- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM learning

Following initialisation there are three learning stages

1. *Competition* (mapping of a continuous input space onto a discrete output space of units)
2. *Cooperation* (lateral interaction through topographic neighbourhood)
3. Weight (synaptic) *adaptation*

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM learning

Following initialisation there are three learning stages

1. *Competition* (mapping of a continuous input space onto a discrete output space of units)
2. *Cooperation* (lateral interaction through topographic neighbourhood)
3. Weight (synaptic) *adaptation*
 - a) topological *ordering*: high learning rate and large neighbourhood
 - b) *convergence*: low learning rate and small neighbourhood
(a long process of fine tuning)

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM learning

Following initialisation there are three learning stages

1. *Competition* (mapping of a continuous input space onto a discrete output space of units)
2. *Cooperation* (lateral interaction through topographic neighbourhood)
3. Weight (synaptic) *adaptation*
 - a) topological *ordering*: high learning rate and large neighbourhood
 - b) *convergence*: low learning rate and small neighbourhood

the key role of neighbourhood!

GLOBAL ordering vs LOCAL fit

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM learning

Following initialisation there are three learning stages

1. *Competition* (mapping of a continuous input space onto a discrete output space of units)
2. *Cooperation* (lateral interaction through topographic neighbourhood)
3. Weight (synaptic) *adaptation*
 - a) topological *ordering*: high learning rate and large neighbourhood
 - b) *convergence*: low learning rate and small neighbourhood

“Global order can arise from local interactions”

Turing

the key role of neighbourhood!

GLOBAL ordering vs LOCAL fit

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM learning

Following initialisation there are three learning stages

-
- The diagram illustrates the three stages of SOM learning, grouped by input and output space. The 'output space' group includes the first two stages, while the 'input space' group includes the third stage. Blue curly braces are used to group the stages on the left side of the list.
- output space**
 - 1. *Competition* (mapping of a continuous input space onto a discrete output space of units)
 - 2. *Cooperation* (lateral interaction through topographic neighbourhood)
 - input space**
 - 3. Weight (synaptic) *adaptation*
 - a) topological *ordering*: high learning rate and large neighbourhood
 - b) *convergence*: low learning rate and small neighbourhood

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM example

High-dimensional feature description

	Dove	Hen	Duck	Goose	Owl	Hawk	Eagle	Fox	Dog	Wolf	Cat	Tiger	Lion	Horse	Zebra	Cow
Small	1	1	1	1	1	1	0	0	0	0	1	0	0	0	0	0
Medium	0	0	0	0	0	0	1	1	1	1	0	0	0	0	0	0
Large	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1
2 legs	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
4 legs	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1
Fur	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1
Hoofs	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1
Mane	0	0	0	0	0	0	0	0	0	1	0	0	1	1	1	0
Feathers	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
Hunter	0	0	0	0	1	1	1	1	0	1	1	1	1	0	0	0
Runner	0	0	0	0	0	0	0	0	1	1	0	1	1	1	1	0
Flyer	1	0	0	1	1	1	1	0	0	0	0	0	0	0	0	0
Swimmer	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

SOM example

2D visualisation

Dog	.	.	Fox	.	.	Cat	.	.	Eagle
.
.	Owl
.	Tiger	.	.	.
Wolf	Hawk
.	.	.	Lion
.	Dove
Horse	Hen	.	.
.	.	.	.	Cow	Goose
Zebra	Duck	.	.

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning


SOM example

2D visualisation


Dog	Dog	Fox	Fox	Fox	Cat	Cat	Cat	Eagle	Eagle
Dog	Dog	Fox	Fox	Fox	Cat	Cat	Cat	Eagle	Eagle
Wolf	Wolf	Wolf	Fox	Cat	Tiger	Tiger	Tiger	Owl	Owl
Wolf	Wolf	Lion	Lion	Lion	Tiger	Tiger	Tiger	Hawk	Hawk
Wolf	Wolf	Lion	Lion	Lion	Tiger	Tiger	Tiger	Hawk	Hawk
Wolf	Wolf	Lion	Lion	Lion	Owl	Dove	Hawk	Dove	Dove
Horse	Horse	Lion	Lion	Lion	Dove	Hen	Hen	Dove	Dove
Horse	Horse	Zebra	Cow	Cow	Cow	Hen	Hen	Dove	Dove
Zebra	Zebra	Zebra	Cow	Cow	Cow	Hen	Hen	Duck	Goose
Zebra	Zebra	Zebra	Cow	Cow	Cow	Duck	Duck	Duck	Goose

- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

The brain analogy of topographic mapping




“Kohonen map captures the essential features of computational maps in the brain”



Sensory experience is multi-dimensional, so there is a need to map them to spatial relations in the cortex preserving topology.


- Vector Quantisation
- **Topology preserving (Kohonen) maps**
- Supervised competitive learning

The brain analogy of topographic mapping



Sensory experience is needed for developing neural circuitry through analogous *neurobiological processes*.

“Kohonen map captures the essential features of computational maps in the brain”



- Vector Quantisation
- Topology preserving (Kohonen) maps
- **Supervised competitive learning**

Learning Vector Quantisation (LVQ)

Learning Vector Quantisation (LVQ) is a *supervised* competitive learning algorithm (classes are known)

- Vector Quantisation
- Topology preserving (Kohonen) maps
- **Supervised competitive learning**

Learning Vector Quantisation (LVQ)

Learning Vector Quantisation (LVQ) is a *supervised* competitive learning algorithm (classes are known)

$$\Delta \vec{w} = +\eta(\vec{x} - \vec{w})$$

if the winner belongs to the *right* class

$$\Delta \vec{w} = -\eta(\vec{x} - \vec{w})$$

if the winner belongs to the *wrong* class