



DD2437 – Artificial Neural Networks and Deep Architectures (annda)

Lecture 2: From perceptron learning rules to backpropagation – supervised learning

Pawel Herman





Computational Science and Technology (CST)

KTH Royal Institute of Technology

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification


Lecture overview

- A quick recap
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron learning, delta rule
- Multi-layer perceptron
- Backpropagation



- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification


From biological inspirations to ANNs



- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Fundamental aspects


nodes




- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Fundamental aspects

nodes



activation
function




- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron


- Multi-layer perceptron
- Backpropagation
- System identification

Fundamental aspects


nodes



learning rule




activation
function




- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Fundamental aspects


nodes






learning rule



activation function




topologies, architectures



- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Learning principles


- **Error correction**
- Competitive learning
- Coincidence detection



- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Learning principles


- Error correction
- **Competitive learning**
- Coincidence detection



- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Learning principles

- Error correction
- Competitive learning
- **Coincidence detection**



- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Learning principles

Learning approaches

- supervised
 - with a teacher that provides a correct answer
 - error correction paradigm

- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Learning principles

Learning approaches

- supervised
- unsupervised (input data only)
 - only input data is available
 - ability to organise information without any error signal to evaluate a potential solution – an explorative approach
 - detecting statistical regularities of the input data and forming internal representations that encode features of the input data

- **Recap**
- Linear feed-forward networks
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Learning principles

Learning approaches


- supervised
- unsupervised (input data only)
- reinforcement
 - simple scalar “reward” signal gives feedback on success

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification


Linear networks

What can be computed?



$$y = \vec{w}^T \cdot \vec{x}$$

\vec{w} - weight vector




$$y = W \cdot \vec{x}$$

W - weight matrix

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Linear networks

What can be computed?



$$y = W \cdot \vec{x}$$


W - weight matrix

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Linear networks

What happens when we concatenate several linear networks?




- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Linear networks

What happens when we concatenate several linear networks?




$$\vec{y} = W_3 (W_2 (W_1 \vec{x})) = (W_3 W_2 W_1) \vec{x}$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Linear networks

What happens when we concatenate several linear networks?



$$\vec{y} = W_3 (W_2 (W_1 \vec{x})) = (W_3 W_2 W_1) \vec{x}$$


$$\text{Let } W = W_3 W_2 W_1 \Rightarrow \vec{y} = W \vec{x}$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Linear networks

What happens when we concatenate several linear networks?



$$\vec{y} = W_3 (W_2 (W_1 \vec{x})) = (W_3 W_2 W_1) \vec{x}$$

$$\text{Let } W = W_3 W_2 W_1 \Rightarrow \vec{y} = W \vec{x}$$

It is still a linear mapping !

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

But how do we find suitable weights?

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

But how do we find suitable weights?

Learning corresponds to adapting weights, often *iteratively*, to achieve better performance

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

But how do we find suitable weights?

Learning corresponds to adapting weights, often iteratively, to achieve better performance

$$w^{(new)} = w^{(old)} + \Delta w_{ij}$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

But how do we find suitable weights?

Learning corresponds to adapting weights, often *iteratively*, to achieve better performance

Hebb's learning hypothesis

Simultaneous activation of two neurons strengthens their synaptic inter-connection

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

But how do we find suitable weights?

Learning corresponds to adapting weights, often *iteratively*, to achieve better performance

Hebb's learning hypothesis

Simultaneous activation of two neurons strengthens their synaptic inter-connection

Common interpretation:

$$\Delta w_{ij} = x_j y_i$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

The program “resides” in weights

But how do we find suitable weights?

Learning corresponds to adapting weights, often *iteratively*, to achieve better performance

Hebb's learning hypothesis

Simultaneous activation of two neurons strengthens their synaptic inter-connection

Common interpretation:

$$\Delta w_{ij} = x_j y_i$$


covariance rule

$$\text{or } \dots \Delta w_{ij} = (x_j - \bar{x})(y_i - \bar{y})$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification


Hebbian learning rule



- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification



Hebbian learning rule



- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification


Hebbian learning rule



- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification


Hebbian learning rule



- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Hebbian learning rule



$$\Delta w_{i,j} = x_j y_i$$

“Fire together, wire together”

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Storing a mapping using Hebb's rule

$$\vec{x}_1 \rightarrow \vec{y}_1 \quad \vec{x}_2 \rightarrow \vec{y}_2 \quad \vec{x}_3 \rightarrow \vec{y}_3 \quad \dots \quad \vec{x}_n \rightarrow \vec{y}_n$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Storing a mapping using Hebb's rule

$$\vec{x}_1 \rightarrow \vec{y}_1 \quad \vec{x}_2 \rightarrow \vec{y}_2 \quad \vec{x}_3 \rightarrow \vec{y}_3 \quad \dots \quad \vec{x}_n \rightarrow \vec{y}_n$$

Hebb's rule

$$\Delta w_{ij} = x_i y_i$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Storing a mapping using Hebb's rule

$$\vec{x}_1 \rightarrow \vec{y}_1 \quad \vec{x}_2 \rightarrow \vec{y}_2 \quad \vec{x}_3 \rightarrow \vec{y}_3 \quad \dots \quad \vec{x}_n \rightarrow \vec{y}_n$$

Hebb's rule

$$\Delta w_{ij} = x_i y_j$$

Result

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

(outer product of vector patterns)

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Storing a mapping using Hebb's rule

$$\vec{x}_1 \rightarrow \vec{y}_1 \quad \vec{x}_2 \rightarrow \vec{y}_2 \quad \vec{x}_3 \rightarrow \vec{y}_3 \quad \dots \quad \vec{x}_n \rightarrow \vec{y}_n$$

Hebb's rule

$$\Delta w_{ij} = x_i y_j$$

Result

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

Correlational memory!

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Retrieving a memory trace

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

$$\vec{x}_k \rightarrow ?$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Retrieving a memory trace

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

$$\vec{x}_k \rightarrow ?$$

$$\vec{y}_{out} = W \vec{x}_k = \sum_{p=1}^n (\vec{y}_p \vec{x}_p^T) \vec{x}_k = \sum_{p=1}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k)$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Retrieving a memory trace

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

$$\vec{x}_k \rightarrow ?$$

$$\begin{aligned} \vec{y}_{out} &= W \vec{x}_k = \sum_{p=1}^n (\vec{y}_p \vec{x}_p^T) \vec{x}_k = \sum_{p=1}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) = \\ &= \underbrace{\vec{y}_k (\vec{x}_k^T \vec{x}_k)}_{\alpha} + \sum_{p \neq k}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) \end{aligned}$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Retrieving a memory trace

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

$$\vec{x}_k \rightarrow ?$$

$$\begin{aligned} \vec{y}_{out} &= W \vec{x}_k = \sum_{p=1}^n (\vec{y}_p \vec{x}_p^T) \vec{x}_k = \sum_{p=1}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) = \\ &= \underbrace{\vec{y}_k (\vec{x}_k^T \vec{x}_k)}_{\alpha} + \sum_{p \neq k}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) \approx \alpha \vec{y}_k \end{aligned}$$

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Retrieving a memory trace

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

$$\vec{x}_k \rightarrow ?$$

$$\begin{aligned} \vec{y}_{out} &= W \vec{x}_k = \sum_{p=1}^n (\vec{y}_p \vec{x}_p^T) \vec{x}_k = \sum_{p=1}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) = \\ &= \underbrace{\vec{y}_k (\vec{x}_k^T \vec{x}_k)}_{\alpha} + \sum_{p \neq k} \vec{y}_p (\vec{x}_p^T \vec{x}_k) \approx \alpha \vec{y}_k \end{aligned}$$

≈ 0

- Recap
- **Linear feed-forward networks**
- Thresholded single-layer networks
- Perceptron

- Multi-layer perceptron
- Backpropagation
- System identification

Storing mappings (memorising)

Retrieving a memory trace

$$W = \sum_{p=1}^n \vec{y}_p \cdot \vec{x}_p^T$$

$$\vec{x}_k \rightarrow ?$$


$$\begin{aligned} \vec{y}_{out} = W \vec{x}_k &= \sum_{p=1}^n (\vec{y}_p \vec{x}_p^T) \vec{x}_k = \sum_{p=1}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) = \\ &= \vec{y}_k (\vec{x}_k^T \vec{x}_k) + \sum_{p \neq k}^n \vec{y}_p (\vec{x}_p^T \vec{x}_k) \approx \alpha \vec{y}_k \end{aligned}$$

Perfect memory only if the patterns \vec{x}_p are orthogonal

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

TLU – how it all started....


Threshold logic unit – McCulloch Pitts neuron (1942)



- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

TLU – McCulloch Pitts

Threshold logic unit – McCulloch Pitts neuron (1942)




$$y' = w_1 x_1 + w_2 x_2 \quad y = f_{step}(y')$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

TLU – McCulloch Pitts

Threshold logic unit – McCulloch Pitts neuron (1942)



$$y' = w_1 x_1 + w_2 x_2 \quad y = f_{step}(y')$$


If threshold is 0, then:

$$w_1 x_1 + w_2 x_2 > 0 \rightarrow y' > 0 \rightarrow y = 1$$


$$w_1 x_1 + w_2 x_2 \leq 0 \rightarrow y' \leq 0 \rightarrow y = 0$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Geometrical interpretation




$$y' = w_1 x_1 + w_2 x_2$$




- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Geometrical interpretation



- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Threshold in TLU



THRESHOLDING with $\theta = 0$:


$$y = f_{step}(y')$$

$$w_1 x_1 + w_2 x_2 > 0 \rightarrow y' > 0 \rightarrow y = 1$$

$$w_1 x_1 + w_2 x_2 \leq 0 \rightarrow y' \leq 0 \rightarrow y = 0$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Threshold in TLU



$$y' = w_1 x_1 + w_2 x_2$$


THRESHOLDING with $\theta \approx 0$:

$$y' > \theta \rightarrow y = 1$$

$$y' \leq \theta \rightarrow y = 0$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Threshold in TLU




$$y' = w_1 x_1 + w_2 x_2$$

THRESHOLDING with $\theta \approx 0$:

$$y' > \theta \rightarrow y = 1$$



$$y' \leq \theta \rightarrow y = 0$$



$$w_1 x_1 + w_2 x_2 > \theta \rightarrow y = 1$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Threshold in TLU – geometrical interpretation





$$w_1 x_1 + w_2 x_2 > \theta \rightarrow w_1 x_1 + w_2 x_2 - \theta > 0$$

$$y' = w_1 x_1 + w_2 x_2 - \theta$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Threshold in TLU – bias trick



$$w_1 x_1 + w_2 x_2 > \theta \rightarrow w_1 x_1 + w_2 x_2 - \theta > 0$$



$$y' = w_1 x_1 + w_2 x_2 - \theta$$

$$y' = w_1 x_1 + w_2 x_2 + w_0 1$$

where: *bias* $w_0 = -\theta$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Threshold in TLU – bias trick



$$w_1 x_1 + w_2 x_2 > \theta \rightarrow w_1 x_1 + w_2 x_2 - \theta > 0$$

$$y' = w_1 x_1 + w_2 x_2 - \theta$$


$$y' = w_1 x_1 + w_2 x_2 + w_0 1$$

where: *bias* $w_0 = -\theta$



$$\vec{w} = \begin{bmatrix} w_1 \\ w_2 \\ -\theta \end{bmatrix} \quad \vec{x} = \begin{bmatrix} x_1 \\ x_2 \\ 1 \end{bmatrix}$$

- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Linear separability with TLU – geometrical interpret.




$$y' = w_1 x_1 + w_2 x_2 - \theta$$





- Recap
- Linear feed-forward networks
- **Thresholded single-layer networks**
- Perceptron
- Multi-layer perceptron
- Backpropagation
- System identification

Linear separability with TLU – geometrical interpret.





$$y' = w_1 x_1 + w_2 x_2 - \theta$$



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification



Binary classification with perceptron



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification


Binary classification with perceptron



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification



Space of weights and inputs - perceptron



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Space of weights and inputs - perceptron






- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Classification with perceptron – how does it work?

2D input space and 3D network's linear output




- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**


- Multi-layer perceptron
- Backpropagation
- System identification

Classification with perceptron

Linear output and perceptron's thresholded output



Separating hyperplane – network's linear output






Output surface – perceptron's thresholded output

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Classification with perceptron

Decision boundary in the input space



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning for classification

Perceptron learning for thresholded single-layer networks

Basic principle: weights are modified if and only if a pattern is erroneously classified:

When the network *output* = 0 but it should be 1 (*target* = 1)

$$\Delta \vec{w} = \eta \vec{x}$$

When the network *output* = 1 but it should be 0 (*target* = 0)


$$\Delta \vec{w} = -\eta \vec{x}$$

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning – geometrical interpretation

When the result is 0 but should be 1: $\Delta \vec{w} = \eta \Delta \vec{x}$




- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning – geometrical interpretation

When the result is 1 but should be 0: $\Delta \vec{w} = -\eta \Delta \vec{x}$



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning – convergence theorem

Convergence theorem


If a solution exists for a finite training dataset then perceptron learning always converges after a finite number of sets (independent of step size/learning rate, η)

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning

Problem: learning terminates prematurely.





- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning

Problem: learning terminates prematurely.




- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Perceptron learning

Problem: learning terminates prematurely.



Negative consequences are likely when patterns are only *approximately similar* to those used for training

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Delta rule

Delta rule (Widrow-Hoff rule, ADALINE)

Delta rule

Delta rule (Widrow-Hoff rule, ADALINE)

1. Symmetric target values: $\{-1, 1\}$
2. Error is measured before thresholding

$$e = t - \vec{w}^T \vec{x}$$

3. Find weights that minimise the error cost function

$$\varepsilon = \frac{e^2}{2}$$

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Delta rule

The task is to minimise the cost function $\varepsilon = \frac{e^2}{2}$

Simple algorithm: **steepest descent**

Delta rule

The task is to minimise the cost function $\varepsilon = \frac{e^2}{2}$

Simple algorithm: **steepest descent**

- Gradient defines the direction in which the error increases most
- *Steepest descent* implies that the move in the opposite direction in the weight space should be taken

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**



- Multi-layer perceptron
- Backpropagation
- System identification

Delta rule

The task is to minimise the cost function $\varepsilon = \frac{e^2}{2}$

Simple algorithm: **steepest descent**

- Gradient defines the direction in which the error increases most
- *Steepest descent* implies that the move in the opposite direction in the weight space should be taken



Delta rule

The task is to minimise the cost function $\varepsilon = \frac{e^2}{2}$

Simple algorithm: **steepest descent**

- Gradient defines the direction in which the error increases most
- *Steepest descent* implies that the move in the opposite direction in the weight space should be taken
- Gradient is calculated as follows:

$$\frac{\partial \varepsilon}{\partial \vec{w}} = e \frac{\partial e}{\partial \vec{w}} = e \frac{\partial (t - \vec{w}^T \vec{x})}{\partial \vec{w}} = -e \vec{x}$$

Delta rule

The task is to minimise the cost function $\varepsilon = \frac{e^2}{2}$

Simple algorithm: **steepest descent**

- Gradient defines the direction in which the error increases most
- *Steepest descent* implies that the move in the opposite direction in the weight space should be taken
- Gradient is calculated as follows:

$$\frac{\partial \varepsilon}{\partial \vec{w}} = e \frac{\partial e}{\partial \vec{w}} = e \frac{\partial (t - \vec{w}^T \vec{x})}{\partial \vec{w}} = -e \vec{x}$$

Delta Rule:

$$\Delta \vec{w} = \eta e \vec{x}$$

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Training of thresholded single-layer networks

Perceptron learning:

Delta rule:

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Training of thresholded single-layer networks

Perceptron learning:

$$\Delta \vec{w} = \eta e \vec{x} \quad \text{where} \quad e = t - y$$

Delta rule:

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Training of thresholded single-layer networks

Perceptron learning:

$$\Delta \vec{w} = \eta e \vec{x} \quad \text{where} \quad e = t - y$$

Delta rule:

$$\Delta \vec{w} = \eta e \vec{x} \quad \text{where} \quad e = t - \vec{w}^T \vec{x}$$

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Separability with TLU / perceptron

Can all sets of patterns be separated?

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**

- Multi-layer perceptron
- Backpropagation
- System identification

Separability with TLU / perceptron

Can all sets of patterns be separated?

Classical counter-example is Exclusive OR (XOR)

$$\begin{bmatrix} 0 \\ 0 \end{bmatrix} \rightarrow 0 \quad \begin{bmatrix} 0 \\ 1 \end{bmatrix} \rightarrow 1 \quad \begin{bmatrix} 1 \\ 0 \end{bmatrix} \rightarrow 1 \quad \begin{bmatrix} 1 \\ 1 \end{bmatrix} \rightarrow 0$$

- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**


- Multi-layer perceptron
- Backpropagation
- System identification

Separability with TLU / perceptron

Can all sets of patterns be separated?

Classical counter-example is Exclusive OR (XOR)

$$\begin{bmatrix} 0 \\ 0 \end{bmatrix} \rightarrow 0 \quad \begin{bmatrix} 0 \\ 1 \end{bmatrix} \rightarrow 1 \quad \begin{bmatrix} 1 \\ 0 \end{bmatrix} \rightarrow 1 \quad \begin{bmatrix} 1 \\ 1 \end{bmatrix} \rightarrow 0$$



- Recap
- Linear feed-forward networks
- Thresholded single-layer networks
- **Perceptron**


- Multi-layer perceptron
- Backpropagation
- System identification

Separability with TLU / perceptron

Can all sets of patterns be separated?

Classical counter-example is Exclusive OR (XOR)

$$\begin{bmatrix} 0 \\ 0 \end{bmatrix} \rightarrow 0 \quad \begin{bmatrix} 0 \\ 1 \end{bmatrix} \rightarrow 1 \quad \begin{bmatrix} 1 \\ 0 \end{bmatrix} \rightarrow 1 \quad \begin{bmatrix} 1 \\ 1 \end{bmatrix} \rightarrow 0$$



Not linearly separable!