

# Generating Expressive Facial Mesh Animation : A Survey

HJW  
Institution1 address  
ykn@rtfm.moe

## Abstract

With technology allowing for increasing realism in games and movies, facial animation is still a very challenging task.

*"Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum."*

## 1. Introduction

Psychologically, Human tend to be very sensitive to facial motion. Slightest uncanniest in facial animation is directly lead to hurt overall experience of embodiment, and overall experience [3]. So, delivering natural expressive facial animation is a great interest in graphics field.

To render realistic 3D face animation that naturally, high-quality animation is required. Animating high-quality expressive face is very labor-intensive job when done by animator. Another approach is to capture human face animation in 3D. Face capture is a well-understood field(cite here), yet such approach requires gigabytes of data from expensive capture system, and is hard to manipulate. Therefore, it is necessary to simplify such process.

To simplify such process, one can automatically generate facial animation or can simplify animating produce.

In this survey, I introduce and compare three research that animate expressive facial animation :

- JALI [1] and VisimeNet [6], a linguistic approach to lip-sync.
- MeshTalk [5], a deep learning method.
- D3DExpression [4], LSTM method which replicate facial expression.




Figure 1. Speaking styles of JALI viseme field

## 2. Methods

### 2.1. JALI and VisimeNet

Creating lip-sync animation is complex and challenging task. Lip-sync is traditionally done by linguistic approach. Mapping text to phonemes, then visemes, the position of lip and jaw [2].

Phonemes to visemes is a complex many-to-many mapping. JALI addresses this problem by animating each jaw and lip multipliers.

Creating lip-sync animation from audio signal only is an attractive approach since it does not require any costly camera or tracking device. This approach requires extracting viseme and jaw-lip model sequence from audio. As shown

on Fig. 1, something something

## References

- [1] Pif Edwards, Chris Landreth, Eugene Fiume, and Karan Singh. JALI: An animator-centric viseme model for expressive lip synchronization. *ACM Transactions on Graphics*, 35(4):1–11, July 2016. 1
- [2] T. Ezzat and T. Poggio. MikeTalk: A talking facial display based on morphing visemes. In *Proceedings Computer Animation '98 (Cat. No.98EX169)*, pages 96–102, June 1998. 1
- [3] David Hanson. Upending the Uncanny Valley. page 8. 1
- [4] Rolandos Alexandros Potamias, Jiali Zheng, Stylianos Ploumpis, Giorgos Bouritsas, Evangelos Ververas, and Stefanos Zafeiriou. Learning to Generate Customized Dynamic 3D Facial Expressions. *arXiv:2007.09805 [cs]*, July 2020. 1
- [5] Alexander Richard, Michael Zollhöfer, Yandong Wen, Fernando de la Torre, and Yaser Sheikh. MeshTalk: 3D Face Animation From Speech Using Cross-Modality Disentanglement. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1173–1182, 2021. 1
- [6] Yang Zhou, Zhan Xu, Chris Landreth, Evangelos Kalogerakis, Subhransu Maji, and Karan Singh. Visemenet: Audio-driven animator-centric speech animation. *ACM Transactions on Graphics*, 37(4):161:1–161:10, July 2018. 1