

Intro to Programming for Public Policy Week 8

Statistics, Regression, and Visualizations

Eric Potash

May 17, 2018

Writing files

Reading

Recall that we could read a file as follows:

```
file = open('filename.txt')  
contents = file.readlines()
```

Writing

Similarly, we can write:

```
file = open('filename.txt', 'w')
file.write('First line')
file.write('Second line')
file.write('Still second line\n')
file.close()
```

- ▶ Note the format argument 'w', indicating that we want to write to the specified file.
 - ▶ 'w' will overwrite any existing file
 - ▶ To append, use 'a'
- ▶ If you don't close the file when you're done, bad things can happen.

with block

To avoid remembering to close the file, you can wrap your writing in a with block. Python will automatically close the file when the block is finished.

```
with open('filename.txt', 'w') as file:  
    file.write('First line')  
    file.write('Second line')  
    file.write('Still second line\n')
```

Reshaping/Pivoting

Hierarchical index

When we groupby with two keys the result has what's called a multiindex or a hierarchical index:

```
In [1]: import pandas as pd
        %matplotlib inline
```

```
In [2]: crimes = pd.read_csv('Crimes_-_2001_to_present.csv')
        crimes['Date'] = pd.to_datetime(crimes.Date)
```

```
In [10]: crimes['Day'] = crimes.Date.dt.date
         crimes['Month'] = crimes.Date.dt.month
```

```
In [16]: crime_months = crimes.groupby(['Community Area', 'Month']).size()
         crime_months
```

```
Out[16]: Community Area  Month
0          5            1
1          1          289
          2          295
          3          289
          4          336
          5          369
          6          347
          7          410
          8          384
          9          355
         10          406
         11          360
         12          291
2          1          307
```

Simpler example

```
>>> df = pd.DataFrame([[0, 1, 2], [3, 4, 5]],  
                        index=['Ohio', 'Colorado'],  
                        columns=['one', 'two', 'three'])
```

```
>>> df
```

	one	two	three
Ohio	0	1	2
Colorado	3	4	5

To *reshape* into a hierarchical index use `stack()`:

```
>>> s = df.stack()
```

```
>>> s
```

Ohio	one	0
	two	1
	three	2
Colorado	one	3
	two	4
	three	5

```
dtype: int64
```


unstack()

The inverse to this operation is `unstack()`:

```
>>> s.unstack()
      one  two  three
Ohio    0    1     2
Colorado 3    4     5
```

Unstack crimes

```
In [18]: crime_months.unstack('Community Area')
```


```
Out[18]:
```

Community Area	0	1	2	3	4	5	6	7	8	9	...	68	69	70	71	72	73
Month																	
1	NaN	289.0	307.0	265.0	163.0	95.0	447.0	367.0	887.0	18.0	...	490.0	557.0	269.0	620.0	70.0	278.0
2	NaN	295.0	236.0	255.0	136.0	100.0	385.0	305.0	795.0	32.0	...	392.0	451.0	226.0	572.0	68.0	199.0
3	NaN	289.0	284.0	242.0	132.0	100.0	386.0	349.0	812.0	20.0	...	443.0	486.0	240.0	559.0	59.0	229.0
4	NaN	336.0	267.0	290.0	118.0	93.0	470.0	308.0	908.0	17.0	...	487.0	502.0	209.0	677.0	66.0	239.0
5	1.0	369.0	298.0	304.0	174.0	147.0	485.0	371.0	937.0	15.0	...	608.0	568.0	184.0	697.0	81.0	280.0
6	NaN	347.0	299.0	299.0	160.0	138.0	551.0	387.0	1085.0	21.0	...	558.0	550.0	194.0	621.0	110.0	291.0
7	NaN	410.0	327.0	345.0	171.0	138.0	555.0	401.0	1150.0	35.0	...	553.0	607.0	186.0	721.0	82.0	269.0
8	NaN	384.0	329.0	334.0	214.0	158.0	544.0	382.0	1237.0	35.0	...	520.0	604.0	191.0	683.0	80.0	257.0
9	NaN	355.0	315.0	339.0	198.0	115.0	512.0	397.0	1123.0	27.0	...	509.0	554.0	196.0	609.0	67.0	282.0
10	NaN	406.0	306.0	331.0	184.0	119.0	570.0	389.0	1165.0	16.0	...	476.0	512.0	199.0	628.0	76.0	272.0
11	NaN	360.0	295.0	263.0	172.0	99.0	375.0	405.0	1062.0	16.0	...	458.0	550.0	211.0	534.0	70.0	257.0
12	NaN	291.0	320.0	281.0	168.0	115.0	432.0	397.0	1104.0	21.0	...	418.0	516.0	185.0	579.0	59.0	217.0

Time series

```
In [19]: crime_months.unstack(level='Community Area')[[1,2,3, 4]].plot(figsize=(10,5))
```

```
Out[19]: <matplotlib.axes._subplots.AxesSubplot at 0x7ff97ba02410>
```



Visualizations

Matplotlib

- ▶ Matplotlib is the core of all plotting in python
- ▶ When you use pandas (or seaborn) to plot, it is using matplotlib.
- ▶ As a result, matplotlib settings will affect pandas plots

Matplotlib rcParams

```
In [75]: import pandas as pd
import matplotlib.pyplot as plt
%matplotlib inline

plt.rcParams['figure.figsize'] = 9,5
plt.rcParams['font.family'] = 'sans-serif'
```

Axes

Plot functions like `DataFrame.plot()` or `Series.hist()` return matplotlib Axes objects:


```
>>> s = pd.Series([1,2,3,4])
>>> ax = s.plot()
>>> ax
<matplotlib.axes._subplots.AxesSubplot at 0x7fa917dac410>
```

You can use these Axes objects to customize the plot.

Axes customization

```
In [10]: ax = s.plot()  
ax.set_xlabel('X axis', fontsize=14)  
ax.set_ylabel('Y axis', fontsize=14)  
  
ax.set_title('Title of plot', fontsize=20)
```

Out[10]: <matplotlib.text.Text at 0x7f9d0b7363d0>



Wages data

```
In [5]: import pandas as pd  
        %matplotlib inline
```

```
In [23]: df = pd.read_csv('wages.csv')  
df
```

```
Out[23]:
```


	EDUCATION	SOUTH	SEX	EXPERIENCE	UNION	WAGE	AGE	RACE	OCCUPATION	SECTOR	MARR
0	8	NORTH	FEMALE	21	False	5.10	35	Hispanic	Other	Manufacturing	True
1	9	NORTH	FEMALE	42	False	4.95	57	White	Other	Manufacturing	True
2	12	NORTH	MALE	1	False	6.67	19	White	Other	Manufacturing	False
3	12	NORTH	MALE	4	False	4.00	22	White	Other	Other	False
4	12	NORTH	MALE	17	False	7.50	35	White	Other	Other	True
5	13	NORTH	MALE	9	True	13.07	28	White	Other	Other	False
6	10	SOUTH	MALE	27	False	4.45	43	White	Other	Other	False
7	12	NORTH	MALE	9	False	19.47	27	White	Other	Other	False
8	16	NORTH	MALE	11	False	13.28	33	White	Other	Manufacturing	True
9	12	NORTH	MALE	9	False	8.75	27	White	Other	Other	False
10	12	NORTH	MALE	17	True	11.35	35	White	Other	Other	True

From 1985 CPS, CSV [here](#).

Boxplot

```
In [3]: df.boxplot('WAGE', by='OCCUPATION')
```

```
Out[3]: <matplotlib.axes._subplots.AxesSubplot at 0x7faf9368ca90>
```




Seaborn

- ▶ Seaborn is a visualization module that builds on matplotlib
 - ▶ So what we know about matplotlib Axes and rcParams still applies
- ▶ Provides a lot of very useful plots and options

Seaborn boxplot

```
In [5]: import seaborn as sns  
sns.boxplot(x='OCCUPATION', y='WAGE', data=df)
```


```
Out[5]: <matplotlib.axes._subplots.AxesSubplot at 0x7faf934e1a10>
```



Seaborn boxplot hue

```
In [6]: sns.boxplot(x='OCCUPATION', y='WAGE', hue='SEX', data=df)
```


```
Out[6]: <matplotlib.axes._subplots.AxesSubplot at 0x7faf8b018410>
```



Seaborn aesthetics

```
In [11]: sns.set_style('whitegrid')  
sns.boxplot(x='OCCUPATION', y='WAGE', hue='SEX', data=df)
```


```
Out[11]: <matplotlib.axes._subplots.AxesSubplot at 0x7faf8a1fdd10>
```



Seaborn pairplot()

```
In [12]: sns.pairplot(df, vars=['WAGE', 'AGE', 'EDUCATION'])
```


```
Out[12]: <seaborn.axisgrid.PairGrid at 0x7faf8a97cf50>
```



Seaborn regplot()

```
In [21]: sns.regplot('EDUCATION', 'WAGE', df)
```


```
Out[21]: <matplotlib.axes._subplots.AxesSubplot at 0x7faf82ad7f90>
```



Another regplot()

```
In [23]: sns.regplot('UNION', 'WAGE', df)
```


```
Out[23]: <matplotlib.axes._subplots.AxesSubplot at 0x7f9d02d00250>
```



Jittering

```
In [26]: sns.regplot('UNION', 'WAGE', df, x_jitter=.1)
```


```
Out[26]: <matplotlib.axes._subplots.AxesSubplot at 0x7f9d02a13250>
```



pairplot kind='reg'

```
In [13]: sns.pairplot(df, vars=['WAGE', 'AGE', 'EDUCATION'], kind='reg')
```


```
Out[13]: <seaborn.axisgrid.PairGrid at 0x7faf8a97cc10>
```



pairplot hue

```
In [25]: sns.pairplot(df, vars=['WAGE', 'AGE', 'EDUCATION'], kind='reg', hue='SEX')
```

```
Out[25]: <seaborn.axisgrid.PairGrid at 0x7faf8367b910>
```



Regression in Python

Statsmodels

- ▶ Statsmodels is an econometrics/statistics library for python.
- ▶ It provides OLS, logistic and other regression functions.
- ▶ There are other modules that can perform regression (e.g. `scipy` and `sklearn`)
 - ▶ But statsmodels has the best output

X,y

One way to run a regression with statsmodels is to provide a exogenous design matrix and an endogenous outcome vector:

```
In [26]: from statsmodels.regression.linear_model import OLS
```

```
In [28]: X = df[['AGE', 'EDUCATION']]  
         y = df['WAGE']
```

statsmodels regression

```
In [32]: res = OLS(y, X)  
         type(res)
```

```
Out[32]: statsmodels.regression.linear_model.OLS
```

```
In [34]: fit = res.fit()  
         type(fit)
```

```
Out[34]: statsmodels.regression.linear_model.RegressionResultsWrapper
```


Regression summary()

In [36]: `fit.summary()`

Out[36]:

OLS Regression Results

Dep. Variable:	WAGE	R-squared:	0.798
Model:	OLS	Adj. R-squared:	0.797
Method:	Least Squares	F-statistic:	1051.
Date:	Thu, 17 May 2018	Prob (F-statistic):	1.73e-185
Time:	00:05:00	Log-Likelihood:	-1580.3
No. Observations:	534	AIC:	3165.
Df Residuals:	532	BIC:	3173.
Df Model:	2		
Covariance Type:	nonrobust		

	coef	std err	t	P> t 	[95.0% Conf. Int.]
AGE	0.0595	0.014	4.309	0.000	0.032 0.087
EDUCATION	0.5351	0.040	13.311	0.000	0.456 0.614

Omnibus:	230.878	Durbin-Watson:	1.789
Prob(Omnibus):	0.000	Jarque-Bera (JB):	1396.245
Skew:	1.805	Prob(JB):	6.45e-304
Kurtosis:	10.052	Cond. No.	8.47

Add a constant

You could add a constant like this and then rerun the regression:

```
In [52]: X['Intercept'] = 1  
fit = OLS(y,X).fit()  
fit.summary()
```

Out[52]: OLS Regression Results

Dep. Variable:	WAGE	R-squared:	0.202
Model:	OLS	Adj. R-squared:	0.199
Method:	Least Squares	F-statistic:	67.21
Date:	Thu, 17 May 2018	Prob (F-statistic):	9.57e-27
Time:	00:08:41	Log-Likelihood:	-1571.1
No. Observations:	534	AIC:	3148.
Df Residuals:	531	BIC:	3161.
Df Model:	2		
Covariance Type:	nonrobust		

	coef	std err	t	P> t	[95.0% Conf. Int.]
AGE	0.1050	0.017	6.112	0.000	0.071 0.139
EDUCATION	0.8211	0.077	10.657	0.000	0.670 0.972
Intercept	-5.5342	1.279	-4.326	0.000	-8.047 -3.021

Fitted values

In [53]: `fit.fittedvalues`

Out[53]:

0	4.710601
1	7.842321
2	6.314583
3	6.629667
4	7.995029
5	8.080941
6	7.193038
7	7.154806
8	11.069402
9	7.154806
10	7.995029
11	8.205085
12	5.340768
13	6.581986
14	6.476958
15	10.095586
16	6.200107
17	8.940280
18	6.963866
19	9.675475

Residuals

```
In [54]: fit.resid
```

```
Out[54]: 0      0.389399  
1     -2.892321  
2      0.355417  
3     -2.629667  
4     -0.495029  
5      4.989059  
6     -2.743038  
7     12.315194  
8      2.210598  
9      1.595194  
10     3.354971  
11     3.294915  
12     1.159232  
13     -0.331986  
14     13.503042  
15     -2.795586  
16     1.799893  
17     13.259720
```

Coefficients

In [55]: `fit.params`

Out[55]:

AGE	0.105028
EDUCATION	0.821107
Intercept	-5.534232

dtype: float64

Formulas

It's more convenient to run a regression using formulas:

```
In [56]: import statsmodels.formula.api as smf
```

```
In [57]: fit = smf.ols('WAGE ~ AGE + EDUCATION', df).fit()  
fit.summary()
```

Out[57]:

OLS Regression Results

Dep. Variable:	WAGE	R-squared:	0.202
Model:	OLS	Adj. R-squared:	0.199
Method:	Least Squares	F-statistic:	67.21
Date:	Thu, 17 May 2018	Prob (F-statistic):	9.57e-27
Time:	00:09:02	Log-Likelihood:	-1571.1
No. Observations:	534	AIC:	3148.
Df Residuals:	531	BIC:	3161.
Df Model:	2		
Covariance Type:	nonrobust		

	coef	std err	t	P> t	[95.0% Conf. Int.]
Intercept	5.5918	1.8729	1.822	0.069	0.947 9.094

Formula anatomy

WAGE ~ AGE + EDUCATION

- ▶ The variable on the left of the ~ is the outcome
- ▶ The variables on the right are separated by plus signs

Formula intercepts

- ▶ Formulas include an intercept term on the right-hand side by default. To remove it use

```
WAGE ~ EDUCATION + AGE - 1
```

- ▶ You can also specify the intercept explicitly (same as not specifying it):

```
WAGE ~ EDUCATION + AGE + 1
```


Formulas with `numpy` functions

With formulas you can apply functions to the covariates or dependent variable:

```
np.log(WAGE) ~ EDUCATION + AGE + 1
```

Formula interactions

Formulas allow you to play around with different specifications easily.

- ▶ To add the interaction of two variables use $a:b$
- ▶ To add the variables and their interaction use $a*b$
 - ▶ So $a*b$ is equivalent to $a + b + a*b$

Formulas with categorical variables

By default, variables with string values become dummy variables (fixed effects) in the regression:

```
In [59]: fit = smf.ols('WAGE ~ AGE + EDUCATION + OCCUPATION', df).fit()  
fit.summary()
```

Out[59]:

OLS Regression Results

Dep. Variable:	WAGE	R-squared:	0.272
Model:	OLS	Adj. R-squared:	0.262
Method:	Least Squares	F-statistic:	28.09
Date:	Thu, 17 May 2018	Prob (F-statistic):	7.28e-33
Time:	00:14:41	Log-Likelihood:	-1546.5
No. Observations:	534	AIC:	3109.
Df Residuals:	526	BIC:	3143.
Df Model:	7		
Covariance Type:	nonrobust		

	coef	std err	t	P> t	[95.0% Conf. Int.]
Intercept	-4.6162	1.566	-2.949	0.003	-7.692 -1.541
OCCUPATION[T.Management]	3.9994	0.764	5.235	0.000	2.499 5.500
OCCUPATION[T.Other]	2.0634	0.589	3.503	0.000	0.906 3.221

Formula C()

For numeric columns to be interpreted as categories use C():

```
In [68]: fit = smf.ols('WAGE ~ AGE + C(EDUCATION) + OCCUPATION + SECTOR + UNION', df).fit()  
fit.summary()
```

Out[68]: OLS Regression Results

Dep. Variable:	WAGE	R-squared:	0.320
Model:	OLS	Adj. R-squared:	0.286
Method:	Least Squares	F-statistic:	9.560
Date:	Thu, 17 May 2018	Prob (F-statistic):	2.88e-29
Time:	00:18:46	Log-Likelihood:	-1528.4
No. Observations:	534	AIC:	3109.
Df Residuals:	508	BIC:	3220.
Df Model:	25		
Covariance Type:	nonrobust		

	coef	std err	t	P> t	[95.0% Conf. Int.]
Intercept	2.6712	4.533	0.589	0.556	-6.235 11.578
C(EDUCATION)[T.3]	-2.9981	6.223	-0.482	0.630	-15.225 9.229
C(EDUCATION)[T.4]	-1.2337	6.180	-0.200	0.842	-13.375 10.908
C(EDUCATION)[T.5]	5.2968	6.252	0.847	0.397	-6.985 17.579
C(EDUCATION)[T.6]	-5.1672	5.088	-1.015	0.310	-15.164 4.830
C(EDUCATION)[T.7]	-2.1600	4.800	-0.450	0.653	-11.589 7.269

Other models

- ▶ Logit
- ▶ Weighted least squares

Statistical testing

SciPy


SciPy (Scientific Python) is a library of scientific tools for python. It includes, among many other things, a submodule `scipy.stats` with a many statistical test functions.

Log wages by sex

```
In [40]: male_wages = df['WAGE'][df.SEX == 'MALE']  
female_wages = df['WAGE'][df.SEX == 'FEMALE']
```

```
In [46]: np.log(male_wages).hist(alpha=.5)  
np.log(female_wages).hist(alpha=.5)
```

```
Out[46]: <matplotlib.axes._subplots.AxesSubplot at 0x7f9d02327f90>
```



t-test

```
In [47]: from scipy.stats import ttest_ind  
         ttest_ind(np.log(male_wages), np.log(female_wages))
```

```
Out[47]: Ttest_indResult(statistic=5.1658066558780682, pvalue=3.3904092752343325e-07)
```

Other stats

- ▶ 1 sample t-test
- ▶ 1- and 2-sample z-test
- ▶ Spearman's rank correlation