

【MainActivity.kt】のコード

```
import androidx.appcompat.app.AppCompatActivity
import android.os.Bundle
import android.widget.Button
import android.widget.TextView
import androidx.lifecycle.LifecycleScope
import kotlinx.coroutines.Dispatchers
import kotlinx.coroutines.launch
import kotlinx.coroutines.withContext
import org.json.JSONException
import org.json.JSONObject
import java.io.BufferedReader
import java.io.IOException
import java.io.InputStreamReader
import java.net.URL

class MainActivity : AppCompatActivity() {

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_main)

        val button = findViewById<Button>(R.id.button)
        val postCodeText = findViewById<TextView>(R.id.postCodeText)
        val mainUrl = "http://zipcloud.ibsnet.co.jp/api/search?zipcode="

        button.setOnClickListener {
            val postCode = postCodeText.text.toString()
            val postCodeUrl = mainUrl + postCode

            postCodeTask(postCodeUrl)
        }
    }

    private fun postCodeTask(postCodeUrl: String) {
        lifecycleScope.launch {
            val result = postCodeBackgroundTask(postCodeUrl)

            postCodeJsonTask(result)
        }
    }
}
```

```

private suspend fun postCodeBackgroundTask(postCodeUrl: String): String {
    val response = withContext(Dispatchers.IO) {
        var httpResult = ""

        try {
            val urlObj = URL(postCodeUrl)

            val br = BufferedReader(InputStreamReader(urlObj.openStream()))

            httpResult = br.readText()
        } catch (e: IOException) {
            e.printStackTrace()
        } catch (e: JSONException) {
            e.printStackTrace()
        }
        return@withContext httpResult
    }

    return response
}

```

```

private fun postCodeJsonTask(result: String) {
    val add1 = findViewById<TextView>(R.id.add1)
    val add2 = findViewById<TextView>(R.id.add2)
    val add3 = findViewById<TextView>(R.id.add3)
    val errText = findViewById<TextView>(R.id.errText)

    val jsonObj = JSONObject(result)
    val perentJsonArray = jsonObj.getJSONArray("results")
    val detailJsonObj = perentJsonArray.getJSONObject(0)
    val errorText: String = jsonObj.getString("message")

    add1.text = detailJsonObj.getString("address1")
    add2.text = detailJsonObj.getString("address2")
    add3.text = detailJsonObj.getString("address3")

    errText.text = errorText
}
}

```