

Introduction to Artificial Intelligence



VICTORIA UNIVERSITY OF
WELLINGTON
TE HERENGA WAKA

COMP307/AIML420

Machine Learning 2: 3-K Techniques

Dr Andrew Lensen

Andrew.Lensen@vuw.ac.nz

Outline

- **K**-Nearest Neighbour method
 - Classification (**Supervised** learning)
 - Basic NN (1-NN)
 - K-Nearest Neighbour (KNN)
 - Distance/Similarity measure
- **K**-fold cross validation
 - Leave-one out cross **validation**
 - K-fold cross validation vs validation set
- **K**-means clustering
 - **Unsupervised** learning

Classification for *Iris* Dataset

- **Three** classes of *Iris* flower
- **Four** features
 - **Length** (cms) and **width** (cms) of:
 - Sepals
 - Petals
- **150** instances (lines)
 - **50** for each class

```
5.1, 3.5, 1.4, 0.2, Iris-setosa
4.9, 3.0, 1.4, 0.2, Iris-setosa
...
7.0, 3.2, 4.7, 1.4, Iris-versicolor
6.4, 3.2, 4.5, 1.5, Iris-versicolor
...
6.3, 3.3, 6.0, 2.5, Iris-virginica
5.8, 2.7, 5.1, 1.9, Iris-virginica
...
```

Setosa



Versicolor



Virginica




(1-)Nearest Neighbour Classifier

- **Directly** use the **training** instances to classify an **unseen** instance (e.g. **test** instance)
 - Assign class from the **most similar** training instance
1. **Compare** the unseen instance to all the training instances;
 2. Find the “**nearest neighbour**” (the training instance that is **closest to** the unseen instance) from the **training set**;
 3. Classify the unseen instance as the **class of the nearest neighbour**.


Q: Is this machine learning (ML)?

K-Nearest Neighbour


- Extension of 1-nearest neighbour method
- But find **k nearest instances from the training set**
- Then choose the **majority** class as the class label of the unseen instance
- **K usually an odd number (why?)**
- **Results depend on k value**
- Need a **distance/similarity measure**




the data



NN classifier



5-NN classifier



Distance Measure

- Given two feature vectors with **numeric values**

- $A = (a_1, \dots, a_n)$ and $B = (b_1, \dots, b_n)$

- **Distance measure (Euclidean distance)**

- $$d = \sqrt{\sum_{i=1}^n \frac{(a_i - b_i)^2}{R_i^2}} = \sqrt{\frac{(a_1 - b_1)^2}{R_1^2} + \frac{(a_2 - b_2)^2}{R_2^2} + \dots + \frac{(a_n - b_n)^2}{R_n^2}}$$

Range of the i th feature

- Why divide by the **range**?
- **Easy to use**, can achieve good results in many cases
- **Efficiency?**

Training and Testing


- We usually divide dataset into **training** and **test** sets
- **Train** a classifier using the **training set**
- Calculate the **test performance** (test error) on the **test/unseen set**
- Different **training/test division** leads to different **test performance**
- Example:
 - Learning algorithms **A** and **B**
 - Dataset: instances 1~100
 - Train on 1~70, test on 71~100: **A** got **96%** accuracy, **B** got **93%** accuracy
 - Train on 31~100, test on 1~30: **A** got **91%** accuracy, **B** got **95%** accuracy
 - Which algorithm is better?
- *K-fold cross validation* makes estimation **less division-dependent**

K-fold Cross Validation

- Idea: chop the data into K equal subsets
- For each subset:
 - Treat it as the test set
 - Treat the rest $K-1$ subsets as the training set
 - Train classifier using the training set, apply it to the test set
- The training/test process is repeated K times (the folds), with each of the K subsets used exactly once as the test set
- The K results from the folds can be then averaged (or otherwise combined) to produce a single estimation
- Can be used for comparing two algorithms, or to measure the performance of one algorithm when the data set is small

K-fold Cross Validation: Example

- 10-fold cross validation
 - Divide into 10 equally-sized subsets



Leave-one-out Cross Validation


- Very similar to k-fold cross validation
- Every time, it only uses **one instance** as the **test set**
- A special case where **size of subsets is 1**
- Repeated **m** times, where **m** is the **number of instances in the entire dataset!**
- K-fold cross validation is *an **experiment design method*** for setting up experiments to test algorithms on **supervised** learning tasks (classification and regression)
- It is **NOT** a ML or classification method/technique.

Validation Set vs Cross Validation

- Validation set
 - A pre-defined dataset
 - Separate dataset from the training and test datasets
 - Used for monitoring the training process but not directly used for learning the classifier
 - Helps to avoid overfitting
- Cross validation
 - Experimental design method
 - In this method, there are only training and test datasets
 - No validation set (usually)

K-means Clustering

- Unlabelled data
- Want to obtain a good *partition* for the data by using ML
- Need clustering techniques, type of unsupervised learning



K-means Clustering

- **K-means clustering** is a method of cluster analysis which aims to **partition m instances into k clusters** in which each instance belongs to the cluster with the **nearest mean**.
- Need a **distance measure** such as **Euclidean distance**
- Generally, need to assume **the number of clusters**

K-means Clustering: Algorithm


- 1. Initialise k initial “means” randomly from the data set
- 2. Create k clusters by assigning every instance to the nearest cluster: based on the nearest mean according to the distance measure

$$c(x) = \arg \min_{i=1,\dots,k} dist(c_i, x)$$


- 3. Replace the old means with the centroid (mean) of each cluster

$$c_i = \frac{1}{|S_i|} \sum_{x_i \in S_i} x_i$$

- 4. Repeat the above two steps until convergence (no change in each cluster centroid).
- Centroid is not an instance*





K-Means Clustering: An Example




Choosing K

- Number of clusters
- A very important parameter
- But hard to determine in real world (need domain knowledge)



- Many methods to estimate K
 - Elbow method
 - X-mean clustering
 - Silhouette method
 - ...



Summary

- Nearest neighbour method for classification
 - K-Nearest neighbour method — classification method
 - Measures of comparing two feature vectors
- K-fold cross validation
 - experimental design method, NOT a ML method
 - validation set is a pre-defined data set
- K-means method – clustering method, NOT for classification
- Next Lecture: Decision tree learning for classification
- Suggested reading: Section 18.3 (both 2nd and 3rd editions) and online materials