

# Programmieren I (Python)

Christian Osendorfer

2023-11-02

# Higher Order Functions

# Higher Order Functions

What are higher-order functions?

A function that either:

- Takes another function as an argument
- Returns a function as its result

All other functions are considered *first-order* functions.

# Generalizing over computational processes

$$\sum_{k=1}^5 k = 1 + 2 + 3 + 4 + 5 = 15$$

$$\sum_{k=1}^5 k^3 = 1^3 + 2^3 + 3^3 + 4^3 + 5^3 = 225$$

The *common structure* among these functions may be a **computational process**, not just a number.

# Functions as arguments

```
1 def cube(k):
2     return k ** 3
3
4 def summation(n, term):
5     """Sum the first N terms of a sequence.
6     >>> summation(5, cube)
7     225
8     """
9     total = 0
10    k = 1
11    while k <= n:
12        total = total + term(k)
13        k = k + 1
14    return total
```

# Functions as return values

# Locally defined functions

Functions defined within other function bodies are bound to names in a local frame (more on **frames** later in the course.)

```
1 def make_adder(n):
2     """Return a function that takes one argument k
3         and returns k + n.
4     >>> add_three = make_adder(3)
5     >>> add_three(4)
6     7
7     """
8     def adder(k):
9         return k + n
10    return adder
```

# Lambda Expressions

A lambda expression is a simple **function definition** that *evaluates* to a function.

The syntax:

```
1 lambda <parameters>: <expression>
```

A function that takes in parameters and returns the result of expression.

A lambda version of the square function:

```
1 square = lambda x: x * x
```

- A function that takes in parameter  $x$  and returns the result of  $x * x$ .



# Lambda syntax tips

A lambda expression does not contain return statements or **any statements at all**.

Incorrect:

```
1 square = lambda x: return x * x
```

Correct:

```
1 square = lambda x: x * x
```

# Def statements vs. Lambda expressions

- Both create a function with the same domain, range, and behavior.
- Both bind that function to the name `square`.
- Only the `def` statement gives the function an intrinsic name, which is available to be called by that name from a python interpreter (see **frames** later in this course).

# Lambda as argument

It's convenient to use a lambda expression when you are passing in a simple function as an argument to another function.

Instead of...

```
1 def cube(k):  
2     return k ** 3  
3  
4 summation(5, cube)
```

... we can use a **lambda**:

```
1 summation(5, lambda k: k ** 3)
```

# Conditional Expressions

# Conditional expressions

A conditional expression has the form:

```
<consequent> if <predicate> else <alternative>
```

Evaluation rule:

- Evaluate the **predicate** expression.
- If it's a **True** value, the value of the whole expression is the value of the .
- Otherwise, the value of the whole expression is the value of the .

# Lambdas with conditionals

This is invalid syntax:

```
1 lambda x: if x > 0: x else: 0
```

Conditional expressions to the rescue!

```
1 lambda x: x if x > 0 else 0
```

# Recursion

# Recursive functions

A function is recursive if the body of that function calls itself, either directly or indirectly.

Recursive functions often operate on increasingly smaller instances of a problem.



# The problems within the problem

- The sum of the digits of 6 is simply 6.
- Generally: the sum of any one-digit non-negative number is that number.
- The sum of the digits of 2021 is the sum of 202 plus 1.
- Generally: the sum of a number is the sum of the first digits (`number // 10`), plus the last digit (`number % 10`).

# Summing digits without a loop

```
1 def sum_digits(n):
2     """Return the sum of the digits of positive integer n.
3     >>> sum_digits(6)
4     6
5     >>> sum_digits(2021)
6     5
7     """
8     if n < 10:
9         return n
10    else:
11        all_but_last = n // 10
12        last = n % 10
13        return sum_digits(all_but_last) + last
```

# Anatomy of a recursive function

- **Base case:** Evaluated without a recursive call (the smallest subproblem).
- **Recursive case:** Evaluated with a recursive call (breaking down the problem further).
- **Conditional statement** to decide if it's a base case.

# Recursive factorial

The factorial (*Fakultät*) of a natural number  $n$  is defined as:

$$n! = \begin{cases} 1 & n = 0 \\ n \cdot (n - 1)! & n > 0 \end{cases}$$

```
1 def fact(n):
2     """
3     >>> fact(0)
4     1
5     >>> fact(4)
6     24
7     """
8     if n == 0:
9         return 1
10    else:
11        return n * fact(n-1)
```

# Tree Recursion

# Tree Recursion

Tree-shaped processes arise whenever a recursive function makes more than one recursive call (*multiple recursion*).

# Recursive Virahanka-Fibonacci

The nth number is defined as:

$$vf(n) = \begin{cases} 0 & n = 0 \\ 1 & n = 1 \\ vf(n-1) + vf(n-2) & \text{otherwise} \end{cases}$$

```
1 def virfib(n):
2     """Compute the nth Virahanka-Fibonacci number, for n >= 1.
3     >>> virfib(2)
4     1
5     >>> virfib(6)
6     8
7     """
8     if n == 0:
9         return 0
10    elif n == 1:
11        return 1
12    else:
13        return virfib(n-1) + virfib(n-2)
```

# Redundant computations

The function is called on the same number multiple times.





