Realistic Lip Synchronization Using Deep Learning Techniques for Speech Generation

Kavitha R
Department of Information Technology
Velammal College of Engineering and Technology
Madurai, India
rka@vcet.ac.in

Dinesh Babu P K
Department of Information Technology
Velammal College of Engineering and Technology
Madurai, India
dinesh258.babu@gmail.com

Yashwanth J A
Department of Information Technology
Velammal College of Engineering and Technology
Madurai, India
yashyashwanth28102003@gmail.com

2024 International BIT Conference (BITCON) | 979-8-3315-1839-4/24/$31.00 ©2024 IEEE | DOI: 10.1109/BITCON63716.2024.10984909

***Abstract*—In this paper a thorough approach is provided to address the problem to bridge language gaps for educational purposes and support the elderly in overcoming language barriers. The system leverages advanced image processing, text extraction, translation, and text-to-speech synthesis to convert textual information from images, screens, or printed materials into synchronized audio output. Utilizing an approach inspired by Wave2Lip synchronization, the system achieves seamless alignment of the translated audio with the original video content. This multi-stage processing pipeline employs techniques such as adaptive thresholding, Optical Character Recognition (OCR), machine translation, and natural language processing to ensure accurate and efficient language conversion. The proposed methodology offers an innovative tool for creating an inclusive and accessible learning environment, enabling real-time language translation and enhancing comprehension, particularly for older adults who may find it difficult to grasp foreign languages. This approach ultimately contributes to breaking down linguistic barriers, fostering cross-cultural understanding, and promoting educational accessibility for diverse populations.**

Keywords— Optical Character Recognition (OCR), Image Processing, Text Extraction, Text-to-Speech Synthesis, Wave2Lip Synchronization, Natural Language Processing (NLP)

I. INTRODUCTION

The rapid advancements in technology have significantly reshaped how information is disseminated and consumed, making it increasingly important to bridge communication gaps in an interconnected, multicultural world. Despite these advances, language barriers continue to pose challenges, particularly for elderly individuals and learners who may struggle with comprehending foreign languages, making it difficult to access valuable educational content. In this context, there is a growing need for systems capable of translating and delivering content in an accessible manner, facilitating seamless interaction across diverse linguistic backgrounds.

This paper introduces an innovative method for overcoming language barriers by integrating image processing, text extraction, translation, and text-to-speech synthesis. The proposed system is designed to capture text from various sources, such as screens, printed materials, or images, and convert this information into synchronized audio that matches the input video. Leveraging advanced techniques like Optical Character Recognition (OCR) and Wave2Lip synchronization, our solution ensures that the spoken output is not only accurate but also in harmony with the original video, thus providing a natural and comprehensible experience.

By employing a multi-stage processing pipeline that incorporates adaptive thresholding, machine translation, and deep learning-based speech synthesis, this system offers a robust means of transforming visual information into auditory content. This enhances accessibility for diverse audiences, particularly older adults and learners, by providing real-time, accurate language translation and synchronization. The proposed methodology aims to foster a more inclusive educational environment, allowing individuals who face linguistic or cognitive challenges to engage with and understand content effectively.

In summary, this paper introduces an innovative and practical solution that addresses the challenges of language comprehension, especially for elderly and educationally disadvantaged populations. By combining state-of-the-art neural networks with traditional image processing techniques, our system contributes to the broader goal of creating an inclusive, technology-driven society where language is no longer a barrier to learning and communication. This novel strategy has high possibilities of improving the accuracy and the speed at which conservation programs are implemented, as it is an effective and flexible for addressing poaching in the world.

II. RELATED WORKS

Recent advancements in gesture recognition have significantly contributed to developing intuitive human-computer interaction systems. Brisinello et al. [1] investigated the effectiveness of different preprocessing techniques to improve the performance of Tesseract Optical Character Recognition (OCR), with particular emphasis on images captured from Set-Top Boxes (STBs), that often-present challenges due to low resolution and poor quality. Their findings indicated that applying specific preprocessing techniques could significantly improve OCR accuracy, particularly in images with complex backgrounds. Md. Abul Hasnat et al. [2] developed an open-source OCR solution for Bangla script, emphasizing the necessity of high-quality input images for optimal recognition results. They reported that images with a resolution of 300% or higher achieved up to 93% accuracy, underscoring the impact of image quality on OCR performance. Furthering this research, Matteo Brisinello et al. [3] introduced a preprocessing method that enhanced Tesseract OCR accuracy in images characterized by colorful backgrounds. By employing a clustering approach and a Naïve Bayes classifier, they achieved a remarkable 95.5% accuracy in identifying text-containing segments. This study highlights the need for automation in locating and cropping text regions to facilitate further improvements.

979-8-3315-1839-4/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: University of New South Wales. Downloaded on October 26,2025 at 17:06:19 UTC from IEEE Xplore. Restrictions apply.

Saurabh Dome et al. [4] explored the creation of a WebApp utilizing Tesseract OCR for converting various types of text within digital images into editable formats. Their project aimed to streamline information extraction from paper documents, significantly reducing manual data entry requirements. Additionally, Sudan Prajapati et al. [5] evaluated the performance of Tesseract OCR in recognizing Nepali script, utilizing a dataset that included various fonts and character samples. They found that while Tesseract demonstrated substantial accuracy during training, Artificial Neural Networks (ANN) outperformed it in testing, indicating the potential for enhanced recognition techniques. Áron Zoltán Kaló et al. [6] developed a key-value pair search system utilizing Tesseract OCR, incorporating post-processing techniques to enhance accuracy. Their research focused on refining the searching process for extracted text, demonstrating a significant advancement in targeted text recognition.

Moreover, Stevan Čakić et al. [7] emphasized the use of Tesseract OCR for serial number recognition on wine labels, a crucial step for food tracking. Their study emphasized the importance of effective image preprocessing in enhancing detection accuracy, suggesting the need for expanded datasets to improve Tesseract's tuning and training capabilities. Meanwhile, Chirag Patel et al. [8] conducted a comparative analysis of Tesseract and commercial OCR tools, identifying Tesseract's strengths in certain applications while acknowledging limitations in others. Chaloupka et al. [9] investigated the implementation of OCR in audio-visual broadcast transcription systems, emphasizing the significance of image pre-processing in reducing word error rates. Their findings indicated substantial improvements in OCR accuracy through carefully designed pre-processing techniques. Lastly, R. Mittal and A. Garg et al. [10] systematically reviewed OCR techniques, emphasizing challenges like noisy data and multilingual text, while highlighting Tesseract's adaptability and advancements in deep learning for improved accuracy.

Triantafyllos Afouras et al. [11] investigate phrase and sentence recognition from a speaking face, addressing both audio and visual aspects. Unlike earlier methods focused on specific words or phrases, this research treats lip reading as an open-world challenge, using unconstrained natural language sentences in real-world videos. The authors evaluate two lip reading models—one based on CTC loss and the other on sequence-to-sequence loss—both built on transformer self-attention architecture. A notable contribution of the study is the LRS2-BBC dataset, featuring thousands of sentences from British television, designed to advance audio-visual speech recognition research. The results show that visual cues significantly boost speech recognition, especially in noisy audio conditions. This research sets new performance benchmarks, demonstrating that integrating audio and visual modalities greatly improves recognition accuracy. Triantafyllos Afouras et al. [12] introduced a deep audio-visual speech enhancement network intended to isolate individual speakers from simultaneous multi-talker speech in videos. Unlike prior studies that concentrate on known speakers in controlled settings, their method utilizes visual data from target speaker's lip movements to predict both the phase of the speech signal and magnitude. This method proves effective in unconstrained settings, successfully isolating the speech of unknown and unseen speakers during training. The authors present substantial quantitative and qualitative results, showcasing the network's ability to generate intelligible speech from difficult, noisy audio segments recorded in real-world scenarios.

Triantafyllos Afouras et al. [13] introduce the LRS3-TED dataset, a innovative multi-source resource aimed at enhancing visual and sound-based speech recognition. This dataset includes facial tracks from more than 400 hours of TED and TEDx videos, along with accompanying subtitles and word alignment markers. Significantly larger in scale than other publicly available datasets, LRS3-TED facilitates supports a range of applications, such as lip reading, video-based speech enhancement and visual-audio speech recognition. The authors highlight its utility for advancing studies in visual-audio learning activities and provide performance benchmarks for recent lip-reading models on this dataset. Lele Chen et al. [14] "Lip Movements Generation at a Glance." University of Rochester, USA. In this paper, the authors address the challenge of generating synthesized lip movements corresponding to arbitrary audio speech. The proposed model aims to retain target identity while ensuring photo-realism, consistency, and smoothness in the generated lip movements. Key advancements feature a unique correlation loss that aligns lip movements with speech variations, allowing for consistent performance across different lip shapes, viewing angles, and facial features. Experimental findings across three datasets, encompassing both controlled lab environments and real-world situations, show substantial enhancements compared to leading methods. Lele Chen et al. [15] introduced a cascade GAN method for creating talking face videos by initially converting audio into facial landmarks and subsequently producing video frames based on those landmarks. This method addresses challenges in audiovisual synchronization and improves video quality through a adaptive pixel-wise loss and a regression-oriented discriminator framework.

III. Proposed Methodology

The proposed system aims to break language barriers by converting text from visual sources into synchronized audio, enabling a more inclusive educational experience, particularly for elderly individuals. The methodology involves several key stages, which are outlined as follows.

A. Image Acquisition and Preprocessing

The first step involves capturing the text from a screen or paper using a camera or pre-existing digital images. To improve the quality and precision of the text extraction process, the captured image is subjected to preprocessing, which involves converting the image to grayscale, removing any unnecessary borders or noise, and applying adaptive thresholding to ensure clearer text regions. These preprocessing techniques help in improving the accuracy of subsequent optical character recognition (OCR).

Authorized licensed use limited to: University of New South Wales. Downloaded on October 26,2025 at 17:06:19 UTC from IEEE Xplore. Restrictions apply.

B. Optical Character Recognition (OCR)

After preprocessing, OCR technology is employed to retrieve textual data from the image . Tesseract OCR, which efficiently converts the processed image into machine-readable text. The system is capable of handling various fonts and sizes, ensuring that the extracted text is accurate, even from complex images. This stage lays the foundation for further translation and audio synthesis by generating the raw textual data from the visual input.




Fig. 1. System Architecture

C. Language Translation

The extracted text is then passed through a translation module, which converts it into the desired target language. The Google Translate API is used for this purpose, allowing for accurate and real-time translation into a wide range of languages. This step is crucial in making the system accessible to elderly users who might be more comfortable with languages other than the original language of the text.

TABLE I. PREPROCESSING TECHNIQUES APPLIED

Preprocessing Technique	Accuracy (%)
No Preprocessing	65.5
Grayscale Conversion	72.3
Gaussian Blur + Thresholding	81.6
Adaptive Thresholding	**93.5**

D. Text-to-Speech (TTS) Synthesis

Once the text has been translated, it is converted into audio format using a Text-to-Speech (TTS) engine like Google Text-to-Speech (gTTS).The TTS system generates high-quality, natural-sounding speech, ensuring that the audio output is clear and comprehensible. This step ensures that users can listen to the translated content, breaking language barriers and enhancing understanding.

E. Video Lip Synchronization

To create an immersive and engaging experience, the synthesized audio is synchronized with the original video input using a technique inspired by Wave2Lip synchronization. This involves aligning the translated speech with the speaker's lip movements in the video, ensuring that the audio matches the visual cues. This step is achieved using Convolutional Neural Networks (CNNs), which analyze and adjust the video frames to create realistic lip synchronization with the generated audio.

IV. IMPLEMENTATION

The implementation of the proposed system involves integrating multiple technologies to achieve accurate text extraction, translation, text-to-speech synthesis, and lip synchronization. Each stage of the process is implemented using appropriate tools and technologies, ensuring efficiency and reliability. The following subsections provide an in-depth explanation of the implementation steps.

A. Image Acquisition and Preprocessing

Tools Used: OpenCV, Python.

Images or video frames are captured using a camera or uploaded by the user through the graphical user interface. Preprocessing is performed using OpenCV functions, where images are converted to grayscale and denoised using Gaussian Blur to enhance text clarity. Adaptive thresholding is applied to improve contrast and make text extraction more efficient.




Fig. 2. Example Photo

Authorized licensed use limited to: University of New South Wales. Downloaded on October 26,2025 at 17:06:19 UTC from IEEE Xplore. Restrictions apply.

B. Optical Character Recognition (OCR)

Tools Used: Tesseract OCR, Python.

Tesseract OCR is incorporated into the system to retrieve text from pre-processed images. The Python wrapper for Tesseract, known as pytesseract, is utilized to manage the text extraction process. The extracted text is stored in a structured format, which serves as input for the translation phase.




Fig. 3. Segmentation of letters in the photo

C. Language Translation

Tools Used: Google Translate API, Python.

The extracted text is passed to the Google Translate API using the googletrans library, which supports multiple languages and provides real-time translation. The system allows users to specify their preferred target language through the interface, and the translated text is then displayed to verify its accuracy before converting it to speech.

D. Text-to-Speech (TTS) Synthesis

Tools Used: Google Text-to-Speech (gTTS), Python.

The translated text is transformed into audio using the gTTS library, which produces a natural-sounding speech file in .mp3 format. The speech synthesis process is efficient, providing clear and high-quality audio output. The system ensures that the generated speech matches the intonation and rhythm of human speech, making it easier for elderly users to understand.

E. Video Lip Synchronization

Tools Used: Wave2Lip, PyTorch, Convolutional Neural Networks (CNNs).

Lip synchronization is achieved using the Wave2Lip model, which utilizes pre-trained CNNs to align the synthesized audio with the speaker's lip movements in the video. The audio and video synchronization process involves analysing each frame of the video, generating synchronized frames that match the audio cues, and rendering a final video output. The Wave2Lip model is integrated using PyTorch, and it is fine-tuned to handle variations in lip movements and facial expressions for different languages.

V. Results and Discussion

In order to evaluate the performance of the system, a series of experiments is conducted using a variety of video and text sources. The evaluation metrics focused on the accuracy of OCR, the quality of the translation, the naturalness of the text-to-speech synthesis, and the effectiveness of the lip synchronization. The system is tested with different languages, image resolutions, and video formats to ensure robustness and adaptability.




Fig. 4. Final output of processed video with synchronized voice

A. OCR Accuracy

This system's OCR accuracy was evaluated using images with varying levels of complexity, including different fonts, sizes, and image quality. The results showed that applying preprocessing techniques like adaptive thresholding and noise reduction significantly improved the OCR accuracy, reaching an average of 92% on clean images and 85% on noisy images.

$$OCR\ Accuracy = \frac{Number\ of\ Correctly\ Recognized\ Images}{Total\ Number\ of\ Characters\ in\ the\ Image} \times 100 \quad (1)$$

B. Translation Quality

The translation quality was assessed by comparing the output of the Google Translate API with human translations. The system performed well across multiple languages, particularly for common language pairs, with an accuracy

Authorized licensed use limited to: University of New South Wales. Downloaded on October 26,2025 at 17:06:19 UTC from IEEE Xplore. Restrictions apply.

TABLE II. PERFORMANCE EVALUATION OF PROPOSED SYSTEM

Process Stage	Tools	Accuracy (%)	Processing Time (ms)	Success Rate (%)
Image Acquisition & Preprocessing	OpenCV, Python	95	150	98
Optical Character Recognition (OCR)	Tesseract OCR, Python	92	120	94
Language Translation	Google Translate API	90	300	93
Text-to-Speech (TTS) Synthesis	Google TTS, Python	92	200	97
VideoLip Synchronization	Wave2Lip, CNNs	96	400	91
Overall System	Complete Process Pipeline	**92**	**1170**	**95**

score of 88% based on human evaluations. Translation quality can be evaluated using the BLEU (Bilingual Evaluation Understudy) score or human evaluation. In this case, human evaluators rated translation accuracy.

$$TQ = \frac{Number\ of\ Corrected\ Translation\ by\ Human\ Eval.}{Total\ Number\ of\ Translation} \times 100 \quad (2)$$

C. Text-to-Speech Naturalness

The naturalness of the synthesized speech was evaluated using a Mean Opinion Score (MOS) test, where participants rated the quality of the audio. The gTTS engine achieved an average score of 4.3 out of 5, indicating that the speech was clear, natural-sounding, and easy to understand.

$$MOS = \frac{\sum_{i=1}^{N} Participants\ Score}{N} \quad (3)$$

D. Lip Synchronization

The quality of lip synchronization was evaluated using a combination of subjective visual assessments and quantitative metrics. The Wave2Lip model was able to achieve a near-perfect synchronization score of 96%, providing a seamless viewing experience where the translated audio aligned accurately with the speaker's lip movements.

$$Lip\ Sync\ Accuracy = \frac{Correctly\ Aligned\ Frames}{Total\ Number\ of\ Frames} \times 100 \quad (4)$$

VI. CONCLUSION

In this paper, a comprehensive novelty approach is designed to break language barriers and enhance educational experiences for elderly individuals and non-native speakers. This approach effectively integrates sophisticated image processing, Optical Character Recognition (OCR), language translation, text-to-speech synthesis, and lip synchronization. The proposed system showcases a multi-stage processing pipeline with accuracy of 92% that captures text from visual sources and converts it into synchronized audio, ensuring that the generated speech aligns accurately with the speaker's lip movements. By leveraging by employing deep learning methods, especially Convolutional Neural Networks (CNNs), to significantly enhanced the realism of the generated speech., creating a natural and immersive user experience. The results demonstrate that the integration of adaptive thresholding for image preprocessing, the robust capabilities of Tesseract OCR for text extraction, and the Google Translate API for real-time translation, combined with high-quality audio generation through the Google Text-to-Speech engine, allows for seamless content comprehension across different languages. This functionality is particularly crucial for elderly users who may face challenges in understanding complex materials presented in unfamiliar languages. Moreover, the application of Wave2Lip synchronization techniques ensures that the audio output is not only clear and comprehensible but also synchronized with visual cues, enhancing the overall learning experience. This synchronization process contributes to the effective communication of ideas, making educational content more accessible and engaging.

In conclusion, the proposed system represents a significant step toward fostering inclusivity in education by providing real-time, accurate language translation and synchronization. By leveraging deep learning and sophisticated multimedia processing, was to create a more inclusive educational environment that empowers diverse audiences to engage with and comprehend information without the constraints of language barriers.

VII. FUTURE WORK

The current system demonstrates significant advancements in lip synchronization and language translation, several areas remain for future exploration and enhancement. The study aims to explore the use of more sophisticated machine learning models, including Transformer-based architectures, to improve the accuracy of text recognition and translation, which could lead to a more

Authorized licensed use limited to: University of New South Wales. Downloaded on October 26,2025 at 17:06:19 UTC from IEEE Xplore. Restrictions apply.

nuanced understanding of context. Additionally, expanding the system's capabilities to support a broader range of languages and dialects, particularly those with less representation in current datasets, will cater to a more diverse user base. To achieve even more realistic and expressive lip movements, exploring alternative methods for lip synchronization that account for coarticulation effects and speaker variations is essential. Furthermore, developing optimizations for real-time processing will enable live translation and synchronization during educational sessions, minimizing latency and effectively handling dynamic content. Implementing adaptive learning algorithms to personalize content delivery based on user preferences and comprehension levels will enhance engagement, especially for elderly learners. Incorporating additional modalities, such as visual aids or gestures, can create a multi-sensory approach that enhances understanding and retention. Exploring the application of this technology beyond education, such as in telemedicine or virtual conferences, can facilitate effective communication across languages in various contexts.

REFERENCES

[1] Brisinello, Matteo, Ratko Grbić, Matija Pul, and Tihomir Anđelić. "Improving optical character recognition performance for low quality images." In 2017 International Symposium ELMAR, pp. 167-171. IEEE, 2017.

[2] Hasnat, Md Abul, Muttakinur Rahman Chowdhury, and Mumit Khan. "An open source tesseract based optical character recognizer for bangla script." In 2009 10th international conference on document analysis and recognition, pp. 671-675. IEEE, 2009

[3] Brisinello, Matteo, Ratko Grbić, Dejan Stefanovič, and Robert Pečkai-Kovač. "Optical Character Recognition on images with colorful background." In 2018 IEEE 8th International Conference on Consumer Electronics-Berlin (ICCE-Berlin), pp. 1-6. IEEE, 2018

[4] [4] Dome, Saurabh, and Asha P. Sathe. "Optical charater recognition using tesseract and classification." In 2021 International Conference on Emerging Smart Computing and Informatics (ESCI), pp. 153-158. IEEE, 2021.

[5] Prajapati, Sudan, Shashidhar Ram Joshi, Aman Maharjan, and Bikash Balami. "Evaluating performance of Nepali script OCR using Tesseract and artificial neural network." In 2018 IEEE 3rd International Conference on Computing, Communication and Security (ICCCS), pp. 104-107. IEEE, 2018.

[6] Kaló, Áron Zoltán, and Miklós László Sipos. "Key-Value Pair Searhing System via Tesseract OCR and Post Processing." In 2021 IEEE 19th World Symposium on Applied Machine Intelligence and Informatics (SAMI), pp. 000461-000464. IEEE, 2021.

[7] Čakić, Stevan, Tomo Popović, Stevan Šandi, Srđan Krčo, and Anita Gazivoda. "The use of tesseract ocr number recognition for food tracking and tracing." In 2020 24th International Conference on Information Technology (IT), pp. 1-4. IEEE, 2020.

[8] Patel, Chirag, Atul Patel, and Dharmendra Patel. "Optical character recognition by open source OCR tool tesseract: A case study." International journal of computer applications 55, no. 10 (2012): 50-56.

[9] Chaloupka, Josef, Karel Paleček, Petr Červa, and Jindřich Žďánský. "Optical character recognition for audio-visual broadcast transcription system." In 2020 11th IEEE International Conference on Cognitive Infocommunications (CogInfoCom), pp. 000229-000232. IEEE, 2020.

[10] R. Mittal and A. Garg, (2020) "Text extraction using OCR: A Systematic Review," 2020 Second International Conference on Inventive Research in Computing Applications (ICIRCA), Coimbatore, India, 2020, pp. 357-362, doi: 10.1109/ICIRCA48905.2020.9183326

[11] T. Afouras, J. S. Chung, A. Senior, O. Vinyals, and A. Zisserman. 2018. Deep Audio-Visual Speech Recognition. In arXiv:1809.02108.

[12] T. Afouras, J. S. Chung, and A. Zisserman. 2018. The Conversation: Deep Audio Visual Speech Enhancement. In INTERSPEECH.

[13] Triantafyllos Afouras, Joon Son Chung, and Andrew Zisserman. 2018. LRS3-TED: a large-scale dataset for visual speech recognition. arXiv preprint arXiv:1809.00496 (2018).

[14] Lele Chen, Zhiheng Li, Ross K Maddox, Zhiyao Duan, and Chenliang Xu. 2018. Lip movements generation at a glance. In Proceedings of the European Conference on Computer Vision (ECCV). 520–535

[15] Lele Chen, Ross K Maddox, Zhiyao Duan, and Chenliang Xu. 2019. Hierarchical cross-modal talking face generation with dynamic pixel-wise loss. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition. 7832–7841.

Authorized licensed use limited to: University of New South Wales. Downloaded on October 26,2025 at 17:06:19 UTC from IEEE Xplore. Restrictions apply.