

mini project 3

ResNet 모델을 전이학습으로 하는 방법을 사용하여, 현업에서 분류가 필요한 영상들을 학습 데이터로 하여 모델을 학습시키기

산업인공지능학과

2020254018

강 윤 구

1. 실습 프로그램#1 (google drive에 Hardware_data를 만들어 사진 파일 사용)

```
%matplotlib inline
from __future__ import print_function, division

import torch
import torch.nn as nn
import torch.optim as optim
from torch.optim import lr_scheduler
import numpy as np
import torchvision
from torchvision import datasets, models, transforms
import matplotlib.pyplot as plt
import time
import os
import copy
plt.ion() #interactive mode

from google.colab import drive
drive.mount('/content/gdrive')

data_transforms = {
    'train': transforms.Compose([
        transforms.RandomResizedCrop(224),
        transforms.RandomHorizontalFlip(),
        transforms.ToTensor(),
        transforms.Normalize([0.485, 0.456, 0.406], [0.229, 0.224, 0.225])
    ]),
    'val': transforms.Compose([
        transforms.Resize(256),
        transforms.CenterCrop(224),
        transforms.ToTensor(),
        transforms.Normalize([0.485, 0.456, 0.406], [0.229, 0.224, 0.225])
    ]),
}

data_dir = '/content/gdrive/MyDrive/Hardware_data'
image_datasets = {x: datasets.ImageFolder(os.path.join(data_dir, x), data_transforms[x]) for x in ['train', 'val']}
dataloaders = {x: torch.utils.data.DataLoader(image_datasets[x], batch_size=4, shuffle=True,
                                              num_workers=4) for x in ['train', 'val']}

dataset_sizes = {x: len(image_datasets[x]) for x in ['train', 'val']}
class_names = image_datasets['train'].classes
device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")

def imshow(inp, title=None):
    inp = inp.numpy().transpose((1, 2, 0))
    mean = np.array([0.485, 0.456, 0.406])
    std = np.array([0.229, 0.224, 0.225])
    inp = std * inp + mean
    inp = np.clip(inp, 0, 1)
    plt.imshow(inp)
    if title is not None:
        plt.title(title)
    plt.pause(0.001)
```

```
inputs, classes = next(iter(dataloaders['train']))
out = torchvision.utils.make_grid(inputs)

imshow(out, title=[class_names[x] for x in classes])

def train_model(model, criterion, optimizer, scheduler, num_epochs = 25):
    since = time.time()
    best_model_wts = copy.deepcopy(model.state_dict())
    best_acc = 0.0

    for epoch in range(num_epochs):
        print('Epoch {}/{}'.format(epoch, num_epochs - 1))
        print('-' * 10)
        for phase in ['train', 'val']:
            if phase == 'train':
                scheduler.step()
                model.train()
            else:
                model.eval()
            running_loss = 0.0
            running_corrects = 0
            for inputs, labels in dataloaders[phase]:
                inputs = inputs.to(device)
                labels = labels.to(device)
                optimizer.zero_grad()
                with torch.set_grad_enabled(phase == 'train'):
                    outputs = model(inputs)
                    _, preds = torch.max(outputs, 1)
                    loss = criterion(outputs, labels)
                    if phase == 'train':
                        loss.backward()
                        optimizer.step()
                running_loss += loss.item() * inputs.size(0)
                running_corrects += torch.sum(preds == labels.data)
            epoch_loss = running_loss / dataset_sizes[phase]
            epoch_acc = running_corrects.double() / dataset_sizes[phase]
            print('{} Loss: {:.4f} Acc: {:.4f}'.format(phase, epoch_loss, epoch_acc))
            if phase == 'val' and epoch_acc > best_acc:
                best_acc = epoch_acc
                best_model_wts = copy.deepcopy(model.state_dict())
        print()


    time_elapsed = time.time() - since
    print('Training complete in {:.0f}m {:.0f}s'.format(time_elapsed // 60, time_elapsed % 60))
    print('Best val Acc: {:.4f}'.format(best_acc))
    model.load_state_dict(best_model_wts)
    return model

def visualize_model(model, num_images=6):
    was_training = model.training
    model.eval()
    images_so_far = 0
    fig = plt.figure()
```

2. 결과#1

Mounted at /content/gdrive

/usr/local/lib/python3.7/dist-packages/torch/utils/data/dataloader.py:477: UserWarning: This cpuset_checked))



Downloading: "<https://download.pytorch.org/models/resnet18-5c106cde.pth>" to /root/.cache/torch/models-44.7M/44.7M [01:16<00:00, 610kB/s]

Epoch 0/24

/usr/local/lib/python3.7/dist-packages/torch/optim/lr_scheduler.py:134: UserWarning: Detect "<https://pytorch.org/docs/stable/optim.html#how-to-adjust-learning-rate>", UserWarning)
train Loss: 0.6700 Acc: 0.6667
val Loss: 0.2687 Acc: 0.9000

Epoch 1/24

train Loss: 0.7136 Acc: 0.7595
val Loss: 0.7407 Acc: 0.7167

Epoch 2/24

train Loss: 0.5706 Acc: 0.7975
val Loss: 0.1723 Acc: 0.9167

⋮

Epoch 23/24

train Loss: 0.2727 Acc: 0.8987
val Loss: 0.1258 Acc: 0.9833

Epoch 24/24

train Loss: 0.2376 Acc: 0.8861
val Loss: 0.1918 Acc: 0.8667

Training complete in 1m 5s
Best val Acc: 0.983333

```
with torch.no_grad():
    for i, (inputs, labels) in enumerate(dataloaders['val']):
        inputs = inputs.to(device)
        labels = labels.to(device)

        outputs = model(inputs)
        _, preds = torch.max(outputs, 1)

        for j in range(inputs.size()[0]):
            images_so_far += 1
            ax = plt.subplot(num_images//2, 2, images_so_far)
            ax.axis('off')
            ax.set_title('predicted: {}'.format(class_names[preds[j]]))
            imshow(inputs.cpu().data[j])

        if images_so_far == num_images:
            model.train(mode=was_training)
            return
        model.train(mode=was_training)

model_ft = models.resnet18(pretrained=True) #사전 학습된 ResNet18 가져오기
num_fts = model_ft.fc.in_features #모델에서 feature extraction 후 FC 층에 입력되는 특징수
model_ft.fc = nn.Linear(num_fts, 2)

model_ft = model_ft.to(device) # cpu나 GPU에 model_ft를 할당
criterion = nn.CrossEntropyLoss()

#모든 파라미터를 학습
optimizer_ft = optim.SGD(model_ft.parameters(), lr=0.001, momentum=0.9)

#매 7 에포크 마다 학습률 0.1배 감소
exp_lr_scheduler = lr_scheduler.StepLR(optimizer_ft, step_size=7, gamma=0.1)
model_ft = train_model(model_ft, criterion, optimizer_ft, exp_lr_scheduler, num_epochs=25)

visualize_model(model_ft)
```

predicted: server



predicted: server



predicted: server



predicted: switch



predicted: switch



predicted: switch



3. 실습 프로그램#2

```
model_conv = torchvision.models.resnet18(pretrained=True)
for param in model_conv.parameters():
    param.requires_grad = False #사전 학습된 모델의 가중치를 상수로 고정. 학습시키지 않음

#새로 생성된 모듈의 파라미터는 기본적으로 requires_grad=True
num_ftrs = model_conv.fc.in_features
model_conv.fc = nn.Linear(num_ftrs, 2)

model_conv = model_conv.to(device)
criterion = nn.CrossEntropyLoss()

#마지막 층의 파라미터만 학습
optimizer_conv = optim.SGD(model_conv.fc.parameters(), lr=0.001, momentum=0.9)

exp_lr_scheduler = lr_scheduler.StepLR(optimizer_conv, step_size=7, gamma=0.1)
model_conv = train_model(model_conv, criterion, optimizer_conv, exp_lr_scheduler, num_epochs=25)

visualize_model(model_conv)

plt.ioff()
plt.show()
```

실행내역

<https://github.com/Yunkoo-GIT/Programming/blob/main/20210526.ipynb>

4. 결과#2

Epoch 24/24

train Loss: 0.3532 Acc: 0.8523
val Loss: 0.5054 Acc: 0.7667

Training complete in 0m 41s
Best val Acc: 0.816667

predicted: server



predicted: server



predicted: switch



predicted: server



predicted: switch



predicted: switch

