

1711.06025 - Learning to Compare: Relation Network for Few-Shot Learning

- **Yunqiu Xu**
 - Related reading:
 - 1706.09529 Learning to Learn: Meta-Critic Networks for Sample Efficient Learning
 - 1710.03463 - Learning to Generalize: Meta-Learning for Domain Generalization
 - Brief introduction:
 - Meta learning for few-shot classification
 - What to meta learn: embedding, as well as distance metric to measure similarity
-

1. Introduction

- Challenges for few-shot learning:
 - Complex inference mechanisms
 - Complex RNN
 - Fine tuning the target problem :
 - 这里例子是 MAML 和 Larochelle 的 LSTM-based meta learner, 注意对比下
 - 说他们的缺点是fine-tuning可能不够快?
- Our method:
 - Similar to train an metric: 区别是他们着重于训练transferrable embedding, 但 metric是固定的(e.g. 欧式距离), 而我们把metric也作为学习目标之一
 - Two-branch Relation Network:
 - Embedding module: generate representations (embedding) of the query and training images
 - Relation module: compare embedding pairs to check whether they are from matching classes or not
 - 之前的工作固定了metric, 而且是linear comparator, 这里我们学习非线性的

2. Related Work

- **Learning to Fine-Tune, 这里作者举了两个例子:**
 - MAML, LSTM-based learner: 这里说这份工作强于MAML, 因为不仅仅训练了初始化参数, 还训练了优化器 → 这样效率更低吧?
 - 这两个工作的缺点: fine-tune on the target problem
 - 我们的工作不需要model updates, 就直接feed forward就行
- **RNN Memory based, 我之前看过ICML2017上的meta network:**
 - RNN: knowledge is accumulated in hidden activations/external memory to solve the problem
 - Drawback: 需要保证memory存储了所有或至少是long term的历史信息而没有遗忘, 一方面不容易得到所有信息, 另一方面会占用很大空间
 - 我们的工作使用feed forward CNN, 避免了RNN
- **Embedding and Metric Learning**
 - Embedding: parameterise the weights of feed-forward classifier, 这里meta学得了是参数化网络, 给定样本集合, 试图参数化一个分类器
 - Metric learning: learn distance evaluation metric, 这里meta学得了是量度
 - 相关工作: prototypical network, siamese network, 重点在学习embedding, 而分类则直接用KNN或者线性分类器量度相似性
 - 我们的工作不固定metric, 而是把metric也当成一个学习目标, 且不限制为线性, 试图学习非线性的分类器
 - 和siamese network相比, 为episodic training strategy
 - 和prototypical network相比, 避免了复杂的RNN embedding
- **Zero-Shot Learning: 这里先略过**

3. Methodology

3.1 Problem definition

- Goal: few-shot classification, recall C-way K-shot is C classes, and K samples for each class
- For each training iteration, sample C classes from train set with K samples for each

class \rightarrow Sample set $\mathcal{S} = \{(x_i, y_i)\}_{i=1}^{K \times C}$

3.2 Model

- 这里先只考虑one-shot, zero-shot 先略过
- Relation Network:
 - Embedding module f_ψ : input images, output feature map
 - Combine (concat) feature map of sample pair
 - Relation module g_ϕ : input concatenated feature map, output similarity between these two samples
- C-way 1-shot: 分辨当前样本 x_j 与每一类的样本 x_i 的相似度 $r_{i,j}$
$$r_{i,j} = g_\phi(C(f_\psi(x_i), f_\psi(x_j))), i = 1, 2, \dots, C$$




Figure 1: Relation Network architecture with a 5-way 1-shot 1-query example.

3.3 Network Architecture

- Naive Network有点像VGG, Deeper有点像ResNet




Figure 2: Relation Network architecture for few-shot learning: (b) naive version, (d) deeper version. Relation Network architecture for (e) zero-shot learning. These are composed of elements including (a) convolutional block, and (b) bottleneck block.

4. Experiment

- 还是经典的Omniglot和MiniImageNet

Model	Fine Tune	5-way Acc.		20-way Acc.	
		1-shot	5-shot	1-shot	5-shot
MANN [31]	N	82.8%	94.9%	-	-
CONVOLUTIONAL SIAMESE NETS [18]	N	96.7%	98.4%	88.0%	96.5%
CONVOLUTIONAL SIAMESE NETS [18]	Y	97.3%	98.4%	88.1%	97.0%
MATCHING NETS [38]	N	98.1%	98.9%	93.8%	98.5%
MATCHING NETS [38]	Y	97.9%	98.7%	93.5%	98.7%
SIAMESE NETS WITH MEMORY [16]	N	98.4%	99.6%	95.0%	98.6%
NEURAL STATISTICIAN [8]	N	98.1%	99.5%	93.2%	98.1%
META NETS [26]	N	99.0%	-	97.0%	-
PROTOTYPICAL NETS [35]	N	98.8%	99.7%	96.0%	98.9%
MAML [10]	Y	98.7 \pm 0.4%	99.9 \pm 0.1%	95.8 \pm 0.3%	98.9 \pm 0.2%
RELATION NET	N	99.6 \pm 0.2%	99.8 \pm 0.1%	97.6 \pm 0.2%	99.1 \pm 0.1%

Table 1: Omniglot few-shot classification. Results are accuracies averaged over 1000 test episodes and with 95% confidence intervals where reported. The best-performing method is highlighted, along with others whose confidence intervals overlap. ‘-’: not reported.

Model	FT	5-way Acc.	
		1-shot	5-shot
MATCHING NETS [38]	N	43.56 \pm 0.84%	55.31 \pm 0.73%
META NETS [26]	N	49.21 \pm 0.96%	-
META-LEARN LSTM [28]	N	43.44 \pm 0.77%	60.60 \pm 0.71%
MAML [10]	Y	48.70 \pm 1.84%	63.11 \pm 0.92%
PROTOTYPICAL NETS [35]	N	49.42 \pm 0.78%	68.20 \pm 0.66%
RELATION NET (NAIVE)	N	51.38 \pm 0.82%	67.07 \pm 0.69%
TCML [25]	N	55.71 \pm 0.99%	68.88 \pm 0.92%
RELATION NET (DEEPER)	N	57.02 \pm 0.92%	71.07 \pm 0.69%

Table 2: Few-shot classification accuracies on *mini*Imagenet. All accuracy results are averaged over 600 test episodes and are reported with 95% confidence intervals, same as [35]. For each task, the best-performing method is highlighted, along with any others whose confidence intervals overlap. ‘-’: not reported.

5. Why does it work?

- 前人的工作:
 - pre-specified metric(e.g. 基于欧式距离), 学习feature embedding, 而metric是固定的
 - Conventional metric learning: 学习简单的曼哈顿metric, 固定feature representation
- 我们的工作: 同时学习embedding, non-linear metric (相似度方程)
- 为什么我们的工作重要:
 - 我们自己学习选择合适的metric而不是手动指定
 - 前人工作固定metric, 需要假定特征可以被element-wise比较, 且假定在embedding后是线性可分的. 因此就非常依赖学到的embedding network, 如果这个网络生成的embedding不足以表达特征, 就傻逼了

- 而我们的工作同时学习非线性的相似度度量以及embedding, 可以更好地区分匹配/不匹配样本对

6. Summary

- 对比前人的工作, 本工作把metric也作为学习的目标, 相当于让模型根据任务选择相似度度量咯
- 感觉创新性一般, 不过可以看下其思路, 现在网上也有相关实现可以学习下