

Analysis report examination with CUBE

Brian Wylie

Julich Supercomputing Centre



























CUBE




- Parallel program analysis report exploration tools
 - Libraries for XML report reading & writing
 - Algebra utilities for report processing
 - GUI for interactive analysis exploration
 - requires Qt4
- Originally developed as part of Scalasca toolset
- Now available as a separate component
 - Can be installed independently of Score-P, e.g., on laptop or desktop
 - Latest release: CUBE 4.1.6 (March 2013)

Analysis presentation and exploration




- Representation of values (severity matrix) on three hierarchical axes
 - Performance property (metric)
 - Call-tree path (program location)
 - System location (process/thread)



- Three coupled tree browsers
- CUBE displays severities
 - As value: for precise comparison
 - As colour: for easy identification of hotspots
 - Inclusive value when closed & exclusive value when expanded
 - Customizable via display mode


Analysis presentation






Analysis report exploration (opening view)






Metric selection






Expanding the system tree






Expanding the call tree








- Inclusive
 - Information of all sub-elements aggregated into single value
- Exclusive
 - Information cannot be subdivided further




Selecting a call path





Source-code view via context menu






Source-code view



/home/geimer/Projects/Tests/NPB3.3-MZ-MPI/BT-MZ/solve_subs.f ×				
cc	ns,c,r)	- - -		
implicit none double precision pivot, dimension lhs(5,5) double precision c(5,5) c pivot = 1.00d0/lhs(1,1) lhs(1,2) = lhs(1,2)*pivot lhs(1,3) = lhs(1,3)*pivot lhs(1,5) = lhs(1,5)*pivot c(1,1) = c(1,1)*pivot c(1,2) = c(1,2)*pivot c(1,3) = c(1,3)*pivot c(1,4) = c(1,4)*pivot), r(5) ot ot ot	-		
Read only	Save	Save as	Font	Close


Flat profile view






Box plot view





Alternative display modes






Important display modes



- Absolute
 - Absolute value shown in seconds/bytes/occurances
- Selection percent
 - Value shown as percentage of the value of the selected node
 "on the left" (metric/call path)
- Peer percent (system tree only)
 - Value shown as percentage relative to the maximum peer value


Multiple selection





Context-sensitive help







Extracting solver sub-tree from analysis report

```
% cube_cut -r '<<SMG.Solve>>' scorep_smg2000/profile.cubex
Writing cut.cubex... done.
```

Calculating difference of two reports

```
% cube_diff scorep_smg2000/profile.cubex cut.cubex Writing diff.cubex... done.
```

- Additional utilities for merging, calculating mean, etc.
 - Default output of cube_utility is a new report utility.cubex
- Further utilities for report scoring & statistics
- Run utility with "-h" (or no arguments) for brief usage info

Further information



CUBE

- Parallel program analysis report exploration tools
 - Libraries for XML report reading & writing
 - Algebra utilities for report processing
 - GUI for interactive analysis exploration
- Available under New BSD open-source license
- Documentation & Sources:
 - http://www.score-p.org
- User guide also part of installation:
 - `cube-config --cube-dir`/share/doc/CubeGuide.pdf
- Contact:
 - mailto: scalasca@fz-juelich.de

