

Description:

Develop a game scene with one object on screen. At the start of each round, an image is loaded asynchronously via Addressables and applied to the object as its texture. A UI text shows the current status ("Loading..." or "Tap the object!").

The player taps the object:

- If the tap hits the object, that's a correct selection. A new image is downloaded and applied to the object, starting the next round, and the status text updates.
- If the tap misses the object (taps empty space), that's an incorrect selection. The object keeps its current image, and an error indicator is shown.

Technical Requirements:**1. Target Object:**

- Spawn 1 object (sphere or cube), loaded from an Addressable prefab, on the scene at the start of the game.
- The object's texture is loaded via Addressables at runtime; loading must be asynchronous (async/await) and must not block the main thread. The expected baseline implementation runs Addressables in local emulation mode (e.g. Simulate Groups / Use Existing Build). Addressables abstract the underlying transport, so what we evaluate here is correct async handling and the Addressables lifecycle.
- If the download fails, an Addressable fallback texture is applied instead so the object is never left without an image.
- If the selection is incorrect, show a negative visual effect (e.g., the object flashes red) or a text message is displayed.

2. Addressables:

- The target object prefab and the fallback texture are both loaded via Addressables, each loaded once at startup and released on teardown.

3. (Optional, recommended) Real network delivery:

- In addition to — or instead of — local emulation, host the built Addressables catalog & bundles yourself and serve them over HTTPS (a simple static host or your own lightweight endpoint is fine), then point the Addressables remote load path at it.

4. User Interface (UI):

- Add a UI element (Text) that shows the current status (e.g. "Loading image...", "Tap the object!").
- Add a UI element showing the score, incremented on each correct tap.
- After each correct selection, a new image is requested and the status text updates accordingly.

5. Selection Algorithm:

- The player should be able to tap the object. If the tap hits the object, a new image is downloaded and applied.
- If the tap misses the object, a negative effect is shown, but the image remains unchanged. • If a new round starts before a previous download finishes, the previous download is cancelled so it cannot overwrite a newer result.

Evaluation:

The task will be evaluated based on:

- Correct implementation of all the points.
- Correct, non-blocking use of async/await for the asynchronous Addressables load.
- Correct Addressables usage and lifecycle (load once, release on teardown).
- Code quality and cleanliness.