

ShellSort

ShellSort is mainly a variation of **Insertion Sort**. In insertion sort, we move elements only one position ahead. When an element has to be moved far ahead, many movements are involved. The idea of **shellSort** is to allow exchange of far items. In **shellSort**, we make the array h-sorted for a large value of h. We keep reducing the value of h until it becomes 1. An array is said to be h-sorted if all sublists of every h'th element is sorted.

3

Following is C++ implementation of **ShellSort**.

C++

```
// C++ implementation of Shell Sort
#include <iostream>
using namespace std;

/* function to sort arr using <a href="#">shellSort</a> */
int <a href="#">shellSort</a>(int arr[], int n)
{
    // Start with a big gap, then reduce the gap
    for (int gap = n/2; gap > 0; gap /= 2)
    {
        // Do a gapped insertion sort for this gap size.
        // The first gap elements a[0..gap-1] are already in gapped order
        // keep adding one more element until the entire array is
        // gap sorted
        for (int i = gap; i < n; i += 1)
        {
            // add a[i] to the elements that have been gap sorted
            // save a[i] in temp and make a hole at position i
            int temp = arr[i];

            // shift earlier gap-sorted elements up until the correct
            // location for a[i] is found
            int j;
            for (j = i; j >= gap && arr[j - gap] > temp; j -= gap)
                arr[j] = arr[j - gap];

            // put temp (the original a[i]) in its correct location
            arr[j] = temp;
        }
    }
    return 0;
}

void printArray(int arr[], int n)
{

```

```

    for (int i=0; i<n; i++)
        cout << arr[i] << " ";
}

int main()
{
    int arr[] = {12, 34, 54, 2, 3}, i;
    int n = sizeof(arr)/sizeof(arr[0]);

    cout << "Array before sorting: \n";
    printArray(arr, n);

    <a href="#">shellSort</a>(arr, n);

    cout << "\nArray after sorting: \n";
    printArray(arr, n);

    return 0;
}

```

[Run on IDE](#)

```

// Java implementation of <a href="#">ShellSort</a>
class <a href="#">ShellSort</a>
{
    /* An utility function to print array of size n*/
    static void printArray(int arr[])
    {
        int n = arr.length;
        for (int i=0; i<n; ++i)
            System.out.print(arr[i] + " ");
        System.out.println();
    }

    /* function to sort arr using <a href="#">shellSort</a> */
    int sort(int arr[])
    {
        int n = arr.length;

        // Start with a big gap, then reduce the gap
        for (int gap = n/2; gap > 0; gap /= 2)
        {
            // Do a gapped insertion sort for this gap size.
            // The first gap elements a[0..gap-1] are already
            // in gapped order keep adding one more element
            // until the entire array is gap sorted
            for (int i = gap; i < n; i += 1)
            {
                // add a[i] to the elements that have been gap
                // sorted save a[i] in temp and make a hole at
                // position i
                int temp = arr[i];

                // shift earlier gap-sorted elements up until
                // the correct location for a[i] is found
                int j;
                for (j = i; j >= gap && arr[j - gap] > temp; j -= gap)
                    arr[j] = arr[j - gap];

                // put temp (the original a[i]) in its correct
                // location
                arr[j] = temp;
            }
        }
        return 0;
    }
}

// Driver method
public static void main(String args[])

```

```

{
    int arr[] = {12, 34, 54, 2, 3};
    System.out.println("Array before sorting");
    printArray(arr);

    <a href="#">ShellSort</a> ob = new <a href="#">ShellSort</a>();
    ob.sort(arr);

    System.out.println("Array after sorting");
    printArray(arr);
}
}
/*This code is contributed by Rajat Mishra */

```

Run on IDE

Python

Python program for implementation of Shell Sort

```

def <a href="#">shellSort</a>(arr):

    # Start with a big gap, then reduce the gap
    n = len(arr)
    gap = n/2

    # Do a gapped insertion sort for this gap size.
    # The first gap elements a[0..gap-1] are already in gapped
    # order keep adding one more element until the entire array
    # is gap sorted
    while gap > 0:

        for i in range(gap,n):

            # add a[i] to the elements that have been gap sorted
            # save a[i] in temp and make a hole at position i
            temp = arr[i]

            # shift earlier gap-sorted elements up until the correct
            # location for a[i] is found
            j = i
            while j >= gap and arr[j-gap] > temp:
                arr[j] = arr[j-gap]
                j -= gap

            # put temp (the original a[i]) in its correct location
            arr[j] = temp
        gap /= 2

```

Driver code to test above

```
arr = [ 12, 34, 54, 2, 3]
```

```

n = len(arr)
print ("Array before sorting:")
for i in range(n):
    print(arr[i]),

```

```
<a href="#">shellSort</a>(arr)
```

```

print ("\nArray after sorting:")
for i in range(n):
    print(arr[i]),

```

This code is contributed by Mohit Kumra

Run on



Output:


```
Array before sorting:  
12 34 54 2 3  
Array after sorting:  
2 3 12 34 54
```

Time Complexity: Time complexity of above implementation of **shellsort** is $O(n^2)$. In the above implementation gap is reduce by half in every iteration. There are many other ways to reduce gap which lead to better time complexity. See [this](#) for more details.

References:

<https://www.youtube.com/watch?v=pGhazjsFW28>

<http://en.wikipedia.org/wiki/Shellsort>

**Snapshots:**

12	34	54	2	3
----	----	----	---	---



Temp

Start with gap = $n/2$ (2 in this case)

One by one select elements to the right of gap and place them at their appropriate position.

12	34		2	3
----	----	--	---	---




Temp

Elements left of 54 are already smaller, so no change.


One by one select elements to the right of gap and place them at their appropriate position.





2
Temp

Compare 2 with $\text{arr}[3-2] = 34$ and shift it to $\text{arr}[\text{gap}+1 = 3]$.



2
Temp

Compare 2 with $\text{arr}[3-2] = 34$ and shift it to $\text{arr}[\text{gap}+1 = 3]$.



3		12	34	54
---	--	----	----	----

2

Temp

Since $3 > 2$

Now gap reduces to $1(n/4)$.

Select all elements starting from `arr[1]` and compare them with elements within the distance of gap.

2	3	12	34	54
---	---	----	----	----

Now gap reduces to 0

Sorting stops and array is sorted.

Quiz on Shell Sort

Other Sorting Algorithms on [GeeksforGeeks/GeeksQuiz](#):

- [Selection Sort](#)
- [Bubble Sort](#)
- [Insertion Sort](#)
- [Merge Sort](#)
- [Heap Sort](#)
- [QuickSort](#)



- Radix Sort
- Counting Sort
- Bucket Sort

Coding practice for sorting.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

GATE CS Corner Company Wise Coding Practice

Sorting

[Login to Improve this Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Recommended Posts:

Comb Sort

Bucket Sort

Insertion Sort

Radix Sort

Merge Sort

Minimum number of subsets with distinct elements

Sorting array of strings (or words) using Trie | Set-2 (Handling Duplicates)

Python | Sort Tuples in Increasing Order by any key

Sum of Manhattan distances between all pairs of points

Maximum triplet sum in array

(Login to Rate)

3

Average Difficulty : **3/5.0**
Based on **11** vote(s)

Basic

Easy

Medium

Hard

Expert



Add to TODO List



Mark as DONE

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Share this post!



4 Comments

GeeksforGeeks

1 Login

 Recommend Share

Sort by Newest



Join the discussion...

LOG IN WITH



OR SIGN UP WITH DISQUS ?

 **Rajat Agrawal** • 2 months ago

error : snapshots are repeated and one is missing

  • Reply • Share > **roottraveller** • 5 months ago




seriously?? do we need this?

  • Reply • Share > **Harsh Sharma** • 7 months ago

" arr (j - gap) = temp " in place of arr (j) = temp. As we need to swap the smaller arr (j) at the (j - gap) index.

  • Reply • Share > **Venkatesh Ellaboina** → Harsh Sharma • 5 months ago

No!! let j is at 4 and j-gap at 2 and the while condition **fails.so** where the temp variable should be inserted. Obviously it is j(4)

  • Reply • Share > Subscribe  Add Disqus to your siteAdd DisqusAdd  Privacy

DISQUS

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Careers!

Privacy

Policy



