

# CSCI 4830 / 5722

# Computer Vision



University of Colorado **Boulder**

# CSCI 4830 / 5722

# Computer Vision



Dr. Ioana Fleming  
Spring 2019  
Lecture 19



University of Colorado **Boulder**

# Reminders

## Submissions:

- Homework 3: Sat 3/2 at 11 pm

## Readings:

- Szeliski:
  - chapter 11 (Stereo correspondence)
- P&F:
  - chapter 7 (Stereopsis)



University of Colorado **Boulder**

# Today

- Stereo vision
- Epipolar geometry


*...with a lot of slides stolen from Steve Seitz, Fei Fei Li, Alexei Efros*



University of Colorado **Boulder**

# Recovering 3D from Images

- How can we automatically compute 3D geometry from images?
  - What cues in the image provide 3D information?



University of Colorado **Boulder**

# Visual Cues for 3D

- Shading




**Merle Norman Cosmetics, Los Angeles**



University of Colorado **Boulder**

# Visual Cues for 3D

- Texture



*The Visual Cliff, by William Vandivert, 1960*



University of Colorado **Boulder**

# Visual Cues for 3D

- Focus



From *The Art of Photography*, Canon



University of Colorado **Boulder**

# Visual Cues for 3D


- Motion



University of Colorado **Boulder**

# Stereo Reconstruction


- The Stereo Problem
  - Shape from two (or more) images
  - Biological motivation



University of Colorado **Boulder**

# Stereo Reconstruction

- The Stereo Problem
  - Shape from two (or more) images
  - Biological motivation



known  
camera  
viewpoints



University of Colorado **Boulder**


# Why do we have two eyes?



Cyclope

vs.

Odysseus



University of Colorado **Boulder**

# 1. Two is better than one




University of Colorado **Boulder**

"Just checking."

## 2. Depth from Convergence

$$d = \frac{c}{2\tan(a/2)}$$




*Human performance: up to 6-8 feet*



University of Colorado **Boulder**

### 3. Depth from Binocular Disparity

- *P: converging point*
- *C: object nearer projects to the outside of the P, disparity = +*
- *F: object farther projects to the inside of the P, disparity = -*



# Human vs Computer Stereopsis

- Fusing the pictures recorded by our two eyes and exploiting the difference (or disparity) between them allows us to gain a strong sense of depth.
- For a human, the eyes change their angle according to the distance to the observed object. To a computer this represents significant extra complexity in the geometrical calculations.
- This chapter is concerned with the design and implementation of algorithms that mimic our ability to perform this task, known as **stereopsis**.



Fusing the pictures recorded by our two eyes and exploiting the difference (or disparity) between them allows us to gain a strong sense of depth

image  $I(x,y)$



Disparity map  $D(x,y)$




image  $I'(x',y')$



$$(x', y') = (x + D(x, y), y)$$

So if we could find **corresponding points** in two images,  
could we **estimate relative depth**?



University of Colorado **Boulder**

# Stereopsis - applications

- visual robot navigation
- cartography
- aerial reconnaissance
- image segmentation for object recognition
- constructing three-dimensional scene models for computer graphics applications





University of Colorado **Boulder**

# Stereopsis – two parts

1. The **correspondence problem** = fusion of features observed by two(or more) eyes
  - establishing correct correspondences is hard
2. The **reconstruction problem** = computing the three-dimensional preimage.
  - pretty straight-forward, for just one feature
  - harder for multiple features




# Stereopsis – binocular fusion problem



University of Colorado **Boulder**

# Stereopsis – solving the correspondence problem



Multiple matching hypotheses, but which one is correct?



University of Colorado **Boulder**

# Why is the correspondence problem difficult?

- Some points in each image will have no corresponding point in the other image, because:
- The cameras may have different fields of view
- Due to occlusion
- A stereo system must be able to determine the image parts that should not be matched.



University of Colorado **Boulder**




- In the above picture, the part with green and red are the parts that show the different viewpoint of the cameras
- The task is to find points, that can be seen for both cameras
- Occlusion is both visible at the right edge of the box



University of Colorado **Boulder**

# Stereo correspondence constraints




- Given  $p$  in left image, where can corresponding point  $p'$  be?




University of Colorado **Boulder**

# Stereo correspondence constraints



# Epipolar constraint




Geometry of two views constrains where the corresponding pixel for some image point in the first view must occur in the second view.

- It must be on the line carved out by a plane connecting the world point and optical centers.



# Epipolar geometry



University of Colorado **Boulder**

# Epipolar geometry: terms

- **Baseline:** line joining the camera centers
  - **Epipole:** point of intersection of baseline with image plane
  - **Epipolar plane:** plane containing baseline and world point
  - **Epipolar line:** intersection of epipolar plane with the image plane
- 
- All epipolar lines intersect at the epipole
  - An epipolar plane intersects the left and right image planes in epipolar lines

*Why is the epipolar constraint useful?*



University of Colorado **Boulder**


# Epipolar constraint



This is useful because it reduces the correspondence problem to a 1D search along an epipolar line.




# Epipolar constraint



Each camera may be internally calibrated, but the rigid transformation separating the two camera coordinate systems is unknown. In this case, the epipolar geometry constrains the set of possible motions.




# What do the epipolar lines look like?




University of Colorado **Boulder**

# What do the epipolar lines look like?

1.





2.




University of Colorado **Boulder**

# Example: converging cameras





University of Colorado **Boulder**  
Figure from Hartley & Zisserman

# Example: parallel cameras



Where are the epipoles?




- So far, we have the explanation in terms of geometry.
- Now, how to express the epipolar constraints algebraically?




University of Colorado **Boulder**

# Stereo geometry, with calibrated cameras



If the stereo rig is calibrated, we know :  
how to **rotate** and **translate** camera reference frame 1 to get to  
camera reference frame 2.  
Rotation:  $3 \times 3$  matrix  $\mathbf{R}$ ; translation: 3 vector  $\mathbf{T}$ .

# Stereo geometry, with calibrated cameras



If the stereo rig is calibrated, we know :  
how to **rotate** and **translate** camera reference frame 1 to get to  
camera reference frame 2.

$$\mathbf{X}'_c = \mathbf{R}\mathbf{X}_c + \mathbf{T}$$

# An aside: cross product

$$\vec{a} \times \vec{b} = \vec{c}$$

$$\begin{aligned}\vec{a} \cdot \vec{c} &= 0 \\ \vec{b} \cdot \vec{c} &= 0\end{aligned}$$


Vector cross product takes two vectors and returns a third vector that's perpendicular to both inputs.

So here, c is perpendicular to both a and b, which means the dot products will be = 0.



University of Colorado **Boulder**

# From geometry to algebra



$$\boxed{\mathbf{X}'} = \boxed{\mathbf{R}}\boxed{\mathbf{X}} + \boxed{\mathbf{T}}$$

$$\mathbf{X}' \cdot (\mathbf{T} \times \mathbf{X}') = \mathbf{X}' \cdot (\mathbf{T} \times \mathbf{R}\mathbf{X})$$

$$\underbrace{\mathbf{T} \times \mathbf{X}'}_{\text{Normal to the plane}} =$$

$$= 0$$

Normal to the plane



University of Colorado Boulder

$\mathbf{T} \times \mathbf{R}\mathbf{X}$

# Cross product as matrix multiplication

$$\vec{a} \times \vec{b} = \begin{bmatrix} 0 & -a_3 & a_2 \\ a_3 & 0 & -a_1 \\ -a_2 & a_1 & 0 \end{bmatrix} \begin{bmatrix} b_1 \\ b_2 \\ b_3 \end{bmatrix} = \vec{c}$$

$$\vec{a} \cdot \vec{c} = 0$$
$$\vec{b} \cdot \vec{c} = 0$$

Can be expressed as a matrix multiplication.

$$[a_x] = \begin{bmatrix} 0 & -a_3 & a_2 \\ a_3 & 0 & -a_1 \\ -a_2 & a_1 & 0 \end{bmatrix}$$


$$\boxed{\vec{a} \times \vec{b} = [a_x] \vec{b}}$$



University of Colorado **Boulder**

$a_x$  is a skew symmetric matrix.

# From geometry to algebra



$$\mathbf{X}' = \mathbf{R}\mathbf{X} + \mathbf{T}$$

$$\underbrace{\mathbf{T} \times \mathbf{X}'}_{\text{Normal to the plane}} = \mathbf{T} \times \mathbf{R}\mathbf{X} + \mathbf{T} \times \mathbf{T}$$

Normal to the plane

$$\mathbf{X}' \cdot (\mathbf{T} \times \mathbf{X}') = \mathbf{X}' \cdot (\mathbf{T} \times \mathbf{R}\mathbf{X})$$

$$= 0$$



University of Colorado Boulder

$\mathbf{T} \times \mathbf{R}\mathbf{X}$


# Essential matrix

$$\mathbf{X}' \cdot (\mathbf{T} \times \mathbf{R}\mathbf{X}) = 0$$

$$\mathbf{X}' \cdot ([\mathbf{T}_x] \mathbf{R}\mathbf{X}) = 0$$

Let  $\mathbf{E} = [\mathbf{T}_x] \mathbf{R}$

$$\mathbf{X}'^T \mathbf{E} \mathbf{X} = 0$$




**E** is called the **essential matrix**, and it relates corresponding image points between both cameras, given the rotation and translation.

If we observe a point in one image, its position in other image is constrained to lie on line defined by above.

Note: these points are in **camera coordinate systems**.


# Essential matrix



- $E x_2$  is the epipolar line associated with  $x_2$  ( $l_1 = E x_2$ )
- $E^T x_1$  is the epipolar line associated with  $x_1$  ( $l_2 = E^T x_1$ )
- $E$  is singular (rank two)
- $E e_2 = 0$  and  $E^T e_1 = 0$



# Essential matrix example: parallel cameras



$$\mathbf{R} = \boxed{\quad}$$

$$\mathbf{p} = [x, y, f]$$

$$\mathbf{T} = \boxed{\quad}$$

$$\mathbf{p}' = [x', y', f]$$

$$\mathbf{E} = [\mathbf{T} \ \mathbf{x}] \mathbf{R} = \boxed{\quad}$$

$$\mathbf{p}'^T \mathbf{E} \mathbf{p} = 0$$

For the parallel cameras, image of any point must lie on same horizontal line in each image plane.



University of Colorado **Boulder**

image  $I(x,y)$



Disparity map  $D(x,y)$




image  $I'(x',y')$



$$(x', y') = (x + D(x, y), y)$$


*What about when cameras' optical axes are not parallel?*



University of Colorado **Boulder**

# Stereo image rectification

In practice, it is convenient if image scanlines (rows) are the epipolar lines.




Re-project image planes onto a common plane parallel to the line between optical centers.

Pixel motion is horizontal after this transformation




University of Colorado **Boulder**  
Slide credit: Li Zhang

# Stereo image rectification



University of Colorado **Boulder**

# Stereo image rectification: example



Source: Alyosha Efros