

# CSCI 4830 / 5722

# Computer Vision



University of Colorado **Boulder**

# CSCI 4830 / 5722

# Computer Vision



Dr. Ioana Fleming  
Spring 2019  
Lecture 21



University of Colorado **Boulder**

# Reminders

## Submissions:

- Homework 4: Wed 3/20 at 11 pm

## Readings:

- Szeliski:
  - chapter 11 (Stereo correspondence)
- P&F:
  - chapter 7 (Stereopsis)



University of Colorado **Boulder**

# Today

- Fundamental Matrix
- Week calibration
- Stereo vision applications


*...with a lot of slides stolen from Steve Seitz, Fei Fei Li, Alexei Efros*



University of Colorado **Boulder**

# Stereo Reconstruction


- The Stereo Problem
  - Shape from two (or more) images
  - Biological motivation



University of Colorado **Boulder**

# Recap: stereo with calibrated cameras

- Given image pair,  $\mathbf{R}$ ,  $\mathbf{T}$
- Detect some features
- Compute essential matrix  $\mathbf{E}$
- Match features using the epipolar and other constraints
- Triangulate for 3d structure



University of Colorado **Boulder**

# Stereo reconstruction pipeline

What will cause errors?

- Camera calibration errors
- Poor image resolution
- Occlusions
- Violations of brightness constancy (specular reflections)
- Large motions
- Low-contrast image regions (textureless)



University of Colorado **Boulder**

# Uncalibrated case

- What if we don't know the camera parameters?

Two possibilities:

1. Calibrate with a calibration object
2. Weak calibration





University of Colorado **Boulder**

# Calibrating a camera

- Compute intrinsic and extrinsic parameters using observed camera data

Main idea

- Place “calibration object” with known geometry in the scene
- Get correspondences
- Solve for mapping from scene to image




The Opti-CAL Calibration Target Image



University of Colorado **Boulder**

# Camera parameters

- **Extrinsic:** location and orientation of camera frame with respect to reference frame
- Intrinsic: how to map pixel coordinates to image plane coordinates



# Extrinsic camera parameters

$$\mathbf{P}_c = \mathbf{R}(\mathbf{P}_w - \mathbf{T})$$

↑  
Camera reference frame      ↑  
World reference frame


$$\mathbf{P}_c = (X, Y, Z)^T$$



University of Colorado **Boulder**

# Camera parameters

- Extrinsic: location and orientation of camera frame with respect to reference frame
- Intrinsic: how to map pixel coordinates to image plane coordinates



University of Colorado **Boulder**

# Intrinsic camera parameters

- Ignoring any geometric distortions from optics, we can describe them by:

$$x = -(x_{im} - o_x)s_x$$

$$y = -(y_{im} - o_y)s_y$$

Coordinates of projected point  
in camera reference frame

Coordinates of  
image point in pixel  
units

Coordinates of image  
center in pixel units

Effective size of a pixel  
(mm)



University of Colorado **Boulder**

# Camera parameters

- We know that in terms of camera reference frame:

$$x = f \frac{X}{Z}$$

$$y = f \frac{Y}{Z}$$

and

$$\begin{aligned}\mathbf{P}_c &= \mathbf{R}(\mathbf{P}_w - \mathbf{T}) \\ \mathbf{P}_c &= (X, Y, Z)^T\end{aligned}$$

- Substituting previous eqns describing intrinsic and extrinsic parameters, can relate *pixels coordinates* to *world points*:

$$-(x_{im} - o_x)s_x = f \frac{\mathbf{R}_1 \cdot (\mathbf{P}_w - \mathbf{T})}{\mathbf{R}_3 \cdot (\mathbf{P}_w - \mathbf{T})}$$

$\mathbf{R}_i$  = Row i of  
rotation matrix

$$-(y_{im} - o_y)s_y = f \frac{\mathbf{R}_2 \cdot (\mathbf{P}_w - \mathbf{T})}{\mathbf{R}_3 \cdot (\mathbf{P}_w - \mathbf{T})}$$



University of Colorado **Boulder**

# Projection matrix

- This can be rewritten as a matrix product using homogeneous coordinates, where:

$$\mathbf{M}_{int} = \begin{bmatrix} -f/s_x & 0 & o_x \\ 0 & -f/s_y & o_y \\ 0 & 0 & 1 \end{bmatrix}$$

$$\begin{bmatrix} wx_{im} \\ wy_{im} \\ w \end{bmatrix} = \mathbf{MP}_w$$

$$\mathbf{M}_{ext} = \begin{bmatrix} r_{11} & r_{12} & r_{13} & -\mathbf{R}_1^T \mathbf{T} \\ r_{21} & r_{22} & r_{23} & -\mathbf{R}_2^T \mathbf{T} \\ r_{31} & r_{32} & r_{33} & -\mathbf{R}_3^T \mathbf{T} \end{bmatrix}$$





University of Colorado **Boulder**

# Calibrating a camera

- Compute intrinsic and extrinsic parameters using observed camera data

Main idea

- Place “calibration object” with known geometry in the scene
- Get correspondences
- Solve for mapping from scene to image: estimate  $\mathbf{M} = \mathbf{M}_{\text{int}} \mathbf{M}_{\text{ext}}$



The Opti-CAL Calibration Target Image



University of Colorado **Boulder**

# When would we calibrate this way?

- Makes sense when geometry of system is not going to change over time



University of Colorado **Boulder**

# Weak calibration

- Want to estimate world geometry without requiring calibrated cameras
  - Archival videos
  - Photos from multiple unrelated users
  - Dynamic camera system
- **Main idea:**
  - Estimate epipolar geometry from a (redundant) set of point correspondences between two uncalibrated cameras



University of Colorado **Boulder**

# From before: Projection matrix

- This can be rewritten as a matrix product using homogeneous coordinates:

$$\mathbf{M}_{int} = \begin{bmatrix} -f/s_x & 0 & o_x \\ 0 & -f/s_y & o_y \\ 0 & 0 & 1 \end{bmatrix}$$

$$\begin{bmatrix} wx_{im} \\ wy_{im} \\ w \end{bmatrix} = \mathbf{M}_{int} \mathbf{M}_{ext} \begin{bmatrix} X_w \\ Y_w \\ Z_w \\ 1 \end{bmatrix}$$

$$\mathbf{M}_{ext} = \begin{bmatrix} r_{11} & r_{12} & r_{13} & -\mathbf{R}_1^T \mathbf{T} \\ r_{21} & r_{22} & r_{23} & -\mathbf{R}_2^T \mathbf{T} \\ r_{31} & r_{32} & r_{33} & -\mathbf{R}_3^T \mathbf{T} \end{bmatrix}$$



University of Colorado **Boulder**

# From before: Projection matrix

- This can be rewritten as a matrix product using homogeneous coordinates:

$$\begin{bmatrix} wx_{im} \\ wy_{im} \\ w \end{bmatrix} = \mathbf{M}_{int} \mathbf{M}_{ext} \begin{bmatrix} X_w \\ Y_w \\ Z_w \\ 1 \end{bmatrix}$$

$$\mathbf{p}_{im} = \mathbf{M}_{int} \underbrace{\mathbf{M}_{ext} \mathbf{P}_w}_{\mathbf{P}_c}$$

$$\mathbf{p}_c$$

---

$$\mathbf{p}_{im} = \mathbf{M}_{int} \mathbf{p}_c$$



University of Colorado **Boulder**

# Uncalibrated case

For a given camera:

$$\mathbf{p}_{im} = \mathbf{M}_{int} \mathbf{p}_c$$

So, for **two** cameras (left and right):

$$\mathbf{p}_{c, left} = \mathbf{M}_{int, left}^{-1} \mathbf{p}_{im, left}$$

$$\mathbf{p}_{c, right} = \mathbf{M}_{int, right}^{-1} \mathbf{p}_{im, right}$$

 Internal calibration matrices,  
one per camera



University of Colorado **Boulder**

$$\begin{aligned}\mathbf{p}_{c,left} &= \mathbf{M}_{int,left}^{-1} \mathbf{p}_{im,left} \\ \mathbf{p}_{c,right} &= \mathbf{M}_{int,right}^{-1} \mathbf{p}_{im,right}\end{aligned}$$

# Uncalibrated case

$$\mathbf{p}_{c,right}^T \mathbf{E} \mathbf{p}_{c,left} = 0$$

From before, the **essential matrix**  $\mathbf{E}$ .

$$\left( \mathbf{M}_{int,right}^{-1} \mathbf{p}_{im,right} \right)^T \mathbf{E} \left( \mathbf{M}_{int,left}^{-1} \mathbf{p}_{im,left} \right) = 0$$

$$\mathbf{p}_{im,right}^T \underbrace{\left( \mathbf{M}_{int,right}^{-T} \mathbf{E} \mathbf{M}_{int,left}^{-1} \right)}_{\mathbf{F}} \mathbf{p}_{im,left} = 0$$

$\mathbf{F}$       “Fundamental matrix”

$$\mathbf{p}_{im,right}^T \mathbf{F} \mathbf{p}_{im,left} = 0$$



University of Colorado **Boulder**

# Computing F from correspondences

Each point correspondence generates one constraint on F

$$\mathbf{p}_{im,right}^T \mathbf{F} \mathbf{p}_{im,left} = 0$$

$$\begin{bmatrix} u' & v' & 1 \end{bmatrix} \begin{bmatrix} f_{11} & f_{12} & f_{13} \\ f_{21} & f_{22} & f_{23} \\ f_{31} & f_{32} & f_{33} \end{bmatrix} \begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = 0$$

Collect n of these constraints

$$\begin{bmatrix} u'_1 u_1 & u'_1 v_1 & u'_1 & v'_1 u_1 & v'_1 v_1 & v'_1 & u_1 & v_1 & 1 \end{bmatrix} \begin{bmatrix} f_{11} \\ f_{12} \\ f_{13} \\ f_{21} \\ f_{22} \\ f_{23} \\ f_{31} \\ f_{32} \\ f_{33} \end{bmatrix} = \mathbf{0}$$

Solve for f , vector of parameters.



University of Color

# Computing F from correspondences

$$\mathbf{W} \begin{pmatrix} u_1u'_1 & u_1v'_1 & u_1 & v_1u'_1 & v_1v'_1 & v_1 & u'_1 & v'_1 & 1 \\ u_2u'_2 & u_2v'_2 & u_2 & v_2u'_2 & v_2v'_2 & v_2 & u'_2 & v'_2 & 1 \\ u_3u'_3 & u_3v'_3 & u_3 & v_3u'_3 & v_3v'_3 & v_3 & u'_3 & v'_3 & 1 \\ u_4u'_4 & u_4v'_4 & u_4 & v_4u'_4 & v_4v'_4 & v_4 & u'_4 & v'_4 & 1 \\ u_5u'_5 & u_5v'_5 & u_5 & v_5u'_5 & v_5v'_5 & v_5 & u'_5 & v'_5 & 1 \\ u_6u'_6 & u_6v'_6 & u_6 & v_6u'_6 & v_6v'_6 & v_6 & u'_6 & v'_6 & 1 \\ u_7u'_7 & u_7v'_7 & u_7 & v_7u'_7 & v_7v'_7 & v_7 & u'_7 & v'_7 & 1 \\ u_8u'_8 & u_8v'_8 & u_8 & v_8u'_8 & v_8v'_8 & v_8 & u'_8 & v'_8 & 1 \end{pmatrix} \begin{pmatrix} F_{11} \\ F_{12} \\ F_{13} \\ F_{21} \\ F_{22} \\ F_{23} \\ F_{31} \\ F_{32} \\ F_{33} \end{pmatrix} = 0$$

- Homogeneous system  $\mathbf{W}\mathbf{f} = 0$
- Rank 8  $\rightarrow$  A non-zero solution exists (unique)
- If  $N>8$   $\rightarrow$  Lsq. solution by SVD!  $\rightarrow \hat{\mathbf{F}}$   $\|\mathbf{f}\| = 1$



University of Colorado **Boulder**

# Fundamental matrix

- Relates **pixel coordinates** in the two views
- More general form than essential matrix: we remove need to know intrinsic parameters
- If we estimate fundamental matrix from correspondences in *pixel coordinates*, can reconstruct epipolar geometry without intrinsic or extrinsic parameters.



# Stereo pipeline with weak calibration

- So, where to start with uncalibrated cameras?
  - Need to find fundamental matrix  $F$  **and** the correspondences (pairs of points  $(u',v') \leftrightarrow (u,v)$ ).



- 1) Find interest points in image
  - 2) Compute correspondences
  - 3) Compute epipolar geometry
  - 4) Refine
- 



University of Colorado **Boulder**

Example from Andrew Zisserman

# Stereo pipeline with weak calibration


1) Find interest points



University of Colorado **Boulder**

# Stereo pipeline with weak calibration

2) Match points within proximity to get putative matches



University of Colorado **Boulder**

# Stereo pipeline with weak calibration

## 3) Compute epipolar geometry -- robustly with RANSAC

Select random sample of putative correspondences


Compute  $F$  using them

- determines epipolar constraint

Evaluate amount of support

- inliers within threshold distance of epipolar line

Choose  $F$  with most support  
(inliers)



University of Colorado **Boulder**



# Summary

- **Rectification:** make epipolar lines align with scanlines
- Stereo solutions:
  - **Correspondence:** dense, or at interest points
  - **Non-geometric stereo constraints** (e.g., similarity, order, smoothness)
- Calibration
  - **With calibration object** in scene: relate world coordinates to image coordinates
  - **Weak calibration:** solve for fundamental matrix, relate image coordinates to image coordinates



# Stereo Vision Applications

## Laser scanning



Digital Michelangelo Project  
<http://graphics.stanford.edu/projects/mich/>

- Optical triangulation
  - Project a single stripe of laser light
  - Scan it across the surface of the object
  - This is a very precise version of structured light scanning



University of Colorado **Boulder**

Source: S. Seitz

# Laser scanned models



University of Colorado  
**Boulder**

*The Digital Michelangelo Project*, Levoy et al.

Source: S. Seitz

# Laser scanned models




University of Colorado **Boulder**

*The Digital Michelangelo Project*, Levoy et al.

Source: S. Seitz

# Laser scanned models




University of Colorado  
**Boulder**

*The Digital Michelangelo Project*, Levoy et al.

Source: S. Seitz

# Laser scanned models




University of Colorado  
**Boulder**

*The Digital Michelangelo Project*, Levoy et al.

Source: S. Seitz

# Laser scanned models

1.0 mm resolution (56 million triangles)



University of Colorado  
**Boulder**

*The Digital Michelangelo Project*, Levoy et al.

Source: S. Seitz

# Stereo Vision Applications

- Example depth maps (pentagon)


left image



right image



range map



range map from the stereo vision system. The image is taken by a camera located to the left of the building. The depth information is calculated by the stereo vision system and is used to create a 3D surface plot. The plot shows the building's structure as a series of peaks and valleys on a flat base. The text "range map" is displayed above the plot.




University

# STEREO (Solar Terrestrial Relations Observatory)

**STEREO** is a solar observation mission. Two nearly identical spacecraft were launched in 2006 into orbits around the Sun that cause them to respectively pull farther ahead of and fall gradually behind the Earth. This enables stereoscopic imaging of the Sun and solar phenomena, such as coronal mass ejections.



# Stereo in machine vision systems



Left : The Stanford cart sports a single camera moving in discrete increments along a straight line and providing multiple snapshots of scenes. Right : The INRIA mobile robot uses three cameras to map its environment

# Real-time stereo



[Nomad robot](#) searches for meteorites in Antarctica  
<http://www.frc.ri.cmu.edu/projects/meteorobot/index.html>

- Used for robot navigation (and other tasks)



University of Colorado **Boulder**

# Face modeling

- From one stereo pair to a 3D head model




[[Frederic Deverney](#), INRIA, 1998]



University of Colorado **Boulder**

# Face modeling

- From multiple stereo pairs to a 3D head model



[Brian Amberg, Basel, 2005]



University of Colorado **Boulder**

# Depth for segmentation




Figure 3 Stereo video frames with computed depth map and edge combination result.

Danijela Markovic and Margrit Gelautz, Interactive Media Systems Group, Vienna University of Technology



University of Colorado **Boulder**

# Depth for segmentation



(a) Original image with snake initialization.



(b) Final snake on original image.



(c) Final snake on depth image.



(d) Original image with snake from (c) overlaid.



(e) Final snake on edge combination image.



(f) Original image with snake from (e) overlaid.

Danijela Markovic and Margrit Gelautz, Interactive Media Systems Group, Vienna University of Technology



University of Colorado **Boulder**