

0.9 Creating Queries

you-said

For this Schema: **Person** (*driver_id*, *name*, *address*) - Primary Keys (*driver_id*) **Car** (*license_plate*, *model*, *year*) - Primary Keys (*license_plate*) **Accident** (*report_number*, *year*, *location*) - Primary Keys (*report_number*) **Own** (*driver_id*, *license_plate*) - Primary Keys (*driver_id*, *license_plate*) **Participated** (*report_number*, *license_plate*, *driver_id*, *damage_amount*) - Primary Keys (*report_number*, *license_plate*) Write a query to find the total number of people who owned cars that were involved in accidents in 2017.

ChatGPT said:

To find the total number of people who owned cars that were involved in accidents in 2017, you can join the **Own**, **Participated**, and **Accident** tables, filtering for accidents that occurred in 2017, and then count the distinct number of people (*driver_id*).

Here's the SQL query:

```

[] sqlCopy codeSELECT COUNT(DISTINCT O.driver_id) AS total_people FROM Own
O JOIN Participated P ON O.license_plate = P.license_plate JOIN Accident A ON P.report_number
= A.report_number WHERE A.year = 2017;

```

explanation

Explanation:

- **Own O**: Contains information about which cars are owned by which people.
- **Participated P**: Contains details of cars and drivers involved in accidents.
- **Accident A**: Contains accident details like the year and location.
- The query joins these three tables on *license_plate* and *report_number*, and filters by accidents that occurred in 2017 (*A.year* = 2017).
- **COUNT(DISTINCT O.driver_id)**: Ensures that the count only includes unique car owners.

you-said-1

write a query to delete all 2010 cars belonging to a person whose ID is '12345'

ChatGPT said:

To delete all cars from the **Car** table that belong to a person with *driver_id* = '12345' and were manufactured in the year 2010, you'll need to use a **DELETE** query that involves a join between the **Car** and **Own** tables.

Here's the SQL query:

```

[] sqlCopy codeDELETE FROM Car WHERE license_plate IN ( SELECT O.license_plate
FROM Own O JOIN Car C ON O.license_plate = C.license_plate WHERE O.driver_id
= '12345' AND C.year = 2010 );
explanation-1

```

Explanation:

- The **DELETE** statement is targeting rows in the **Car** table.
- The subquery finds all the **license_plate** values from the **Own** table that are owned by the person with **driver_id = '12345'** and where the car's **year** is 2010.
- The **WHERE** clause of the main query then deletes all cars that match the **license_plate** values from the subquery.

This ensures that only the cars from 2010 owned by the person with ID 12345 are deleted.

you-said-2

what is the difference between this query "DELETE FROM Car WHERE license_plate IN (SELECT O.license_plate FROM Own O JOIN Car C ON O.license_plate = C.license_plate WHERE O.driver_id = '12345' AND C.year = 2010); " and "Delete Car Where year = 2010 and license_plate in (Select license_plate FROM Owns o Where o.driver_id = '12345') Which is better?

ChatGPT said:

Both queries aim to delete cars from the **Car** table that belong to a person with **driver_id = '12345'** and were manufactured in the year 2010. However, they differ slightly in their structure and execution. Let's break down each query and compare them:

query-1

Query 1:

```

[] sqlCopy codeDELETE FROM Car WHERE license_plate IN ( SELECT O.license_plate
FROM Own O JOIN Car C ON O.license_plate = C.license_plate WHERE O.driver_id
= '12345' AND C.year = 2010 );

```

- **Subquery:** This subquery joins the **Own** and **Car** tables to first filter the **license_plate** for cars owned by **driver_id = '12345'** and manufactured in the year 2010.
- **Delete Condition:** The main query deletes all records from **Car** where the **license_plate** matches the result of the subquery.

query-2

Query 2:

```
sqlCopy codeDELETE FROM Car WHERE year = 2010 AND license_plate IN (
SELECT license_plate FROM Own O WHERE O.driver_id = '12345');
```

- **Subquery:** This subquery directly selects the `license_plate` from the `Own` table for the person with `driver_id = '12345'`.
- **Delete Condition:** The main query deletes cars from `Car` where the `license_plate` is owned by the person and the car's `year` is 2010.

key-differences

Key Differences:

1. Join vs. Filtering:

- **Query 1:** Performs an explicit JOIN between `Own` and `Car` in the subquery to check both ownership and the car's year in the same step.
- **Query 2:** Separates the logic by filtering the year directly in the main query and selecting only based on ownership in the subquery.

2. Efficiency:

- **Query 1:** Could potentially be less efficient because it performs a JOIN in the subquery, which might slow down performance if the tables are large.
- **Query 2:** Is likely more efficient because it directly checks the `year = 2010` in the main query and only looks for ownership in the subquery. This reduces the complexity of the subquery and narrows down the cars earlier.

which-is-better

Which is Better?

Query 2 is likely better in terms of performance because:

- It avoids a JOIN in the subquery, making the filtering process more straightforward.

- The condition `year = 2010` is applied directly in the `DELETE` statement, reducing the number of rows processed in the subquery.

However, both queries will yield the same result. If performance isn't a major concern (for small datasets), either approach works fine. But for larger datasets, **Query 2** is generally the preferred option.

you-said-3

University Schema and Data.pdf
PDF

create a relation `marks(ID, score)` and populate it with random score for all student's courses that conforms with the grades of the students. Where grade is F if `score < 40`, grade is C if `40 <= score < 60`, grade is B if `60 <= score < 80` and grade is A is `80 <= score`. Use University Schema and Data.

section

To create a **Marks** relation and populate it with random scores that conform to the grade data in the **Takes** table from the University Schema, follow these steps:

1. **Create the Marks table:**

```
sqlCopy codeCREATE TABLE Marks ( ID VARCHAR(5), score INT CHECK
(score >= 0 AND score <= 100), PRIMARY KEY (ID) );
```

2. **Insert random scores** for all students' courses and map them to grades. Based on the given grade system:

- **F** if `score < 40`
- **C** if `40 <= score < 60`
- **B** if `60 <= score < 80`
- **A** if `80 <= score <= 100`

3. **Generate random scores** and populate the **Marks** table based on the grades. Use SQL to insert the scores into the table, matching the grade conditions from the **Takes** table. You can assign random values within the score ranges for each grade.

Here is an example script to insert random scores based on the existing grades in the **Takes** table:

```
sqlCopy code-- Insert random scores into Marks based on the student's grades from
the Takes table INSERT INTO Marks (ID, score) SELECT T.ID, CASE WHEN T.grade
```

```
= 'A' THEN FLOOR(RANDOM() * (100 - 80 + 1)) + 80 -- Random score between 80
and 100 WHEN T.grade = 'B' THEN FLOOR(RANDOM() * (79 - 60 + 1)) + 60 --
Random score between 60 and 79 WHEN T.grade = 'C' THEN FLOOR(RANDOM() *
(59 - 40 + 1)) + 40 -- Random score between 40 and 59 WHEN T.grade = 'F' THEN
FLOOR(RANDOM() * (39 - 0 + 1)) + 0 -- Random score between 0 and 39 ELSE NULL
-- Handle null or unknown grades END AS score FROM Takes T;
explanation-2
```

Explanation:

- **Random score generation:** `FLOOR(RANDOM() * (upper_limit - lower_limit + 1)) + lower_limit` generates a random integer within the specified range for each grade.
- **Grades:** Based on the `Takes` table, scores are assigned according to the grading system.

This will populate the `Marks` table with random scores that correspond to each student's grade for their respective courses.

you-said-4

in SQL create a new relation `marks(ID, score)` and populate it with random data for 10 students.

ChatGPT said:

To create a new `Marks` relation and populate it with random data for 10 students in SQL, you can follow these steps:

1. Create the Marks table:

```
[] sqlCopy codeCREATE TABLE Marks ( ID VARCHAR(5), score INT CHECK
(score >= 0 AND score <= 100), PRIMARY KEY (ID) );
```

2. Insert random scores for 10 students using random data generation. The `RANDOM()` function generates a random float between 0 and 1, and we can scale it to get a score between 0 and 100.

Here's the SQL script to insert random scores for 10 students:

```
[] sqlCopy code-- Create the Marks table CREATE TABLE Marks ( ID VARCHAR(5),
score INT CHECK (score >= 0 AND score <= 100), PRIMARY KEY (ID) );
-- Insert random scores for 10 students INSERT INTO Marks (ID, score) VALUES
('S001', FLOOR(RANDOM() * 101)), -- Random score between 0 and 100 ('S002',
FLOOR(RANDOM() * 101)), ('S003', FLOOR(RANDOM() * 101)), ('S004', FLOOR(RANDOM()
```

```
* 101)), ('S005', FLOOR(RANDOM() * 101)), ('S006', FLOOR(RANDOM() * 101)),
('S007', FLOOR(RANDOM() * 101)), ('S008', FLOOR(RANDOM() * 101)), ('S009',
FLOOR(RANDOM() * 101)), ('S010', FLOOR(RANDOM() * 101));
```

explanation-3

Explanation:

- **FLOOR(RANDOM() * 101)**: This generates a random integer between 0 and 100 for each student's score.
- The ID values are hardcoded as **S001**, **S002**, etc., representing the student IDs.

This query creates the **Marks** table and populates it with random scores for 10 students.
you-said-5

Here grade is F if score < 40, grade is C if 40 <= score < 60, grade is B if 60 <= score < 80 and grade is A is 80 <= score. Write a query to find number of students with each grade.

ChatGPT said:

To find the number of students with each grade based on their scores, you can use a **CASE** statement to categorize the **score** into the corresponding grade (**F**, **C**, **B**, **A**). Then, you can use **GROUP BY** to count the number of students in each grade category.

Here's the SQL query:

```
sqlCopy codeSELECT CASE WHEN score < 40 THEN 'F' WHEN score >= 40
AND score < 60 THEN 'C' WHEN score >= 60 AND score < 80 THEN 'B' WHEN
score >= 80 THEN 'A' END AS grade, COUNT(*) AS number_of_students FROM Marks
GROUP BY grade;
```

explanation-4

Explanation:

- The **CASE** statement checks the **score** and assigns the appropriate grade:
 - **F** if **score** < 40
 - **C** if 40 <= **score** < 60
 - **B** if 60 <= **score** < 80
 - **A** if 80 <= **score**
- The **COUNT(*)** counts the number of students in each grade category.

- The query groups the result by the **grade** to show the number of students for each grade.

This query will return the number of students in each grade category (A, B, C, F).

you-said-6

For this Employee Schema Employee (id, person_name, street, city) - Primary Keys (id) Works (id, company_name, salary) - Primary Keys (id) Company (company_name, city) - Primary Keys (company_name) Manages (id, manager_id) - Primary Keys (id) write a query to find the id, name, city of residence of each employee who works for "First Bank Corporation" and earns more than \$10,000.

ChatGPT said:

To find the **id**, **person_name**, and **city** of residence of each employee who works for the company "First Bank Corporation" and earns more than \$10,000, you need to join the **Employee** and **Works** tables and apply the relevant conditions.

Here's the SQL query:

```
sqlCopy codeSELECT E.id, E.person_name, E.city FROM Employee E JOIN Works W ON E.id = W.id WHERE W.company_name = 'First Bank Corporation' AND W.salary > 10000;
```

explanation-5

Explanation:

- **Employee E:** Contains employee details like **id**, **person_name**, and **city**.
- **Works W:** Contains information about where employees work, including their **salary** and **company_name**.
- The **JOIN** is done on **id** to match employees with their work details.
- The **WHERE** clause filters employees who work for "**First Bank Corporation**" and have a salary greater than \$10,000.

This query returns the **id**, **person_name**, and **city** of residence for all employees who meet the specified criteria.

you-said-7

For this Employee Schema Employee (id, person_name, street, city) - Primary Keys (id) Works (id, company_name, salary) - Primary Keys (id) Company (company_name, city) - Primary Keys (company_name) Manages (id, manager_id) - Primary Keys (id) write a query to find the id of each employee who earns more than every employee of "Small Bank Corporation"

ChatGPT said:

To find the **id** of each employee who earns more than every employee of "**Small Bank Corporation**", you need to compare the salary of employees in other companies to the highest salary of employees working for "**Small Bank Corporation**".

You can achieve this using a **WHERE** clause that ensures the employee's salary is greater than the maximum salary of employees at "**Small Bank Corporation**".

Here's the SQL query:

```
sqlCopy codeSELECT W1.id FROM Works W1 WHERE W1.salary > ( SELECT
MAX(W2.salary) FROM Works W2 WHERE W2.company_name = 'Small Bank Corpo-
ration' );
```

explanation-6

Explanation:

- **Works W1:** Represents all employees' work details, including their **salary**.
- **Subquery:** The subquery finds the maximum salary of employees working for "**Small Bank Corporation**".
- **Main Query:** The main query selects the **id** of employees whose salary is greater than the maximum salary found in the subquery.

This query will return the **id** of each employee who earns more than every employee working for "**Small Bank Corporation**".

you-said-8

University Schema and Data.pdf
PDF

Write a query to Display a list of all instructors, showing each instructor's ID and the number of sections taught. Make sure to show the number of sections as 0 for instructors who have not taught any section. Your query should use an outer join, and should not use subqueries. Write the query on University Schema and Data

section-1

To display the list of all instructors, showing each instructor's ID and the number of sections taught, including instructors who have not taught any sections (with the count as 0), you can use an **outer join** between the **instructor** and **teaches** tables.

Here is the SQL query to achieve this:

```
sqlCopy codeSELECT I.ID, I.name, COUNT(T.course_id) AS number_of_sections
FROM instructor I LEFT JOIN teaches T ON I.ID = T.ID GROUP BY I.ID, I.name;
```

explanation-7

Explanation:

- **LEFT JOIN:** This ensures that all instructors from the **instructor** table are included in the result, even if they do not have matching records in the **teaches** table.
- **COUNT(T.course_id):** Counts the number of sections each instructor has taught. If the instructor has not taught any sections, the count will be 0.
- **GROUP BY I.ID, I.name:** Groups the results by the instructor's ID and **name** to aggregate the section count for each instructor.

This query will return a list of instructors with their ID, name, and the number of sections they have taught, with a count of 0 for those who haven't taught any sections.

You've hit the Free plan limit for GPT-4o.

Responses will use another model until your limit resets after 11:08 PM.

Get Plus
prompt-textarea

composer-background