NEOVOLT



Single Phase

HYBRID INVERTER



PRODUCT MODEL

- BW-INV-SPH6K (Hybrid Inverter)

HIGH PERFORMANCE

- 166% PV over management;
- 200% backup overload capacity, 60A battery current;
- Max. efficiency 97.3%, Battery efficiency 97%;
- Load monitoring accuracy 10W, Battery discharging threshold 10W.

HIGH RELIABILITY

- UPS level redundant protection against backup load breakdown;
- Three-level firmware and two-level hardware battery protection;
- Multiple temperature monitoring, delicate thermal management.

HIGH INTELLIGENCE

- Internal EMS optimizes home energy supply automatically;
- PV production forecast;
- Built-in electric power service, FCAS, VPP, etc;
- Online monitoring, online diagnosis, online service.

PARAMETERS

NEOVOLT

INVERTER MODEL	BW-INV-SPH6K
BATTERY PORT	
Battery Type	Li-on / Lead-acid
Nominal Battery Voltage	96V
Battery Voltage Range	80~467.2V
Max. Charging Current	60A
Max. Discharging Current	60A
PV INPUT	
Max. PV Input Power	10kW
Max. PV Input Voltage	580V
MPPT Range	100~550V
Startup Voltage	100V
Max. Input Current	15A / 15A
Max. Short Circuit Current	22.5A / 22.5A
MPPT Trackers	2
Strings Per MPPT Tracker	1 / 1
GRID PORT	
Rated Output Power	6kW
Max. Output Current	27.2A / 26A
Max. Output Apparent Power	6kVA
Max. Input Power	11.5kVA
Rated Grid Voltage	220Vac / 230Vac
Grid Voltage Range	180~270Vac
Rated Grid Frequency	50/60Hz
Power Factor	-0.8~+0.8
THDi	<3%
BACKUP PORT	
Surge Backup Power	11.5kVA
Rated Backup Power	6kVA
Rated Backup Voltage	220Vac / 230Vac
Rated Backup Frequency	50/60Hz
THDv	<3% (Linear Load) / <5% (Non-linear Load)
DCV	<100mV
Crest Ratio	3 : 1
Transfer Time	<10ms
EFFICIENCY	
Max. Efficiency	97.3%
European Efficiency	96.2%
MPPT Efficiency	99.9%
Max. Round Trip Efficiency	90%
GENERAL DATA	
Operating Temperature Range	-20°C~60°C
Relative Humidity	0~95% (No Condensing)
Operating Altitude	≤3000m (>3000m Derating)
Cooling	Natural Convection
Noise	<30dB
Topology	Transformerless
Dimensions (W*H*D)	590x405x205mm
Protection Degree	IP65
Weight	20.5kg
Warranty	5 Years / 10 Years
HMI&COMM.	
Communication with BMS	CAN / RS-485
Load Monitoring	Meter / CT / Backup box
External Communication	RS-485 / WIFI / 4G / Ethernet
User Interface	LED / LCD
CERTIFICATE	
Grid Regulation	CEI 0-21, NRS 097-2-1, IEC 61727, IEC 62116, EREC G99
Safety Regulation	IEC/EN 62109-1, IEC/EN 62109-2
EMC	IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4

Note: Specifications are subject to change without advance notice.

BYTEWATT TECHNOLOGY CO., LTD.
E-mail: info@byte-watt.com Web: www.byte-watt.com