



Clustered Interval Calibration And Synthetic Segmentation Robustness

Uncertainty calibration across clustered data and segmentation stress cases

Research Presentation Program

Department of Statistics & Data Science

2026-08-27



香港中文大學
The Chinese University of Hong Kong



Clustered outcomes separate center and individual variation

$$Y_{ij} = \beta_0 + \beta_1 T_{ij} + u_j + \varepsilon_{ij}, \quad u_j \sim N(0, \tau^2), \quad \varepsilon_{ij} \sim N(0, \sigma^2)$$

Center effects set $\rho = \tau^2 / (\tau^2 + \sigma^2)$, so interval calibration depends on cluster count.

Model components


- clustered outcome equation
- center random effect
- individual error

Interpretation

The source model makes center-level dependence explicit before interval comparison.



Cluster-robust intervals recover coverage as ICC increases



Data source: 400 simulation replicates per cell; y-axis shows 95% interval coverage.

Small-G, high-ICC imbalance still suppresses coverage; cluster-robust intervals recover toward nominal as clusters increase.



Synthetic clustered-data example; intervals compared on coverage, width, and bias.



Simulation varies clustering before interval procedures are compared

DGP stress grid

- centers $G = 8, 20, 50$
- ICC $\rho = 0, .1, .3, .5$
- balanced or imbalanced clusters




The connector direction encodes data generation before interval estimation and coverage diagnostics.



Small-G settings remain anti-conservative after robustification

G=8 with imbalanced clusters: coverage by ICC




The failure region is adjacent to the diagnostic explanation instead of hidden in a note.

Negative evidence is completed; CR2 and wild cluster bootstrap remain the next test.



Next experiment tests whether batch selection reduces fragile coverage




Coverage evidence determines which batch-query strategy to validate next; CR2 and wild bootstrap remain proposed comparators.



Same-case panels keep the segmentation error interpretable

Workstream transition

Segmentation robustness: independent workstream; no causal bridge asserted.



All panels and zoom crops come from one case and one ROI; TP/FP/FN colors remain adjacent to the error crop.