



UNIVERSITY OF
ILLINOIS
URBANA - CHAMPAIGN

Ippatsu

Dilhan Salgado, Yuuki Sawanoi, Zhikun Wang

ICPC World Finals

2025

1	Contest
2	Mathematics
3	Data structures
4	Numerical
5	Number theory
6	Combinatorial
7	Graph
8	Geometry
9	Strings
10	Various

Contest (1)

```
template.cpp18 lines
#include <bits/stdc++.h>
using namespace std;

#define int ll
#define rep(i, a, b) for(int i = a; i < (b); ++i)
#define per(i, a, b) for(int i = (b) - 1; i >= a; --i)
#define all(x) x.begin(), x.end()
#define sz(x) (int)(x).size()
#define dbg(x) cerr << ">>> " << #x << " = " << x << endl;
typedef long long ll;
typedef pair<int, int> pii;
typedef vector<int> vi;

signed main() {
    //cout << setprecision(20) << fixed;
    cin.sync_with_stdio(0); cin.tie(0);
    cin.exceptions(cin.failbit);
}

hash.sh1 lines
tr -d '[:space:]' | md5sum

hash-cpp.sh2 lines
clang -xc++ -E -dD -P - | sed -E '/^#/d/' | tr -d '[:space:]' |
    ↪md5sum | cut -c-6
# cpp -dD -P -fpreprocessed | tr -d '[:space:]' | md5sum

.bashrc5 lines
alias c='g++ -Wall -Wconversion -Wfatal-errors -Wno-shadow -g -
    ↪std=c++20 -fsanitize=undefined,address'
h() {
    cpp -dD -P "$1" | sed -E '/^#/d/' | tr -d '[:space:]' | md5sum
    ↪ | cut -c-6
}
xmodmap -e 'clear lock' -e 'keycode 66=less greater' #caps =◇
```

Mathematics (2)

2.1 Equations

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

2.2 Recurrences

If $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$, and r_1, \dots, r_k are distinct roots of $x^k - c_1x^{k-1} - \dots - c_k$, there are d_1, \dots, d_k s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g. $a_n = (d_1n + d_2)r^n$.

2.3 Trigonometry

$$\begin{aligned}\sin(v + w) &= \sin v \cos w + \cos v \sin w \\ \cos(v + w) &= \cos v \cos w - \sin v \sin w\end{aligned}$$

$$\begin{aligned}\tan(v + w) &= \frac{\tan v + \tan w}{1 - \tan v \tan w} \\ \sin v + \sin w &= 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2} \\ \cos v + \cos w &= 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}\end{aligned}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$\begin{aligned}a \cos x + b \sin x &= r \cos(x - \phi) \\ a \sin x + b \cos x &= r \sin(x + \phi)\end{aligned}$$

where $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$.

2.4 Geometry

2.4.1 Triangles

Side lengths: a, b, c

$$\begin{aligned}\text{Semiperimeter: } p &= \frac{a + b + c}{2} \\ \text{Area: } A &= \sqrt{p(p - a)(p - b)(p - c)}\end{aligned}$$

$$\text{Circumradius: } R = \frac{abc}{4A}$$

$$\text{Inradius: } r = \frac{A}{p}$$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$$

$$\text{Law of sines: } \frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$$

$$\text{Law of cosines: } a^2 = b^2 + c^2 - 2bc \cos \alpha$$

$$\text{Law of tangents: } \frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$$


2.4.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$.

2.4.3 Spherical coordinates



$$\begin{aligned}x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \text{acos}(z / \sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \text{atan2}(y, x)\end{aligned}$$

2.5 Derivatives/Integrals

$$\frac{d}{dx} \arcsin x = \frac{1}{\sqrt{1 - x^2}} \quad \frac{d}{dx} \arccos x = -\frac{1}{\sqrt{1 - x^2}}$$

$$\frac{d}{dx} \tan x = 1 + \tan^2 x \quad \frac{d}{dx} \arctan x = \frac{1}{1 + x^2}$$

$$\int \tan ax = -\frac{\ln |\cos ax|}{a} \quad \int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2}$$

$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2} \text{erf}(x) \quad \int xe^{ax} dx = \frac{e^{ax}}{a^2} (ax - 1)$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6 Sums

$$c^a+c^{a+1}+\cdots+c^b=\frac{c^{b+1}-c^a}{c-1}, c\neq 1$$

$$1+2+3+\cdots+n=\frac{n(n+1)}{2}$$

$$1^2+2^2+3^2+\cdots+n^2=\frac{n(2n+1)(n+1)}{6}$$

$$1^3+2^3+3^3+\cdots+n^3=\frac{n^2(n+1)^2}{4}$$

$$1^4+2^4+3^4+\cdots+n^4=\frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

2.7 Series

$$e^x=1+x+\frac{x^2}{2!}+\frac{x^3}{3!}+\ldots, (-\infty < x < \infty)$$

$$\ln(1+x)=x-\frac{x^2}{2}+\frac{x^3}{3}-\frac{x^4}{4}+\ldots, (-1 < x \leq 1)$$

$$\sqrt{1+x}=1+\frac{x}{2}-\frac{x^2}{8}+\frac{2x^3}{32}-\frac{5x^4}{128}+\ldots, (-1 \leq x \leq 1)$$

$$\sin x=x-\frac{x^3}{3!}+\frac{x^5}{5!}-\frac{x^7}{7!}+\ldots, (-\infty < x < \infty)$$

$$\cos x=1-\frac{x^2}{2!}+\frac{x^4}{4!}-\frac{x^6}{6!}+\ldots, (-\infty < x < \infty)$$

2.8 Probability theory

2.8.1 Discrete distributions

Bin(n, p): $p(k) = \binom{n}{k} p^k (1-p)^{n-k}$, $\mu = np$, $\sigma^2 = np(1-p)$.

Approximately Po(np) for small p .

Fs(p): $p(k) = p(1-p)^{k-1}$, $\mu = \frac{1}{p}$, $\sigma^2 = \frac{1-p}{p^2}$

Po(λ): $p(k) = e^{-\lambda} \frac{\lambda^k}{k!}$, $\mu = \lambda$, $\sigma^2 = \lambda$

2.8.2 Continuous distributions

U(a, b): $f(x) = \frac{1}{b-a}$ for $a < x < b$, $\mu = \frac{a+b}{2}$, $\sigma^2 = \frac{(b-a)^2}{12}$

Exp(λ): $f(x) = \lambda e^{-\lambda x}$ for $x \geq 0$, $\mu = \frac{1}{\lambda}$, $\sigma^2 = \frac{1}{\lambda^2}$

$\mathcal{N}(\mu, \sigma^2)$: $f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$. Linear combination:

$aX_1 + bX_2 + c \sim \mathcal{N}(a\mu_1 + b\mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$

Data structures (3)

OrderStatisticTree.h

Description: A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change null_type. **Time:** $\mathcal{O}(\log N)$

```
#include <bits/extc++.h>
using namespace __gnu_pbds;
```

template hash hash-cpp .bashrc

```
template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
    Tree<int> t, t2; t.insert(8);
    auto it = t.insert(10).first;
    assert(it == t.lower_bound(9));
    assert(t.order_of_key(10) == 1);
    assert(t.order_of_key(11) == 2);
    assert(*t.find_by_order(0) == 8);
    t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

HashMap.h

Description: Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
    const uint64_t C = 11(4e18 * acos(0)) | 71;
    ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({}, {}, {}, {}, {}, {1<<16});
```

SegmentTree.h

Description: Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit. **Time:** $\mathcal{O}(\log N)$

```
struct Tree {
    typedef int T;
    static constexpr T unit = 0;
    T f(T a, T b) { return max(a, b); } // (any associative fn)
    vector<T> s; int n;
    Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
    void update(int pos, T val) {
        for (s[pos += n] = val; pos /= 2;)
            s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
    }
    T query(int b, int e) { // query [b, e)
        T ra = unit, rb = unit;
        for (b += n, e += n; b < e; b /= 2, e /= 2) {
            if (b % 2) ra = f(ra, s[b++]);
            if (e % 2) rb = f(s[--e], rb);
        }
        return f(ra, rb);
    }
};
```

STWalk.h

Description: Assumes p(unit) = True. If p is monotone returns the max r such that p(f(s[l], s[l + 1], ..., s[r - 1])) = True

```
template <class F>
int search(int node, F& p, T pref) {
    if (node >= n) return node - n;
    T nex = f(pref, s[2 * node]);
    if (p(nex)) return search(2 * node + 1, p, nex);
    return search(2 * node, p, pref);
}

template <class F>
int walk(int b, int e, F& p) {
    int ee = e;
    vector<int> l, r;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
        if (b % 2) l.pb(b++);
```

```
        if (e % 2) r.pb(--e);
    }
    reverse(all(r));
    l.insert(l.end(), all(r));
    T curr = unit;
    for (auto i : l) {
        T nex = f(curr, s[i]);
        if (!p(nex)) return search(i, p, curr);
    }
    return ee;
}
```

LazySegmentTree.h

Description: Segment tree with ability to add or set values of large intervals, and compute max of intervals. Can be changed to other things. Use with a bump allocator for better performance, and SmallPtr or implicit indices to save memory.

Usage: Node* tr = new Node(v, 0, sz(v));

Time: $\mathcal{O}(\log N)$.

```
"/various/BumpAllocator.h"
34ecf5, 51 lines

const int inf = 1e9;
struct Node {
    Node *l = 0, *r = 0;
    int lo, hi, mset = inf, madd = 0, val = -inf; //=0
    Node(int lo, int hi) : lo(lo), hi(hi) {} // Large interval of -inf
    Node(vi& v, int lo, int hi) : lo(lo), hi(hi) { // hash-cpp-1
        if (lo + 1 < hi) {
            int mid = lo + (hi - lo)/2;
            l = new Node(v, lo, mid); r = new Node(v, mid, hi);
            val = max(l->val, r->val); //+
        }
        else val = v[lo];
    } // hash-cpp-1 = 34bc67
    int query(int L, int R) { // hash-cpp-2
        if (R <= lo || hi <= L) return -inf; //0
        if (L <= lo && hi <= R) return val;
        push();
        return max(l->query(L, R), r->query(L, R)); //+
    } // hash-cpp-2 = f1d44a
    void set(int L, int R, int x) { // hash-cpp-3
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) mset = val = x, madd = 0;
        //if (L <= lo && hi <= R) mset = x, val = x * (hi - lo),
            //madd = 0;
        else {
            push(), l->set(L, R, x), r->set(L, R, x);
            val = max(l->val, r->val); //+
        }
    } // hash-cpp-3 = 12aac9
    void add(int L, int R, int x) { // hash-cpp-4
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) {
            if (mset != inf) mset += x;
            else madd += x;
            val += x; // * (hi - lo);
        }
        else {
            push(), l->add(L, R, x), r->add(L, R, x);
            val = max(l->val, r->val); //+
        }
    } // hash-cpp-4 = aee0a0
    void push() { // hash-cpp-5
        if (!l) {
            int mid = lo + (hi - lo)/2;
            l = new Node(lo, mid); r = new Node(mid, hi);
        }
        if (mset != inf)
            l->set(lo,hi,mset), r->set(lo,hi,mset), mset = inf;
        else if (madd)
```

```
l->add(lo,hi,madd), r->add(lo,hi,madd), madd = 0;
} // hash-cpp-5 = 4bcf1f
};
```

LichaoTree.h

0baef3, 25 lines

```
struct LichaoTree {
    inline bool check(int i, int j, int x) {
        return fabs(f(i, x) - f(j, x)) < eps? i < j: f(i, x) > f(j,
            ↪ x);
    }
    void update(int l, int r, int cl, int cr, int idx, int val) {
        if (l <= cl && r >= cr) {
            if (check(val, tree[idx], cl) && check(val, tree[idx], cr
                ↪)) tree[idx] = val;
            else if (check(val, tree[idx], cl) || check(val, tree[idx
                ↪], cr)) {
                int mid = cl + cr >> 1;
                if (check(val, tree[idx], mid)) swap(tree[idx], val);
                if (check(val, tree[idx], cl)) update(l, r, cl, mid,
                    ↪idx << 1, val);
                else update(l, r, mid + 1, cr, idx << 1 | 1, val);
            }
            return;
        }
        int mid = cl + cr >> 1;
        if (l <= mid) update(l, r, cl, mid, idx << 1, val);
        if (r > mid) update(l, r, mid + 1, cr, idx << 1 | 1, val);
    }
    double query(int val, int cl, int cr, int idx) {
        if (cl == cr) return f(tree[idx], val);
        int mid = cl + cr >> 1;
        return max(f(tree[idx], val), val <= mid? query(val, cl,
            ↪mid, idx << 1): query(val, mid + 1, cr, idx << 1 |
            ↪1));
    }
}
```

UnionFind.h

Description: Disjoint-set data structure.

Time: $\mathcal{O}(\alpha(N))$

7aa27c, 14 lines

```
struct UF {
    vi e;
    UF(int n) : e(n, -1) {}
    bool sameSet(int a, int b) { return find(a) == find(b); }
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : e[x] = find(e[x]); }
    bool join(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (e[a] > e[b]) swap(a, b);
        e[a] += e[b]; e[b] = a;
        return true;
    }
};
```

UnionFindRollback.h

Description: Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().

Usage: int t = uf.time(); ...; uf.rollback(t);

Time: $\mathcal{O}(\log(N))$

de4ad0, 21 lines

```
struct RollbackUF {
    vi e; vector<pii> st;
    RollbackUF(int n) : e(n, -1) {}
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : find(e[x]); }
    int time() { return sz(st); }
```

```
void rollback(int t) {
    for (int i = time(); i --> t;)
        e[st[i].first] = st[i].second;
    st.resize(t);
}
bool join(int a, int b) {
    a = find(a), b = find(b);
    if (a == b) return false;
    if (e[a] > e[b]) swap(a, b);
    st.push_back({a, e[a]});
    st.push_back({b, e[b]});
    e[a] += e[b]; e[b] = a;
    return true;
}
};
```

SubMatrix.h

Description: Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).

Usage: SubMatrix<int> m(matrix);

m.sum(0, 0, 2, 2); // top left 4 elements

Time: $\mathcal{O}(N^2 + Q)$

c59ada, 13 lines

```
template<class T>
struct SubMatrix {
    vector<vector<T>>> p;
    SubMatrix(vector<vector<T>>& v) {
        int R = sz(v), C = sz(v[0]);
        p.assign(R+1, vector<T>(C+1));
        rep(r,0,R) rep(c,0,C)
            p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][c];
    }
    T sum(int u, int l, int d, int r) {
        return p[d][r] - p[d][l] - p[u][r] + p[u][l];
    }
};
```

Matrix.h

Description: Basic operations on square matrices.

Usage: Matrix<int, 3> A;

A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};

vector<int> vec = {1,2,3};

vec = (A^N) * vec;

c43c7d, 26 lines

```
template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i,0,N) rep(j,0,N)
            rep(k,0,N) a.d[i][j] += d[i][k]*m.d[k][j];
        return a;
    }
    vector<T> operator*(const vector<T>& vec) const {
        vector<T> ret(N);
        rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
        return ret;
    }
    M operator^(ll p) const {
        assert(p >= 0);
        M a, b(*this);
        rep(i,0,N) a.d[i][i] = 1;
        while (p) {
            if (p&1) a = a*b;
            b = b*b;
            p >>= 1;
        }
        return a;
    }
};
```

LineContainer.h

Description: Container where you can add lines of the form $kx+m$, and query maximum values at points x . Useful for dynamic programming (“convex hull trick”).

Time: $\mathcal{O}(\log N)$

Sec1c7, 30 lines

```
struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) { // hash-cpp-1
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    } // hash-cpp-1 = 2fac86
    void add(ll k, ll m) { // hash-cpp-2
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    } // hash-cpp-2 = 08625f
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};
```

Treap.h

Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.

Time: $\mathcal{O}(\log N)$

9556fc, 55 lines

```
struct Node { // hash-cpp-1
    Node *l = 0, *r = 0;
    int val, y, c = 1;
    Node(int val) : val(val), y(rand()) {}
    void recalc();
};

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }

template<class F> void each(Node* n, F f) {
    if (n) { each(n->l, f); f(n->val); each(n->r, f); }
} // hash-cpp-1 = cfbf7f

pair<Node*, Node*> split(Node* n, int k) { // hash-cpp-2
    if (!n) return {};
    if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
        auto pa = split(n->l, k);
        n->l = pa.second;
        n->recalc();
        return {pa.first, n};
    } else {
        auto pa = split(n->r, k - cnt(n->l) - 1); // and just "k"
        n->r = pa.first;
        n->recalc();
    }
}
```

```
        return {n, pa.second};
    }
} // hash-cpp-2 = ca03af

Node* merge(Node* l, Node* r) { // hash-cpp-3
    if (!l) return r;
    if (!r) return l;
    if (l->y > r->y) {
        l->r = merge(l->r, r);
        l->recalc();
        return l;
    } else {
        r->l = merge(l, r->l);
        r->recalc();
        return r;
    }
} // hash-cpp-3 = db131d

Node* ins(Node* t, Node* n, int pos) { // hash-cpp-4
    auto pa = split(t, pos);
    return merge(merge(pa.first, n), pa.second);
} // hash-cpp-4 = 9a5c62
```

```
// Example application: move the range [l, r) to index k
void move(Node*& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
    if (k <= l) t = merge(ins(a, b, k), c);
    else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h
Description: Computes partial sums $a[0] + a[1] + \dots + a[\text{pos} - 1]$, and updates single elements $a[i]$, taking the difference between the old and new value.
Time: Both operations are $\mathcal{O}(\log N)$.

```
struct FT { // hash-cpp-1
    vector<ll> s;
    FT(int n) : s(n) {}
    void update(int pos, ll dif) { // a[pos] += dif
        for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
    }
    ll query(int pos) { // sum of values in [0, pos)
        ll res = 0;
        for (; pos > 0; pos &= pos - 1) res += s[pos-1];
        return res;
    } // hash-cpp-1 = 585cdd
    int lower_bound(ll sum) { // min pos st sum of [0, pos] >= sum
        // Returns n if no sum is >= sum, or -1 if empty sum is.
        if (sum <= 0) return -1;
        int pos = 0;
        for (int pw = 1 << 25; pw; pw >>= 1) {
            if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
                pos += pw, sum -= s[pos-1];
        }
        return pos;
    }
};
```

FenwickTree2d.h
Description: Computes sums $a[i,j]$ for all $i < I, j < J$, and increases single elements $a[i,j]$. Requires that the elements to be updated are known in advance (call `fakeUpdate()` before `init()`).
Time: $\mathcal{O}(\log^2 N)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

"FenwickTree.h"57f07, 22 lines

```
struct FT2 {
    vector<vi> ys; vector<FT> ft;
    FT2(int limx) : ys(limx) {}
```

```
void fakeUpdate(int x, int y) {
    for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
}

void init() {
    for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
}

int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
        ft[x].update(ind(x, y), dif);
}

ll query(int x, int y) {
    ll sum = 0;
    for (; x; x &= x - 1)
        sum += ft[x-1].query(ind(x-1, y));
    return sum;
}
};
```

RMQ.h
Description: Range Minimum Queries on an array. Returns $\min(V[a], V[a + 1], \dots, V[b - 1])$ in constant time.
Usage: `RMQ rmq(values);`
`rmq.query(inclusive, exclusive);`
Time: $\mathcal{O}(|V| \log |V| + Q)$

```
template<class T>
struct RMQ {
    vector<vector<T>> jmp;
    RMQ(const vector<T>& V) : jmp(1, V) {
        for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
            jmp.emplace_back(sz(V) - pw * 2 + 1);
            rep(j, 0, sz(jmp[k]))
                jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
        }
    }
    T query(int a, int b) {
        assert(a < b); // or return inf if a == b
        int dep = 31 - __builtin_clz(b - a);
        return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
    }
};
```

MoQueries.h
Description: Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change step to add/remove the edge (a, c) and remove the initial add call (but keep in).
Time: $\mathcal{O}(N\sqrt{Q})$

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vi mo(vector<pii> Q) { // hash-cpp-1
    int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s;
    #define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
    for (int qi : s) {
        pii q = Q[qi];
        while (L > q.first) add(--L, 0);
        while (R < q.second) add(R++, 1);
        while (L < q.first) del(L++, 0);
        while (R > q.second) del(--R, 1);
        res[qi] = calc();
    }
}
```

```
return res;
} // hash-cpp-1 = 25cfac

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
    // hash-cpp-2
    int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
    add(0, 0), in[0] = 1;
    auto dfs = [&](int x, int p, int dep, auto& f) -> void {
        par[x] = p;
        L[x] = N;
        if (dep) I[x] = N++;
        for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
        if (!dep) I[x] = N++;
        R[x] = N;
    };
    dfs(root, -1, 0, dfs);
    #define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
    for (int qi : s) rep(end, 0, 2) {
        int &a = pos[end], b = Q[qi][end], i = 0;
    #define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
        else { add(c, end); in[c] = 1; } a = c; }
        while (! (L[b] <= L[a] && R[a] <= R[b]))
            I[i++] = b, b = par[b];
        while (a != b) step(par[a]);
        while (i--) step(I[i]);
        if (end) res[qi] = calc();
    }
    return res;
} // hash-cpp-2 = 446d76
```

SkewHeap.h
Description: Skew Heap. Mergeable Heaps. To make 'persistent' update merge function to return `*new*` SkewHeap

```
using T = int;
struct SkewHeap {
    SkewHeap *l = 0, *r = 0;
    T val;
    SkewHeap (T v) : val(v) {}
    static SkewHeap* merge (SkewHeap* a, SkewHeap* b) {
        if (a == 0) return b;
        if (b == 0) return a;
        if (a->val > b->val) swap(a, b);

        auto x = a->r;
        a->r = SkewHeap::merge(a->l, b);
        a->l = x;
        return a;
    };
};

T pop (SkewHeap* &a) {
    T out = a->val;
    a = SkewHeap::merge(a->l, a->r);
    return out;
};

void insert (SkewHeap* &a, T v) {
    a = SkewHeap::merge(a, new SkewHeap(v));
}
```

Numerical (4)

4.1 Polynomials and recurrences

Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val *= x) += a[i];
        return val;
    }
    void diff() {
        rep(i,1,sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
        a.pop_back();
    }
};
```

PolyRoots.h

Description: Finds the real roots to a polynomial.
Usage: polyRoots({{2,-3,1}},-1e9,1e9) // solve x²-3x+2 = 0
Time: $\mathcal{O}(n^2 \log(1/\epsilon))$

"Polynomial.h"

b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i,0,sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it,0,60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.push_back((l + h) / 2);
        }
    }
    return ret;
}
```

PolyInterpolate.h

Description: Given n points $(x[i], y[i])$, computes an $n-1$ -degree polynomial p that passes through them: $p(x) = a[0] * x^0 + \dots + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$.
Time: $\mathcal{O}(n^2)$

08bf48, 13 lines

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
```

```
    }
    return res;
}
```

BerlekampMassey.h

Description: Recovers any n -order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.
Usage: berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}
Time: $\mathcal{O}(N^2)$

"../number-theory/ModPow.h"

96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
    int n = sz(s), L = 0, m = 0;
    vector<ll> C(n), B(n), T;
    C[0] = B[0] = 1;

    ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }

    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
}
```

LinearRecurrence.h

Description: Generates the k 'th term of an n -order linear recurrence $S[i] = \sum_j S[i - j - 1]tr[j]$, given $S[0 \dots n - 1]$ and $tr[0 \dots n - 1]$. Faster than matrix multiplication. Useful together with Berlekamp-Massey.
Usage: linearRec({0, 1}, {1, 1}, k) // k 'th Fibonacci number
Time: $\mathcal{O}(n^2 \log k)$

f4e444, 26 lines

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);

    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
        res.resize(n + 1);
        return res;
    };

    Poly pol(n + 1), e(pol);
    pol[0] = e[1] = 1;

    for (++k; k; k /= 2) {
        if (k % 2) pol = combine(pol, e);
        e = combine(e, e);
    }

    ll res = 0;
    rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
    return res;
}
```

FloorSum.h

Description: Finds $\sum_{i=0}^{n-1} \left\lfloor \frac{a \cdot i + b}{m} \right\rfloor \bmod 2^{64}$.
Time: $\mathcal{O}(\log n)$

ce2fd6, 36 lines

typedef unsigned long long ull;

ull floor_sum_unsigned(ull n, ull m, ull a, ull b) { // hash-
 ↪ cpp-1
 ull ans = 0;
 while (true) {
 if (a >= m) {
 ans += n * (n - 1) / 2 * (a / m);
 a %= m;
 }
 if (b >= m) {
 ans += n * (b / m);
 b %= m;
 }
 ull y_max = a * n + b;
 if (y_max < m) break;
 n = (ull)(y_max / m);
 b = (ull)(y_max % m);
 std::swap(m, a);
 }
 return ans;
} // hash-cpp-1 = 166e9e

ll floor_sum(ll n, ll m, ll a, ll b) {
 ull ans = 0;
 if (a < 0) {
 ll a2 = a % m; if(a2 < 0) a2 += m;
 ans -= 1ULL * n * (n - 1) / 2 * (((ull)a2 - a) / m);
 a = a2;
 }
 if (b < 0) {
 ll b2 = b % m; if(b2 < 0) b2 += m;
 ans -= 1ULL * n * (((ull)b2 - b) / m);
 b = b2;
 }
 return ans + floor_sum_unsigned(n, m, a, b);
}

4.2 Optimization

GoldenSectionSearch.h

Description: Finds the argument minimizing the function f in the interval $[a, b]$ assuming f is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is eps . Works equally well for maximization with a small change in the code. See Ternary-Search.h in the Various chapter for a discrete version.
Usage: double func(double x) { return 4+x+.3*x*x; }
double xmin = gss(-1000,1000,func);
Time: $\mathcal{O}(\log((b - a)/\epsilon))$

31d45b, 14 lines

```
double gss(double a, double b, double (*f)(double)) {
    double r = (sqrt(5)-1)/2, eps = 1e-7;
    double x1 = b - r*(b-a), x2 = a + r*(b-a);
    double f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else {
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        }
    return a;
}
```

HillClimbing.h
Description: Poor man’s optimization for unimodal functions. Seeeaf, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
    pair<double, P> cur(f(start), start);
    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
        rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
            P p = cur.second;
            p[0] += dx*jmp;
            p[1] += dy*jmp;
            cur = min(cur, make_pair(f(p), p));
        }
    }
    return cur;
}
```

Integrate.h
Description: Simple integration of a function over an interval using Simpson’s rule. The error should be proportional to h^4 , although in practice you will want to verify that the result is stable to desired precision when epsilon changes. 4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

IntegrateAdaptive.h
Description: Fast integration using an adaptive Simpson’s rule.
Usage: double sphereVolume = quad(-1, 1, [](double x) {
return quad(-1, 1, [&](double y) {
return quad(-1, 1, [&](double z) {
return x*x + y*y + z*z < 1; });});});}; dc0291, 15 lines

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

template <class F>
d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}

template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
}
```

Simplex.h
Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b, x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal x (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.
Usage: vvd A = {{1,-1}, {-1,1}, {-1,-2}};
vvd b = {1,1,-4}, c = {-1,-1}, x;
T val = LPSolver(A, b, c).solve(x);
Time: $\mathcal{O}(NM * \#pivots)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}(2^n)$ in the general case. 745a0e, 68 lines

```
typedef double T; // long double, Rational, double + modP>...
typedef vector<T> vd;
```

```
typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {
    int m, n;
    vi N, B;
    vvd D;

    LPSolver(const vvd& A, const vd& b, const vd& c) :
        m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) { // hash
        ↪cpp-1
        rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
        rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
        rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
        N[n] = -1; D[m+1][n] = 1;
    } // hash-cpp-1 = 6ff8e9

    void pivot(int r, int s) { // hash-cpp-2
        T *a = D[r].data(), inv = 1 / a[s];
        rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
            T *b = D[i].data(), inv2 = b[s] * inv;
            rep(j,0,n+2) b[j] -= a[j] * inv2;
            b[s] = a[s] * inv2;
        }
        rep(j,0,n+2) if (j != s) D[r][j] *= inv;
        rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
        D[r][s] = inv;
        swap(B[r], N[s]);
    } // hash-cpp-2 = 9cd0a8

    bool simplex(int phase) { // hash-cpp-3
        int x = m + phase - 1;
        for (;;) {
            int s = -1;
            rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
            if (D[x][s] >= -eps) return true;
            int r = -1;
            rep(i,0,m) {
                if (D[i][s] <= eps) continue;
                if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                    < MP(D[r][n+1] / D[r][s], B[r])) r = i;
            }
            if (r == -1) return false;
            pivot(r, s);
        }
    } // hash-cpp-3 = f15644

    T solve(vd &x) { // hash-cpp-4
        int r = 0;
        rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
        if (D[r][n+1] < -eps) {
            pivot(r, n);
            if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
            rep(i,0,m) if (B[i] == -1) {
                int s = 0;
                rep(j,1,n+1) ltj(D[i]);
                pivot(i, s);
            }
        }
        bool ok = simplex(1); x = vd(n);
        rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
        return ok ? D[m][n+1] : inf;
    } // hash-cpp-4 = 396a95
};
```

4.3 Matrices
Determinant.h
Description: Calculates determinant of a matrix. Destroys the matrix.
Time: $\mathcal{O}(N^3)$ bd5cec, 15 lines

```
double det(vector<vector<double>>& a) {
    int n = sz(a); double res = 1;
    rep(i,0,n) {
        int b = i;
        rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
        if (i != b) swap(a[i], a[b]), res *= -1;
        res *= a[i][i];
        if (res == 0) return 0;
        rep(j,i+1,n) {
            double v = a[j][i] / a[i][i];
            if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
        }
    }
    return res;
}
```

IntDeterminant.h
Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
Time: $\mathcal{O}(N^3)$ 3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
    int n = sz(a); ll ans = 1;
    rep(i,0,n) {
        rep(j,i+1,n) {
            while (a[j][i] != 0) { // gcd step
                ll t = a[i][i] / a[j][i];
                if (t) rep(k,i,n)
                    a[i][k] = (a[i][k] - a[j][k] * t) % mod;
                swap(a[i], a[j]);
                ans *= -1;
            }
        }
        ans = ans * a[i][i] % mod;
        if (!ans) return 0;
    }
    return (ans + mod) % mod;
}
```

SolveLinear.h
Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.
Time: $\mathcal{O}(n^2m)$ 44c9ab, 38 lines

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
    int n = sz(A), m = sz(x), rank = 0, br, bc;
    if (n) assert(sz(A[0]) == m);
    vi col(m); iota(all(col), 0);

    rep(i,0,n) {
        double v, bv = 0;
        rep(r,i,n) rep(c,i,m)
            if ((v = fabs(A[r][c])) > bv)
                br = r, bc = c, bv = v;
        if (bv <= eps) {
            rep(j,i,n) if (fabs(b[j]) > eps) return -1;
            break;
        }
        swap(A[i], A[br]);
        swap(b[i], b[br]);
```

```
swap(col[i], col[bc]);
rep(j,0,n) swap(A[j][i], A[j][bc]);
bv = 1/A[i][i];
rep(j,i+1,n) {
    double fac = A[j][i] * bv;
    b[j] -= fac * b[i];
    rep(k,i+1,m) A[j][k] -= fac*A[i][k];
}
rank++;
}

x.assign(m, 0);
for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
}
return rank; // (multiple solutions if rank < m)
```

SolveLinear2.h
Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:

"SolveLinear.h"08e495, 7 lines

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
    x[col[i]] = b[i] / A[i][i];
fail:; }
```

SolveLinearBinary.h
Description: Solves $Ax = b$ over \mathbb{F}_2 . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b .
Time: $\mathcal{O}(n^2m)$

typedef bitset<1000> bs;fa2d7a, 34 lines

```
int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
    int n = sz(A), rank = 0, br;
    assert(m <= sz(x));
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if(b[j]) return -1;
            break;
        }
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        }
        rep(j,i+1,n) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        }
        rank++;
    }

    x = bs();
    for (int i = rank; i--;) {
        if (!b[i]) continue;
        x[col[i]] = 1;
        rep(j,0,i) b[j] ^= A[j][i];
    }
```

```
return rank; // (multiple solutions if rank < m)
}
```

MatrixInverse.h
Description: Invert matrix A . Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of $A \pmod p$, and k is doubled in each step.
Time: $\mathcal{O}(n^3)$

ebfff6, 35 lines

```
int matInv(vector<vector<double>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<double>> tmp(n, vector<double>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;

    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n)
            if (fabs(A[j][k]) > fabs(A[r][c]))
                r = j, c = k;
        if (fabs(A[r][c]) < 1e-12) return i;
        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
        rep(j,0,n)
            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
        swap(col[i], col[c]);
        double v = A[i][i];
        rep(j,i+1,n) {
            double f = A[j][i] / v;
            A[j][i] = 0;
            rep(k,i+1,n) A[j][k] -= f*A[i][k];
            rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
        }
        rep(j,i+1,n) A[i][j] /= v;
        rep(j,0,n) tmp[i][j] /= v;
        A[i][i] = 1;
    }

    for (int i = n-1; i > 0; --i) rep(j,0,i) {
        double v = A[j][i];
        rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
    }

    rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
    return n;
}
```

Tridiagonal.h
Description: $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type
$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, 1 \leq i \leq n,$$
where a_0, a_{n+1}, b_i, c_i and d_i are known. a can then be obtained from
$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, \dots, -1, 1\}, \{0, c_1, c_2, \dots, c_n\}, \{b_1, b_2, \dots, b_n, 0\}, \{a_0, d_1, d_2, \dots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.
If $|d_i| > |p_i| + |q_{i-1}|$ for all i , or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither tr nor the check for $\text{diag}[i] == 0$ is needed.
Time: $\mathcal{O}(N)$

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>& super,
    const vector<T>& sub, vector<T> b) {
    int n = sz(b); vi tr(n);
    rep(i,0,n-1) {
        if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
            b[i+1] -= b[i] * diag[i+1] / super[i];
            if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
            diag[i+1] = sub[i]; tr[++i] = 1;
        } else {
            diag[i+1] -= super[i]*sub[i]/diag[i];
            b[i+1] -= b[i]*sub[i]/diag[i];
        }
    }
    for (int i = n; i--;) {
        if (tr[i]) {
            swap(b[i], b[i-1]);
            diag[i-1] = diag[i];
            b[i] /= super[i-1];
        } else {
            b[i] /= diag[i];
            if (i) b[i-1] -= b[i]*super[i-1];
        }
    }
    return b;
}
```

4.4 Fourier transforms

FastFourierTransform.h
Description: $\text{fft}(a)$ computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k . N must be a power of 2. Useful for convolution: $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n , reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16} ; higher for random inputs). Otherwise, use NTT/FFTMod.
Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{22}$)

3dd197, 38 lines

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) { // hash-cpp-1
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1); // (^ 10% faster if double)
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n); rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            // C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
            auto x = (double *)&rt[j+k], y = (double *)&a[i+j+k];
            C z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*y[0]);
            a[i + j + k] = a[i + j] - z;
            a[i + j] += z;
        }
} // hash-cpp-1 = 2258f7

vd conv(const vd& a, const vd& b) { // hash-cpp-2
    if (a.empty() || b.empty()) return {};
    vd res(sz(a) + sz(b) - 1);
    int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
    vector<C> in(n), out(n);
    copy(all(a), begin(in));
```



```
rep(i,0,sz(b)) in[i].imag(b[i]);
fft(in);
for (C& x : in) x *= x;
rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
fft(out);
rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
return res;
} // hash-cpp-2 = 873509
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N\log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

```
"FastFourierTransform.h" b82773, 22 lines

typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    vl res(sz(a) + sz(b) - 1);
    int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
    rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
    fft(L), fft(R);
    rep(i,0,n) {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(outl), fft(outs);
    rep(i,0,sz(res)) {
        ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
        ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

NumberTheoreticTransform.h

Description: ntt(a) computes $\hat{f}(k) = \sum_x a[x]g^{xk}$ for all k , where $g = \text{root}^{(\text{mod}-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most 2^a . For arbitrary modulo, see FFTMod. conv(a, b) = c, where $c[x] = \sum a[i]b[x - i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$

```
"../number-theory/ModPow.h" ced03d, 36 lines

const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) { // hash-cpp-1
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vl rt(2, 1);
    for (static int k = 2, s = 2; k < n; k *= 2, s++) {
        rt.resize(n);
        ll z[] = {1, modpow(root, mod >> s)};
        rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
    }
    vl rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
            a[i + j + k] = ai - z + (z > ai ? mod : 0);
            ai += (ai + z >= mod ? z - mod : z);
        }
```

```
    }
} // hash-cpp-1 = 3b763b

vl conv(const vl &a, const vl &b) { // hash-cpp-2
    if (a.empty() || b.empty()) return {};
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
        n = 1 << B;
    int inv = modpow(n, mod - 2);
    vl L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n)
        out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
    ntt(out);
    return {out.begin(), out.begin() + s};
} // hash-cpp-2 = 3876bf
```

FastSubsetTransform.h

Description: Transform to a basis with fast convolutions of the form

$c[z] = \sum_{z=x\oplus y} a[x] \cdot b[y]$, where \oplus is one of AND, OR, XOR. The size of a must be a power of two.

Time: $\mathcal{O}(N \log N)$

```
25c175, 16 lines

void FST(vi& a, bool inv) { // hash-cpp-1
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,istep) {
            int &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pii(v - u, u) : pii(v, u + v); // AND
                // inv ? pii(v, u - v) : pii(u + v, u); // OR
                // pii(u + v, u - v); // XOR
        }
        // if (inv) for (int& x : a) x /= sz(a); // XOR only
    } // hash-cpp-1 = a727eb
    vi conv(vi a, vi b) { // hash-cpp-2
        FST(a, 0); FST(b, 0);
        rep(i,0,sz(a)) a[i] *= b[i];
        FST(a, 1); return a;
    } // hash-cpp-2 = 3cbd18
```

Number theory (5)

5.1 Modular arithmetic

ModularArithmetic.h

Description: Operators for modular arithmetic. You need to set mod to some number first and then you can use the structure.

```
"euclid.h" 35bfea, 18 lines

const ll mod = 17; // change to something else
struct Mod {
    ll x;
    Mod(ll xx) : x(xx) {}
    Mod operator+(Mod b) { return Mod((x + b.x) % mod); }
    Mod operator-(Mod b) { return Mod((x - b.x + mod) % mod); }
    Mod operator*(Mod b) { return Mod((x * b.x) % mod); }
    Mod operator/(Mod b) { return *this * invert(b); }
    Mod invert(Mod a) {
        ll x, y, g = euclid(a.x, mod, x, y);
        assert(g == 1); return Mod((x + mod) % mod);
    }
    Mod operator^(ll e) {
        if (!e) return Mod(1);
        Mod r = *this ^ (e / 2); r = r * r;
        return e&1 ? *this * r : r;
    }
};
```

ModInverse.h

Description: Pre-computation of modular inverses. Assumes $\text{LIM} \leq \text{mod}$ and that mod is a prime.

```
b4a981, 3 lines

// const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

ModPow.h

```
b83e45, 8 lines

const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
    ll ans = 1;
    for (; e; b = b * b % mod, e /= 2)
        if (e & 1) ans = ans * b % mod;
    return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used to calculate the order of a .

Time: $\mathcal{O}(\sqrt{m})$

```
c040b8, 11 lines

ll modLog(ll a, ll b, ll m) {
    ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<ll, ll> A;
    while (j <= n && (e = f = e * a % m) != b % m)
        A[e * b % m] = j++;
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        rep(i,2,n+2) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
}
```

ModSum.h

Description: Sums of mod'ed arithmetic progressions.

modsum(to, c, k, m) = $\sum_{i=0}^{\text{to}-1} (ki + c) \% m$. divsum is similar but for floored division.

Time: $\log(m)$, with a large constant.

```
5c5bc5, 16 lines

typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
```

```
ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (!k) return res;
    ull to2 = (to * k + c) / m;
    return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}
```

```
ll modsum(ull to, ll c, ll k, ll m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \pmod c$ (or $a^b \pmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.

Time: $\mathcal{O}(1)$ for modmul, $\mathcal{O}(\log b)$ for modpow

```
bbbd8f, 11 lines

typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    ll ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
```

```
for (; e; b = modmul(b, b, mod), e /= 2)
    if (e & 1) ans = modmul(ans, b, mod);
return ans;
}
```

ModSqrt.h
Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod{p}$ ($-x$ gives the other solution).
Time: $\mathcal{O}(\log^2 p)$ worst case, $\mathcal{O}(\log p)$ for most p

"ModPow.h"	19a793, 24 lines
------------	------------------

```
ll sqrt(ll a, ll p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
    ll s = p - 1, n = 2;
    int r = 0, m;
    while (s % 2 == 0)
        ++r, s /= 2;
    while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
    ll x = modpow(a, (s + 1) / 2, p);
    ll b = modpow(a, s, p), g = modpow(n, s, p);
    for (; r == m) {
        ll t = b;
        for (m = 0; m < r && t != 1; ++m)
            t = t * t % p;
        if (m == 0) return x;
        ll gs = modpow(g, 1LL << (r - m - 1), p);
        g = gs * gs % p;
        x = x * gs % p;
        b = b * g % p;
    }
}
```

5.2 Primality

FastEratosthenes.h
Description: Prime sieve for generating all primes smaller than LIM.
Time: LIM=1e9 \approx 1.5s

const int LIM = 1e6; bitset<LIM> isPrime; vi eratosthenes() { const int S = (int)round(sqrt(LIM)), R = LIM / 2; vi pr = {2}, sieve(S+1); pr.reserve(int(LIM/log(LIM)*1.1)); vector<pii> cp; for (int i = 3; i <= S; i += 2) if (!sieve[i]) { cp.push_back({i, i * i / 2}); for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1; } for (int L = 1; L <= R; L += S) { array<bool, S> block{}; for (auto &[p, idx] : cp) for (int i=idx; i < S+L; idx = (i+=p)) block[i-L] = 1; rep(i,0,min(S, R - L)) if (!block[i]) pr.push_back((L + i) * 2 + 1); } for (int i : pr) isPrime[i] = 1; return pr; }	6b2912, 20 lines
--	------------------

MillerRabin.h
Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.
Time: 7 times the complexity of $a^b \bmod c$.

"ModMulLL.h"	60dcd1, 12 lines
--------------	------------------

```
bool isPrime(u11 n) {
```

```
if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
u11 A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
s = __builtin_ctzll(n-1), d = n >> s;
for (u11 a : A) { // ^ count trailing zeroes
    u11 p = modpow(a%n, d, n), i = s;
    while (p != 1 && p != n - 1 && a % n && i--)
        p = modmul(p, p, n);
    if (p != n-1 && i != s) return 0;
}
return 1;
}
```

Factor.h
Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
Time: $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h"	d8d98d, 18 lines
-------------------------------	------------------

```
u11 pollard(u11 n) {
    u11 x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    auto f = [&](u11 x) { return modmul(x, x, n) + i; };
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
        x = f(x), y = f(f(y));
    }
    return __gcd(prd, n);
}
vector<u11> factor(u11 n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    u11 x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), all(r));
    return l;
}
}
```

5.3 Divisibility

euclid.h
Description: Finds two integers x and y , such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If a and b are coprime, then x is the inverse of $a \pmod{b}$.

ll euclid(ll a, ll b, ll &x, ll &y) { if (!b) return x = 1, y = 0, a; ll d = euclid(b, a % b, y, x); return y -= a/b * x, d; }	33ba8f, 5 lines
--	-----------------

CRT.h
Description: Chinese Remainder Theorem.
crt(a, m, b, n) computes x such that $x \equiv a \pmod{m}, x \equiv b \pmod{n}$. If $|a| < m$ and $|b| < n$, x will obey $0 \leq x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.
Time: $\log(n)$

"euclid.h"	04d93a, 7 lines
------------	-----------------

```
ll crt(ll a, ll m, ll b, ll n) {
    if (n > m) swap(a, b), swap(m, n);
    ll x, y, g = euclid(m, n, x, y);
    assert((a - b) % g == 0); // else no solution
    x = (b - a) % n * x % n / g * m + a;
    return x < 0 ? x + m*n/g : x;
}
```

5.3.1 Bézout’s identity
For $a \neq, b \neq 0$, then $d = \gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h
Description: Euler’s ϕ function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n . $\phi(1) = 1, p$ prime $\Rightarrow \phi(p^k) = (p - 1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} \dots p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1-1} \dots (p_r - 1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n} (1 - 1/p)$.
 $\sum_{d|n} \phi(d) = n, \sum_{1 \leq k \leq n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$
Euler’s thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod{n}$.
Fermat’s little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod{p} \forall a$.

const int LIM = 5000000; int phi[LIM]; void calculatePhi() { rep(i,0,LIM) phi[i] = i&1 ? i : i/2; for (int i = 3; i < LIM; i += 2) if(phi[i] == i) for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i; }	cf7d6d, 8 lines
--	-----------------

5.4 Fractions

ContinuedFractions.h
Description: Given N and a real number $x \geq 0$, finds the closest rational approximation p/q with $p, q \leq N$. It will obey $|p/q - x| \leq 1/qN$.
For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. (p_k/q_k alternates between $> x$ and $< x$.) If x is rational, y eventually becomes ∞ ; if x is the root of a degree 2 polynomial the a ’s eventually become cyclic.
Time: $\mathcal{O}(\log N)$

typedef double d; // for N ~ 1e7; long double for N ~ 1e9 pair<ll, ll> approximate(d x, ll N) { ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x; for (;) { ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf), a = (ll)floor(y), b = min(a, lim), NP = b*P + LP, NQ = b*Q + LQ; if (a > b) { // If b > a/2, we have a semi-convergent that gives us a // better approximation; if b = a/2, we *may* have one. // Return {P, Q} here for a more canonical approximation. return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ? make_pair(NP, NQ) : make_pair(P, Q); } if (abs(y = 1/(y - (d)a)) > 3*N) { return {NP, NQ}; } LP = P; P = NP; LQ = Q; Q = NQ; } }	dd6c5e, 21 lines
---	------------------

FracBinarySearch.h
Description: Given f and N , finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \leq N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.

Usage: fracBS([](Frac f) { return f.p>=3*f.q; }, 10); // {1,3}
Time: $\mathcal{O}(\log(N))$

27ab3e, 25 lines

```

struct Frac { ll p, q; };

```

```

template<class F>
Frac fracBS(F f, ll N) {
    bool dir = 1, A = 1, B = 1;
    Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
    if (f(lo)) return lo;
    assert (f(hi));
    while (A || B) {
        ll adv = 0, step = 1; // move hi if dir, else lo
        for (int si = 0; step; (step *= 2) >= si) {
            adv += step;
            Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
            if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
                adv -= step; si = 2;
            }
        }
        hi.p += lo.p * adv;
        hi.q += lo.q * adv;
        dir = !dir;
        swap(lo, hi);
        A = B; B = !!adv;
    }
    return dir ? hi : lo;
}

```

5.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \; b = k \cdot (2mn), \; c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

5.6 Primes

$p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a , except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

5.7 Estimates

$\sum_{d \mid n} d = O(n \log \log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

5.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d \mid n} f(d) \Leftrightarrow f(n) = \sum_{d \mid n} \mu(d) g(n/d)$$

Other useful formulas/forms:

IntPerm multinomial

$\sum_{d \mid n} \mu(d) = [n = 1]$ (very useful)

$$g(n) = \sum_{n \mid d} f(d) \Leftrightarrow f(n) = \sum_{n \mid d} \mu(d/n) g(d)$$

$$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$$

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

IntPerm.h

Description: Permutation -> integer conversion. (Not order preserving.)

Integer -> permutation can use a lookup table.

Time: $\mathcal{O}(n)$

044568, 6 lines

```

int permToInt(vi& v) {
    int use = 0, i = 0, r = 0;
    for (int x:v) r = r * ++i + __builtin_popcount(use & ~(1<<x)),
        use |= 1 << x; // (note: minus, not ~!)
    return r;
}

```

6.1.2 Cycles

Let $g_S(n)$ be the number of n -permutations whose cycle lengths all belong to the set S . Then

$$\sum_{n=0}^\infty g_S(n) \frac{x^n}{n!} = \exp \left(\sum_{n \in S} \frac{x^n}{n} \right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1) + D(n-2)) = nD(n-1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

6.1.4 Burnside’s lemma

Given a group G of symmetries and a set X , the number of elements of X *up to symmetry* equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

10

If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k \mid n} f(k) \phi(n/k).$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \; p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	$\sim 2e5$	$\sim 2e8$

6.2.2 Lucas’ Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + \dots + n_1 p + n_0$ and $m = m_k p^k + \dots + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod{p}$.

6.2.3 Binomials

multinomial.h

Description: Computes $\binom{k_1 + \dots + k_n}{k_1, k_2, \dots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \dots k_n!}$.

a0a312, 6 lines

```

ll multinomial(vi& v) {
    ll c = 1, m = v.empty() ? 1 : v[0];
    rep(i, 1, sz(v)) rep(j, 0, v[i])
        c = c * ++m / (j+1);
    return c;
}

```

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able).

$$B[0, \dots] = [1, -\tfrac{1}{2}, \tfrac{1}{6}, 0, -\tfrac{1}{30}, 0, \tfrac{1}{42}, \dots]$$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^\infty f(i) = \int_m^\infty f(x) dx - \sum_{k=1}^\infty \frac{B_k}{k!} f^{(k-1)}(m)$$

$$\approx \int_m^\infty f(x) dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n,k)=c(n-1,k-1)+(n-1)c(n-1,k),\; c(0,0)=1$$
$$\sum_{k=0}^nc(n,k)x^k=x(x+1)\ldots(x+n-1)$$

$$c(8,k)=8,0,5040,13068,13132,6769,1960,322,28,1$$
$$c(n,2)=0,0,1,3,11,50,274,1764,13068,109584,\ldots$$

6.3.3 Eulerian numbers

Number of permutations $\pi\in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j)>\pi(j+1)$, $k+1$ j :s s.t. $\pi(j)\geq j$, k j :s s.t. $\pi(j)>j$.

$$E(n,k)=(n-k)E(n-1,k-1)+(k+1)E(n-1,k)$$
$$E(n,0)=E(n,n-1)=1$$
$$E(n,k)=\sum_{j=0}^k(-1)^j\binom{n+1}{j}(k+1-j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n,k)=S(n-1,k-1)+kS(n-1,k)$$
$$S(n,1)=S(n,n)=1$$
$$S(n,k)=\frac{1}{k!}\sum_{j=0}^k(-1)^{k-j}\binom{k}{j}j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n)=1,1,2,5,15,52,203,877,4140,21147,\ldots$ For p prime,

$$B(p^m+n)\equiv mB(n)+B(n+1)\pmod{p}$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i : $n_1n_2\cdots n_kn^{k-2}$
with degrees d_i : $(n-2)!/(d_1-1)!\cdots(d_n-1)!$

6.3.7 Catalan numbers

$$C_n=\frac{1}{n+1}\binom{2n}{n}=\binom{2n}{n}-\binom{2n}{n+1}=\frac{(2n)!}{(n+1)!n!}$$
$$C_0=1,\; C_{n+1}=\frac{2(2n+1)}{n+2}C_n,\; C_{n+1}=\sum C_iC_{n-i}$$
$$C_n=1,1,2,5,14,42,132,429,1430,4862,16796,58786,\ldots$$

- sub-diagonal monotone paths in an $n\times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).

BellmanFord FloydWarshallTopoSort PushRelabel

- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

Graph (7)

7.1 Fundamentals

BellmanFord.h

Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get $\text{dist} = \text{inf}$; nodes reachable through negative-weight cycles get $\text{dist} = -\text{inf}$. Assumes $V^2\max|w_i|<\sim 2^{63}$.
Time: $\mathcal{O}(VE)$

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
    nodes[s].dist = 0;
    sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

    int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
    rep(i,0,lim) for (Ed ed : eds) {
        Node cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        ll d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = (i < lim-1 ? d : -inf);
        }
    }
    rep(i,0,lim) for (Ed e : eds) {
        if (nodes[e.a].dist == -inf)
            nodes[e.b].dist = -inf;
    }
}
```

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m , where $m[i][j] = \text{inf}$ if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j , inf if no path, or $-\text{inf}$ if the path goes through a negative-weight cycle.
Time: $\mathcal{O}(N^3)$

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
    int n = sz(m);
    rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
    rep(k,0,n) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) {
            auto newDist = max(m[i][k] + m[k][j], -inf);
            m[i][j] = min(m[i][j], newDist);
        }
    rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

TopoSort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n – nodes reachable from cycles will not be returned.
Time: $\mathcal{O}(|V|+|E|)$

```
vi topoSort(const vector<vi>& gr) {
```

```
vi indeg(sz(gr)), ret;
for (auto& li : gr) for (int x : li) indeg[x]++;
queue<int> q; // use priority_queue for lexic. largest ans.
rep(i,0,sz(gr)) if (indeg[i] == 0) q.push(i);
while (!q.empty()) {
    int i = q.front(); // top() for priority queue
    ret.push_back(i);
    q.pop();
    for (int x : gr[i])
        if (--indeg[x] == 0) q.push(x);
}
return ret;
}
```

7.2 Network flow

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}(V^2\sqrt{E})$

```
0ae1d4, 48 lines

struct PushRelabel {
    struct Edge { // hash-cpp-1
        int dest, back;
        ll f, c;
    };
    vector<vector<Edge>> g;
    vector<ll> ec;
    vector<Edge*> cur;
    vector<vi> hs; vi H;
    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {} //
        ↪ hash-cpp-1 = 4de9df

    void addEdge(int s, int t, ll cap, ll rcap=0) { // hash-cpp-2
        if (s == t) return;
        g[s].push_back({t, sz(g[t]), 0, cap});
        g[t].push_back({s, sz(g[s])-1, 0, rcap});
    } // hash-cpp-2 = 817b95

    void addFlow(Edge& e, ll f) { // hash-cpp-3
        Edge &back = g[e.dest][e.back];
        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
        e.f += f; e.c -= f; ec[e.dest] += f;
        back.f -= f; back.c += f; ec[back.dest] -= f;
    } // hash-cpp-3 = 340b4e
    ll calc(int s, int t) { // hash-cpp-4
        int v = sz(g); H[s] = v; ec[t] = 1;
        vi co(2*v); co[0] = v-1;
        rep(i,0,v) cur[i] = g[i].data();
        for (Edge& e : g[s]) addFlow(e, e.c);

        for (int hi = 0;;) {
            while (hs[hi].empty()) if (!hi--) return -ec[s];
            int u = hs[hi].back(); hs[hi].pop_back();
            while (ec[u] > 0) // discharge u
                if (cur[u] == g[u].data() + sz(g[u])) {
                    H[u] = 1e9;
                    for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
                        H[u] = H[e.dest]+1, cur[u] = &e;
                    if (++co[H[u]], !--co[hi] && hi < v)
                        rep(i,0,v) if (hi < H[i] && H[i] < v)
                            --co[H[i]], H[i] = v + 1;
                    hi = H[u];
                }
            else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
                addFlow(*cur[u], min(ec[u], cur[u]->c));
            else ++cur[u];
        }
    } // hash-cpp-4 = 291fbf
```

```
bool leftOfMinCut(int a) { return H[a] >= sz(g); }
};
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(FE \log(V))$ where F is max flow. $\mathcal{O}(VE)$ for setpi.

135b73, 78 lines

```
// #include <bits/extc++.h>

const ll INF = numeric_limits<ll>::max() / 4;

struct MCMF {
    struct edge { // hash-cpp-1
        int from, to, rev;
        ll cap, cost, flow;
    };
    int N;
    vector<vector<edge>> ed;
    vi seen;
    vector<ll> dist, pi;
    vector<edge*> par;

    MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}
    // hash-cpp-1 = 4313b6

    void addEdge(int from, int to, ll cap, ll cost) { // hash-cpp
        // -2
        if (from == to) return;
        ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
        ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
    } // hash-cpp-2 = c71528

    void path(int s) { // hash-cpp-3
        fill(all(seen), 0);
        fill(all(dist), INF);
        dist[s] = 0; ll di;

        __gnu_pbds::priority_queue<pair<ll, int>> q;
        vector<decltype(q)::point_iterator> its(N);
        q.push({ 0, s });

        while (!q.empty()) {
            s = q.top().second; q.pop();
            seen[s] = 1; di = dist[s] + pi[s];
            for (edge& e : ed[s]) if (!seen[e.to]) {
                ll val = di - pi[e.to] + e.cost;
                if (e.cap - e.flow > 0 && val < dist[e.to]) {
                    dist[e.to] = val;
                    par[e.to] = &e;
                    if (its[e.to] == q.end())
                        its[e.to] = q.push({ -dist[e.to], e.to });
                    else
                        q.modify(its[e.to], { -dist[e.to], e.to });
                }
            }
            rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
        } // hash-cpp-3 = 7e4cbe

        pair<ll, ll> maxflow(int s, int t) { // hash-cpp-4
            ll totflow = 0, totcost = 0;
            while (path(s), seen[t]) {
                ll fl = INF;
                for (edge* x = par[t]; x; x = par[x->from])
                    fl = min(fl, x->cap - x->flow);

                totflow += fl;
```

```
                for (edge* x = par[t]; x; x = par[x->from]) {
                    x->flow += fl;
                    ed[x->to][x->rev].flow -= fl;
                }
            }
            rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
            return {totflow, totcost/2};
        } // hash-cpp-4 = 24f5a0
        // If some costs can be negative, call this before maxflow:
        void setpi(int s) { // (otherwise, leave this out) // hash-
            // -5
            fill(all(pi), INF); pi[s] = 0;
            int it = N, ch = 1; ll v;
            while (ch-- && it--)
                rep(i,0,N) if (pi[i] != INF)
                    for (edge& e : ed[i]) if (e.cap)
                        if ((v = pi[i] + e.cost) < pi[e.to])
                            pi[e.to] = v, ch = 1;
            assert(it >= 0); // negative cost cycle
        } // hash-cpp-5 = 6847d8
    };
};
```

EdmondsKarp.h

Description: Flow algorithm with guaranteed complexity $\mathcal{O}(VE^2)$. To get edge flow values, compare capacities before and after, and take the positive values only.

482fe0, 36 lines

```
template<class T> T edmondsKarp(vector<unordered_map<int, T>>&
    graph, int source, int sink) { // hash-cpp-1
    assert(source != sink);
    T flow = 0;
    vi par(sz(graph)), q = par;

    for (;;) {
        fill(all(par), -1);
        par[source] = 0;
        int ptr = 1;
        q[0] = source;

        rep(i,0,ptr) {
            int x = q[i];
            for (auto e : graph[x]) {
                if (par[e.first] == -1 && e.second > 0) {
                    par[e.first] = x;
                    q[ptr++] = e.first;
                    if (e.first == sink) goto out;
                }
            }
        }
        return flow; // hash-cpp-1 = ef75ac
    out:
    T inc = numeric_limits<T>::max();
    for (int y = sink; y != source; y = par[y])
        inc = min(inc, graph[par[y]][y]);

    flow += inc;
    for (int y = sink; y != source; y = par[y]) {
        int p = par[y];
        if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
        graph[y][p] += inc;
    }
}

Dinic.h
Description: Flow algorithm with complexity  $\mathcal{O}(VE \log U)$  where  $U = \max|cap|$ .  $\mathcal{O}(\min(E^{1/2}, V^{2/3})E)$  if  $U = 1$ ;  $\mathcal{O}(\sqrt{VE})$  for bipartite match-
ing.
d7f0f1, 42 lines
```

```
struct Dinic {
    struct Edge { // hash-cpp-1
        int to, rev;
        ll c, oc;
        ll flow() { return max(oc - c, 0LL); } // if you need flows
    };
    vi lvl, ptr, q;
    vector<vector<Edge>> adj;
    Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
    void addEdge(int a, int b, ll c, ll rcap = 0) {
        adj[a].push_back({b, sz(adj[b]), c, c});
        adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
    } // hash-cpp-1 = a9ee70
    ll dfs(int v, int t, ll f) { // hash-cpp-2
        if (v == t || !f) return f;
        for (int& i = ptr[v]; i < sz(adj[v]); i++) {
            Edge& e = adj[v][i];
            if (lvl[e.to] == lvl[v] + 1)
                if (ll p = dfs(e.to, t, min(f, e.c))) {
                    e.c -= p, adj[e.to][e.rev].c += p;
                    return p;
                }
        }
        return 0;
    } // hash-cpp-2 = 0922b8
    ll calc(int s, int t) { // hash-cpp-3
        ll flow = 0; q[0] = s;
        rep(L,0,31) do { // 'int L=30' maybe faster for random data
            lvl = ptr = vi(sz(q));
            int qi = 0, qe = lvl[s] = 1;
            while (qi < qe && !lvl[t]) {
                int v = q[qi++];
                for (Edge e : adj[v])
                    if (!lvl[e.to] && e.c >> (30 - L))
                        q[qi++] = e.to, lvl[e.to] = lvl[v] + 1;
            }
            while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
        } while (lvl[t]);
        return flow;
    } // hash-cpp-3 = 3eb6d1
    bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s , only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.

Time: $\mathcal{O}(V^3)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
    pair<int, vi> best = {INT_MAX, {}};
    int n = sz(mat);
    vector<vi> co(n);
    rep(i,0,n) co[i] = {i};
    rep(ph,1,n) {
        vi w = mat[0];
        size_t s = 0, t = 0;
        rep(it,0,n-ph) { //  $\mathcal{O}(V^2) \rightarrow \mathcal{O}(E \log V)$  with prio. queue
            w[t] = INT_MIN;
            s = t, t = max_element(all(w)) - w.begin();
            rep(i,0,n) w[i] += mat[t][i];
        }
        best = min(best, {w[t] - mat[t][t], co[t]});
        co[s].insert(co[s].end(), all(co[t]));
    }
```

```
    rep(i,0,n) mat[s][i] += mat[t][i];
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
}
return best;
}
```

GomoryHu.h
Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.
Time: $\mathcal{O}(V)$ Flow Computations

"PushRelabel.h"	0418b3, 13 lines
-----------------	------------------

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
    vector<Edge> tree;
    vi par(N);
    rep(i,1,N) {
        PushRelabel D(N); // Dinic also works
        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
        tree.push_back({i, par[i], D.calc(i, par[i])});
        rep(j,i+1,N)
            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
    }
    return tree;
}
```

7.3 Matching

hopcroftKarp.h
Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Usage: vi btoa(m, -1); hopcroftKarp(g, btoa);
Time: $\mathcal{O}(\sqrt{VE})$

f612e4, 42 lines

```
bool dfs(int a, int L, vector<vi>& g, vi& btoa, vi& A, vi& B) {
    ↪ // hash-cpp-1
    if (A[a] != L) return 0;
    A[a] = -1;
    for (int b : g[a]) if (B[b] == L + 1) {
        B[b] = 0;
        if (btoa[b] == -1 || dfs(btoa[b], L + 1, g, btoa, A, B))
            return btoa[b] = a, 1;
    }
    return 0;
} // hash-cpp-1 = 9e7938
```

```
int hopcroftKarp(vector<vi>& g, vi& btoa) { // hash-cpp-2
    int res = 0;
    vi A(g.size()), B(btoa.size()), cur, next;
    for (;) {
        fill(all(A), 0);
        fill(all(B), 0);
        cur.clear();
        for (int a : btoa) if (a != -1) A[a] = -1;
        rep(a,0,sz(g)) if (A[a] == 0) cur.push_back(a);
        for (int lay = 1; ; lay++) {
            bool islast = 0;
            next.clear();
            for (int a : cur) for (int b : g[a]) {
                if (btoa[b] == -1) {
                    B[b] = lay;
                    islast = 1;
                }
                else if (btoa[b] != a && !B[b]) {
                    B[b] = lay;
                    next.push_back(btoa[b]);
                }
            }
        }
    }
}
```

```
    }
    }
    if (islast) break;
    if (next.empty()) return res;
    for (int a : next) A[a] = lay;
    cur.swap(next);
}
rep(a,0,sz(g))
    res += dfs(a, 0, g, btoa, A, B);
} // hash-cpp-2 = 1b579b
```

DFSMatching.h
Description: Simple bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Usage: vi btoa(m, -1); dfsMatching(g, btoa);
Time: $\mathcal{O}(VE)$

522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
    if (btoa[j] == -1) return 1;
    vis[j] = 1; int di = btoa[j];
    for (int e : g[di])
        if (!vis[e] && find(e, g, btoa, vis)) {
            btoa[e] = di;
            return 1;
        }
    return 0;
}
int dfsMatching(vector<vi>& g, vi& btoa) {
    vi vis;
    rep(i,0,sz(g)) {
        vis.assign(sz(btoa), 0);
        for (int j : g[i])
            if (find(j, g, btoa, vis)) {
                btoa[j] = i;
                break;
            }
    }
    return sz(btoa) - (int)count(all(btoa), -1);
}
```

MinimumVertexCover.h
Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"DFSMatching.h"	da4196, 20 lines
-----------------	------------------

```
vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = dfsMatching(g, match);
    vector<bool> lfound(n, true), seen(m);
    for (int it : match) if (it != -1) lfound[it] = false;
    vi q, cover;
    rep(i,0,n) if (lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int i = q.back(); q.pop_back();
        lfound[i] = 1;
        for (int e : g[i]) if (!seen[e] && match[e] != -1) {
            seen[e] = true;
            q.push_back(match[e]);
        }
    }
    rep(i,0,n) if (!lfound[i]) cover.push_back(i);
    rep(i,0,m) if (seen[i]) cover.push_back(n+i);
    assert (sz(cover) == res);
    return cover;
}
```

WeightedMatching.h
Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j] and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires $N \leq M$.
Time: $\mathcal{O}(N^2M)$

1e0fe9, 31 lines

```
pair<int, vi> hungarian(const vector<vi> &a) {
    if (a.empty()) return {0, {}};
    int n = sz(a) + 1, m = sz(a[0]) + 1;
    vi u(n), v(m), p(m), ans(n - 1);
    rep(i,1,n) {
        p[0] = i;
        int j0 = 0; // add "dummy" worker 0
        vi dist(m, INT_MAX), pre(m, -1);
        vector<bool> done(m + 1);
        do { // dijkstra
            done[j0] = true;
            int i0 = p[j0], j1, delta = INT_MAX;
            rep(j,1,m) if (!done[j]) {
                auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
                if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
                if (dist[j] < delta) delta = dist[j], j1 = j;
            }
            rep(j,0,m) {
                if (done[j]) u[p[j]] += delta, v[j] -= delta;
                else dist[j] -= delta;
            }
            j0 = j1;
        } while (p[j0]);
        while (j0) { // update alternating path
            int j1 = pre[j0];
            p[j0] = p[j1], j0 = j1;
        }
    }
    rep(j,1,m) if (p[j]) ans[p[j] - 1] = j - 1;
    return {-v[0], ans}; // min cost
}
```

GeneralMatching.h
Description: Matching for general graphs. Fails with probability N/mod .
Time: $\mathcal{O}(N^3)$

"../numerical/MatrixInverse-mod.h"	cb1912, 41 lines
------------------------------------	------------------

```
vector<pii> generalMatching(int N, vector<pii>& ed) { // hash-
    ↪ cpp-1
    vector<vector<ll>> mat(N, vector<ll>(N)), A;
    for (pii pa : ed) {
        int a = pa.first, b = pa.second, r = rand() % mod;
        mat[a][b] = r, mat[b][a] = (mod - r) % mod;
    }

    int r = matInv(A = mat), M = 2*N - r, fi, fj;
    assert (r % 2 == 0);

    if (M != N) do {
        mat.resize(M, vector<ll>(M));
        rep(i,0,N) {
            mat[i].resize(M);
            rep(j,N,M) {
                int r = rand() % mod;
                mat[i][j] = r, mat[j][i] = (mod - r) % mod;
            }
        }
    } while (matInv(A = mat) != M); // hash-cpp-1 = c9966b

    vi has(M, 1); vector<pii> ret; // hash-cpp-2
    rep(it,0,M/2) {
        rep(i,0,M) if (has[i])
```

```
        rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
            fi = i; fj = j; goto done;
        } assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw,0,2) {
        ll a = modpow(A[fi][fj], mod-2);
        rep(i,0,M) if (has[i] && A[i][fj]) {
            ll b = A[i][fj] * a % mod;
            rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
        }
        swap(fi,fj);
    }
}
return ret; // hash-cpp-2 = 3a2ba4
}
}
```

7.4 DFS algorithms

SCC.h
Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.
Usage: scc(graph, [&](vi& v) { ... }) visits all components in reverse topological order. comp[i] holds the component index of a node (a component only has edges to components with lower index). ncomps will contain the number of components.
Time: $\mathcal{O}(E + V)$

76b5c9, 24 lines

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) { // hash
    ↪-cpp-1
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ?: dfs(e,g,f));

    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncomps;
            cont.push_back(x);
        } while (x != j);
        f(cont); cont.clear();
        ncomps++;
    }
    return val[j] = low;
} // hash-cpp-1 = 3513bd
template<class G, class F> void scc(G& g, F f) { // hash-cpp-2
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
} // hash-cpp-2 = 56b050
```

BiconnectedComponents.h
Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two distinct paths between any two nodes. Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.
Usage: int eid = 0; ed.resize(N);
for each edge (a,b) {
ed[a].emplace_back(b, eid);
ed[b].emplace_back(a, eid++); }
bicomps([&](const vi& edgelist) {...});
Time: $\mathcal{O}(E + V)$

c6b7c7, 32 lines

```
vi num, st;
```

```
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
    int me = num[at] = ++Time, top = me;
    for (auto [y, e] : ed[at]) if (e != par) {
        if (num[y]) {
            top = min(top, num[y]);
            if (num[y] < me)
                st.push_back(e);
        } else {
            int si = sz(st);
            int up = dfs(y, e, f);
            top = min(top, up);
            if (up == me) {
                st.push_back(e);
                f(vi(st.begin() + si, st.end()));
                st.resize(si);
            }
            else if (up < me) st.push_back(e);
            else { /* e is a bridge */ }
        }
    }
    return top;
}

template<class F>
void bicomps(F f) {
    num.assign(sz(ed), 0);
    rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

TwinCut.h
Description: Twin-Cut Tree. Be careful with the root.

d83564, 62 lines

```
using vvi = vector<vi>;
struct TwinCut { // hash-cpp-1
    vvi _adj;
    int n;
    vvi adj;
    vi par, art, ord, pari, topo, lo;
    int dfs(vvi &adj, int u) {
        lo[u] = ord[u] = sz(topo);
        topo.push_back(u);
        for (auto v : adj[u]) {
            if (ord[v] == -1) {
                pari[v] = u;
                lo[u] = min(lo[u], dfs(adj, v));
            } else if (v != pari[u]) {
                lo[u] = min(lo[u], ord[v]);
            }
        }
        return lo[u];
    }
}
TwinCut(vvi adj_o) : _adj(adj_o), n(sz(_adj)), adj(2 * n),
    ↪par(2 * n), art(n), ord(n, -1), pari(n), lo(n) {
    dfs(adj_o, 0);
    rep(i, 0, n) {
        int u = topo[i];
        par[2 * u + 1] = 2 * u;
        if (i) {
            int p = pari[u];
            if (lo[u] >= ord[p]) {
                par[2 * u] = 2 * p + 1;
                art[p] = 1;
            } else {
                par[2 * u] = 2 * p;
            }
        }
    }
}
```

```
    }
    art[0] = count(all(pari), 0) > 2;
    rep(i, 1, 2 * n) {
        adj[par[i]].push_back(i);
        adj[i].push_back(par[i]);
    }
} // hash-cpp-1 = d457be

void trav(vvi adj) { // hash-cpp-2
    TwinCut tree(adj);
    vi vis(2 * sz(adj));
    rep(i, 1, sz(adj)) {
        if (vis[2 * i] == 0) continue;
        if (sz(adj[i]) == 1) continue;
        vi st = {2 * i};
        vis[2 * i] = i;
        while (!st.empty()) {
            int u = st.back(); st.pop_back();
            if (u & 1) continue;
            for (auto v : tree.adj[u]) {
                if (vis[v] == i) continue;
                if (tree.ord[v / 2] < tree.lo[u / 2]) continue;
                vis[v] = i;
                st.push_back(v);
            }
        }
    } // hash-cpp-2 = a1bf62
```

2sat.h
Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $a||b)&&(!a||c)&&(d||!b)&&...$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).
Usage: TwoSat ts(number of boolean variables);
ts.either(0, ~3); // Var 0 is true or var 3 is false
ts.setValue(2); // Var 2 is true
ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true
ts.solve(); // Returns true iff it is solvable
ts.values[0..N-1] holds the assigned values to the vars
Time: $\mathcal{O}(N + E)$, where N is the number of boolean variables, and E is the number of clauses.

5f9706, 55 lines

```
struct TwoSat {
    int N;
    vector<vi> gr;
    vi values; // 0 = false, 1 = true

    TwoSat(int n = 0) : N(n), gr(2*n) {}

    int addVar() { // (optional)
        gr.emplace_back();
        gr.emplace_back();
        return N++;
    }

    void either(int f, int j) { // hash-cpp-1
        f = max(2*f, -1-2*f);
        j = max(2*j, -1-2*j);
        gr[f].push_back(j^1);
        gr[j].push_back(f^1);
    } // hash-cpp-1 = 516db0
    void setValue(int x) { either(x, x); } //e7ae31
    void atMostOne(const vi& li) { // (optional) // hash-cpp-2
        if (sz(li) <= 1) return;
        int cur = ~li[0];
        rep(i,2,sz(li)) {
            int next = addVar();
```

```
        either(cur, ~li[i]);
        either(cur, next);
        either(~li[i], next);
        cur = ~next;
    }
    either(cur, ~li[1]);
} // hash-cpp-2 = 10f2ea

vi val, comp, z; int time = 0; // hash-cpp-3
int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
        low = min(low, val[e] ? dfs(e));
    if (low == val[i]) do {
        x = z.back(); z.pop_back();
        comp[x] = low;
        if (values[x>>1] == -1)
            values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
} // hash-cpp-3 = d4b021

bool solve() { // hash-cpp-4
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
} // hash-cpp-4 = 2bb76d
};
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}(V + E)$

780b64, 15 lines

```
vi eulerWalk(vector<vector<pii>&& gr, int nedges, int src=0) {
    int n = sz(gr);
    vi D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
        if (it == end){ ret.push_back(x); s.pop_back(); continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;
            eu[e] = 1; s.push_back(y);
        }
    }
    for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
    return {ret.rbegin(), ret.rend()};
}
```

7.5 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D , computes a $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. (D -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

Time: $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
    for (pii e : eds) ++cc[e.first], ++cc[e.second];
    int u, v, ncols = *max_element(all(cc)) + 1;
    vector<vi> adj(N, vi(ncols, -1));
    for (pii e : eds) {
```

```
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);
        int at = u, end = u, d, c = free[u], ind = 0, i = 0;
        while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
            loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
        cc[loc[d]] = c;
        for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
            swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
        while (adj[fan[i]][d] != -1) {
            int left = fan[i], right = fan[++i], e = cc[i];
            adj[u][e] = left;
            adj[left][e] = u;
            adj[right][e] = -1;
            free[right] = e;
        }
        adj[u][d] = fan[i];
        adj[fan[i]][d] = u;
        for (int y : {fan[0], u, end})
            for (int& z = free[y] = 0; adj[y][z] != -1; z++);
    }
    rep(i,0,sz(eds))
        for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
    return ret;
}
```

7.6 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, q, S, old;
    void init(vv& r) { // hash-cpp-1
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
        sort(all(r), [](auto a, auto b) { return a.d > b.d; });
        int mxD = r[0].d;
        rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
    }
```

```
    } // hash-cpp-1 = 7c428e
    void expand(vv& R, int lev = 1) { // hash-cpp-2
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
        while (sz(R)) {
            if (sz(q) + R.back().d <= sz(qmax)) return;
            q.push_back(R.back().i);
            vv T;
            for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
            if (sz(T)) {
                if (S[lev]++ / ++pk < limit) init(T);
                int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
                C[1].clear(), C[2].clear();
                for (auto v : T) {
                    int k = 1;
                    auto f = [&](int i) { return e[v.i][i]; };
                    while (any_of(all(C[k]), f)) k++;
                    if (k > mxk) mxk = k, C[mxk + 1].clear();
                    if (k < mnk) T[j++].i = v.i;
                    C[k].push_back(v.i);
                }
                if (j > 0) T[j - 1].d = 0;
                rep(k,mnk,mxk + 1) for (int i : C[k])
                    T[j].i = i, T[j++].d = k;
                expand(T, lev + 1);
            } else if (sz(q) > sz(qmax)) qmax = q;
            q.pop_back(), R.pop_back();
        }
    } // hash-cpp-2 = f0a49d
    vi maxClique() { init(V), expand(V); return qmax; }
    Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
        rep(i,0,sz(e)) V.push_back({i});
    }
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertex-Cover.

bfce85, 25 lines

7.7 Trees

BinaryLifting.h

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.

Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

bfce85, 25 lines

```
vector<vi> treeJump(vi& P) {
    int on = 1, d = 1;
    while(on < sz(P)) on *= 2, d++;
    vector<vi> jmp(d, P);
    rep(i,1,d) rep(j,0,sz(P))
        jmp[i][j] = jmp[i-1][jmp[i-1][j]];
    return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
    rep(i,0,sz(tbl))
        if(steps&(1<<i)) nod = tbl[i][nod];
    return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
    if (depth[a] < depth[b]) swap(a, b);
    a = jmp(tbl, a, depth[a] - depth[b]);
    if (a == b) return a;
    for (int i = sz(tbl); i--;) {
        int c = tbl[i][a], d = tbl[i][b];
        if (c != d) a = c, b = d;
    }
```



```
    }
    return tbl[0][a];
}
```

LCA.h
Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.

Time: $\mathcal{O}(N \log N + Q)$
"../data-structures/RMQ.h" 0f62fb, 21 lines

```
struct LCA {
    int T = 0;
    vi time, path, ret;
    RMQ<int> rmq;

    LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C,0,-1), ret)) {}
    void dfs(vector<vi>& C, int v, int par) {
        time[v] = T++;
        for (int y : C[v]) if (y != par) {
            path.push_back(v), ret.push_back(time[v]);
            dfs(C, y, v);
        }
    }

    int lca(int a, int b) {
        if (a == b) return a;
        tie(a, b) = minmax(time[a], time[b]);
        return path[rmq.query(a, b)];
    }
    //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

CompressTree.h
Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S| - 1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

Time: $\mathcal{O}(|S| \log |S|)$
"LCA.h" 9775a0, 21 lines

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
    static vi rev; rev.resize(sz(lca.time));
    vi li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(all(li), cmp);
    int m = sz(li)-1;
    rep(i,0,m) {
        int a = li[i], b = li[i+1];
        li.push_back(lca.lca(a, b));
    }
    sort(all(li), cmp);
    li.erase(unique(all(li)), li.end());
    rep(i,0,sz(li)) rev[li[i]] = i;
    vpi ret = {pii(0, li[0])};
    rep(i,0,sz(li)-1) {
        int a = li[i], b = li[i+1];
        ret.emplace_back(rev[lca.lca(a, b)], b);
    }
    return ret;
}
```

HLD.h

Description: Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most $\log(n)$ light edges. Code does additive modifications and max queries, but can support commutative segtree modifications/queries on paths and subtrees. Takes as input the full adjacency list. VALS.EDGES being true means that values are stored in the edges, as opposed to the nodes. All values initialized to the segtree default. Root must be 0.

Time: $\mathcal{O}((\log N)^2)$
"../data-structures/LazySegmentTree.h" 6f34db, 46 lines

```
template <bool VALS_EDGES> struct HLD { // hash-cpp-1
    int N, tim = 0;
    vector<vi> adj;
    vi par, siz, depth, rt, pos;
    Node *tree;
    HLD(vector<vi> adj_)
        : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1), depth(N),
          rt(N), pos(N), tree(new Node(0, N)){ dfsSz(0); dfsHld(0); }
        ⇨ // hash-cpp-1 = ef2f12
    void dfsSz(int v) { // hash-cpp-2
        if (par[v] != -1) adj[v].erase(find(all(adj[v]), par[v]));
        for (int& u : adj[v]) {
            par[u] = v, depth[u] = depth[v] + 1;
            dfsSz(u);
            siz[v] += siz[u];
            if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
        }
    } // hash-cpp-2 = 70faac
    void dfsHld(int v) { // hash-cpp-3
        pos[v] = tim++;
        for (int u : adj[v]) {
            rt[u] = (u == adj[v][0] ? rt[v] : u);
            dfsHld(u);
        }
    } // hash-cpp-3 = 044fde
    template <class B> void process(int u, int v, B op) { // hash
        ⇨-cpp-4
        for (; rt[u] != rt[v]; v = par[rt[v]]) {
            if (depth[rt[u]] > depth[rt[v]]) swap(u, v);
            op(pos[rt[v]], pos[v] + 1);
        }
        if (depth[u] > depth[v]) swap(u, v);
        op(pos[u] + VALS_EDGES, pos[v] + 1);
    } // hash-cpp-4 = 90b70e
    void modifyPath(int u, int v, int val) { // hash-cpp-5
        process(u, v, [&](int l, int r) { tree->add(l, r, val); });
    } // hash-cpp-5 = a181b8
    int queryPath(int u, int v) { // Modify depending on problem
        ⇨// hash-cpp-6
        int res = -1e9;
        process(u, v, [&](int l, int r) {
            res = max(res, tree->query(l, r));
        });
        return res;
    } // hash-cpp-6 = 1a6944
    int querySubtree(int v) { // modifySubtree is similar // hash
        ⇨-cpp-7
        return tree->query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
    } // hash-cpp-7 = e86b89
};
```

LinkCutTree.h
Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

Time: All operations take amortized $\mathcal{O}(\log N)$.
0fb462, 90 lines

```
struct Node { // Splay tree. Root's pp contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
```

```
Node() { c[0] = c[1] = 0; fix(); }
void fix() { // hash-cpp-1
    if (c[0]) c[0]->p = this;
    if (c[1]) c[1]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
} // hash-cpp-1 = 454758
void pushFlip() { // hash-cpp-2
    if (!flip) return;
    flip = 0; swap(c[0], c[1]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[1]) c[1]->flip ^= 1;
} // hash-cpp-2 = 0cc949
int up() { return p ? p->c[1] == this : -1; }
void rot(int i, int b) { // hash-cpp-3
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p = p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
        x->c[h] = y->c[h ^ 1];
        y->c[h ^ 1] = x;
    }
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
} // hash-cpp-3 = 1cf643
void splay() { // Splay this up to the root. Always finishes
    ⇨without flip set. // hash-cpp-4
    for (pushFlip(); p; ) {
        if (p->p) p->p->pushFlip();
        p->pushFlip(); pushFlip();
        int c1 = up(), c2 = p->up();
        if (c2 == -1) p->rot(c1, 2);
        else p->p->rot(c2, c1 != c2);
    }
} // hash-cpp-4 = bfb1f7
Node* first() { // Return the min element of the subtree
    ⇨rooted at this, splayed to the top.
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
}
};
```

```
struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}

    void link(int u, int v) { // add an edge (u, v) // hash-cpp-5
        assert(!connected(u, v));
        makeRoot(&node[u]);
        node[u].pp = &node[v];
    } // hash-cpp-5 = 60799e
    void cut(int u, int v) { // remove an edge (u, v) // hash-cpp
        ⇨-6
        Node *x = &node[u], *top = &node[v];
        makeRoot(top); x->splay();
        assert(top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else {
            x->c[0] = top->p = 0;
            x->fix();
        }
    } // hash-cpp-6 = a58ec7
    bool connected(int u, int v) { // are u, v in the same tree?
        ⇨// hash-cpp-7
        Node* nu = access(&node[u])->first();
        return nu == access(&node[v])->first();
    } // hash-cpp-7 = b80a22
```

```
void makeRoot(Node* u) { // Move u to root of represented
    ↪tree. // hash-cpp-8
    access(u);
    u->splay();
    if(u->c[0]) {
        u->c[0]->p = 0;
        u->c[0]->flip ^= 1;
        u->c[0]->pp = u;
        u->c[0] = 0;
        u->fix();
    }
} // hash-cpp-8 = 74c908
Node* access(Node* u) { // Move u to root aux tree. Return
    ↪the root of the root aux tree. // hash-cpp-9
    u->splay();
    while (Node* pp = u->pp) {
        pp->splay(); u->pp = 0;
        if (pp->c[1]) {
            pp->c[1]->p = 0; pp->c[1]->pp = pp; }
        pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
} // hash-cpp-9 = 4ac291
};
```

DirectedMST.h
Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.
Time: $\mathcal{O}(E \log V)$

```
"/data-structures/UnionFindRollback.h" 39e620, 60 lines
struct Edge { int a, b; ll w; }; // hash-cpp-1
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    }
    Edge top() { prop(); return key; }
}; // hash-cpp-1 = 67708e
Node *merge(Node *a, Node *b) { // hash-cpp-2
    if (!a || !b) return a ?: b;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); } //
    ↪hash-cpp-2 = 36054f

pair<ll, vi> dmst(int n, int r, vector<Edge*& g) { // hash-cpp
    ↪-3
    RollbackUF uf(n);
    vector<Node*> heap(n);
    for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
    ll res = 0;
    vi seen(n, -1), path(n), par(n);
    seen[r] = r;
    vector<Edge> Q(n), in(n, {-1,-1}), comp;
    deque<tuple<int, int, vector<Edge*>>> cycs;
    rep(s,0,n) {
        int u = s, qi = 0, w;
        while (seen[u] < 0) {
            if (!heap[u]) return {-1,{};};
            Edge e = heap[u]->top();
            heap[u]->delta -= e.w, pop(heap[u]);
```

```
Q[qi] = e, path[qi++] = u, seen[u] = s;
    res += e.w, u = uf.find(e.a);
    if (seen[u] == s) {
        Node* cyc = 0;
        int end = qi, time = uf.time();
        do cyc = merge(cyc, heap[w = path[--qi]]);
        while (uf.join(u, w));
        u = uf.find(u), heap[u] = cyc, seen[u] = -1;
        cycs.push_front({u, time, {Q[qi], Q[end]}});
    }
}
rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
}

for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
}
rep(i,0,n) par[i] = in[i].a;
return {res, par};
} // hash-cpp-3 = efa3a4
```

7.7.1 Number of Spanning Trees
Create an $N \times N$ matrix mat , and for each edge $a \rightarrow b \in G$, do $\text{mat}[a][b]--$, $\text{mat}[b][b]++$ (and $\text{mat}[b][a]--$, $\text{mat}[a][a]++$ if G is undirected). Remove the i th row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

7.7.2 Erdős–Gallai theorem
A simple graph with node degrees $d_1 \geq \dots \geq d_n$ exists iff $d_1 + \dots + d_n$ is even and for every $k = 1 \dots n$,

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k).$$

Geometry (8)


8.1 Geometric primitives

```
Point.h
Description: Class to handle points in the plane. T can be e.g. double or
long long. (Avoid int.)
47ec0a, 28 lines

template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
```

```
double dist() const { return sqrt((double)dist2()); }
// angle to x-axis in interval [-pi, pi]
double angle() const { return atan2(y, x); }
P unit() const { return *this/dist(); } // makes dist()==1
P perp() const { return P(-y, x); } // rotates +90 degrees
P normal() const { return perp().unit(); }
// returns point rotated 'a' radians ccw around the origin
P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};
```


lineDistance.h
Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. $a==b$ gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.



"/Point.h" f6bf6b, 4 lines

```
template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double) (b-a).cross(p-a) / (b-a).dist();
}
```


SegmentDistance.h
Description:
Returns the shortest distance between point p and the line segment from point s to e.



"/Point.h" 5c88f4, 6 lines

```
typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(.0, (p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h
Description:
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.



"/Point.h", "/OnSegment.h" 9d57f2, 13 lines

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
        oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-endpoint point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
    if (onSegment(a, b, c)) s.insert(c);
```

```
    if (onSegment(a, b, d)) s.insert(d);
    return {all(s)};
}
```

lineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.
Usage: auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " << res.second << endl;

"Point.h"

a01f81, 8 lines

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-(s1.cross(e1, s2) == 0), P(0, 0)};
    auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
    return {1, (s1 * p + e1 * q) / d};
}
```

sideOf.h

Description: Returns where *p* is as seen from *s* towards *e*. $1/0/-1 \Leftrightarrow$ left/on line/right. If the optional argument *eps* is given 0 is returned if *p* is within distance *eps* from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.
Usage: bool left = sideOf(p1,p2,q)==1;

"Point.h"

3af81c, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }
```

template<class P>
int sideOf(**const** P& s, **const** P& e, **const** P& p, **double** eps) {
 auto a = (e-s).cross(p-s);
 double l = (e-s).dist()*eps;
 return (a > l) - (a < -l);
}

OnSegment.h

Description: Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p)<=epsilon) instead when using Point<double>.

"Point.h"

c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

linearTransformation.h

Description:

Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.

"Point.h"

03a306, 6 lines

```
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.
Usage: vector<Angle> v = {w[0], w[0].t360() ...}; // sorted
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }
// sweeps j such that (j-i) represents the number of positively oriented triangles with vertices at 0 and i

0f0602, 35 lines

```
struct Angle { // hash-cpp-1
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }
    Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
    Angle t180() const { return {-x, -y, t + half()}; }
    Angle t360() const { return {x, y, t + 1}; }
}; // hash-cpp-1 = e258c0
bool operator<(Angle a, Angle b) { // hash-cpp-2
    // add a.dist2() and b.dist2() to also compare distances
    return make_tuple(a.t, a.half(), a.y * (1l)b.x) <
        make_tuple(b.t, b.half(), a.x * (1l)b.y);
} // hash-cpp-2 = ce5ed3
```

```
// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) { // hash-
    ↪cpp-3
    if (b < a) swap(a, b);
    return (b < a.t180() ?
        make_pair(a, b) : make_pair(b, a.t360()));
} // hash-cpp-3 = 5eac29
Angle operator+(Angle a, Angle b) { // point a + vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
    int tu = b.t - a.t; a.t = b.t;
    return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}
```

AngularSweep.h

3ec7ae, 16 lines

```
inline bool cmp(point p1, point p2) {
    return angle(p1) < angle(p2) || (angle(p1) == angle(p2) &&
        ↪dist(p1, p) < dist(p2, p));
}
int solve(int r) {
    int maxi = 0;
    vector<pdi> v;
    for (int i = 0; i < n; i++) {
        if (dist(a[i], p) > 2 * r) continue;
        double a1 = angle(a[i] - p), a2 = acos(dist(a[i], p) /
            ↪(2 * r));
        v.pb({a1 + a2, -1}); v.pb({a1 - a2, 1}); v.pb({a1 + a2
            ↪+ 2 * PI, -1}); v.pb({a1 - a2 + 2 * PI, 1});
    }
    sort(v.begin(), v.end(), [&](pdi p1, pdi p2) { return p1.
        ↪first < p2.first || (p1.first == p2.first && p1.
            ↪second > p2.second);});
    for (int i = 0, sum = 0; i < v.size(); i++)
        sum += v[i].second, maxi = max(maxi, sum);
    return maxi;
}
```

8.2 Circles

CircleIntersection.h

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

"Point.h"

84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
        p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
    *out = {mid + per, mid - per};
    return true;
}
```

CircleTangents.h

Description: Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

"Point.h"

b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```

CirclePolygonIntersection.h

Description: Returns the area of the intersection of a circle with a ccw polygon.
Time: $\mathcal{O}(n)$

".././content/geometry/Point.h"

e28e40, 19 lines

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = p + d * t;
        return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
    };
    auto sum = 0.0;
    rep(i,0,sz(ps))
        sum += tri[ps[i] - c, ps[(i + 1) % sz(ps)] - c];
    return sum;
}
```

circumcircle.h

Description:

The circumcircle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.

"Point.h"

1caa3a, 9 lines

```
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()* (C-B).dist()* (A-C).dist() /
        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

MinimumEnclosingCircle.h

Description:

Computes the minimum circle that encloses a set of points.

Time: expected $\mathcal{O}(n)$

"circumcircle.h"

09dd0a, 17 lines

```
pair<P, double> mec(vector<P> ps) {
    shuffle(all(ps), mt19937(time(0)));
    P o = ps[0];
    double r = 0, EPS = 1 + 1e-8;
    rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
        o = ps[i], r = 0;
        rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
            o = (ps[i] + ps[j]) / 2;
            r = (o - ps[i]).dist();
            rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
                o = ccCenter(ps[i], ps[j], ps[k]);
                r = (o - ps[i]).dist();
            }
        }
    }
    return {o, r};
}
```

8.3 Polygons

InsidePolygon.h

Description:

Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

Usage: vector<P> v = {P{4,4}, P{1,2}, P{2,1}};

bool in = insidePolygon(v, P{3, 3}, false);

Time: $\mathcal{O}(n)$

"Point.h", "OnSegment.h", "SegmentDistance.h"

2bf504, 11 lines

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
    int cnt = 0, n = sz(p);
    rep(i,0,n) {
        P q = p[(i + 1) % n];
        if (onSegment(p[i], q, a)) return !strict;
        //or: if (segDist(p[i], q, a) <= eps) return !strict;
        cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
    }
    return cnt;
}
```

PolygonArea.h

Description:

Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h"

f12300, 6 lines

template<class T>
T polygonArea2(vector<Point<T>>& v) {

```
T a = v.back().cross(v[0]);
rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
return a;
}
```

PolygonCenter.h

Description:

Returns the center of mass for a polygon.

Time: $\mathcal{O}(n)$

"Point.h"

9706dc, 9 lines

```
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}
```

PolygonCut.h

Description:

Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.

Usage: vector<P> p = ...;

p = polygonCut(p, P(0,0), P(1,0));

"Point.h", "lineIntersection.h"

f2b7d4, 13 lines

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    rep(i,0,sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] : poly.back();
        bool side = s.cross(e, cur) < 0;
        if (side != (s.cross(e, prev) < 0))
            res.push_back(lineInter(s, e, cur, prev).second);
        if (side)
            res.push_back(cur);
    }
    return res;
}
```

ConvexHull.h

Description:

Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.

Time: $\mathcal{O}(n \log n)$

"Point.h"

310954, 13 lines

```
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
    if (sz(pts) <= 1) return pts;
    sort(all(pts));
    vector<P> h(sz(pts)+1);
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(all(pts)))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
            h[t++] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h

Description:

Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).

Time: $\mathcal{O}(n)$

"Point.h"

c571b8, 12 lines

typedef Point<ll> P;

```
array<P, 2> hullDiameter(vector<P> S) {
    int n = sz(S), j = n < 2 ? 0 : 1;
    pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
    rep(i,0,j)
        for (;; j = (j + 1) % n) {
            res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
            if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
                break;
        }
    return res.second;
}
```

PointInsideHull.h

Description:

Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.

Time: $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h"

71446b, 14 lines

typedef Point<ll> P;

```
bool inHull(const vector<P>& l, P p, bool strict = true) {
    int a = 1, b = sz(l) - 1, r = !strict;
    if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
    if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
    if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
    }
    return sgn(l[a].cross(l[b], p)) < r;
}
```

LineHullIntersection.h

Description:

Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet(-1, -1)$ if no collision, $\bullet(i, -1)$ if touching the corner i , $\bullet(i, i)$ if along side $(i, i + 1)$, $\bullet(i, j)$ if crossing sides $(i, i + 1)$ and $(j, j + 1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i, i + 1)$. The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

Time: $\mathcal{O}(\log n)$

"Point.h"

46048c, 39 lines

```
#define cmp(i, j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
    ↪ // hash-cpp-1

#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
    int n = sz(poly), lo = 0, hi = n;
    if (extr(0)) return 0;
    while (lo + 1 < hi) {
        int m = (lo + hi) / 2;
        if (extr(m)) return m;
        int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
    }
    return lo;
} // hash-cpp-1 = 4caf99
```

```
#define cmpL(i) sgn(a.cross(poly[i], b)) // hash-cpp-2
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
    rep(i,0,2) {
```

```

    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
        int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
        (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
}
if (res[0] == res[1]) return {res[0], -1};
if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
        case 0: return {res[0], res[0]};
        case 2: return {res[1], res[1]};
    }
return res;
} // hash-cpp-2 = f6931f

```

HalfPlane.h

Description: Computes the intersection of a set of half-planes. Input is given as a set of planes, facing left. Output is the convex polygon representing the intersection. The points may have duplicates and be collinear. Will not fail catastrophically if ‘eps > sqrt(2)(line intersection error)’. Likely to work for more ranges if 3 half planes are never guaranteed to intersect at the same point.

Time: $\mathcal{O}(n \log n)$

"Point.h", "sideOf.h", "lineIntersection.h"
e6ce94, 31 lines

```

typedef Point<double> P;
typedef array<P, 2> Line;
#define sp(a) a[0], a[1]
#define ang(a) (a[1] - a[0]).angle()

```

```

int angDiff(Line a, Line b) { return sgn(ang(a) - ang(b)); }

```

```

bool cmp(Line a, Line b) {
    int s = angDiff(a, b);
    return (s ? s : sideOf(sp(a), b[0])) < 0;
}

```

```

vector<P> halfPlaneIntersection(vector<Line> vs) {
    const double EPS = sqrt(2) * 1e-8;
    sort(all(vs), cmp);
    vector<Line> deq(sz(vs) + 5);
    vector<P> ans(sz(vs) + 5);
    deq[0] = vs[0];
    int ah = 0, at = 0, n = sz(vs);
    rep(i, 1, n+1) {
        if (i == n) vs.push_back(deq[ah]);
        if (angDiff(vs[i], vs[i - 1]) == 0) continue;
        while (ah<at && sideOf(sp(vs[i]), ans[at-1], EPS) < 0)
            at--;
        while (i!=n && ah<at && sideOf(sp(vs[i]), ans[ah], EPS)<0)
            ah++;
        auto res = lineInter(sp(vs[i]), sp(deq[at]));
        if (res.first != 1) continue;
        ans[at++] = res.second, deq[at] = vs[i];
    }
    if (at - ah <= 2) return {};
    return {ans.begin() + ah, ans.begin() + at};
}

```

8.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.

Time: $\mathcal{O}(n \log n)$

"Point.h"
ac41a6, 17 lines

```

typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(all(v), [](P a, P b) { return a.y < b.y; });
}

```

HalfPlane ClosestPair kdTree FastDelaunay

```

pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
int j = 0;
for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
        ret = min(ret, {( *lo - p).dist2(), { *lo, p}});
    S.insert(p);
}
return ret.second;
}

```

kdTree.h

981556, 85 lines

```

struct KDTree {
    const double alpha = .75;
    struct point { int a[dim]; };
    struct node {
        point p; int mini[dim], maxi[dim], size, ls, rs;
    } tree[1111111];
    stack<int> ind; int ans;
    inline void pushup(int idx) { // hash-cpp-1
        for (int i = 0; i < dim; i++) {
            tree[idx].maxi[i] = tree[idx].mini[i] = tree[idx].p.a[i];
            if (tree[idx].ls) {
                tree[idx].maxi[i] = max(tree[idx].maxi[i], tree[tree[
                    ↳idx].ls].maxi[i]);
                tree[idx].mini[i] = min(tree[idx].mini[i], tree[tree[
                    ↳idx].ls].mini[i]);
            }
            if (tree[idx].rs) {
                tree[idx].maxi[i] = max(tree[idx].maxi[i], tree[tree[
                    ↳idx].rs].maxi[i]);
                tree[idx].mini[i] = min(tree[idx].mini[i], tree[tree[
                    ↳idx].rs].mini[i]);
            }
        }
        tree[idx].size = tree[tree[idx].ls].size + tree[tree[idx].
            ↳rs].size + 1;
    } // hash-cpp-1 = a8a328
    int build(int l, int r, int axis) { // hash-cpp-2
        if (l > r) return 0;
        int mid = l + r >> 1, idx;
        nth_element(p + l, p + mid, p + r + 1, [&](point p1, point
            ↳p2) {
            return p1.a[axis] < p2.a[axis];
        });
        if (ind.empty()) idx = ++ts;
        else {idx = ind.top(); ind.pop();}
        tree[idx].p = p[mid];
        tree[idx].ls = build(l, mid - 1, (axis + 1) % dim);
        tree[idx].rs = build(mid + 1, r, (axis + 1) % dim);
        pushup(idx);
        return idx;
    } // hash-cpp-2 = 17230a
    void flatten(int idx, int cnt) { // hash-cpp-3
        if (tree[idx].ls) flatten(tree[idx].ls, cnt);
        p[cnt + tree[tree[idx].ls].size] = tree[idx].p;
        ind.push(idx);
        if (tree[idx].rs) flatten(tree[idx].rs, cnt + tree[tree[idx]
            ↳.ls].size + 1);
    } // hash-cpp-3 = 8703a9
    void insert(const point& p, int& idx, int axis) { // hash-cpp
        ↳-4
        if (!idx) {
            idx = ++ts, tree[idx].p = p, pushup(idx);
            return;
        }
    }
}

```

```

    if (p.a[axis] < tree[idx].p.a[axis]) insert(p, tree[idx].ls
        ↳, (axis + 1) % dim);
    else insert(p, tree[idx].rs, (axis + 1) % dim);
    pushup(idx);
    if (tree[tree[idx].ls].size > tree[idx].size * alpha ||
        ↳tree[tree[idx].rs].size > tree[idx].size * alpha) {
        flatten(idx, 0);
        idx = build(0, tree[idx].size - 1, axis);
    }
} // hash-cpp-4 = 5390e6
inline int tree_dist(const point& p, int idx) { // hash-cpp-5
    int ans = 0;
    for (int i = 0; i < dim; i++)
        ans += max(0, p.a[i] - tree[idx].maxi[i]) + max(0, tree[
            ↳idx].mini[i] - p.a[i]);
    return ans;
} // hash-cpp-5 = 279b7e
void query(const point& p, int idx) { // hash-cpp-6
    ans = min(ans, dist(p, tree[idx].p));
    int lans = tree[idx].ls? tree_dist(p, tree[idx].ls):
        ↳INT_MAX;
    int rans = tree[idx].rs? tree_dist(p, tree[idx].rs):
        ↳INT_MAX;
    if (lans < rans) {
        if (lans < ans) query(p, tree[idx].ls);
        if (rans < ans) query(p, tree[idx].rs);
    } else {
        if (rans < ans) query(p, tree[idx].rs);
        if (lans < ans) query(p, tree[idx].ls);
    }
} // hash-cpp-6 = 334bd0
ll query(const point& p1, const point& p2, int idx) { // hash
    ↳-cpp-7
    if (p1.a[0] <= tree[idx].mini[0] && p1.a[1] <= tree[idx].
        ↳mini[1] && p2.a[0] >= tree[idx].maxi[0] && p2.a[1]
        ↳>= tree[idx].maxi[1])
        return tree[idx].sum;
    else if (p1.a[0] > tree[idx].maxi[0] || p1.a[1] > tree[idx]
        ↳.maxi[1] || p2.a[0] < tree[idx].mini[0] || p2.a[1]
        ↳< tree[idx].mini[1])
        return 0;

    ll ans = (tree[idx].p.a[0] >= p1.a[0] && tree[idx].p.a[1]
        ↳>= p1.a[1] && tree[idx].p.a[0] <= p2.a[0] && tree[
            ↳idx].p.a[1] <= p2.a[1]) * tree[idx].p.a[2];
    if (tree[idx].ls) ans += query(p1, p2, tree[idx].ls);
    if (tree[idx].rs) ans += query(p1, p2, tree[idx].rs);

    return ans;
} // hash-cpp-7 = 1d564a
}

```

FastDelaunay.h

Description: Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in ‘circ’. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.

Time: $\mathcal{O}(n \log n)$

"Point.h"
bd978c, 88 lines

```

typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t ll1; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX, LLONG_MAX); // not equal to any other point

struct Quad { // hash-cpp-1
    Q rot, o; P p = arb; bool mark;
    P& F() { return r()->p; }
    Q& r() { return rot->rot; }
}

```

```
Q prev() { return rot->o->rot; }
Q next() { return r()->prev(); }
} *H;

bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
    ll p2 = p.dist2(), A = a.dist2()-p2,
        B = b.dist2()-p2, C = c.dist2()-p2;
    return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
} // hash-cpp-1 = 1b2ec1
Q makeEdge(P orig, P dest) { // hash-cpp-2
    Q r = H ? H : new Quad{new Quad{new Quad{new Quad{0}}}};
    H = r->o; r->r()->r() = r;
    rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
    r->p = orig; r->F() = dest;
    return r;
}

void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}

Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
} // hash-cpp-2 = a850a4
```

```
pair<Q,Q> rec(const vector<P>& s) { // hash-cpp-3
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = s[0].cross(s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
    }
}
```

```
#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
Q A, B, ra, rb;
int half = sz(s) / 2;
tie(ra, A) = rec({all(s) - half});
tie(B, rb) = rec({sz(s) - half + all(s)});
while ((B->p.cross(H(A)) < 0 && (A = A->next())) ||
        (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
Q base = connect(B->r(), A);
if (A->p == ra->p) ra = base->r();
if (B->p == rb->p) rb = base;
```

```
#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
        Q t = e->dir; \
        splice(e, e->prev()); \
        splice(e->r(), e->r()->prev()); \
        e->o = H; H = e; e = t; \
    }
for (;;) {
    DEL(LC, base->r(), o); DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
        base = connect(RC, base->r());
    else
        base = connect(base->r(), LC->r());
}
return { ra, rb };
} // hash-cpp-3 = 067084
```

```
vector<P> triangulate(vector<P> pts) { // hash-cpp-4
    sort(all(pts)); assert(unique(all(pts)) == pts.end());
    if (sz(pts) < 2) return {};
```

```
Q e = rec(pts).first;
vector<Q> q = {e};
int qi = 0;
while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
    q.push_back(c->r()); c = c->next(); } while (c != e); }
ADD; pts.clear();
while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
return pts;
} // hash-cpp-4 = 8a4a2c
```

MinkowskiSum.h

Time: $\mathcal{O}(n+m)$

e5b223, 14 lines

```
void Minkowski() {
    // Suppose ca, cb are convex hulls
    vector<point> v1, v2;
    for (int i = 0; i < ca.size(); i++) v1.pb(ca[(i + 1) % ca.
        ↪size()] - ca[i]);
    for (int i = 0; i < cb.size(); i++) v2.pb(cb[(i + 1) % cb.
        ↪size()] - cb[i]);
    c[cnt++] = ca[0] + cb[0];
    int i = 0, j = 0;
    while (i < v1.size() || j < v2.size()) {
        if (j >= v2.size() || (i < v1.size() && cross(v1[i], v2
            ↪[j]) >= 0))
            c[cnt] = c[cnt - 1] + v1[i], cnt++, i++;
        else c[cnt] = c[cnt - 1] + v2[j], cnt++, j++;
    }
    // Do convex hull on c again
}
```

8.5 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
    double v = 0;
    for (auto i : trilst) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

```
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
    bool operator<(R p) const {
        return tie(x, y, z) < tie(p.x, p.y, p.z); }
    bool operator==(R p) const {
        return tie(x, y, z) == tie(p.x, p.y, p.z); }
    P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
    P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
    P operator*(T d) const { return P(x*d, y*d, z*d); }
    P operator/(T d) const { return P(x/d, y/d, z/d); }
    T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
    P cross(R p) const {
        return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
    }
    T dist2() const { return x*x + y*y + z*z; }
    double dist() const { return sqrt((double)dist2()); }
    //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
    double phi() const { return atan2(y, x); }
```

```
//Zenith angle (latitude) to the z-axis in interval [0, pi]
double theta() const { return atan2(sqrt(x*x+y*y),z); }
P unit() const { return *this/(T)dist(); } //makes dist()==1
//returns unit vector normal to *this and p
P normal(P p) const { return cross(p).unit(); }
//returns point rotated 'angle' radians ccw around axis
P rotate(double angle, P axis) const {
    double s = sin(angle), c = cos(angle); P u = axis.unit();
    return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
}
};
```

3dHull.h

Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.

Time: $\mathcal{O}(n^2)$

```
"Point3D.h"
2644ea, 49 lines

typedef Point3D<double> P3;

struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};
```

```
struct F { P3 q; int a, b, c; };
```

```
vector<F> hull3d(const vector<P3>& A) { // hash-cpp-1
    assert(sz(A) >= 4);
    vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
    vector<F> FS;
    auto mf = [&](int i, int j, int k, int l) {
        P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
        if (q.dot(A[l]) > q.dot(A[i]))
            q = q * -1;
        F f(q, i, j, k);
        E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
        FS.push_back(f);
    };
    rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
        mf(i, j, k, 6 - i - j - k);
```

```
rep(i,4,sz(A)) {
    rep(j,0,sz(FS)) {
        F f = FS[j];
        if (f.q.dot(A[i]) > f.q.dot(A[f.a])) {
            E(a,b).rem(f.c);
            E(a,c).rem(f.b);
            E(b,c).rem(f.a);
            swap(FS[j--], FS.back());
            FS.pop_back();
        }
    }
    int nw = sz(FS);
    rep(j,0,nw) {
        F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
        C(a, b, c); C(a, c, b); C(b, c, a);
    }
}
for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
    A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
return FS;
}; // hash-cpp-1 = e004e3
```


sphericalDistance.h

Description: Returns the shortest distance on the sphere with radius r adius between the points with azimuthal angles (longitude) f_1 (ϕ_1) and f_2 (ϕ_2) from x axis and zenith angles (latitude) t_1 (θ_1) and t_2 (θ_2) from z axis ($0 =$ north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. $dx * radius$ is then the difference between the two points in the x direction and $d * radius$ is the total distance between the points.

611f07, 8 lines

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
}
```

Strings (9)

KMP.h

Description: $pi[x]$ computes the length of the longest prefix of s that ends at x , other than $s[0...x]$ itself (abacaba -> 0010123). Can be used to find all occurrences of a string.

Time: $\mathcal{O}(n)$

d4375c, 16 lines

```
vi pi(const string& s) {
    vi p(sz(s));
    rep(i,1,sz(s)) {
        int g = p[i-1];
        while (g && s[i] != s[g]) g = p[g-1];
        p[i] = g + (s[i] == s[g]);
    }
    return p;
}
```

```
vi match(const string& s, const string& pat) {
    vi p = pi(pat + '\0' + s), res;
    rep(i,sz(p)-sz(s),sz(p))
        if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
    return res;
}
```

Zfunc.h

Description: $z[i]$ computes the length of the longest common prefix of $s[i:]$ and s , except $z[0] = 0$. (abacaba -> 0010301)

Time: $\mathcal{O}(n)$

ee09e2, 12 lines

```
vi Z(const string& S) {
    vi z(sz(S));
    int l = -1, r = -1;
    rep(i,1,sz(S)) {
        z[i] = i >= r ? 0 : min(r - i, z[i - l]);
        while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
            z[i]++;
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    return z;
}
```

Manacher.h

Description: For each position in a string, computes $p[0][i] =$ half length of longest even palindrome around pos i , $p[1][i] =$ longest odd (half rounded down).

Time: $\mathcal{O}(N)$

e7ad79, 13 lines

```
array<vi, 2> manacher(const string& s) {
```

```
    int n = sz(s);
    array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
        int t = r-i+!z;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
        int L = i-p[z][i], R = i+p[z][i]-!z;
        while (L>=1 && R+1<n && s[L-1] == s[R+1])
            p[z][i]++, L--, R++;
        if (R>r) l=L, r=R;
    }
    return p;
}
```

MinRotation.h

Description: Finds the lexicographically smallest rotation of a string.
Usage: rotate(v.begin(), v.begin()+minRotation(v), v.end());
Time: $\mathcal{O}(N)$

d07a42, 8 lines

```
int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
        if (s[a+k] > s[b+k]) {a = b; break;}
    }
    return a;
}
```

SuffixArray.h

Description: Builds suffix array for a string. $sa[i]$ is the starting index of the suffix which is i 'th in the sorted suffix array. The returned vector is of size $n + 1$, and $sa[0] = n$. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: $lcp[i] = lcp(sa[i], sa[i-1])$, $lcp[0] = 0$. The input string must not contain any zero bytes.

Time: $\mathcal{O}(n \log n)$

38db9f, 23 lines

```
struct SuffixArray {
    vi sa, lcp;
    SuffixArray(string& s, int lim=256) { // or basic_string<int>
        int n = sz(s) + 1, k = 0, a, b;
        vi x(all(s)+1), y(n), ws(max(n, lim)), rank(n);
        sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
            p = j, iota(all(y), n - j);
            rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            rep(i,0,n) ws[x[i]]++;
            rep(i,1,lim) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
                (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
        }
        rep(i,1,n) rank[sa[i]] = i;
        for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k)
            for (k && k--, j = sa[rank[i] - 1];
                s[i + k] == s[j + k]; k++);
    }
};
```

SuffixTree.h

Description: Ukkonen's algorithm for online suffix tree construction. Each node contains indices $[l, r)$ into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining $[l, r)$ substrings. The root is 0 (has $l = -1, r = 0$, non-existent children are -1. To get a complete tree, append a dummy symbol - otherwise it may contain an incomplete path (still useful for substring matching, though).

Time: $\mathcal{O}(26N)$

aae0b8, 50 lines

```
struct SuffixTree {
```

```
    enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
    int toi(char c) { return c - 'a'; }
    string a; // v = cur node, q = cur position
    int t[N][ALPHA], l[N], r[N], p[N], s[N], v=0, q=0, m=2;
```

```
void ukkadd(int i, int c) { suff: // hash-cpp-1
    if (r[v]<=q) {
        if (t[v][c]==-1) { t[v][c]=m; l[m]=i;
            p[m++]=v; v=s[v]; q=r[v]; goto suff; }
        v=t[v][c]; q=l[v];
    }
    if (q==-1 || c==toi(a[q])) q++; else {
        l[m+1]=i; p[m+1]=m; l[m]=l[v]; r[m]=q;
        p[m]=p[v]; t[m][c]=m+1; t[m][toi(a[q])]=v;
        l[v]=q; p[v]=m; t[p[m]][toi(a[l[m]])]=m;
        v=s[p[m]]; q=l[m];
        while (q<r[m]) { v=t[v][toi(a[q])]; q+=r[v]-l[v]; }
        if (q==r[m]) s[m]=v; else s[m]=m+2;
        q=r[v]-(q-r[m]); m+=2; goto suff;
    }
} // hash-cpp-1 = 89ac6c
```

```
SuffixTree(string a) : a(a) { // hash-cpp-2
    fill(r,r+N,sz(a));
    memset(s, 0, sizeof s);
    memset(t, -1, sizeof t);
    fill(t[1],t[1]+ALPHA,0);
    s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
    rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
} // hash-cpp-2 = c4056f
```

```
// example: find longest common substring (uses ALPHA = 28)
pii best; // hash-cpp-3
int lcs(int node, int i1, int i2, int olen) {
    if (l[node] <= i1 && i1 < r[node]) return 1;
    if (l[node] <= i2 && i2 < r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node] - l[node]) : 0;
    rep(c,0,ALPHA) if (t[node][c] != -1)
        mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
        best = max(best, {len, r[node] - len});
    return mask;
} // hash-cpp-3 = c8b0c2
static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (char)('z' + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
}
};
```

Hashing.h

Description: Self-explanatory methods for string hashing.

2d2a67, 44 lines

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H { // hash-cpp-1
    ull x; H(ull x=0) : x(x) {}
    H operator+(H o) { return x + o.x + (x + o.x < x); }
    H operator-(H o){ return *this + ~o.x; }
    H operator*(H o){ auto m = (__uint128_t)x * o.x;
        return H((ull)m) + (ull)(m >> 64); }
    ull get() const { return x + !~x; }
    bool operator==(H o) const { return get() == o.get(); }
    bool operator<(H o) const { return get() < o.get(); }
};
```

```
static const H C = (11)1e11+3; // (order ~ 3e9; random also ok)
    ↪ // hash-cpp-1 = bac680

struct HashInterval { // hash-cpp-2
    vector<H> ha, pw;
    HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
        pw[0] = 1;
        rep(i,0,sz(str))
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    }
    H hashInterval(int a, int b) { // hash [a, b)
        return ha[b] - ha[a] * pw[b - a];
    }
}; // hash-cpp-2 = 122649

vector<H> getHashes(string& str, int length) { // hash-cpp-3
    if (sz(str) < length) return {};
    H h = 0, pw = 1;
    rep(i,0,length)
        h = h * C + str[i], pw = pw * C;
    vector<H> ret = {h};
    rep(i,length,sz(str)) {
        ret.push_back(h = h * C + str[i] - pw * str[i-length]);
    }
    return ret;
} // hash-cpp-3 = aaa3c7

H hashString(string& s){H h{}; for(char c:s) h=h*C+c;return h;}
```

AhoCorasick.h
Description: Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(−, word) finds all words (up to $N\sqrt{N}$ many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.
Time: Construction takes $\mathcal{O}(26N)$, where N = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$.

f35677, 66 lines

```
struct AhoCorasick {
    enum {alpha = 26, first = 'A'}; // change this!
    struct Node {
        // (nmatches is optional)
        int back, next[alpha], start = -1, end = -1, nmatches = 0;
        Node(int v) { memset(next, v, sizeof(next)); }
    };
    vector<Node> N;
    vi backp;
    void insert(string& s, int j) { // hash-cpp-1
        assert(!s.empty());
        int n = 0;
        for (char c : s) {
            int& m = N[n].next[c - first];
            if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
            else n = m;
        }
        if (N[n].end == -1) N[n].start = j;
        backp.push_back(N[n].end);
        N[n].end = j;
        N[n].nmatches++;
    } // hash-cpp-1 = 0bbeb6
    AhoCorasick(vector<string&& pat) : N(1, -1) { // hash-cpp-2
        rep(i,0,sz(pat)) insert(pat[i], i);
        N[0].back = sz(N);
        N.emplace_back(0);
    }
};
```

```
queue<int> q;
for (q.push(0); !q.empty(); q.pop()) {
    int n = q.front(), prev = N[n].back;
    rep(i,0,alpha) {
        int &ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1) ed = y;
        else {
            N[ed].back = y;
            (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
                = N[y].end;
            N[ed].nmatches += N[y].nmatches;
            q.push(ed);
        }
    }
}
} // hash-cpp-2 = cb04be
vi find(string word) { // hash-cpp-3
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
        n = N[n].next[c - first];
        res.push_back(N[n].end);
        // count += N[n].nmatches;
    }
    return res;
} // hash-cpp-3 = 8c02f9
vector<vi> findAll(vector<string>& pat, string word) { //
    ↪hash-cpp-4
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
        int ind = r[i];
        while (ind != -1) {
            res[i - sz(pat[ind]) + 1].push_back(ind);
            ind = backp[ind];
        }
    }
    return res;
} // hash-cpp-4 = a03981
};
```

SuffixAutomaton.h

Description: Used infrequently. Constructs minimal deterministic finite automaton (DFA) that recognizes all suffixes of a string. len corresponds to the maximum length of a string in the equivalence class, pos corresponds to the first ending position of such a string, lnk corresponds to the longest suffix that is in a different class. Suffix links correspond to suffix tree of the reversed string!
Time: $\mathcal{O}(N \log \Sigma)$

d443e2, 60 lines

```
struct SuffixAutomaton {
    int N = 1; vi lnk{-1}, len{0}, pos{-1}; // max length of
        ↪state, suffix link, last pos of first occurrence of
        ↪state
    vector<map<char,int>> nex{1}; vector<bool> isClone{0}; //
        ↪transitions, cloned → not terminal state
    vector<vi> iLnk; // inverse links
    int add(int p, char c) { // ~p is nonzero if p != -1 // hash-
        ↪cpp-1
        auto getNext = [&]() {
            if (p == -1) return 0;
            int q = nex[p][c]; if (len[p]+1 == len[q]) return q;
            int clone = N++; lnk.pb(lnk[q]); lnk[q] = clone;
            len.pb(len[p]+1); nex.pb(nex[q]), pos.pb(pos[q]), isClone
                ↪.pb(1);
            for (; ~p && nex[p][c] == q; p = lnk[p]) nex[p][c] =
                ↪clone;
            return clone;
        };
    }
};
```

```
    // if (nex[p].count(c)) return getNext(); <- need if adding
        ↪→ 1 string
    int cur = N++; // make new state
    lnk.pb(), len.pb(len[p]+1), nex.pb(), pos.pb(pos[p]+1),
        ↪isClone.pb(0);
    for (; ~p && !nex[p].count(c); p = lnk[p]) nex[p][c] = cur;
    int x = getNext(); lnk[cur] = x;
    return cur;
} // hash-cpp-1 = 1a3722
void init(str s) { int p = 0; each(x,s) p = add(p,x); } //
    ↪add string to automaton // hash-cpp-2
void genIlnk() { iLnk.rsz(N); FOR(v,1,N) iLnk[lnk[v]].pb(v);
    ↪} // inverse links //355caf
// APPLICATIONS
void getAllOccur(vi& oc, int v) {
    if (!isClone[v]) oc.pb(pos[v]); // terminal position
    each(u,iLnk[v]) getAllOccur(oc,u); } // hash-cpp-2 = 186c2d
vi allOccur(str s) { // get all occurrences of s in automaton
    ↪ // hash-cpp-3
    int cur = 0;
    each(x,s) {
        if (!nex[cur].count(x)) return {};
        cur = nex[cur][x]; }
    vi oc; getAllOccur(oc,cur); each(t,oc) t += 1-sz(s); //
        ↪convert end pos → start pos
    sort(all(oc)); return oc;
} // hash-cpp-3 = f05dbc
vl distinct; // hash-cpp-4
ll getDistinct(int x) { // # of distinct strings starting at
    ↪state x
    if (distinct[x]) return distinct[x];
    distinct[x] = 1; each(y,nex[x]) distinct[x] += getDistinct(
        ↪y.s);
    return distinct[x]; }
ll numDistinct() { // # distinct substrings including empty
    distinct.rsz(N); return getDistinct(0); }
ll numDistinct2() { // assert(numDistinct() == numDistinct2())
    ↪};
    ll ans = 1; FOR(i,1,N) ans += len[i]-len[lnk[i]];
    return ans; } // hash-cpp-4 = b14654
};
```

```
SuffixAutomaton S; // hash-cpp-5
vi sa; str s;
void dfs(int x) {
    if (!S.isClone[x]) sa.pb(sz(s)-1-S.pos[x]);
    vector<pair<char,int>> chr;
    each(t,S.iLnk[x]) chr.pb({s[S.pos[t]-S.len[x]],t});
    sort(all(chr)); each(t,chr) dfs(t.s);
} // hash-cpp-5 = 93bb3e

int main() {
    re(s); reverse(all(s));
    S.init(s); S.genIlnk();
    dfs(0); ps(sa); // generating suffix array for s
}
```

Various (10)

10.1 Intervals

IntervalContainer.h
Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).
Time: $\mathcal{O}(\log N)$

edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
```



```
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
    return is.insert(before, {L,R});
}
```

```
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}
```

IntervalCover.h
Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).
Time: $\mathcal{O}(N \log N)$

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0);
    sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { // (A)
        pair<T, int> mx = make_pair(cur, -1);
        while (at < sz(I) && I[S[at]].first <= cur) {
            mx = max(mx, make_pair(I[S[at]].second, S[at]));
            at++;
        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
    return R;
}
```

ConstantIntervals.h
Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.
Usage: constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});
Time: $\mathcal{O}(k \log \frac{n}{k})$

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}
```

```
    }
    template<class F, class G>
    void constantIntervals(int from, int to, F f, G g) {
        if (to <= from) return;
        int i = from; auto p = f(i), q = f(to-1);
        rec(from, to-1, f, g, i, p, q);
        g(i, to, q);
    }
}
```

10.2 Misc. algorithms

TernarySearch.h
Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \dots < f(i) \geq \dots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the $<$ marked with (A) to $<=$, and reverse the loop at (B). To minimize f , change it to $>$, also at (B).
Usage: int ind = ternSearch(0,n-1,[&](int i){return a[i];});
Time: $\mathcal{O}(\log(b-a))$

```
template<class F>
int ternSearch(int a, int b, F f) {
    assert(a <= b);
    while (b - a >= 5) {
        int mid = (a + b) / 2;
        if (f(mid) < f(mid+1)) a = mid; // (A)
        else b = mid+1;
    }
    rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
    return a;
}
```

LIS.h
Description: Compute indices for the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$

```
template<class I> vi lis(const vector<I>& S) {
    if (S.empty()) return {};
    vi prev(sz(S));
    typedef pair<I, int> p;
    vector<p> res;
    rep(i,0,sz(S)) {
        // change 0  $\rightarrow$  i for longest non-decreasing subsequence
        auto it = lower_bound(all(res), p{S[i], 0});
        if (it == res.end()) res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
    int L = sz(res), cur = res.back().second;
    vi ans(L);
    while (L--) ans[L] = cur, cur = prev[cur];
    return ans;
}
```

FastKnapsack.h
Description: Given N non-negative integer weights w and a non-negative target t , computes the maximum $S \leq t$ such that S is the sum of some subset of the weights.
Time: $\mathcal{O}(N \max(w_i))$

```
int knapsack(vi w, int t) {
    int a = 0, b = 0, x;
    while (b < sz(w) && a + w[b] <= t) a += w[b++];
    if (b == sz(w)) return a;
    int m = *max_element(all(w));
    vi u, v(2*m, -1);
    v[a+m-t] = b;
    rep(i,b,sz(w)) {
        u = v;
        rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
        for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])

```

```
        v[x-w[j]] = max(v[x-w[j]], j);
    }
    for (a = t; v[a+m-t] < 0; a--);
    return a;
}
```

10.3 Dynamic programming

KnuthDP.h
Description: When doing DP on intervals: $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$, where the (minimal) optimal k increases with both i and j , one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b, c) \leq f(a, d)$ and $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
Time: $\mathcal{O}(N^2)$

DivideAndConquerDP.h
Description: Given $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$ where the (minimal) optimal k increases with i , computes $a[i]$ for $i = L..R-1$.
Time: $\mathcal{O}((N + (hi-lo)) \log N)$

```
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best(LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
            best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

10.4 Debugging tricks

- signal(SIGSEGV, [](int) { _Exit(0); }); converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). _GLIBCXX_DEBUG failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- feenableexcept(29); kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks

__builtin_ia32_ldmxcsr(40896); disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- $x \ \& \ -x$ is the least bit in x .
- for (int x = m; x;) { --x &= m; ... } loops over all subset masks of m (except m itself).

- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K))`
if `(i & 1 << b) D[i] += D[i^(1 << b)]`;
computes all sums of subsets.

10.5.2 Pragmas

- `#pragma GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- `#pragma GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- `#pragma GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

FastMod.h
Description: Compute *a%b* about 5 times faster than usual, where *b* is constant but not known at compile time. Returns a value congruent to *a* (mod *b*) in the range [0,2*b*].

```
typedef unsigned long long ull;
struct FastMod {
    ull b, m;
    FastMod(ull b) : b(b), m(-1ULL / b) {}
    ull reduce(ull a) { // a % b + (0 or b)
        return a - (ull)((__uint128_t(m) * a) >> 64) * b;
    }
};
```

FastInput.h
Description: Read an integer from stdin. Usage requires your program to pipe in input from file.
Usage: ./a.out < input.txt
Time: About 5x as fast as cin/scanf.

```
inline char gc() { // like getchar()
    static char buf[1 << 16];
    static size_t bc, be;
    if (bc >= be) {
        buf[0] = 0, bc = 0;
        be = fread(buf, 1, sizeof(buf), stdin);
    }
    return buf[bc++]; // returns 0 on EOF
}
```

```
int readInt() {
    int a, c;
    while ((a = gc()) < 40);
    if (a == '-' ) return -readInt();
    while ((c = gc()) >= 48) a = a * 10 + c - 48;
    return a - 48;
}
```

BumpAllocator.h
Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation.

```
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
    static size_t i = sizeof buf;
    assert(s < i);
    return (void*)&buf[i -= s];
}
```

```
}
void operator delete(void*) {}
```

SmallPtr.h
Description: A 32-bit pointer that points into BumpAllocator memory.

```
"BumpAllocator.h"
template<class T> struct ptr {
    unsigned ind;
    ptr(T* p = 0) : ind(p ? unsigned((char*)p - buf) : 0) {
        assert(ind < sizeof buf);
    }
    T& operator*() const { return *(T*)(buf + ind); }
    T* operator->() const { return &*this; }
    T& operator[](int a) const { return (&***this)[a]; }
    explicit operator bool() const { return ind; }
};
```

BumpAllocatorSTL.h
Description: BumpAllocator for STL containers.
Usage: vector<vector<int, small<int>>>> ed(N);

```
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;

template<class T> struct small {
    typedef T value_type;
    small() {}
    template<class U> small(const U&) {}
    T* allocate(size_t n) {
        buf_ind -= n * sizeof(T);
        buf_ind &= 0 - alignof(T);
        return (T*)(buf + buf_ind);
    }
    void deallocate(T*, size_t) {}
};
```

SIMD.h
Description: Cheat sheet of SSE/AVX intrinsics, for doing arithmetic on several numbers at once. Can provide a constant factor improvement of about 4, orthogonal to loop unrolling. Operations follow the pattern `__mnm(256)?_name_(si(128|256)|epi(8|16|32|64)|pd|ps)"`. Not all are described here; grep for `__mm_` in `/usr/lib/gcc/*/4.9/include/` for more. If AVX is unsupported, try 128-bit operations, "emmintrin.h" and `#define _SSE_` and `__MMX__` before including it. For aligned memory use `__mm_malloc(size, 32)` or `int buf[N] alignas(32)`, but prefer `loadu/storeu`.

```
#pragma GCC target ("avx2") // or sse4.1
#include "immintrin.h"

typedef __m256i mi;
#define L(x) __mm256_loadu_si256((mi*)&(x))

// High-level/specific methods:
// load(u)?_si256, store(u)?_si256, setzero_si256, __mm_malloc
// blendv_(epi8|ps|pd) (z?y:x), movemask_epi8 (hibits of bytes)
// i32gather_epi32(addr, x, 4): map addr[] over 32-b parts of x
// sad_epu8: sum of absolute differences of u8, outputs 4xi64
// maddubs_epi16: dot product of unsigned i7's, outputs 16xi15
// madd_epi16: dot product of signed i16's, outputs 8xi32
// extractf128_si256(. i) (256->128), cvtsi128_si32 (128->lo32)
// permute2f128_si256(x,x,1) swaps 128-bit lanes
// shuffle_epi32(x, 3*64+2*16+1*4+0) == x for each lane
// shuffle_epi8(x, y) takes a vector instead of an imm

// Methods that work with most data types (append e.g. _epi32):
// set1, blend (i8?x:y), add, adds (sat.), mullo, sub, and/or,
// andnot, abs, min, max, sign(1,x), cmp(gt|eq), unpack(lo|hi)
```

```
int sumi32(mi m) { union {int v[8]; mi m;} u; u.m = m;
    int ret = 0; rep(i,0,8) ret += u.v[i]; return ret; }
mi zero() { return __mm256_setzero_si256(); }
mi one() { return __mm256_set1_epi32(-1); }
bool all_zero(mi m) { return __mm256_testz_si256(m, m); }
bool all_one(mi m) { return __mm256_testc_si256(m, one()); }

ll example_filteredDotProduct(int n, short* a, short* b) {
    int i = 0; ll r = 0;
    mi zero = __mm256_setzero_si256(), acc = zero;
    while (i + 16 <= n) {
        mi va = L(a[i]), vb = L(b[i]); i += 16;
        va = __mm256_and_si256(__mm256_cmpgt_epi16(vb, va), va);
        mi vp = __mm256_madd_epi16(va, vb);
        acc = __mm256_add_epi64(__mm256_unpacklo_epi32(vp, zero),
            __mm256_add_epi64(acc, __mm256_unpackhi_epi32(vp, zero)));
    }
    union {ll v[4]; mi m;} u; u.m = acc; rep(i,0,4) r += u.v[i];
    for (;i<n;++i) if (a[i] < b[i]) r += a[i]*b[i]; // <- equiv
    return r;
}
```

```
template<typename T, size_t len>
using simd [[gnu::vector_size(len * sizeof(T))]] = T;
using i64x4 = simd<int64_t, 4>;
using u64x4 = simd<uint64_t, 4>;
using u32x8 = simd<uint32_t, 8>;
using i32x4 = simd<int32_t, 4>;
using u32x4 = simd<uint32_t, 4>;
using i16x4 = simd<int16_t, 4>;
using u8x32 = simd<uint8_t, 32>;
using dx4 = simd<double, 4>;
```